1 Perturbation of the spin motion

The spin precession axis of a particle involved in betatron motion precesses about the stable invariant spin axis defined on the closed orbit (CO).

This precession can be observed in polarization data as a rapid, small-amplitude oscillation (see Figure 2) on top of the *major effect* oscillation caused by the precession of spin about the CO axis. The frequency of this latter oscillation is used in the FD methodology as the EDM observable. It is estimated by fitting polarimetry data by a sine function. The rapid oscillations, therefore, constitute a model error.¹

This model error will introduce a bias into the frequency estimate (the amplitude growth of the blue line oscillation in Figure 1 is due to the bias). In the following we investigate how this bias changes depending on the beam revolution direction, its stability over time, and the EDM estimate error introduced by it.

1.1 Simulation: Uniform beam

For simulation, we used an imperfect FS lattice, with E+B elements randomly tilted about the optical axis by angles picked from the normal distribution $N(8 \cdot 10^{-2} \text{ [rad]}, 10^{-2} \text{ [rad]})$. The systematic $\langle \Theta_{tilt} \rangle = 8 \cdot 10^{-2}$ radians was selected to ensure a high radial precession rate and reduce tracking time requirements. Tilts are simulated by applying a spin rotation axis as discussed in Section ??. By doing it this way, we do not affect the orbital transfer map; that is, the closed orbit remains unchanged.

The beam was represented by an ensemble E of 4,000 rays, split into four groups of 1,000 rays: 1) rays offset from the CO at injection time in the x coordinate, 2) in the y coordinate, 3) in both x and y, 4) in $d := \frac{\Delta K}{K_0}$. The x and y coordinates were uniformly sampled in the range ± 5 mm, d in the range $\pm 5 \cdot 10^{-4}$. The reference energy $K_0 = 270.0092$ MeV (Frozen Spin energy for this lattice).

The beam polarization was computed from spin tracking data as

$$oldsymbol{P} = rac{\sum_{i \in E} oldsymbol{s}_i}{||\sum_{i \in E} oldsymbol{s}_i||}.$$

Then the vertical polarization component was fitted with the fit function $f=\sin(2\pi\cdot f\cdot t)$, with f the only fitted parameter. This procedure was carried out for the (identical at injection) CW and CCW revolving beams. We also estimated the reference rays' (CW & CCW) precession frequencies in the same way, by fitting the vertical spin component S_y^0 of the reference particle. The fit results are presented in Table 1. From this table, one can see that the polarization estimate is clearly biased toward the reference ray's estimate; however, the CW vs CCW estimates of either the reference ray or the polarization are

¹A more sophisticated, for example autoregressive, model would solve this problem; however at a cost to precision.

statistically indistinguishable (assuming a normal distribution of the estimates, the hypothesis test for equality gives p-values of 30% and higher).




Figure 1: Vertical polarization residuals, computed as the difference between P_y (data) and: (red) \hat{P}_y (model prediction), (blue) S_y^{co} (reference particle vertical spin component). The oscillations of the residuals are due to the rapid oscillations caused by the precession axis instability.




Figure 2: A zoom of Figure 1.

As a last step, we conducted a moving frame fit of polarization data, in order to assess whether the model error might cause the frequency estimate to vary

Table 1: Frequency estimates for the Uniform CW & CCW beams, reference ray and full beam, in Hz

Data		Polarization		Reference ray	
Frequency	Offset	CW	CCW	CW	CCW
Estimate	360.1103	$3.986 \cdot 10^{-5}$	$3.985 \cdot 10^{-5}$	$9.88274 \cdot 10^{-5}$	$9.88274 \cdot 10^{-5}$
SE	_	$3 \cdot 10^{-8}$	$3 \cdot 10^{-8}$	$5 \cdot 10^{-10}$	$5 \cdot 10^{-10}$

over time. The results are presented in Figure 3.




Figure 3: Moving frame frequency estimates.

1.2 Simulation: Gaussian distribution beam

For this test we injected a beam of the same size, with x, y and d coordinates distributed normally (with standard deviations 1 mm, 1 mm, and 10^{-4} respectively). The coordinate distributions of the CW & CCW beams are presented in Figures 4 and 5. As one can see, the beam's centroids are split by 0.02 mm in the horizontal direction, and 0.003 mm in the vertical direction. This split will have an effect on the resultant frequency estimate bias difference.

The fit results are summarized in Table 2.




Figure 4: The x and y initial beam distributions.

Table 2: Frequency estimates for the Gaussian CW & CCW beams, reference ray and full beam, in ${\rm Hz}$

Data		Polarization		Reference ray	
Frequency	Offset	CW	CCW	CW	CCW
Estimate	3900.353	$3.81688 \cdot 10^{-4}$	$3.87826 \cdot 10^{-4}$	$7.613845 \cdot 10^{-4}$	$7.613845 \cdot 10^{-4}$
SE	_	$2 \cdot 10^{-9}$	$6 \cdot 10^{-9}$	$5 \cdot 10^{-12}$	$4 \cdot 10^{-11}$

The polarization frequency estimate difference

$$\varepsilon := \hat{f}_{CW} - \hat{f}_{CCW} = 6 \cdot 10^{-6} \pm 6 \cdot 10^{-9} \text{ [Hz]}.$$

One can see that the difference cannot be explained by statistical uncertainty.

Together with the uniform beam simulation, the above result drives the conclusion that the beam distribution asymmetry is a source of systematic error via spin precession axis direction variation. This systematic effect should reduce with the beam size, as in that case the coordinate distributions become more symmetrical.

Considering the last point, assume ε is proportional to the beam distribution centroid difference, defined by the coordinate distribution means. The expectation values of the coordinate distributions are located on the closed orbit,




Figure 5: The d initial beam distributions.

which is the same for the CW and CCW beams. The actual beam centroids are distributed about this point in a normal distribution with some standard deviation. Denote that standard deviation $\sigma_{mean} \equiv \sigma_{4k}$ for the beams used in the simulation above. This standard deviation gives us a frequency estimate variation on the order of 10^{-6} Hz (while the statistical uncertainty standard deviation is 10^{-9} Hz). The standard error of the mean is computed as

$$\sigma_{mean} = \frac{\sigma}{\sqrt{n}},$$

where n is the sample size, which in our case is the number of beam particles. Now, if we used a $n = 4 \cdot 10^9$ particle beam instead of the $n = 4 \cdot 10^3$ one, we'd have $\sigma_{4b} = \sigma_{4k} \cdot 10^{-3}$. Assuming a linear relationship between the centroid difference and the frequency bias difference, the latter's standard deviation would reduce to 10^{-9} , which is then comparable with statistical error.

1.3 The effect of the beam distribution centroid difference on spin precession

Now we will test the hypothesis that the estimate bias difference is proportional to the beam centroid difference.

This time we repeated the test from the previous section for multiple (30) trials. We used the same imperfect lattice on each trial; trials only differ by their initial beam distributions. An example of the polarization oscillations in this lattice is given in Figure 6.





Figure 6: Example of polarization oscillations in the used lattice.

For each beam, we computed its centroid, defined as $\mathbf{c} = (\langle x_0 \rangle, \langle y_0 \rangle, \langle d_0 \rangle)$, and took the difference $\Delta \mathbf{c} := \mathbf{c}_i^{CW} - \mathbf{c}_i^{CCW}$ (*i* the trial number). We then regressed (non-weighted linear regression) ε_i on the components of $\Delta \mathbf{c}_i$. The results are plotted in Figure 7. We found a statistically significant dependence on the vertical centroid difference component (p-value $2.8 \cdot 10^{-2}\%$).


In order to make sure that the bias difference is not related to the change of the beam revolution direction, we checked the centroid difference dependence of the bias on the same direction beams. The dependence remains.

References

Weighted linear regression gives even more statistically significant results; for example, for the y case, the p-value drops to $10^{-2}\%$, and for x, it drops from 12% to 8%



(a) The x coordinate.



(b) The y coordinate.




Figure 7: Frequency estimate difference vs a beam centroid split coordinate.