

HPC Induction

Part III: Software

Jascha Schewtschenko

Royal Observatory of Edinburgh, University of Edinburgh

May 14, 2025



Outline

- 1 System Software
 - Operating System
 - Inter-Process Communication
 - Resource & Job Management
- 2 Software: Environments & Applications
- 3 Etiquette



SOFTWARE

Environments & Applications

SYSTEM SOFTWARE

Resource & Job Management

Runtime System Interprocess Comm

Operating System

VIRTUALISATION

Cloud computing / OpenStack

HARDWARE

Network Interconnects

Memory & Data Storage

Processors & Accelerators



Operating System



OS: Basics

- While there are many server OS out there (FreeBSD, z/OS, MS Windows Server, etc.), there is one dominating the HPC market





OS: Basics

- While there are many server OS out there (FreeBSD, z/OS, MS Windows Server, etc.), there is one dominating the HPC market

Linux Runs on All of the Top 500 Supercomputers, Again!

Last updated June 21, 2019 By [Abhishek Prakash](#) — [15 Comments](#)



Build and develop apps with Azure.
Free until you say otherwise.

Try Azure Free >

Linux might be struggling for a decent desktop market share but it is definitely ruling the world of supercomputers. Linux is the supercomputer operating system by choice.





OS: Basics

- While there are many server OS out there (FreeBSD, z/OS, MS Windows Server, etc.), there is one dominating the HPC market

Linux Runs on All of the Top 500 Supercomputers, Again!


Last updated June 21, 2019 By [Abhishek Prakash](#) — [15 Comments](#)



Build and develop apps with Azure.
Free until you say otherwise.


Try Azure Free >

Linux might be struggling for a decent desktop market share but it is definitely ruling the world of supercomputers. Linux is the supercomputer operating system by choice.



OS: Basics (cont.)

- Few distros dominate the market




Note: All operating systems of the TOP500 systems use [Linux](#), but Linux above is *generic* Linux



OS: Basics (cont.)

- Few distros dominate the market




Note: All operating systems of the TOP500 systems use [Linux](#), but Linux above is *generic* Linux

- That gives you an environment you are familiar with when logging to new HPC infrastructure



OS: Basics (cont.)

- Few distros dominate the market



Note: All operating systems of the TOP500 systems use [Linux](#), but Linux above is *generic* Linux

- That gives you an environment you are familiar with when logging to new HPC infrastructure
- For a tutorial on how to use Linux (or Unix), please see:

Linux Induction Lecture [Link]

(it is **ESSENTIAL** that you know these very few basics BEFORE you start working on the system, especially if you are using the command-line interfaces (CLI))



OS: Authentication

- When logging into a (remote) system you have to provide verification of your identity as a user



OS: Authentication

- When logging into a (remote) system you have to provide verification of your identity as a user
- traditionally, passwords were used, but disadvantage is that they can easily be stolen (phishing/spoofing, guessing, key loggers, "looking over shoulder")




OS: Authentication

- When logging into a (remote) system you have to provide verification of your identity as a user
- traditionally, passwords were used, but disadvantage is that they can easily be stolen (phishing/spoofing, guessing, key loggers, "looking over shoulder")
- nowadays many system use SSH key authentication (e.g. RSA)



OS: Authentication



Pass Phrase

Associated with the key is a Pass Phrase.
It is mandatory to use a Pass Phrase.

Private Key File

Stored on your desktop or laptop

The pass phrase protects the private key



TOP SECRET!!

NEVER share a private key !!


Public Key File

Stored on remote server



OS: Authentication

- consists of an asymmetric key pair (like for PGP): a **SECRET** private key and a public key




OS: Authentication

- consists of an asymmetric key pair (like for PGP): a **SECRET** private key and a public key
- private key stored on your computer, public key on the server
(on Linux in `~/.ssh/authorized_keys`)




OS: Authentication

- consists of an asymmetric key pair (like for PGP): a **SECRET** private key and a public key
- private key stored on your computer, public key on the server
(on Linux in `~/.ssh/authorized_keys`)
- the private key can sign a message (e.g. login request), while the public key can be used to verify the signature (but not to create it)




OS: Authentication

- consists of an asymmetric key pair (like for PGP): a **SECRET** private key and a public key
- private key stored on your computer, public key on the server
(on Linux in `~/.ssh/authorized_keys`)
- the private key can sign a message (e.g. login request), while the public key can be used to verify the signature (but not to create it)
- Avoids identity theft by methods listed above as no secret authentication data ever leaves user's computer




OS: Authentication

- consists of an asymmetric key pair (like for PGP): a **SECRET** private key and a public key
- private key stored on your computer, public key on the server
(on Linux in `~/.ssh/authorized_keys`)
- the private key can sign a message (e.g. login request), while the public key can be used to verify the signature (but not to create it)
- Avoids identity theft by methods listed above as no secret authentication data ever leaves user's computer
- Yet, to avoid key theft/misuse, you **MUST** protect the private key with a passphrase




OS: SSH Fingerprints

- So-called SSH fingerprints are used to ensure that your connection to the server is secure (i.e. that you are connected to the real server and/or not a 'Man-in-the-Middle' (MitM))



OS: SSH Fingerprints

- So-called SSH fingerprints are used to ensure that your connection to the server is secure (i.e. that you are connected to the real server and/or not a 'Man-in-the-Middle' (MitM))



- It is a hash based on the public SSH key of the server.

OS: SSH Fingerprints (cont.)

- When you log in for the first time to a server (e.g. login node), you will be notified that the server is not known yet to your system and this fingerprint will be shown

```
[schewtsj@angB-158 ~]$ ssh -Y jschewts@login1.sciama.icg.port.ac.uk
The authenticity of host 'login1.sciama.icg.port.ac.uk (148.197.5.17)' can't be established.
ECDSA key fingerprint is SHA256:JZMx5thY7zQv7dVfGuG+PKcUvUVuXrdrv3nWrzJM4sw.
ECDSA key fingerprint is MD5:f1:8e:7f:e5:b6:03:62:77:9a:b8:8d:65:fe:ac:59:49.
Are you sure you want to continue connecting (yes/no)?
```



OS: SSH Fingerprints (cont.)

- When you log in for the first time to a server (e.g. login node), you will be notified that the server is not known yet to your system and this fingerprint will be shown

```
[schewtsj@angB-158 ~]$ ssh -Y jschewts@login1.sciama.icg.port.ac.uk
The authenticity of host 'login1.sciama.icg.port.ac.uk (148.197.5.17)' can't be established.
Warning: Permanently added 'login1.sciama.icg.port.ac.uk,148.197.5.17' (ECDSA) to the list of known hosts.
ECDSA key fingerprint is SHA256:JZMx5thY7zQv7dVfGuG+PKcUvUVuXrdrv3nWrzJM4sw.
ECDSA key fingerprint is MD5:f1:8e:7f:e5:b6:03:62:77:9a:b8:8d:65:fe:ac:59:49.
Are you sure you want to continue connecting (yes/no)?
```

- After logging in, you should confirm the validity of the server key

```
Are you sure you want to continue connecting (yes/no)? yes
Warning: Permanently added 'login1.sciama.icg.port.ac.uk,148.197.5.17' (ECDSA) to the list of known hosts.
Last login: Sun Oct 20 19:17:47 2019 from 148.197.150.18
===== Welcome to Sciama 4 =====
For any questions, please consult the knowledge base at
http://icg.port.ac.uk/support-kbtopic/sciama

[jschewts@login1(sciama) ~]$ cd /etc/ssh
[jschewts@login1(sciama) ssh]$ for file in *pub; do ssh-keygen -E md5 -lf $file; done
256 MD5:f1:8e:7f:e5:b6:03:62:77:9a:b8:8d:65:fe:ac:59:49 no comment (ECDSA)
256 MD5:4a:5e:80:88:85:5d:2a:c5:cd:5f:89:88:5b:21:59:d4 no comment (ED25519)
2048 MD5:05:49:7a:73:de:bb:e5:af:ef:72:8b:04:03:81:5c:b4 no comment (RSA)
[jschewts@login1(sciama) ssh]$
```



OS: SSH Fingerprints (cont.)

- When you log in for the first time to a server (e.g. login node), you will be notified that the server is not known yet to your system and this fingerprint will be shown

```
[schewtsj@angB-158 ~]$ ssh -Y jschewts@login1.sciama.icg.port.ac.uk
Warning: The authenticity of host 'login1.sciama.icg.port.ac.uk (148.197.5.17)' can't be established.
ECDSA key fingerprint is SHA256:JZMx5thY7zQv7dVfGuG+PKcUvUVuXrdrv3nWrzJM4sw.
ECDSA key fingerprint is MD5:f1:8e:7f:e5:b6:03:62:77:9a:b8:8d:65:fe:ac:59:49.
Are you sure you want to continue connecting (yes/no)?
```

- After logging in, you should confirm the validity of the server key

```
Are you sure you want to continue connecting (yes/no)? yes
Warning: Permanently added 'login1.sciama.icg.port.ac.uk,148.197.5.17' (ECDSA) to the list of known hosts.
Last login: Sun Oct 20 19:17:47 2019 from 148.197.150.18
===== Welcome to Sciama 4 =====
For any questions, please consult the knowledge base at
http://icg.port.ac.uk/support-kbtopic/sciama

[jschewts@login1(sciama) ~]$ cd /etc/ssh
[jschewts@login1(sciama) ssh]$ for file in *pub; do ssh-keygen -E md5 -lf $file; done
256 MD5:f1:8e:7f:e5:b6:03:62:77:9a:b8:8d:65:fe:ac:59:49 no comment (ECDSA)
256 MD5:4a:5e:80:88:85:5d:2a:c5:cd:5f:89:88:5b:21:59:d4 no comment (ED25519)
2048 MD5:05:49:7a:73:de:bb:e5:af:ef:72:8b:04:03:81:5c:b4 no comment (RSA)
[jschewts@login1(sciama) ssh]$
```

- This protects well against MitM attacks. Any such attempt will result in non-matching SSH fingerprints



OS: SSH Fingerprints (cont.)

- When you log in for the first time to a server (e.g. login node), you will be notified that the server is not known yet to your system and this fingerprint will be shown

```
[schewtsj@angB-158 ~]$ ssh -Y jschewts@login1.sciama.icg.port.ac.uk
The authenticity of host 'login1.sciama.icg.port.ac.uk (148.197.5.17)' can't be established.
ECDSA key fingerprint is SHA256:JZMx5thY7zQv7dVfGuG+PKcUvUVuXrdrv3nWrzJM4sw.
ECDSA key fingerprint is MD5:f1:8e:7f:e5:b6:03:62:77:9a:b8:8d:65:fe:ac:59:49.
Are you sure you want to continue connecting (yes/no)?
```

- After logging in, you should confirm the validity of the server key

```
Are you sure you want to continue connecting (yes/no)? yes
Warning: Permanently added 'login1.sciama.icg.port.ac.uk,148.197.5.17' (ECDSA) to the list of known hosts.
Last login: Sun Oct 20 19:17:47 2019 from 148.197.150.18
===== Welcome to Sciama 4 =====
For any questions, please consult the knowledge base at
http://icg.port.ac.uk/support-kbtopic/sciama

[jschewts@login1(sciama) ~]$ cd /etc/ssh
[jschewts@login1(sciama) ssh]$ for file in *pub; do ssh-keygen -E md5 -lf $file; done
256 MD5:f1:8e:7f:e5:b6:03:62:77:9a:b8:8d:65:fe:ac:59:49 no comment (ECDSA)
256 MD5:4a:5e:80:88:85:5d:2a:c5:cd:5f:89:88:5b:21:59:d4 no comment (ED25519)
2048 MD5:05:49:7a:73:de:bb:e5:af:ef:72:8b:04:03:81:5c:b4 no comment (RSA)
[jschewts@login1(sciama) ssh]$
```

- This protects well against MitM attacks. Any such attempt will result in non-matching SSH fingerprints
- But it is less reliably against spoofing if this happens on first login and you do not know the fingerprints in advance




OS: Login

- Usually, HPC system have a couple of special login nodes accessible from the outside



OS: Login

- Usually, HPC system have a couple of special login nodes accessible from the outside
- Login nodes may support graphical (NoMachine,X2Go,etc.) and/or command-line based (rlogin,telnet,SSH,etc.) remote shells to access them



```
[schewtsj@ang8-158 ~]$ ssh -Y jschewts@login1.sciama.icg.port.ac.uk
Last login: Sun Oct 20 19:17:47 2019 from 148.197.150.18
===== Welcome to Sciama 4 =====
For any questions, please consult the knowledge base at
http://icg.port.ac.uk/support-kbtopic/sciama

[jschewts@login1] sc1ama ~]$
```

OS: Login (Artemis)

- For Artemis, the login nodes can be found at `ood.artemis.hrc.sussex.ac.uk`



OS: Login (Artemis)

- For Artemis, the login nodes can be found at `ood.artemis.hrc.sussex.ac.uk`
- Artemis's login node supports CLI-based (SSH) remote shell access as well as a graphical user interface with remote desktop access



OS: Login (Artemis)

- For Artemis, the login nodes can be found at `ood.artemis.hrc.sussex.ac.uk`
- Artemis's login node supports CLI-based (SSH) remote shell access as well as a graphical user interface with remote desktop access
- Login nodes can be used for any work with a **SMALL** resource footprint (both memory and CPU-wise) i.e. coding, compiling, plotting, etc.



OS: Login (Artemis)

- For Artemis, the login nodes can be found at `ood.artemis.hrc.sussex.ac.uk`
- Artemis's login node supports CLI-based (SSH) remote shell access as well as a graphical user interface with remote desktop access
- Login nodes can be used for any work with a **SMALL** resource footprint (both memory and CPU-wise) i.e. coding, compiling, plotting, etc.
- Anything else **MUST** be run on the compute nodes (via `slurm`)



OS: Data Storage/Access

- Usually, HPC system have network storage to share data among the nodes as well as to provide space to store results



OS: Data Storage/Access

- Usually, HPC system have network storage to share data among the nodes as well as to provide space to store results
- Home directories with their config files are often network-mounted; so are folders containing applications & their modules



OS: Data Storage/Access

- Usually, HPC system have network storage to share data among the nodes as well as to provide space to store results
- Home directories with their config files are often network-mounted; so are folders containing applications & their modules
- Either hard- or soft-quotas may apply to all provided storage



OS: Data Storage/Access

- Usually, HPC system have network storage to share data among the nodes as well as to provide space to store results
- Home directories with their config files are often network-mounted; so are folders containing applications & their modules
- Either hard- or soft-quotas may apply to all provided storage
- Part of the storage may be backup-ed automatically in regular intervals (in which case, system admins will ask you to keep your storage footprint to the essentials to avoid wasting storage space on keeping backups on unimportant data)



OS: Data Storage/Access

- Usually, HPC system have network storage to share data among the nodes as well as to provide space to store results
- Home directories with their config files are often network-mounted; so are folders containing applications & their modules
- Either hard- or soft-quotas may apply to all provided storage
- Part of the storage may be backup-ed automatically in regular intervals (in which case, system admins will ask you to keep your storage footprint to the essentials to avoid wasting storage space on keeping backups on unimportant data)
- Additionally, many data centres also provide the possibility to do long-term backups on data tapes



OS: Data Transfer

- (For non-cloud storage,) there are various methods for transferring files between Artemis and other computers



OS: Data Transfer

- (For non-cloud storage,) there are various methods for transferring files between Artemis and other computers
- The simplest way to transfer data is using the CLI tool `scp` and the protocol of the same name (based on SSH) e.g.

```
scp  
juser@ood.artemis.hrc.sussex.ac.uk:/home/juser/some.file  
/Documents/
```



OS: Data Transfer

- (For non-cloud storage,) there are various methods for transferring files between Artemis and other computers
- The simplest way to transfer data is using the CLI tool `scp` and the protocol of the same name (based on SSH) e.g.

```
scp  
juser@ood.artemis.hrc.sussex.ac.uk:/home/juser/some.file  
/Documents/
```

- `scp` can also compress the data, thus speeding up the transfer.



OS: Data Transfer

- (For non-cloud storage,) there are various methods for transferring files between Artemis and other computers
- The simplest way to transfer data is using the CLI tool `scp` and the protocol of the same name (based on SSH) e.g.

```
scp  
juser@ood.artemis.hrc.sussex.ac.uk:/home/juser/some.file  
/Documents/
```

- `scp` can also compress the data, thus speeding up the transfer.
- For backups/synchronizing (remote) folders, the SSH-based CLI tool `rsync` not only compresses transfers, but also only transfers the differences between files, which may significantly reduce the amount of data transferred.



OS: Data Transfer

- (For non-cloud storage,) there are various methods for transferring files between Artemis and other computers
- The simplest way to transfer data is using the CLI tool `scp` and the protocol of the same name (based on SSH) e.g.

```
scp
juser@ood.artemis.hrc.sussex.ac.uk:/home/juser/some.file
/Documents/
```

- `scp` can also compress the data, thus speeding up the transfer.
- For backups/synchronizing (remote) folders, the SSH-based CLI tool `rsync` not only compresses transfers, but also only transfers the differences between files, which may significantly reduce the amount of data transferred.
- Alternatively, you can use the SFTP protocol, either via CLI tools or using GUI-based tools (e.g. many Linux file managers support it natively, FileZilla on Windows)



OS: Data Storage/Transfer - Cloud

- For backups, you have to store your data off-site.



OS: Data Storage/Transfer - Cloud

- For backups, you have to store your data off-site.
- A convenient way to do this is to use cloud storage e.g. GoogleDrive storage



Dropbox



OneDrive



Google Drive



OS: Data Transfer - Globus

- For larger amounts of data (e.g. exchange of simulation data \sim TB between data centres), “standard” transfer methods are not feasible.



OS: Data Transfer - Globus

- For larger amounts of data (e.g. exchange of simulation data \sim TB between data centres), “standard” transfer methods are not feasible.
- Globus provides framework to transfer large amounts of research data “efficiently, securely & reliably” (using parallel transfer protocol)




OS: Data Transfer - Globus

- For larger amounts of data (e.g. exchange of simulation data \sim TB between data centres), “standard” transfer methods are not feasible.
- Globus provides framework to transfer large amounts of research data “efficiently, securely & reliably” (using parallel transfer protocol)
- Many research data centres have Globus nodes



OS: Data Transfer - Globus

- For larger amounts of data (e.g. exchange of simulation data \sim TB between data centres), “standard” transfer methods are not feasible.
- Globus provides framework to transfer large amounts of research data “efficiently, securely & reliably” (using parallel transfer protocol)
- Many research data centres have Globus nodes
- Uses a web interface to manage transfers (works as a download/upload manager)



Inter-Process Communication




Inter-Process Communication

Two models of IPC

Message Passing - communication takes place by means of messages exchanged between the cooperating process.

Shared Memory - a region of memory that is shared by cooperating processes is established then exchange information takes place by reading and writing data to the shared area



MUCH more on this on Day 2 & 3 !!

Resource & Job Management



Role of Resource Manager

- Allocate resources within a cluster



Role of Resource Manager

- Allocate resources within a cluster
- Launch and manage jobs




Role of Resource Manager

- Allocate resources within a cluster
- Launch and manage jobs
- If resources required for jobs exceed available resources at the moment, a scheduling strategy is needed




Role of Job Scheduler

- When there is more work than resources, the job scheduler manages queue(s) of work



Role of Job Scheduler

- When there is more work than resources, the job scheduler manages queue(s) of work
- Usually supports complex scheduling algorithms to decide which jobs in the queue(s) are executed to optimize usage of resources:



Role of Job Scheduler

- When there is more work than resources, the job scheduler manages queue(s) of work
- Usually supports complex scheduling algorithms to decide which jobs in the queue(s) are executed to optimize usage of resources:
 - ▶ Optimized for network topology, fair-share scheduling, advanced reservations, preemption, gang scheduling, backfill scheduling, etc.




Figure 3. Job scheduling algorithms

Role of Job Scheduler

- When there is more work than resources, the job scheduler manages queue(s) of work
- Usually supports complex scheduling algorithms to decide which jobs in the queue(s) are executed to optimize usage of resources:
 - ▶ Optimized for network topology, fair-share scheduling, advanced reservations, preemption, gang scheduling, backfill scheduling, etc.
 - ▶ Job can be prioritized by e.g. job age, job partition, job size, etc.




Figure 3. Job scheduling algorithms

Role of Job Scheduler

- When there is more work than resources, the job scheduler manages queue(s) of work
- Usually supports complex scheduling algorithms to decide which jobs in the queue(s) are executed to optimize usage of resources:
 - ▶ Optimized for network topology, fair-share scheduling, advanced reservations, preemption, gang scheduling, backfill scheduling, etc.
 - ▶ Job can be prioritized by e.g. job age, job partition, job size, etc.
- Supports resource limits (by queue, user, group/project, etc.)




Figure 3. Job scheduling algorithms

Resource Management / Scheduling Software

- There is a variety of software packages for HPC resource management and Job scheduling:

<u>Resource Managers</u>	<u>Schedulers</u>
ALPS (Cray)	Maui
Torque	Moab
LoadLeveler (IBM)	
Slurm	
LSF	
PBS Pro	

Many packages cover both roles.

Resource Management / Scheduling Software

- There is a variety of software packages for HPC resource management and Job scheduling:

<u>Resource Managers</u>	<u>Schedulers</u>
ALPS (Cray)	Maui
Torque	Moab
LoadLeveler (IBM)	
Slurm	
LSF	
PBS Pro	

Many packages cover both roles.

- While you can encounter any of them out there on HPC systems, we focus here on open-source software `slurm` in particular as it is used by Artemis.



slurm: General



- Historically Slurm was an acronym standing for **S**imple **L**inux **U**tility for **R**esource **M**anagement



slurm: General



- Historically Slurm was an acronym standing for **S**imple **L**inux **U**tility for **R**esource **M**anagement
- Development started in 2002 at Lawrence Livermore National Laboratory as a resource manager for Linux clusters



slurm: General



- Historically Slurm was an acronym standing for **S**imple **L**inux **U**tility for **R**esource **M**anagement
- Development started in 2002 at Lawrence Livermore National Laboratory as a resource manager for Linux clusters
- Sophisticated scheduling plugins added in 2008



slurm: General



- Historically Slurm was an acronym standing for **S**imple **L**inux **U**tility for **R**esource **M**anagement
- Development started in 2002 at Lawrence Livermore National Laboratory as a resource manager for Linux clusters
- Sophisticated scheduling plugins added in 2008
- Used on many of the world's largest computers (e.g. managing 3.1 million core Tianhe-2)



slurm: General



- Historically Slurm was an acronym standing for **S**imple **L**inux **U**tility for **R**esource **M**anagement
- Development started in 2002 at Lawrence Livermore National Laboratory as a resource manager for Linux clusters
- Sophisticated scheduling plugins added in 2008
- Used on many of the world's largest computers (e.g. managing 3.1 million core Tianhe-2)
- Plugins for various MPI libraries available (i.e. MPI “talks” to `slurm` to determine number of tasks)



slurm: Terminology

Job Each `srun`, `sbatch` or `salloc` that is started from the CLI and not already part of a job creates a new job.



slurm: Terminology

- Job** Each `srun`, `sbatch` or `salloc` that is started from the CLI and not already part of a job creates a new job.
- Task** A job has at least one task. A task can be thought of as a single process. You may be running several processes/tasks in tandem within a job (such as with MPI)



slurm: Terminology

- Job** Each `srun`, `sbatch` or `salloc` that is started from the CLI and not already part of a job creates a new job.
- Task** A job has at least one task. A task can be thought of as a single process. You may be running several processes/tasks in tandem within a job (such as with MPI)
- Step** A job may or may not consist of one or more steps started with `srun` which run sequentially, but each step may have multiple tasks running in parallel. If started from CLI, there will be one step, in a new job. If included in a batch script, each `srun` will be a new step. Useful to attach different input (cf. `sattach`).



slurm: Terminology

- Job** Each `srun`, `sbatch` or `salloc` that is started from the CLI and not already part of a job creates a new job.
- Task** A job has at least one task. A task can be thought of as a single process. You may be running several processes/tasks in tandem within a job (such as with MPI)
- Step** A job may or may not consist of one or more steps started with `srun` which run sequentially, but each step may have multiple tasks running in parallel. If started from CLI, there will be one step, in a new job. If included in a batch script, each `srun` will be a new step. Useful to attach different input (cf. `sattach`).
- Array** A job may be an array job, i.e. several tasks that do not need to run in parallel and that are submitted through a single command.



slurm: Terminology

Job Each `srun`, `sbatch` or `salloc` that is started from the CLI and not already part of a job creates a new job.

Task A job has at least one task. A task can be thought of as a single process. You may be running several processes/tasks in tandem within a job (such as with MPI)

Step A job may or may not consist of one or more steps started with `srun` which run sequentially, but each step may have multiple tasks running in parallel. If started from CLI, there will be one step, in a new job. If included in a batch script, each `srun` will be a new step. Useful to attach different input (cf. `sattach`).

Array A job may be an array job, i.e. several tasks that do not need to run in parallel and that are submitted through a single command.

Partition A logical grouping of nodes. Partitions may overlap



slurm: Terminology

Job Each `srun`, `sbatch` or `salloc` that is started from the CLI and not already part of a job creates a new job.

Task A job has at least one task. A task can be thought of as a single process. You may be running several processes/tasks in tandem within a job (such as with MPI)

Step A job may or may not consist of one or more steps started with `srun` which run sequentially, but each step may have multiple tasks running in parallel. If started from CLI, there will be one step, in a new job. If included in a batch script, each `srun` will be a new step. Useful to attach different input (cf. `sattach`).

Array A job may be an array job, i.e. several tasks that do not need to run in parallel and that are submitted through a single command.

Partition A logical grouping of nodes. Partitions may overlap.

CPU here used as a synonym for core (e.g. in `--cpus-per-task`)



slurm: Job Submission

`sbatch` This submits a background/*batch job* to the cluster (the job doesn't stay connected to the terminal); requires a job script



slurm: Job Submission

- sbatch** This submits a background/*batch job* to the cluster (the job doesn't stay connected to the terminal); requires a job script
- srun** This command is used for starting jobs that may be single tasks or multiple tasks in parallel. When run from CLI, **srun** blocks while job runs on compute nodes. When run inside a job, it creates a new step.



slurm: Job Submission

- sbatch** This submits a background/*batch job* to the cluster (the job doesn't stay connected to the terminal); requires a job script
- srun** This command is used for starting jobs that may be single tasks or multiple tasks in parallel. When run from CLI, **srun** blocks while job runs on compute nodes. When run inside a job, it creates a new step.
- salloc** When the system is able to allocate the requested resources, **salloc** will run the command supplied to it (by default a shell) on the system calling **salloc** (!).



slurm: Job Submission

- sbatch** This submits a background/*batch job* to the cluster (the job doesn't stay connected to the terminal); requires a job script
- srun** This command is used for starting jobs that may be single tasks or multiple tasks in parallel. When run from CLI, **srun** blocks while job runs on compute nodes. When run inside a job, it creates a new step.
- salloc** When the system is able to allocate the requested resources, **salloc** will run the command supplied to it (by default a shell) on the system calling **salloc** (!).



slurm: Job Submission / Interactive Jobs

- You can execute programs on the resources interactively by using `srun` e.g.

```
$ srun --pty bash
```

If you run it without `salloc`, this will try to allocate a single slot on the cluster. Otherwise, it will use one of the slots requested by `salloc`. You will then have to wait until the resources are available.



slurm: Job Submission / Interactive Jobs

- You can execute programs on the resources interactively by using `srun` e.g.

```
$ srun --pty bash
```

If you run it without `salloc`, this will try to allocate a single slot on the cluster. Otherwise, it will use one of the slots requested by `salloc`. You will then have to wait until the resources are available.

- Once the resources are allocated, a new shell on a compute node opens. The resources stay allocated until you close this shell (or when you hit your defined time limit).



slurm: Job Submission / Interactive Jobs

- You can execute programs on the resources interactively by using `srun` e.g.

```
$ srun --pty bash
```

If you run it without `salloc`, this will try to allocate a single slot on the cluster. Otherwise, it will use one of the slots requested by `salloc`. You will then have to wait until the resources are available.

- Once the resources are allocated, a new shell on a compute node opens. The resources stay allocated until you close this shell (or when you hit your defined time limit).
- The waiting time can be substantial and any loss of your ssh connection to the login node would result in loss of the allocation (request). You can use e.g. `screen` to prevent that (see exercises).

```
$ screen -S my_useful_name  
[user@artemis-login-0 ~]$ srun --pty bash
```



slurm: Job Submission / Batch job (simple job)

- `sbatch` requires a batch script to specify the request of resources and commands to be run on these resources



slurm: Job Submission / Batch job (simple job)

- sbatch requires a batch script to specify the request of resources and commands to be run on these resources
- example script for a simple single-threaded, single-process program:

```
#!/bin/bash
#SBATCH --job-name=test_simple
#SBATCH --output=test_simple.log
#SBATCH --partition=discnet
#SBATCH --nodes=4
#SBATCH --ntasks=4
#SBATCH --time=1:00

echo "$SLURM_JOB_NODELIST #:$SLURM_NTASKS"
hostname
echo "== srun"
srun hostname
echo "== srun -n1 -N1"
srun -n1 -N1 hostname
echo "== srun -n$SLURM_NTASKS"
srun -n$SLURM_NTASKS hostname
```



slurm: Job Submission / Batch job (simple job)

- sbatch requires a batch script to specify the request of resources and commands to be run on these resources
- example script for a simple single-threaded, single-process program:

```
#!/bin/bash
#SBATCH --job-name=test_simple
#SBATCH --output=test_simple.log
#SBATCH --partition=discnet
#SBATCH --nodes=4
#SBATCH --ntasks=4
#SBATCH --time=1:00
```

```
echo "$SLURM_JOB_NODELIST #:$SLURM_NTASKS"
hostname
echo "== srun"
srun hostname
echo "== srun -n1 -N1"
srun -n1 -N1 hostname
echo "== srun -n$SLURM_NTASKS"
srun -n$SLURM_NTASKS hostname
```

Content of test_simple.log:

```
node[111,114,172,194] #:4
==
node111.pri.sciama3.alces.network
== srun
node111.pri.sciama3.alces.network
node114.pri.sciama3.alces.network
node172.pri.sciama3.alces.network
node194.pri.sciama3.alces.network
== srun -n1 -N1
node111.pri.sciama3.alces.network
== srun -n4
node111.pri.sciama3.alces.network
node114.pri.sciama3.alces.network
node172.pri.sciama3.alces.network
node194.pri.sciama3.alces.network
```



slurm: Job Submission / Batch job (simple job)

- sbatch requires a batch script to specify the request of resources and commands to be run on these resources
- example script for a simple single-threaded, single-process program:

```
#!/bin/bash
#SBATCH --job-name=test_simple
#SBATCH --output=test_simple.log
#SBATCH --partition=discnet
#SBATCH --nodes=4
#SBATCH --ntasks=4
#SBATCH --time=1:00
```

```
echo "$SLURM_JOB_NODELIST #:$SLURM_NTASKS"
hostname
echo "== srun"
srun hostname
echo "== srun -n1 -N1"
srun -n1 -N1 hostname
echo "== srun -n$SLURM_NTASKS"
srun -n$SLURM_NTASKS hostname
```

Content of test_simple.log:

```
node[111,114,172,194] #:4
==
node111.pri.sciama3.alces.network
== srun
node111.pri.sciama3.alces.network
node114.pri.sciama3.alces.network
node172.pri.sciama3.alces.network
node194.pri.sciama3.alces.network
== srun -n1 -N1
node111.pri.sciama3.alces.network
== srun -n4
node111.pri.sciama3.alces.network
node114.pri.sciama3.alces.network
node172.pri.sciama3.alces.network
node194.pri.sciama3.alces.network
```

- there is a login (here running on node111) for bootstrapping



slurm: Job Submission / Batch job (simple job)

- sbatch requires a batch script to specify the request of resources and commands to be run on these resources
- example script for a simple single-threaded, single-process program:

```
#!/bin/bash
#SBATCH --job-name=test_simple
#SBATCH --output=test_simple.log
#SBATCH --partition=discnet
#SBATCH --nodes=4
#SBATCH --ntasks=4
#SBATCH --time=1:00
```

```
echo "$SLURM_JOB_NODELIST #:$SLURM_NTASKS"
hostname
echo "== srun"
srun hostname
echo "== srun -n1 -N1"
srun -n1 -N1 hostname
echo "== srun -n$SLURM_NTASKS"
srun -n$SLURM_NTASKS hostname
```

Content of test_simple.log:

```
node[111,114,172,194] #:4
==
node111.pri.sciama3.alces.network
== srun
node111.pri.sciama3.alces.network
node114.pri.sciama3.alces.network
node172.pri.sciama3.alces.network
node194.pri.sciama3.alces.network
== srun -n1 -N1
node111.pri.sciama3.alces.network
== srun -n4
node111.pri.sciama3.alces.network
node114.pri.sciama3.alces.network
node172.pri.sciama3.alces.network
node194.pri.sciama3.alces.network
```

- there is a login (here running on node111) for bootstrapping
- Make sure to wrap your commands into srun if you want them to run on any other than the login node (actually, nothing but VERY light-weight tasks should be run without srun)



slurm: Job Submission / Batch job (multi-threading)

- example script for a multi-threaded, single-process program:

```
#!/bin/bash
#
#SBATCH --job-name=test_threading
#SBATCH --output=test_threading.log.%j
#
#SBATCH --partition=discnet
#SBATCH --ntasks=1
#SBATCH --cpus-per-task=4
#SBATCH --time=1:00

module purge
module load intel/2022a

echo "#:$SLURM_NTASKS *:$SLURM_CPUS_PER_TASK"
export OMP_NUM_THREADS=$SLURM_CPUS_PER_TASK

echo "=="
./test_threading
echo "== srun"
srun ./test_threading
```



slurm: Job Submission / Batch job (multi-threading)

- example script for a multi-threaded, single-process program:

```
#!/bin/bash
#
#SBATCH --job-name=test_threading
#SBATCH --output=test_threading.log.%j
#
#SBATCH --partition=discnet
#SBATCH --ntasks=1
#SBATCH --cpus-per-task=4
#SBATCH --time=1:00

module purge
module load intel/2022a

echo ":#$SLURM_NTASKS *:$SLURM_CPUS_PER_TASK"
export OMP_NUM_THREADS=$SLURM_CPUS_PER_TASK

echo "=="
./test_threading
echo "== srun"
srun ./test_threading
```

- The %j in the output file pattern will be substituted by the JOB_ID (i.e. make it easier to manage output file from multiple submissions of the same script)



slurm: Job Submission / Batch job (multi-processing)

- example script for a multi-threaded, single-process program:

```
#!/bin/bash
#
#SBATCH --job-name=test_mpi
#SBATCH --output=test_mpi.log.%j.%t
#
#SBATCH --partition=discnet
#SBATCH --ntasks=4
#SBATCH --time=1:00

module purge
module load intel/2022a
module load OpenMPI/4.1.4-GCC-11.3.0

echo $SLURM_JOB_NODELIST
echo "[:$SLURM_NTASKS *]: $SLURM_NTASKS"

echo "=="
mpirun ./test_mpi
echo "== srun"
srun --mpi=pmi2 ./test_mpi
```



slurm: Job Submission / Batch job (multi-processing)

- example script for a multi-threaded, single-process program:

```
#!/bin/bash
#
#SBATCH --job-name=test_mpi
#SBATCH --output=test_mpi.log.%j.%t
#
#SBATCH --partition=discnet
#SBATCH --ntasks=4
#SBATCH --time=1:00

module purge
module load intel/2022a
module load OpenMPI/4.1.4-GCC-11.3.0

echo $SLURM_JOB_NODELIST
echo "#:$SLURM_NTASKS *:$SLURM_NTASKS"

echo "=="
mpirun ./test_mpi
echo "==" srun
srun --mpi=pmi2 ./test_mpi
```

- both methods work without explicitly passing on the number of tasks (MPI "talks" to slurm)



slurm: Job Submission / Batch job (multi-processing)

- example script for a multi-threaded, single-process program:

```
#!/bin/bash
#
#SBATCH --job-name=test_mpi
#SBATCH --output=test_mpi.log.%j.%t
#
#SBATCH --partition=discnet
#SBATCH --ntasks=4
#SBATCH --time=1:00

module purge
module load intel/2022a
module load OpenMPI/4.1.4-GCC-11.3.0

echo $SLURM_JOB_NODELIST
echo "[:$SLURM_NTASKS *: $SLURM_NTASKS"

echo ""
mpirun ./test_mpi
echo ""
srun --mpi=pmi2 ./test_mpi
```

- both methods work without explicitly passing on the number of tasks (MPI "talks" to slurm)
- it is preferable to use srun rather than mpirun for bootstrapping (but skip the --mpi=pmi2 for Intel MPI as it is not supported)



slurm: Job Submission / Batch job (Arrays)

- To submit a lot of similar tasks efficiently, you can use job arrays:

```
# Submit a job array with index values between 0 and 31
$ sbatch --array=0-31 <batch file>
```

```
# Submit a job array with index values of 1, 3, 5 and 7
$ sbatch --array=1,3,5,7 <batch file>
```

```
# Submit a job array with index values between 1 and 7
# with a step size of 2 (i.e. 1, 3, 5 and 7)
$ sbatch --array=1-7:2 <batch file>
```

```
# Submit a job array with index values between 1 and 7
# but limit the number of simultaneously running tasks to 4
$ sbatch --array=1-7%4 <batch file>
```



slurm: Job Submission / Batch job (Arrays)

- To submit a lot of similar tasks efficiently, you can use job arrays:

```
# Submit a job array with index values between 0 and 31
$ sbatch --array=0-31 <batch file>
```

```
# Submit a job array with index values of 1, 3, 5 and 7
$ sbatch --array=1,3,5,7 <batch file>
```

```
# Submit a job array with index values between 1 and 7
# with a step size of 2 (i.e. 1, 3, 5 and 7)
$ sbatch --array=1-7:2 <batch file>
```

```
# Submit a job array with index values between 1 and 7
# but limit the number of simultaneously running tasks to 4
$ sbatch --array=1-7%4 <batch file>
```

- you can then use e.g. the env variable `SLURM_ARRAY_JOB_ID` to assign the right data to each of the jobs inside the array's batch script or your program



slurm: Job Submission / Batch job (Arrays)

- To submit a lot of similar tasks efficiently, you can use job arrays:

```
# Submit a job array with index values between 0 and 31
$ sbatch --array=0-31 <batch file>
```

```
# Submit a job array with index values of 1, 3, 5 and 7
$ sbatch --array=1,3,5,7 <batch file>
```

```
# Submit a job array with index values between 1 and 7
# with a step size of 2 (i.e. 1, 3, 5 and 7)
$ sbatch --array=1-7:2 <batch file>
```

```
# Submit a job array with index values between 1 and 7
# but limit the number of simultaneously running tasks to 4
$ sbatch --array=1-7%4 <batch file>
```

- you can then use e.g. the env variable `SLURM_ARRAY_JOB_ID` to assign the right data to each of the jobs inside the array's batch script or your program
- it also helps to keep the scheduler/queues not being overwhelmed by 100s of single submissions/job requests



slurm: Job Submission / Batch job (Dependencies)

- Sometimes, jobs may require other jobs to run, their results or are only required to run if another job fails



slurm: Job Submission / Batch job (Dependencies)

- Sometimes, jobs may require other jobs to run, their results or are only required to run if another job fails
- slurm allows to define dependencies for those cases

```
# Wait for specific job to be started  
sbatch --depend=after:123 my.job
```

```
# Wait for jobs to complete  
sbatch --depend=afterany:123:126 my.job
```

```
# Wait for jobs to complete successfully  
sbatch --depend=afterok:123 my.job
```

```
# Wait for job / entire job array to complete and at least one task fails  
sbatch --depend=afternotok:123 my.job
```



slurm: Job Submission / Batch job (Dependencies)

- Sometimes, jobs may require other jobs to run, their results or are only required to run if another job fails
- slurm allows to define dependencies for those cases

```
# Wait for specific job to be started  
sbatch --depend=after:123 my.job
```

```
# Wait for jobs to complete  
sbatch --depend=afterany:123:126 my.job
```

```
# Wait for jobs to complete successfully  
sbatch --depend=afterok:123 my.job
```

```
# Wait for job / entire job array to complete and at least one task fails  
sbatch --depend=afternotok:123 my.job
```

- You can create complex dependencies by combining conditions e.g.

```
# Wait for specific jobs to be started and another to fail  
sbatch --depend=after:123:126,afternotok:125 my.job
```



slurm: Additional arguments

There are many additional arguments that can be passed to the resource manager:

- Scheduling/resource allocation:

`--nodes=<N>` / `--nodes=<N-M>` Request that a minimum of N (and a maximum of M) nodes be allocated to this job

`--tasks-per-node=<N>` Requests that (a maximum of) N tasks be invoked on each node

`--mem=<size>` / `--mem-per-cpu=<size>` Specify the real memory required per node / allocated core

`--exclusive` Requests, that nodes must not be shared with other running jobs



slurm: Additional arguments

There are many additional arguments that can be passed to the resource manager:

- Scheduling/resource allocation:

`--nodes=<N>` / `--nodes=<N-M>` Request that a minimum of N (and a maximum of M) nodes be allocated to this job

`--tasks-per-node=<N>` Requests that (a maximum of) N tasks be invoked on each node

`--mem=<size>` / `--mem-per-cpu=<size>` Specify the real memory required per node / allocated core

`--exclusive` Requests, that nodes must not be shared with other running jobs

- Logging:

`--error=<filename>` Instruct Slurm to connect stderr directly to the file specified (by default same as `--output`)

`--mail-type=<type>` Requests notifications by email to user (email address stored in system)



slurm: Resources/Accounting (sinfo)

- The command `sinfo` lists the nodes and their states belonging to the various partitions (aka queues) of the computational resources.

```
[jschevts@login1 ~]$ sinfo
PARTITION AVAIL  TIMELIMIT  NODES  STATE MODELIST
sciama4.q up      infinite    1     mix node304
sciama4.q up      infinite    8     alloc node[300-303,308-311]
sciama4.q up      infinite    3     idle node[305-307]
sciama4-12.q up      infinite    1     drain node312
sciama4-12.q up      infinite    1     mix node315
sciama4-12.q up      infinite    2     alloc node[313-314]
sciama4-12.q up      infinite   12     idle node[316-327]
sciama2.q* up      infinite    1     drain* node125
sciama2.q* up      infinite    2     down* node[100,194]
sciama2.q* up      infinite    1     drain node137
sciama2.q* up      infinite   17     mix node[101-105,127-129,158,162,169,172,178-180,190-191]
sciama2.q* up      infinite   73     alloc node[106-124,126,130-136,138-157,159-161,163-168,170-171,173-177,181-189,192]
sciama2.q* up      infinite    1     idle node193
sciama3.q up      infinite    1     drain node200
sciama3.q up      infinite   16     mix node[201-212,225-228]
sciama3.q up      infinite   16     alloc node[213-224,229-232]
sciama3.q up      infinite   15     idle node[233-247]
himem.q up      infinite    1     idle vmem01
rsm1.q up      infinite    2     mix node[190-191]
rsm1.q up      infinite    5     alloc node[186-189,192]
rsm1.q up      infinite    1     idle node193
```



slurm: Resources/Accounting (sinfo)

- The command `sinfo` lists the nodes and their states belonging to the various partitions (aka queues) of the computational resources.

```
[jschewts@login1:~]$ sinfo
PARTITION AVAIL  TIMELIMIT  NODES  STATE NODELIST
sciama4.q up        infinite    1     mix  node304
sciama4.q up        infinite    8     alloc node[300-303,308-311]
sciama4.q up        infinite    3     idle  node[305-307]
sciama4-12.q up       infinite    1     drain node312
sciama4-12.q up       infinite    1     mix  node315
sciama4-12.q up       infinite    2     alloc node[313-314]
sciama4-12.q up       infinite   12     idle  node[316-327]
sciama2.q* up        infinite    1     drain* node125
sciama2.q* up        infinite    2     down* node[100,194]
sciama2.q* up        infinite    1     drain node137
sciama2.q* up        infinite   17     mix  node[101-105,127-129,158,162,169,172,178-180,190-191]
sciama2.q* up        infinite   73     alloc node[106-124,126,130-136,138-157,159-161,163-168,170-171,173-177,181-189,192]
sciama2.q* up        infinite    1     idle  node193
sciama3.q up        infinite    1     drain node200
sciama3.q up        infinite   16     mix  node[201-212,225-228]
sciama3.q up        infinite   16     alloc node[213-224,229-232]
sciama3.q up        infinite   15     idle  node[233-247]
himem.q up        infinite    1     idle  vmem01
rsm1.q up        infinite    2     mix  node[190-191]
rsm1.q up        infinite    5     alloc node[186-189,192]
rsm1.q up        infinite    1     idle  node193
```

- There are various states, nodes can be in: e.g. `alloc/mixed/idle`, `drng/drain/down`; For the latter, reasons are provided

```
[jschewts@login1:~]$ sinfo -R
REASON      USER      TIMESTAMP      NODELIST
Investigation jschewts  2019-10-01T20:39:31 node312
Infiniband fault root      2019-07-30T14:56:26 node125
Not responding nobody    2019-08-23T19:36:50 node100
Not responding nobody    2019-10-11T14:44:56 node194
batch job complete f nobody    2019-08-28T07:20:28 node137
investigation lustre jschewts  2019-10-19T12:44:19 node200
```



slurm: Resources/Accounting (sacct)

- There is a record of each job a user submits/runs

```
[jjschewts@login1:~]$ sacct --format=User,JobID,Jobname,partition,state,time,start,end,elapsed,MaxRss,MaxVmsize,nnodes,ncpus,nodelist -u [redacted]
```

User	JobID	JobName	Partition	State	TimeLimit	Start	End	Elapsed	MaxRSS	MaxVMSize	NNodes	NCPU	NodeList
[redacted]	1135959	starccm	sciana4.q	RUNNING	2-00:00:00	2019-10-23T15:17:11	Unknown	1-02:14:01			1	8	node300
[redacted]	1135959.0	bash		RUNNING		2019-10-23T15:17:40	Unknown	1-02:13:32			1	8	node300
[redacted]	1153763	starccm	sciana4.q	CANCELLED+	2-00:00:00	2019-10-23T14:44:31	2019-10-23T14:47:47	00:03:16			1	8	node300
[redacted]	1153763.bat+	batch		CANCELLED		2019-10-23T14:44:31	2019-10-23T14:47:48	00:03:17	7492K	414804K	1	8	node300
[redacted]	1153763.0	bash		CANCELLED		2019-10-23T14:44:54	2019-10-23T14:47:47	00:02:53	375156K	3085040K	1	8	node300
[redacted]	1153770	starccm	sciana4.q	CANCELLED+	2-00:00:00	2019-10-23T14:47:31	2019-10-23T14:49:59	00:02:28			1	8	node300
[redacted]	1153770.bat+	batch		CANCELLED		2019-10-23T14:47:31	2019-10-23T14:50:00	00:02:29	7496K	414804K	1	8	node300
[redacted]	1153770.0	bash		CANCELLED		2019-10-23T14:47:52	2019-10-23T14:50:00	00:02:08	356672K	3075008K	1	8	node300
[redacted]	1153778	starccm	sciana4.q	COMPLETED	2-00:00:00	2019-10-23T14:50:02	2019-10-23T14:50:24	00:00:22			1	8	node300
[redacted]	1153778.bat+	batch		COMPLETED		2019-10-23T14:50:02	2019-10-23T14:50:24	00:00:22	1360K	157252K	1	8	node300
[redacted]	1153778.0	bash		COMPLETED		2019-10-23T14:50:22	2019-10-23T14:50:24	00:00:02	1152K	225628K	1	8	node300
[redacted]	1153805	starccm	sciana4.q	COMPLETED	2-00:00:00	2019-10-23T14:53:02	2019-10-23T14:53:24	00:00:22			1	8	node300
[redacted]	1153805.bat+	batch		COMPLETED		2019-10-23T14:53:02	2019-10-23T14:53:24	00:00:22	1360K	157252K	1	8	node300
[redacted]	1153805.0	bash		COMPLETED		2019-10-23T14:53:22	2019-10-23T14:53:24	00:00:02	1148K	225628K	1	8	node300
[redacted]	1153825	starccm	sciana4.q	COMPLETED	2-00:00:00	2019-10-23T15:00:04	2019-10-23T15:00:30	00:00:26			1	8	node300



slurm: Resources/Accounting (sacct)

- There is a record of each job a user submits/runs

```
jjschewts@login1:~$ sacct --format=User,JobID,JobName,partition,state,time,start,end,elapsed,MaxRss,MaxVmsize,nnodes,ncpus,nodelist -u [redacted]
```

User	JobID	JobName	Partition	State	TimeLimit	Start	End	Elapsed	MaxRSS	MaxVMSize	NNodes	NCPU	NodeList
[redacted]	1135959	starccm	sciana4.q	RUNNING	2-00:00:00	2019-10-23T15:17:11	Unknown	1-02:14:01			1	8	node300
[redacted]	1135959.0	bash		RUNNING		2019-10-23T15:17:40	Unknown	1-02:13:32			1	8	node300
[redacted]	1153763	starccm	sciana4.q	CANCELLED+	2-00:00:00	2019-10-23T14:44:31	2019-10-23T14:47:47	00:03:16			1	8	node308
[redacted]	1153763.bat+	batch		CANCELLED		2019-10-23T14:44:31	2019-10-23T14:47:48	00:03:17	7492K	414804K	1	8	node308
[redacted]	1153763.0	bash		CANCELLED		2019-10-23T14:44:54	2019-10-23T14:47:47	00:02:53	375156K	3085040K	1	8	node308
[redacted]	1153770	starccm	sciana4.q	CANCELLED+	2-00:00:00	2019-10-23T14:47:31	2019-10-23T14:49:59	00:02:28			1	8	node308
[redacted]	1153770.bat+	batch		CANCELLED		2019-10-23T14:47:31	2019-10-23T14:50:00	00:02:29	7496K	414804K	1	8	node308
[redacted]	1153770.0	bash		CANCELLED		2019-10-23T14:47:52	2019-10-23T14:50:00	00:02:08	356672K	3075008K	1	8	node308
[redacted]	1153778	starccm	sciana4.q	COMPLETED	2-00:00:00	2019-10-23T14:50:02	2019-10-23T14:50:24	00:00:22			1	8	node308
[redacted]	1153778.bat+	batch		COMPLETED		2019-10-23T14:50:02	2019-10-23T14:50:24	00:00:22	1360K	157252K	1	8	node308
[redacted]	1153778.0	bash		COMPLETED		2019-10-23T14:50:22	2019-10-23T14:50:24	00:00:02	1152K	225628K	1	8	node308
[redacted]	1153805	starccm	sciana4.q	COMPLETED	2-00:00:00	2019-10-23T14:53:02	2019-10-23T14:53:24	00:00:22			1	8	node308
[redacted]	1153805.bat+	batch		COMPLETED		2019-10-23T14:53:02	2019-10-23T14:53:24	00:00:22	1360K	157252K	1	8	node308
[redacted]	1153805.0	bash		COMPLETED		2019-10-23T14:53:22	2019-10-23T14:53:24	00:00:02	1148K	225628K	1	8	node308
[redacted]	1153825	starccm	sciana4.q	COMPLETED	2-00:00:00	2019-10-23T15:00:04	2019-10-23T15:00:30	00:00:26			1	8	node309

- on public HPC framework, this accounting is used to keep track/limit resource usage for charging users/project



slurm: Resources/Accounting (sacct)

- There is a record of each job a user submits/runs

```
jjschewts@login1:~$ sacct --format=User,JobID,JobName,Partition,State,TimeLimit,Start,End,Elapsed,MaxRss,MaxVmsize,nnodes,ncpus,nodelist -u [redacted]
```

User	JobID	JobName	Partition	State	TimeLimit	Start	End	Elapsed	MaxRss	MaxVmsize	NNodes	NCPUS	NodeList
[redacted]	1135959	starccm	sciana4.q	RUNNING	2-00:00:00	2019-10-23T15:17:11	Unknown	1-02:14:01			1	8	node300
[redacted]	1135959.0	bash		RUNNING		2019-10-23T15:17:40	Unknown	1-02:13:32			1	8	node300
[redacted]	1153763	starccm	sciana4.q	CANCELLED+	2-00:00:00	2019-10-23T14:44:31	2019-10-23T14:47:47	00:03:16			1	8	node308
[redacted]	1153763.bat+	batch		CANCELLED		2019-10-23T14:44:31	2019-10-23T14:47:48	00:03:17	7492K	414804K	1	8	node308
[redacted]	1153763.0	bash		CANCELLED		2019-10-23T14:44:54	2019-10-23T14:47:47	00:02:53	375156K	3085040K	1	8	node308
[redacted]	1153770	starccm	sciana4.q	CANCELLED+	2-00:00:00	2019-10-23T14:47:31	2019-10-23T14:49:59	00:02:28			1	8	node308
[redacted]	1153770.bat+	batch		CANCELLED		2019-10-23T14:47:31	2019-10-23T14:50:00	00:02:29	7496K	414804K	1	8	node308
[redacted]	1153770.0	bash		CANCELLED		2019-10-23T14:47:52	2019-10-23T14:50:00	00:02:08	356672K	3075008K	1	8	node308
[redacted]	1153778	starccm	sciana4.q	COMPLETED	2-00:00:00	2019-10-23T14:50:02	2019-10-23T14:50:24	00:00:22			1	8	node308
[redacted]	1153778.bat+	batch		COMPLETED		2019-10-23T14:50:02	2019-10-23T14:50:24	00:00:22	1360K	157252K	1	8	node308
[redacted]	1153778.0	bash		COMPLETED		2019-10-23T14:50:22	2019-10-23T14:50:24	00:00:02	1152K	225628K	1	8	node308
[redacted]	1153805	starccm	sciana4.q	COMPLETED	2-00:00:00	2019-10-23T14:53:02	2019-10-23T14:53:24	00:00:22			1	8	node308
[redacted]	1153805.bat+	batch		COMPLETED		2019-10-23T14:53:02	2019-10-23T14:53:24	00:00:22	1360K	157252K	1	8	node308
[redacted]	1153805.0	bash		COMPLETED		2019-10-23T14:53:22	2019-10-23T14:53:24	00:00:02	1148K	225628K	1	8	node308
[redacted]	1153825	starccm	sciana4.q	COMPLETED	2-00:00:00	2019-10-23T15:00:04	2019-10-23T15:00:30	00:00:26			1	8	node309

- on public HPC framework, this accounting is used to keep track/limit resource usage for charging users/project
- on Artemis, it can be used for debugging or obtaining useful statistics to optimize your resource requests (e.g. MaxRSS size tells you about your actual memory requirements)



Resource Management / Scheduling: Controlling

- Once you submitted a job, you can keep track of its process using the command `squeue` (e.g. use `squeue -u <username>` to list all of the active (i.e. queued or running) jobs of a specific user



Resource Management / Scheduling: Controlling

- Once you submitted a job, you can keep track of its process using the command `squeue` (e.g. use `squeue -u <username>` to list all of the active (i.e. queued or running) jobs of a specific user
- You can also cancel steps within jobs (or if there is only one step), using `scancel <jobid>`.



Resource Management / Scheduling: Controlling

- Once you submitted a job, you can keep track of its process using the command `squeue` (e.g. use `squeue -u <username>` to list all of the active (i.e. queued or running) jobs of a specific user)
- You can also cancel steps within jobs (or if there is only one step), using `scancel <jobid>`.
- Furthermore, `scontrol` allows you to make changes to your submitted jobs (e.g. holding them in the queue)



slurm: Man Pages / Cheat Sheet


- For more details on all the presented commands, please check their man pages (e.g. `man sbatch`)



slurm: Man Pages / Cheat Sheet

- For more details on all the presented commands, please check their man pages (e.g. `man sbatch`)
- There is a also handy slurm cheat sheet which you can download from e.g.

<https://slurm.schedmd.com/pdfs/summary.pdf>

			
Job Submission submit - Offer a job allocation. cancel - Submit a batch script for later execution. rmjob - Cancel a job allocation (as needed) and execute an application.			
<code>--array=idrange</code> (e.g. <code>--array=1-100</code>)	Job array specification (which contains only 1)	<code>--cancel=taskname</code>	Cancel a task charged for resources later.
<code>--account=name</code>	Initiate job after specified time. (e.g. <code>--after=10:00:00</code>)	<code>--partition=name</code>	Partition/queue to which to send a job.
<code>--chgrp=group</code>	Chown() to run the job (which contains only 1)	<code>--qos=name</code>	Quality Of Service
<code>--constraint=constraint</code>	Required node features	<code>--signal=[ID name (file)]</code>	Signal job when approaching time limit.
<code>--cpus-per-task=count</code>	Number of CPUs required per task.	<code>--time=constraint_string</code>	Wait clock time limit.
<code>--dependency=constraintjobid</code>	Dependency on other specified jobs which specified jobs must complete first.	<code>--wtime=constraint_string</code>	Wait specified constraint in a range "X" - "Y" shell (which contains only 1)
<code>--error=filename</code>	File in which to store job error messages.	Accounting	
<code>--exclude=name</code>	Specific host names to exclude from job allocation.	<code>--show=</code>	Display accounting data.
<code>--exclusive=name</code>	Affected nodes can not be shared with other jobs.	<code>--showers</code>	Displays all users jobs.
<code>--export=constraintvariable</code>	Export identified environment variables.	<code>--account=name</code>	Displays jobs with specified account.
<code>--gres=resource</code>	Generic resources required per task.	<code>--endtime=time</code>	End of reporting period.
<code>--hold=constraint</code>	Jobs from which to wait input data.	<code>--name=jobname</code>	Displays jobs that have any of those names.
<code>--job=taskname</code>	Job name.	<code>--partition=name</code>	Common requested list of partitions to select jobs and job steps from.
<code>--label</code>	Prepared task ID to use (which contains only 1)	<code>--state=state_list</code>	Displays jobs with specified states.
<code>--license=licensecommand</code>	License resources required for various jobs.	<code>--starttime=time</code>	Start of reporting period.
		CherryMD Data Support and Transformation	
		View and modify account information.	
		Options:	
		<code>--immediate</code>	Commit changes immediately.
		<code>--portable</code>	Output delimited by ?
		Commands:	
		<code>add -[ENTRY] -[SPEC] -[SPEC]</code>	Add an entry. Identical to the create command.
		<code>delete -[ENTRY] where</code>	Delete the specified entries.
		<code>list -[ENTRY] -[SPEC] -[SPEC]</code>	Display information about the specific entry.
		<code>modify -[ENTRY] where</code>	Modify an entry.
		<code>specify -[ENTRY] -[SPEC] -[SPEC]</code>	Specify an entry.
		Entities:	
		<code>account</code>	Account associated with jobs.
		<code>cluster</code>	ClusterName parameter in the submit command.
		<code>qos</code>	Quality of Service.
		<code>user</code>	User name in system.
		Job Management	
		show - Transfer file to a job computer nodes.	
		About [filename] SOURCE DESTINATION	
		<code>file</code>	High-resolution costing file.
		<code>procure</code>	Preprocess modification data, account status, and job permissions.
		scanout - Signal jobs, job arrays, or job steps.	
		<code>--account=name</code>	Operate only on jobs charging the specified account.
		<code>--name=name</code>	Operate only on jobs with specified name.
		<code>--partition=name</code>	Operate only on jobs in the specified partition/queue.
		<code>--qos=name</code>	Operate only on jobs using the specified quality of service.

SOFTWARE

Environments & Applications

SYSTEM SOFTWARE

Resource & Job Management

Runtime System Interprocess Comm

Operating System

VIRTUALISATION

Cloud computing / OpenStack

HARDWARE

Network Interconnects

Memory & Data Storage

Processors & Accelerators



Environments & Applications



System Environment & Multi-user systems

- Single-user computer usually have a single system environment (i.e. each program and library exists in a single version/configuration)



System Environment & Multi-user systems

- Single-user computer usually have a single system environment (i.e. each program and library exists in a single version/configuration)
- Multi-user systems require a more complex setup: Users may require either different conflicting libraries or different versions of the same program/library



System Environment & Multi-user systems

- Single-user computer usually have a single system environment (i.e. each program and library exists in a single version/configuration)
- Multi-user systems require a more complex setup: Users may require either different conflicting libraries or different versions of the same program/library
- Often, even the same user faces this problem to need different setups for different software



System Environment & Multi-user systems

- Single-user computer usually have a single system environment (i.e. each program and library exists in a single version/configuration)
- Multi-user systems require a more complex setup: Users may require either different conflicting libraries or different versions of the same program/library
- Often, even the same user faces this problem to need different setups for different software
- Thus, it requires a way to adapt a system environment for each user/purpose: Environment variables / modules



Environment variables: General

- Environment variables are used in Unix-like shells to store configuration settings (for the shell and programs to be used at runtime)



Environment variables: General

- Environment variables are used in Unix-like shells to store configuration settings (for the shell and programs to be used at runtime)
- In `bash`, these are set by a statement

```
export <VARNAME>=<VALUE>
```



Environment variables: General

- Environment variables are used in Unix-like shells to store configuration settings (for the shell and programs to be used at runtime)
- In `bash`, these are set by a statement

```
export <VARNAME>=<VALUE>
```

- Environmental variables are only visible within the same shell, they were defined in (`.bashrc` offers a way to set 'default' variables).



Environment variables: General

- Environment variables are used in Unix-like shells to store configuration settings (for the shell and programs to be used at runtime)
- In `bash`, these are set by a statement

```
export <VARNAME>=<VALUE>
```

- Environmental variables are only visible within the same shell, they were defined in (`.bashrc` offers a way to set 'default' variables).
- The `export` statement is optional, but necessary, if this environmental variable should be also visible within processes spawned by that shell (e.g. programs) (if in doubt, use it)



Environment variables: General

- Environment variables are used in Unix-like shells to store configuration settings (for the shell and programs to be used at runtime)
- In `bash`, these are set by a statement

```
export <VARNAME>=<VALUE>
```

- Environmental variables are only visible within the same shell, they were defined in (`.bashrc` offers a way to set 'default' variables).
- The `export` statement is optional, but necessary, if this environmental variable should be also visible within processes spawned by that shell (e.g. programs) (if in doubt, use it)
- `${VARNAME}` returns the value of the variable (i.e. `echo ${VARNAME}` would then print its value)



Environment variables: General

- Environment variables are used in Unix-like shells to store configuration settings (for the shell and programs to be used at runtime)
- In `bash`, these are set by a statement

```
export <VARNAME>=<VALUE>
```
- Environmental variables are only visible within the same shell, they were defined in (`.bashrc` offers a way to set 'default' variables).
- The `export` statement is optional, but necessary, if this environmental variable should be also visible within processes spawned by that shell (e.g. programs) (if in doubt, use it)
- `${<VARNAME>}` returns the value of the variable (i.e. `echo ${<VARNAME>}` would then print its value)
- `env` prints all environmental variables



Environment variables: PATH

- One of the most important variables for the shell itself is PATH



Environment variables: PATH

- One of the most important variables for the shell itself is PATH
- It contains a colon-separated list of folders that are searched by the shell for commands/programs to be executed



Environment variables: PATH

- One of the most important variables for the shell itself is PATH
- It contains a colon-separated list of folders that are searched by the shell for commands/programs to be executed
- If you install a new program in a folder that is not already listed, but want it available in the shell as command (without providing the path to it), you have to prepend the folder containing the program binary/script to the path



Environment variables: PATH

- One of the most important variables for the shell itself is PATH
- It contains a colon-separated list of folders that are searched by the shell for commands/programs to be executed
- If you install a new program in a folder that is not already listed, but want it available in the shell as command (without providing the path to it), you have to prepend the folder containing the program binary/script to the path
- the first occurrence found in PATH is used

```
export PATH=<INSTALL PATH>/bin:$PATH
```



Environment variables: LDFLAGS,CFLAGS,FFLAGS,etc.

- For compilers, there are a set of variables containing compiler arguments to point to headers, libraries, etc.



Environment variables: LDFLAGS,CFLAGS,FFLAGS,etc.

- For compilers, there are a set of variables containing compiler arguments to point to headers, libraries, etc.
- Similar to PATH, if you want to make custom-installed libraries available to the compiler, the resp. `include`, `lib`, etc. folders have to be added to the variables e.g.

```
export CFLAGS="-I<INSTALL PATH>/include $CFLAGS"
```

or

```
export LDFLAGS="-L<LIB PATH> -Wl,-rpath=<LIB PATH> $LDFLAGS"
```



Modules: General

- So-called (environmental) modules in Linux/Unix are (mostly) a convenient way to customize these variables (and thus the system environment) automatically



Modules: General

- So-called (environmental) modules in Linux/Unix are (mostly) a convenient way to customize these variables (and thus the system environment) automatically
- Loading the module for a specific program or library will amend the variables as described above, while unloading it, removes these alterations again



Modules: General

- So-called (environmental) modules in Linux/Unix are (mostly) a convenient way to customize these variables (and thus the system environment) automatically
- Loading the module for a specific program or library will amend the variables as described above, while unloading it, removes these alterations again
- This allows to switch out e.g. different versions of the same library



Modules: General

- So-called (environmental) modules in Linux/Unix are (mostly) a convenient way to customize these variables (and thus the system environment) automatically
- Loading the module for a specific program or library will amend the variables as described above, while unloading it, removes these alterations again
- This allows to switch out e.g. different versions of the same library
- Additionally, some built-in commands and additional Tcl scripting allows to check for potential conflicts of libraries and missing dependencies



Modules: General

- So-called (environmental) modules in Linux/Unix are (mostly) a convenient way to customize these variables (and thus the system environment) automatically
- Loading the module for a specific program or library will amend the variables as described above, while unloading it, removes these alterations again
- This allows to switch out e.g. different versions of the same library
- Additionally, some built-in commands and additional Tcl scripting allows to check for potential conflicts of libraries and missing dependencies
- MODULESPATH is a list of folders checked for modules (similar to PATH for commands). You can append it to add custom modules



Modules: Usage

- There are a few important commands:

`module av` lists available modules

`module load <modulename>` loads a module

`module unload <modulename>` unloads a module

`module list` lists all currently loaded modules

`module spider <string>` lists all modules matching search string

`module purge` unloads all loaded modules

`module help <modulename>` shows a help page for the module

`module show <modulename>` lists content of module



Modules: Usage

- There are a few important commands:

`module av` lists available modules

`module load <modulename>` loads a module

`module unload <modulename>` unloads a module

`module list` lists all currently loaded modules

`module spider <string>` lists all modules matching search string

`module purge` unloads all loaded modules

`module help <modulename>` shows a help page for the module

`module show <modulename>` lists content of module

- if you want to have certain modules loaded by default, simply modify the `.bashrc` and/or `.bash_profile` in your home directory accordingly



Modules: Artemis

- Artemis uses LMod (i.e. Lua-based reimplementaion of original TCL/L-based module system)

```
[js2347@artemis-login-0 ~]$ module av
----- /opt/ohpc/pub/modulefiles -----
gnu12/12.2.0      hwloc/2.11.1 (D)  libfabric/1.18.0  as      papi/6.0.0      pmix/4.2.9      prun/2.2      ucx/1.17.0
----- /mnt/shared/easybuild/modules/all -----
ANSYS/2023r1      OpenMPI/4.0.6-GCC-10.3.0      groff/1.22.4-GCCcore-11.2.0
ATK/2.36.0-GCCcore-11.2.0      OpenMPI/4.0.7-GCC-10.3.0      groff/1.22.4-GCCcore-11.3.0
ATK/2.38.0-GCCcore-11.3.0      OpenMPI/4.1.1-GCC-10.3.0      groff/1.22.4-GCCcore-12.2.0
ATK/2.38.0-GCCcore-12.2.0      OpenMPI/4.1.1-GCC-11.2.0      groff/1.22.4-GCCcore-12.3.0
ATK/2.38.0-GCCcore-12.3.0      OpenMPI/4.1.4-GCC-11.3.0      groff/1.23.0-GCCcore-12.3.0
ATK/2.38.0-GCCcore-13.2.0      OpenMPI/4.1.4-GCC-12.2.0      grpcio/1.57.0-GCCcore-12.3.0 (D)
Abseil/20230125.2-GCCcore-12.2.0      OpenMPI/4.1.5-GCC-12.3.0      gzl/1.10-GCCcore-10.2.0
Abseil/20230125.3-GCCcore-12.3.0      OpenMPI/4.1.6-GCC-13.2.0      gzl/1.10-GCCcore-10.3.0
Anaconda3/2022.10      OpenMPI/5.0.3-GCC-13.3.0      gzl/1.10-GCCcore-11.2.0
Arnadillo/11.4.3-foss-2022b      OpenMPI/5.0.3-GCC-13.3.0      gzl/1.12-GCCcore-11.3.0
Arnadillo/12.6.2-foss-2023a      OpenMPI/5.0.3-GCC-13.3.0      gzl/1.12-GCCcore-12.2.0
Arnadillo/12.8.0-foss-2023b      OpenMPI/5.0.3-GCC-13.3.0      gzl/1.12-GCCcore-12.3.0
Autoconf/2.69-GCCcore-9.3.0      OpenMPI/5.0.3-GCC-13.3.0      gzl/1.13-GCCcore-13.2.0
Autoconf/2.69-GCCcore-10.2.0      OpenMPI/5.0.3-GCC-13.3.0      gzl/1.13-GCCcore-13.3.0 (D)
Autoconf/2.71-GCCcore-10.3.0      OpenMPI/5.0.3-GCC-13.3.0      h5py/3.2.1-foss-2021a
Autoconf/2.71-GCCcore-11.2.0      OpenMPI/5.0.3-GCC-13.3.0      h5py/3.9.0-foss-2023a (D)
Autoconf/2.71-GCCcore-11.3.0      OpenMPI/5.0.3-GCC-13.3.0      hatchling/1.18.0-GCCcore-12.3.0
Autoconf/2.71-GCCcore-12.2.0      OpenMPI/5.0.3-GCC-13.3.0      hatchling/1.18.0-GCCcore-12.3.0 (D)
Autoconf/2.71-GCCcore-12.3.0      OpenMPI/5.0.3-GCC-13.3.0      help2man/1.47.12-GCCcore-9.3.0
Autoconf/2.71-GCCcore-13.2.0      OpenMPI/5.0.3-GCC-13.3.0      help2man/1.47.16-GCCcore-10.2.0
Autoconf/2.71      OpenMPI/5.0.3-GCC-13.3.0      help2man/1.48.3-GCCcore-10.3.0
Autoconf/2.72-GCCcore-13.3.0      OpenMPI/5.0.3-GCC-13.3.0      help2man/1.48.3-GCCcore-11.2.0
Automake/1.16.1-GCCcore-9.3.0      OpenMPI/5.0.3-GCC-13.3.0      help2man/1.49.2-GCCcore-11.3.0
Automake/1.16.2-GCCcore-10.2.0      OpenMPI/5.0.3-GCC-13.3.0      help2man/1.49.2-GCCcore-12.2.0
Automake/1.16.3-GCCcore-10.3.0      OpenMPI/5.0.3-GCC-13.3.0      help2man/1.49.3-GCCcore-12.3.0 (D)
```

- Modules resolve dependencies automatically, **BUT** loading a new module with conflicts (e.g. dependency with different version) replaces already loaded(!)

```
[js2347@artemis-login-0 ~]$ module load intel
[js2347@artemis-login-0 ~]$ module load GCC

The following have been reloaded with a version change:
1) GCCcore/11.3.0 => GCCcore/13.3.0      2) binutils/2.38-GCCcore-11.3.0 => binutils/2.42-GCCcore-13.3.0      3) zlib/1.2.12-GCCcore-11.3.0 => zlib/1.3.1-GCCcore-13.3.0
```



Containers: Singularity/Apptainer

- Containers are self-contained, standard units of software
- contain code and all its dependencies, allowing applications to run consistently and reliably across different computing environments



Containers: Singularity/Apptainer

- Containers are self-contained, standard units of software
- contain code and all its dependencies, allowing applications to run consistently and reliably across different computing environments
- images can be easily built/customized via scripts from base images
- visualisation “light” e.g. unlike VMs restricted to host’s architecture



Containers: Singularity/Apptainer

- Containers are self-contained, standard units of software
- contain code and all its dependencies, allowing applications to run consistently and reliably across different computing environments
- images can be easily built/customized via scripts from base images
- visualisation “light” e.g. unlike VMs restricted to host’s architecture
- popular software:

Docker (requires root privileges)

Singularity/Apptainer (supported on Artemis)



Etiquette



Etiquette: Being a good user

When using an HPC system (e.g. Artemis) make sure to follow these simple rules:

- Know the basics from this course



Etiquette: Being a good user

When using an HPC system (e.g. Artemis) make sure to follow these simple rules:

- Know the basics from this course
- pay attention to the “house rules” & guidelines of the visiting system



Etiquette: Being a good user

When using an HPC system (e.g. Artemis) make sure to follow these simple rules:

- Know the basics from this course
- pay attention to the “house rules” & guidelines of the visiting system
- Do not clog up the login nodes



Etiquette: Being a good user

When using an HPC system (e.g. Artemis) make sure to follow these simple rules:

- Know the basics from this course
- pay attention to the “house rules” & guidelines of the visiting system
- Do not clog up the login nodes
- When submitting jobs, try to request only the resources you really need:



Etiquette: Being a good user

When using an HPC system (e.g. Artemis) make sure to follow these simple rules:

- Know the basics from this course
- pay attention to the “house rules” & guidelines of the visiting system
- Do not clog up the login nodes
- When submitting jobs, try to request only the resources you really need:
 - ▶ give good estimate of walltime (for efficient scheduling)



Etiquette: Being a good user

When using an HPC system (e.g. Artemis) make sure to follow these simple rules:

- Know the basics from this course
- pay attention to the “house rules” & guidelines of the visiting system
- Do not clog up the login nodes
- When submitting jobs, try to request only the resources you really need:
 - ▶ give good estimate of walltime (for efficient scheduling)
 - ▶ try not to waste resources i.e. especially at busy times, only request the cores you really need, free up licenses again



Etiquette: Being a good user

When using an HPC system (e.g. Artemis) make sure to follow these simple rules:

- Know the basics from this course
- pay attention to the “house rules” & guidelines of the visiting system
- Do not clog up the login nodes
- When submitting jobs, try to request only the resources you really need:
 - ▶ give good estimate of walltime (for efficient scheduling)
 - ▶ try not to waste resources i.e. especially at busy times, only request the cores you really need, free up licenses again
- Again, do **NOT** clog up the login nodes



Recap: HPC as a service

