

## Assignment 2 - COSC 3320

Alex Bennett (ID: 1901408)

### Theory Problem 1

(a)

To check if an element in  $L_1$  is in  $L_2$  we must iterate over each element of  $L_1$  ( $n$  elements), and then compare each element of  $L_1$  with every element of  $L_2$ . Thus the lower bound is  $O(n^2)$ .

(b)

### Theory Problem 2

### Theory Problem 3

To determine the average number of scalar multiplications for a sequence of  $n$  matrices we will use the following informal algorithm:

$$S[i, i] = 0$$

$$S[i, i + 1] = p_i + p_{i+1} + p_{i+2}$$

$$S[i, j] = \text{avg}(S[i, k] + S[k + 1, j] + p_i + p_{k+1} + p_{k+1}), \text{ for } i \leq k \leq j - 1$$

Where  $S[i, j]$  is the matrix representing the average work for a parentheses configuration grouping every element from  $i$  to  $j$  and  $p_i$  represents the  $i$ th dimension of the original matrix sequence. The average work is equal to the sum of scalar multiplications for possible  $k$ -values divided by the total number of  $k$ -values.

Since this algorithm will be iterated over 3 nested for-loops the time complexity is  $O(n^3)$ . Since  $S$  is two dimensional our space complexity is  $O(n^2)$

# Programming Problem 1

## Procedure

In this program we use three two-dimensional arrays  $X$ ,  $Y$ , and  $Z$ , each of size  $n$ , with  $X$  and  $Y$  initialized to 1 for each entry. We then add corresponding entries of  $X$  and  $Y$  together via matrix addition to generate an entry in  $Z$ . We use two different algorithms to perform the addition, the first traversing the arrays in row-major order and the second traversing them in column-major order, and compare their timings. The program is written in C++ and run on a MacOS supporting VMM.

## Hypothesis

Given that both algorithms have the same number of operations, one might expect that the timings for the two algorithms will be similar. However, as we've studied in class, if a multidimensional array is stored in memory using row-major order then row-major traversal is significantly faster than column-major traversal. Given that C++ must store these arrays in either row-major or column-major order, my hypothesis is that there will be significant difference in timing between the two algorithms.

## C++ Implementation

```
1  #include <stdio.h>
2  #include <time.h>
3  #include <stdlib.h>
4
5  int main(int argc, char *argv[]) {
6
7      char *arg = argv[1];
8      int n = atoi(arg);
9
10     int** X = new int*[n];
11     int** Y = new int*[n];
12     int** Z = new int*[n];
13
14     //Initialize X, Y, Z
15     for (int i = 0; i < n; i++) {
16         X[i] = new int[n];
```

```

17         Y[i] = new int[n];
18         Z[i] = new int[n];
19     }
20
21     for (int i = 0; i < n; i++) {
22         for (int j = 0; j < n; j++) {
23             X[i][j] = 1;
24             Y[i][j] = 1;
25         }
26     }
27
28     //Version 1
29     clock_t begin1 = clock();
30     for (int i = 0; i < n; i++) {
31         for (int j = 0; j < n; j++) {
32             Z[i][j] = X[i][j] + Y[i][j];
33         }
34     }
35     clock_t end1 = clock();
36
37     //Version 2
38     clock_t begin2 = clock();
39     for (int j = 0; j < n; j++) {
40         for (int i = 0; i < n; i++) {
41             Z[i][j] = X[i][j] + Y[i][j];
42         }
43     }
44     clock_t end2 = clock();
45
46     int time1 = (double)(end1 - begin1)/(CLOCKS_PER_SEC/1000);
47     int time2 = (double)(end2 - begin2)/(CLOCKS_PER_SEC/1000);
48
49     printf("Version 1: %d milliseconds\n", time1);
50     printf("Version 2: %d milliseconds\n", time2);
51
52 }

```

## Results

Dimension of Array	Time of Vers. 1 (ms)	Time of Vers. 2 (ms)
128	0	0
256	0	0
512	0	3
1024	5	22
2048	20	108
4096	81	545
8192	325	2609
16384	1421	15618
32768	11147	109160
65536	46973	824990

## Explanation

My hypothesis was correct: there was a substantial difference in timing between Version 1 and Version 2. As explained in the hypothesis depending on how programming languages store arrays in memory, row-major and column-major traversals of an array can vary quite significantly in their timings. Since Version 1 (row-major) was much faster than Version 2 (column-major), we can conclude that C++ stores multidimensional arrays in row-major order. In fact this is true for most languages of the C family.

## Programming Problem 2

### Procedure

In this program we take an  $n$  by  $n$  matrix, initializing each entry to zero, then perform  $m$  simple operations (adding a random number between 0-100 to a random entry in the matrix) for  $m = 1677721600$  and  $m = 13421772800$ . The program is written in Java and run on a MacOS supporting VMM.

### Hypothesis

The algorithm is fairly simple, performing  $m$  computations on the same matrix. However since we will be dealing with fairly large matrices, I expect that for certain values of  $n$  the program will exceed physical memory and thus require the VMM to transfer data to disk storage. My hypothesis is that the timing of the program will jump up dramatically for particular  $n$ , and all larger  $n$  will take significantly more time.

## Java Implementation

```
1  import java.util.Random;
2
3  public class Prog2 {
4
5      public static void main (String[] args) {
6
7          int n = Integer.parseInt(args[0]);
8
9          int[] [] M = new int[n] [n];
10
11         for (int k = 0; k < n; k++) {
12             for (int q = 0; q < n; q++) {
13                 M[k] [q] = 0;
14             }
15         }
16
17         long start1 = System.currentTimeMillis();
18         long m_1 = 1677721600;
19         Random r = new Random();
20
21         for (long k = 0; k < m_1; k++) {
22             int x = r.nextInt(100) + 1;
23             int j = r.nextInt(n);
24             int i = r.nextInt(n);
25             M[i] [j] = M[i] [j] + x;
26         }
27
28         long end1 = System.currentTimeMillis();
29
30         long start2 = System.currentTimeMillis();
31         long m_2 = 13421772800L;
32
33         for (long k = 0; k < m_2; k++) {
34             int x = r.nextInt(100) + 1;
35             int j = r.nextInt(n);
36             int i = r.nextInt(n);
37             M[i] [j] = M[i] [j] + x;
38         }
```

```

39
40         long end2 = System.currentTimeMillis();
41
42         System.out.println("Time elapsed for n=" + n + " for m_1:
↪      " + (end1 - start1) + " milliseconds");
43         System.out.println("Time elapsed for n=" + n + " for m_2:
↪      " + (end2 - start2) + " milliseconds");
44
45     }
46 }
47

```

## Results

n	Time for m=1677721600 (ms)	Time for m=13421772800 (ms)
16	55336	430628
64	55951	424845
256	59988	445868
1024	121313	795774
4096	232810	1858610
16384	286520	2290697

## Explanation

## Programming Problem 3

## Procedure

## Hypothesis

## Java Implementation

```

1  import java.util.Random;
2
3  class Node {
4      int val;
5      int[] matrix;
6      Node left;
7      Node right;

```

```

8         int height;
9     }
10
11     class AVLtree {
12         int M_0 = (int) Math.pow(2, 20);
13         int M_1 = (int) (Math.pow(2, 19) + Math.pow(2, 18));
14         int M_2 = (int) (Math.pow(2, 18) + Math.pow(2, 17));
15         int inserts = 0;
16         int deletes = 0;
17         int nodes = 0;
18         Node root;
19
20         public void AVLtree() {
21             this.root = null;
22         }
23
24         public void AVL_insert(int a) {
25             this.root = insert(a, this.root);
26         }
27
28         public void AVL_remove(int a) {
29             this.root = remove(a, this.root);
30         }
31
32         public int getNodeCount() {
33             return this.nodes;
34         }
35
36         public int getInserts() {
37             return this.inserts;
38         }
39
40         public int getDeletes() {
41             return this.deletes;
42         }
43
44         public void resetInsertCount() {
45             this.inserts = 0;
46         }
47

```

```

48     private Node insert(int a, Node b) {
49         int mod = a % 3;
50
51         if (b == null) {
52             this.inserts++;
53             b = new Node();
54             this.nodes++;
55
56             b.height = 0;
57             b.left = null;
58             b.right = null;
59
60             if (mod == 0) {
61                 b.matrix = new int[M_0];
62             } else if (mod == 1) {
63                 b.matrix = new int[M_1];
64             } else {
65                 b.matrix = new int[M_2];
66             }
67         } else if (a < b.val) {
68             b.left = insert(a, b.left);
69
70             if (height(b.left) - height(b.right) == 2) {
71                 if (a < b.left.val) b =
72                     ↪ singRightRotate(b);
73                 else b = doubRightRotate(b);
74             }
75         } else if (a > b.val) {
76             b.right = insert(a, b.right);
77             if (height(b.right) - height(b.left) == 2) {
78                 if (a > b.right.val) b =
79                     ↪ singLeftRotate(b);
80                 else b = doubLeftRotate(b);
81             }
82         }
83
84         b.height = Math.max(height(b.left), height(b.right)) + 1;
85         return b;
86     }

```



```

86     private Node singRightRotate(Node b) {
87
88         if (b == null || b.left == null) {
89             return b;
90         } else {
91             Node temp = b.left;
92             b.left = temp.right;
93             temp.right = b;
94             b.height = Math.max(height(b.left),
95                 ↪ height(b.right)) + 1;
96             temp.height = Math.max(height(temp.left),
97                 ↪ b.height) + 1;
98             return temp;
99         }
100     }
101
102     private Node singLeftRotate(Node b) {
103
104         if (b == null || b.right == null) {
105             return b;
106         } else {
107             Node temp = b.right;
108             b.right = temp.left;
109             temp.left = b;
110             b.height = Math.max(height(b.left),
111                 ↪ height(b.right)) + 1;
112             temp.height = Math.max(height(b.right), b.height)
113                 ↪ + 1;
114             return temp;
115         }
116     }
117
118     private Node doubleLeftRotate(Node b) {
119         b.right = singRightRotate(b.right);
120         return singLeftRotate(b);
121     }
122
123     private Node doubleRightRotate(Node b) {
124         b.left = singLeftRotate(b.left);
125         return singRightRotate(b);
126     }

```

```

122     }
123
124     private Node remove(int a, Node b) {
125         Node temp;
126
127         if (b == null) return null;
128         else if (a < b.val) b.left = remove(a, b.left);
129         else if (a > b.val) b.right = remove(a, b.right);
130         else if (b.left != null && b.right != null) {
131             temp = findMin(b.right);
132             b.val = temp.val;
133             b.right = remove(b.val, b.right);
134         } else {
135             temp = b;
136             if (b.left == null) b = b.right;
137             else if (b.right == null) b = b.left;
138
139             this.nodes--;
140             this.deletes++;
141         }
142         if (b == null) return b;
143
144         b.height = Math.max(height(b.left), height(b.right)) + 1;
145
146         if ((height(b.left) - height(b.right)) == 2) {
147             if ((height(b.left.left) - height(b.left.right))
148                 ↪ == 1) return singLeftRotate(b);
149             else return doubLeftRotate(b);
150         } else if ((height(b.right) - height(b.left)) == 2) {
151             if ((height(b.right.right) - height(b.right.left))
152                 ↪ == 1) return singRightRotate(b);
153             else return doubRightRotate(b);
154         }
155         return b;
156     }
157
158     private Node findMin(Node b) {
159         if (b == null) return null;
160         else if (b.left == null) return b;
161         else return findMin(b.left);

```

```

160     }
161
162     private int height(Node b) {
163         return (b == null ? -1 : b.height);
164     }
165 }
166
167 public class Prog3 {
168
169     public static void main(String[] args) {
170
171         AVLtree tree = new AVLtree();
172         Random r = new Random();
173
174         double begin = System.currentTimeMillis();
175
176         while(tree.getNodeCount() < 50) {
177             tree.AVL_insert(r.nextInt(299));
178         }
179
180         double initialTime = System.currentTimeMillis() - begin;
181
182         double insertTime, removeTime;
183         insertTime = removeTime = 0;
184
185         tree.resetInsertCount();
186
187         for (int i = 0; i < 100000; i++) {
188
189             while (tree.getNodeCount() < 50) {
190                 begin = System.currentTimeMillis();
191                 tree.AVL_insert(r.nextInt(299));
192                 insertTime += (System.currentTimeMillis()
193                     ↪ - begin);
194             }
195
196             while (tree.getNodeCount() >= 50) {
197                 begin = System.currentTimeMillis();
198                 tree.AVL_remove(r.nextInt(299));
199                 removeTime += (System.currentTimeMillis()
200                     ↪ - begin);

```

```

199         }
200     }
201
202     System.out.println("Average time for initial insertion: "
203         ↪ + (initialTime/50) + " ms");
204     System.out.println("Average time for insertions: " +
205         ↪ (insertTime/tree.getInserts()) + " ms");
206     System.out.println("Average time for removals: " +
207         ↪ (removeTime/tree.getDeletes()) + " ms");
208 }
209 }

```

## Results

Average time for initial insertion	1.8 ms
Average time for subsequent insertions	0.3037 ms
Average time for removals	0.03291 ms

## Explanation

## Programming Problem 4

### Procedure

### Hypothesis

### Java Implementation

```

1  import com.sun.management.OperatingSystemMXBean;
2  import java.lang.management.ManagementFactory;
3
4  public class Prog4 {
5
6      public static void main (String[] args) {
7
8          OperatingSystemMXBean opsys =
9              ↪ ManagementFactory.getPlatformMXBean(OperatingSystemMXBean.class);
10         System.out.println("Phys Mem: " +
11             ↪ opsys.getFreePhysicalMemorySize());

```

```

10      System.out.println("Virtual Mem: " +
      ↪ opsys.getCommittedVirtualMemorySize());
11      System.out.println("Free swap space: " +
      ↪ opsys.getFreeSwapSpaceSize());
12
13      double[] C = {0.5, 0.6, 0.7, 0.8, 0.9, 0.95, 0.99, 1.0,
      ↪ 1.01, 1.1, 1.5, 2, 5, 10, 50};
14      long freeBytes = opsys.getFreePhysicalMemorySize();
15
16      for (int i = 0; i < 15; i++) {
17          System.out.println("-----\n" +
      ↪ "Cache Size: " + C[i] + "*M");
18          long start = System.currentTimeMillis();
19
20          int numBytes = Math.abs((int)(C[i] *
      ↪ (freeBytes)));
21          int size = numBytes/4;
22          int[] testArr = new int[size];
23
24          System.out.println("Phys Mem: " +
      ↪ opsys.getFreePhysicalMemorySize());
25          System.out.println("Virtual Mem: " +
      ↪ opsys.getCommittedVirtualMemorySize());
26          System.out.println("Free swap space: " +
      ↪ opsys.getFreeSwapSpaceSize());
27
28          for (int j = 0; j < size; j++) {
29              testArr[j] = i + 1;
30          }
31          for (int j = 0; j < size; j++) {
32              testArr[j] -= 2;
33          }
34
35          System.out.println("Time elapsed: " + ((double)
      ↪ System.currentTimeMillis() - start) + "
      ↪ milliseconds");
36
37      }
38
39  }

```

## Results

Cache Size	Free Physical Mem (bytes)	Free Virtual Mem (bytes)	Free Swap Space (bytes)	Time (ms)
Start	292106240	10460585984	766246912	N/A
0.5*M	142024704	10476437504	766246912	138
0.6*M	105308160	10485899264	766246912	98
0.7*M	92807168	10486038528	766246912	78
0.8*M	78573568	10487099392	766246912	89
0.9*M	78573568	10488160256	766246912	102
0.95*M	78573568	10488160256	766246912	98
0.99*M	78573568	10488160256	766246912	100
1.0*M	78573568	10496548864	766246912	99
1.01*M	78573568	10496548864	766246912	100
1.1*M	78573568	10496548864	766246912	116
1.5*M	21618688	10496548864	766246912	187
2.0*M	22835200	10496548864	766246912	246
5.0*M	23138304	10498646016	766246912	1072
10.0*M	23121920	10499694592	766246912	824
50.0*M	21336064	10499796992	766246912	663

## Explanation

### Programming Problem 5

#### Description of algorithm

Our algorithm for generating an optimal Huffman code works as follows. We first take characters and their frequencies as input from the user. We create tree nodes for each character and its frequency, and store them in a priority queue sorted by frequency. We then take the two least frequent nodes in the queue and construct a new node connecting the two, whose frequency is derived from their two frequencies combined. This new node is added back into the queue. We continue this process until only one node remains. This resultant tree supplies our Huffman encoding.

## Java Implementation

```
1  import java.util.Scanner;
2  import java.util.Comparator;
3  import java.util.ArrayList;
4  import java.util.PriorityQueue;
5
6  class Node {
7      char ch;
8      int freq;
9      Node left;
10     Node right;
11 }
12
13 class HuffComparator implements Comparator<Node> {
14     public int compare(Node a, Node b) {
15         return a.freq - b.freq;
16     }
17 }
18
19 public class Prog5 {
20
21     public static void main(String[] args) {
22
23         Scanner reader = new Scanner(System.in);
24         ArrayList<Character> chars = new ArrayList<Character>();
25         ArrayList<Integer> frequency = new ArrayList<Integer>();
26         boolean check = true;
27
28         while(check) {
29             System.out.println("Enter character (to exit enter
30             ↪ '0')");
31             char elem = reader.nextLine().charAt(0);
32
33             if (elem == '0') {
34                 check = false;
35             } else {
36                 System.out.println("What is the frequency
37                 ↪ for the character?");
38                 int freq =
39                 ↪ Integer.parseInt(reader.nextLine());
```

```

37         chars.add(elem);
38         frequency.add(freq);
39     }
40 }
41
42 PriorityQueue<Node> queue = new
↳ PriorityQueue<Node>(chars.size(), new
↳ HuffComparator());
43
44 for (int i = 0; i < chars.size(); i++) {
45     Node newNode = new Node();
46
47     newNode.ch = chars.get(i);
48     newNode.freq = frequency.get(i);
49     newNode.right = null;
50     newNode.left = null;
51
52     queue.add(newNode);
53 }
54
55 Node root = null;
56
57 while (queue.size() > 1) {
58
59     Node a = queue.peek();
60     queue.poll();
61     Node b = queue.peek();
62     queue.poll();
63
64     Node c = new Node();
65
66     c.freq = a.freq + b.freq;
67     c.ch = '-';
68     c.left = a;
69     c.right = b;
70     root = c;
71
72     queue.add(c);
73
74 }

```



```

75         printCode(root, "");
76
77     }
78
79     public static void printCode(Node root, String code) {
80         if (root.left == null && root.right == null &&
81             ↪ Character.isLetter(root.ch)) {
82             System.out.println(root.ch + ": " + code);
83             return;
84         }
85
86         printCode(root.left, code + "0");
87         printCode(root.right, code + "1");
88     }
89
90 }

```

## Sample Huffman Code

For character—frequency input:

a—8 v—1 z—1 b—5 c—6 p—4 e—10

Our algorithm generates the Huffman code:

c: 00 a: 01 e: 10 b: 110 v: 11100 z: 11101 p: 1111