



Design and Analysis of Algorithms

Network Flow

Si Wu

School of CSE, SCUT

cswusi@scut.edu.cn

TA: 1684350406@qq.com



Topics

- **Image Segmentation**
- **Bipartite Matching**
- **Disjoint Paths**



Image Segmentation


Image segmentation.

- Central problem in image processing.
- Divide image into coherent regions.

Ex. Three people standing in front of complex background scene. Identify each person as a coherent object.



Semantic segmentation



liver and hepatic vascularization segmentation



Image Segmentation

Foreground/background segmentation.

- Label each pixel in picture as belonging to foreground or background.
- V = set of pixels, E = pairs of neighboring pixels.
- $a_i \geq 0$ is likelihood pixel i in foreground.
- $b_i \geq 0$ is likelihood pixel i in background.
- $p_{ij} \geq 0$ is separation penalty for labeling one of i and j as foreground, and the other as background.






Image Segmentation

Foreground/background segmentation.

- Label each pixel in picture as belonging to foreground or background.
- V = set of pixels, E = pairs of neighboring pixels.
- $a_i \geq 0$ is likelihood pixel i in foreground.
- $b_i \geq 0$ is likelihood pixel i in background.
- $p_{ij} \geq 0$ is separation penalty for labeling one of i and j as foreground, and the other as background.

Goals.

- Accuracy: if $a_i > b_i$ in isolation, prefer to label i in foreground.
- Smoothness: if many neighbors of i are labeled foreground, we should be inclined to label i as foreground.
- Find partition (A, B) that maximizes:

$$\sum_{i \in A} a_i + \sum_{j \in B} b_j - \sum_{(i,j) \in E, |A \cap \{i,j\}|=1} p_{ij}$$



Image Segmentation

Formulate as min-cut problem.

- Maximization
- No source or sink.
- Undirected graph.

Turn into minimization problem.

- Maximizing $\sum_{i \in A} a_i + \sum_{j \in B} b_j - \sum_{(i,j) \in E, |A \cap \{i,j\}|=1} p_{ij}$
- Is equivalent to minimizing

$$\sum_{i \in V} a_i + \sum_{j \in V} b_j - \sum_{i \in A} a_i - \sum_{j \in B} b_j + \sum_{(i,j) \in E, |A \cap \{i,j\}|=1} p_{ij}$$

- Or alternatively $\sum_{j \in B} a_j + \sum_{i \in A} b_i + \sum_{(i,j) \in E, |A \cap \{i,j\}|=1} p_{ij}$




Image Segmentation

Formulate as min-cut problem $G' = (V', E')$.

- Include node for each pixel.
- Use two antiparallel edges instead of undirected edge.
- Add source s to correspond to foreground.
- Add sink t to correspond to background.

edge in G



two antiparallel edges in G'







Image Segmentation

Consider min cut (A, B) in G' .

- A = foreground.

$$cap(A, B) = \sum_{j \in B} a_j + \sum_{i \in A} b_i + \sum_{(i,j) \in E, i \in A, j \in B} p_{ij}$$

- The quantity we want to minimize.








Image Segmentation






Bipartite Matching

Def. A graph G is bipartite if the nodes can be partitioned into two subsets L and R such that every edge connects a node in L to one in R .

Bipartite matching. Given a bipartite graph $G = (L \cup R, E)$, find a max-cardinality matching.






Bipartite Matching

Def. A graph G is bipartite if the nodes can be partitioned into two subsets L and R such that every edge connects a node in L to one in R .

Bipartite matching. Given a bipartite graph $G = (L \cup R, E)$, find a max-cardinality matching.


The Ford-Fulkerson algorithm can be implemented to solve the bipartite matching problem.





Bipartite Matching: Max-Flow Formulation

- Create digraph $G' = (L \cup R \cup \{s, t\}, E')$.
- Direct all edges from L to R , and assign infinite (or unit) capacity.
- Add source s , and unit-capacity edges from s to each node in L .
- Add sink t , and unit-capacity edges from each node in R to t .






Max-Flow Formulation: Proof of Correctness

Theorem. Max cardinality of a matching in G = value of max flow in G' .

Pf. \leq

- Given a max matching M of cardinality k .
- Consider flow f that sends 1 unit along each of k paths.
- f is a flow, and has value k .







Max-Flow Formulation: Proof of Correctness

Theorem. Max cardinality of a matching in $G =$ value of max flow in G' .

Pf. \geq

- Let f be a max flow in G' of value k .
- Integrality theorem $\Rightarrow k$ is integral and can assume f is 0-1.
- Consider $M =$ set of edges from L to R with $f(e) = 1$.
 - Each node in L and R participates in at most one edge in M
 - $|M| = k$: consider cut $(L \cup \{s\}, R \cup \{t\})$.





Bipartite Matching

Bipartite matching. Can solve via reduction to maximum flow.


Flow. During Ford-Fulkerson, all residual capacities and flows are 0-1; flow corresponds to edges in a matching M .

Residual graph G_M simplifies to:

- If $(x, y) \notin M$, then (x, y) is in G_M .
- If $(x, y) \in M$, then (y, x) is in G_M .

Augmenting path simplifies to:

- Edge from s to an unmatched node $x \in X$,
- Alternating sequence of unmatched and matched edges,
- Edge from unmatched node $y \in Y$ to t .






Alternating Path

Def. An **alternating path** P with respect to a matching M is an alternating sequence of unmatched and matched edges, starting from an unmatched node $x \in X$ and going to an unmatched node $y \in Y$.

Key property. Can use P to increase by one the cardinality of the matching.






Edge-Disjoint Paths

Def. Two paths are **edge-disjoint** if they have no edge in common.

Disjoint path problem. Given a digraph $G = (V, E)$ and two nodes s and t , find the max number of edge-disjoint $s \rightarrow t$ paths.






Edge-Disjoint Paths

Def. Two paths are **edge-disjoint** if they have no edge in common.

Disjoint path problem. Given a digraph $G = (V, E)$ and two nodes s and t , find the max number of edge-disjoint $s \rightarrow t$ paths.






Edge-Disjoint Paths

Max-flow formulation. Assign unit capacity to every edge.

Theorem. Max number of edge-disjoint $s \rightarrow t$ paths equals value of max flow.

Pf. \leq

- Suppose there are k edge-disjoint $s \rightarrow t$ paths P_1, \dots, P_k .
- Set $f(e) = 1$ if e participates in some path P_j , else set $f(e) = 0$.
- Since paths are edge-disjoint, f is a flow of value k .






Edge-Disjoint Paths

Max-flow formulation. Assign unit capacity to every edge.

Theorem. Max number of edge-disjoint $s \rightarrow t$ paths equals value of max flow.

Pf. \geq

- Suppose max flow value is k .
- Integrality theorem \Rightarrow there exists 0-1 flow f of value k .
- Consider edge (s, u) with $f(s, u) = 1$.
 - By flow conservation, there exists an edge (u, v) with $f(u, v) = 1$
 - Continue until reach t , always choosing a new edge
- Produces k edge-disjoint paths.






Network Connectivity

Def. A set of edges $F \subseteq E$ **disconnects t from s** if every $s \rightarrow t$ path uses at least one edge in F .

Network connectivity. Given a digraph $G = (V, E)$ and two nodes s and t , find min number of edges whose removal disconnects t from s .







Menger's Theorem

Theorem. The max number of edge-disjoint $s \rightarrow t$ paths equals the min number of edges whose removal disconnects t from s .

Pr. \leq

- Suppose the removal of $F \subseteq E$ disconnects t from s , and $|F| = k$.
- Every $s \rightarrow t$ path uses at least one edge in F .
- Hence, the number of edge-disjoint paths is $\leq k$.





Menger's Theorem

Theorem. The max number of edge-disjoint $s \rightarrow t$ paths equals the min number of edges whose removal disconnects t from s .

Pr. \geq

- Suppose max number of edge-disjoint paths is k .
- Then value of max flow = k .
- Max-flow min-cut theorem \Rightarrow there exists a cut (A, B) of capacity k .
- Let F be set of edges going from A to B .
- $|F| = k$ and disconnects t from s .

