

Monitoring

Service Description

Abstract

Monitoring of any microsystem and its produced and consumed microservices is important in a professional industrial context. The Monitoring service provides one very basic interface and mechanisms for dynamically update it self with modified, new or even removed interfaces.

Contents

1	Overview	3
1.1	Significant Prior Art	3
1.2	How This Service Is Meant to Be Used	3
1.3	Important Delimitations and Dependencies	3
2	Service Interface	4
2.1	Interface operation Echo	4
2.2	Interface operation Power	4
2.3	Interface operation Update	4
3	Information Model	4
3.1	struct echo	4
3.2	struct power	4
3.3	struct CC	4
3.4	Primitives	4
4	Revision History	5
4.1	Amendments	5
4.2	Quality Assurance	5

1 Overview

This document describes the Monitoring service, which enables very basic basic monitoring of a microsystem and its microservices. The Monitoring service provides one very basic interface and mechanisms for dynamically update it self with modified, new or even removed interfaces.

The rest of this document is organized as follows. In Section 2, we describe the abstract message operations provided by the service. In Section 3, we end the document by presenting the data types used by the mentioned operations.

1.1 Significant Prior Art

Monitoring is not a simple service. For Arrowhead v4.6 and earlier individual services may have an echo interface.

1.2 How This Service Is Meant to Be Used

The monitoring service is a mandatory service for all core and support microsystems and a highly recommended service for any application microsystem.

The general idea is that a Monitor microsystem subscribes to all available Monitoring service. The subscription can hold conditions like e.g. time interval, battery level below X%, error reports.

The usage scenario is depicted in Figure 1




Figure 1: The general architectural usage of the Monitoring service isSysML SD diagram of the Monitoring service and its basic interfaces

This service is intended to provides the capability to monitor status of a microsystem and its associated microservices. Example of statuses are:

- Echo alive
- Power monitoring
- Test consumption of service for which the microsystem has a consumer.
- Internal state of the microsystem, e.g. remaining usefull life,
- Trigger a subscription push of data to a consumer
- Update of the monitoring service

1.3 Important Delimitations and Dependencies

The service provides only a very limited basic monitoring interfaces. Dynamically the service can be modified with updated, new or revoked interfaces. A specific update interface will be provided. This one can be protected and thus limited to only accept systems or user consumptions with certain certificate level. Specific security concerns need to be addressed while using this Update interface.

2 Service Interface

The Monitoring service has the interface depicted in 2

Figure 2: SysML SD diagram of the Monitoring service and its basic interfaces

The following interfaces are available.

2.1 Interface operation **Echo (-)** : **StatusCodeKind**

The Echo interface will respond with an TCP respnde code e.g. 100. Thus indicateing things are working as expected.

2.2 Interface operation **Power (type,level)** : **type, level**

The Power interface input parameters are: type and level. The responses are: Type=line—battery—harvesting
Level= 0-100%

2.3 Interface operation **Update (TBD)** : **StatusCodeKind**

The Update interface enables the update of the service with a modified, new or rewoked interface. The response will be a status code.

3 Information Model

3.1 struct **echo**

This structure is used to get an echo from the Monitoring service based on StatuCodeKind.

3.2 struct **power**

Provide type of power supply e.g. line, battery, harvesting. Provides level of power e.g. %, energy

3.3 struct **CC**

EXAMPLE: This structure is used to query service offering registered in the Service Registry. Please also refer to the activity diagram in Figure ??

3.4 Primitives

Types and structures mentioned throughout this document that are assumed to be available to implementations of this service. The concrete interpretations of each of these types and structures must be provided by any IDD document claiming to implement this service.

4 Revision History

4.1 Amendments

No.	Date	Version	Subject of Amendments	Author
1	2024-05-26	5.0.0		Jerker Delsing
2		5.0.0		
3		5.0.0		

4.2 Quality Assurance

No.	Date	Version	Approved by
1		5.0.0	