

Document title
Service Discovery Query
Date
2021-01-15
Author
Szvetlin Tanyi
Contact
szvetlin@aitia.ai

Document type SD
Version
4.3.0
Status
RELEASE
Page
1 (6)

# Service Discovery Query Service Description

Service ID: "query"

#### **Abstract**

This document describes a variant of the Service Discovery Query service.





Version 4.3.0 Status RELEASE Page 2 (6)

## **Contents**

1 Overview			
	Service Interfaces 2.1 function Query	<b>4</b> 4	
	Information Model 3.1 struct ServiceQueryForm	<b>5</b> 5	
	Revision History 4.1 Amendments		



Version 4.3.0 Status RELEASE Page 3 (6)

#### 1 Overview

This document describes the Service Discovery Query Eclipse Arrowhead service, which enables clients to query other Core System services. Examples of this interaction is a system that wants to check how can it call the orchestration service offered by the Orchestration core system.

The rest of this document is organized as follows. In Section 2, we describe the abstract message functions provided by the service. In Section 3, we end the document by presenting the data types used by the mentioned functions.



Version
4.3.0
Status
RELEASE
Page
4 (6)

#### 2 Service Interfaces

This section lists the functions that must be exposed by Service Discovery Query service in alphabetical order. In particular, each subsection names an abstract interface, an input type and an output type, in that order. The input type is named inside parentheses, while the output type is preceded by a colon. Input and output types are only denoted when accepted or returned, respectively, by the interface in question.

All abstract data types named in this section are defined in Section 3.

#### 2.1 function Query (ServiceQueryForm)

The Query function is used to query services. The services will contain various metadata as well as a physical endpoint. The various parameters are representing the endpoint information.

Version 4.3.0 Status RELEASE Page 5 (6)

#### 3 Information Model

Here, all data objects that can be part of Service Discovery Register service calls are listed in alphabetic order. Note that each subsection, which describes one type of object, begins with the *struct* keyword, which is used to denote a collection of named fields, each with its own data type. As a complement to the explicitly defined types in this section, there is also a list of implicit primitive types in Section 3.2, which are used to represent things like hashes and identifiers.

#### 3.1 struct ServiceQueryForm

This structure is used to register a service offering into the Service Registry.

Object Field	Value Type	Description
"interfaceRequirements"	Array <interface></interface>	List of the required interfaces.
"maxVersionRequirement"	Version	Maximum version.
"minVersionRequirement"	Version	Minimum version.
"metadataRequirements"	Metadata	Metadata.
"pingProviders".	Boolean	Checks the availability of the providers if true
"securityRequirements"	Name	Type of security.
"serviceDefinitionRequirement"	Name	Service Definition.
"versionRequirement"	Version	Version of the service.

#### 3.2 Primitives

Types and structures mentioned throughout this document that are assumed to be available to implementations of this service. The concrete interpretations of each of these types and structures must be provided by any IDD document claiming to implement this service.

Туре	Description	
Boolean	One out of true or false.	
Interface Any suitable type chosen by the implementor of the service.		
Version	Specifies a service version.	
List <a></a>	An array of a known number of items, each having type A.	
Name	A string identifier that is intended to be both human and machine-readable.	



Version 4.3.0 Status RELEASE Page 6 (6)

# 4 Revision History

### 4.1 Amendments

No.	Date	Version	Subject of Amendments	Author
1	2020-12-05	1.0.0		Tanyi Szvetlin

### 4.2 Quality Assurance

No.	Date	Version	Approved by
1			