

IoT Environmental Monitoring System

Final Project Report

1. Introduction

This project implements an IoT environmental monitoring system using MQTT, Python, MongoDB, MySQL, and Neo4j. The system simulates IoT devices that publish environmental and network data through MQTT topics. A Python subscriber receives the MQTT messages, processes the incoming JSON data, generates alerts, validates measurements, and routes information to different database systems based on the topic and type of data.

2. Project Objectives


- Implement MQTT-based communication.
- Process environmental sensor data in real time.
- Use topic-based routing for data processing.
- Integrate MongoDB, MySQL, and Neo4j in one architecture.
- Generate alerts for abnormal sensor readings.
- Model network topology using graph relationships.

3. Technologies Used

Technology	Purpose
Python	Main programming language
MQTT	Communication protocol
Mosquitto	MQTT broker
MongoDB	Flexible document storage
MySQL	Structured relational storage
Neo4j	Graph relationship modeling
Docker	Containerized infrastructure

4. System Architecture

The architecture uses MQTT publishers, a Mosquitto broker, and a Python subscriber processing engine. Data is routed based on MQTT topics. Routing Logic: - sensors/environment → MongoDB + MySQL - sensors/network → MongoDB + Neo4j



```

      ↓
MQTT Broker (Mosquitto)
      ↓
Python Subscriber
      ↓
MongoDB + Neo4j

```

5. MongoDB Enriched Event Storage

MongoDB stores enriched environmental event documents. The documents contain nested sensor readings, alert arrays, threshold values, timestamps, and metadata. The alert system generates warnings for: - high temperature - high humidity - poor air quality




Figure 1: MongoDB enriched alert document.

6. MySQL Structured Storage

MySQL stores validated environmental measurements in a structured relational table. Only valid data is inserted into MySQL after required-field and range validation. The table stores: - sensor ID - location - temperature - humidity - air quality - timestamp

The Python subscriber acts as the central processing engine. Responsibilities: - receive MQTT messages - process JSON data - generate alerts - validate measurements - route data to appropriate databases



```
PS C:\Users\dmx\Desktop\iot_environment-monitor> python subscriber/subscriber.py
C:\Users\dmx\Desktop\iot_environment-monitor\subscriber\subscriber.py:182: DeprecationWarning: Callback API version 1 is deprecated, update to latest version
  client = mqtt.Client()
waiting for messages..
connected to MQTT!
Network event stored in MongoDB
Network relationship inserted into Neo4j
Network event stored in MongoDB
Network relationship inserted into Neo4j

Event inserted into MongoDB
Valid data inserted into MySQL
Network event stored in MongoDB
Network relationship inserted into Neo4j

Event inserted into MongoDB
Valid data inserted into MySQL
Network event stored in MongoDB
Network relationship inserted into Neo4j

Event inserted into MongoDB
Valid data inserted into MySQL
Network event stored in MongoDB
Network relationship inserted into Neo4j

Event inserted into MongoDB
Invalid data no insert into MySQL
Network event stored in MongoDB
Network relationship inserted into Neo4j
```

Figure 4: Subscriber processing output.

9. Conclusion

The project successfully demonstrated MQTT communication, topic-based routing, multi-database integration, alert generation, graph relationship modeling, and event-driven processing. The architecture uses polyglot persistence by combining MongoDB, MySQL, and Neo4j, each optimized for different types of data.

Author: Alex Demse

University of Messina - Data Analysis Program