


ISOMETRIC IFC - CHECK LIST

Line I	Number	021921PNW	V0132			Stress CN / Leve	el		Nº		Level:								
-			21PNW0132 0	11		Process Approv			YES	_	NO 🕢		Cá	PAII!		ToohninE	MC – Butte	rfly Draiga	
1301110	stric Number	021A102192	21FNW0132_0	/·I			•		_	Ϊ—			Ua	ıyııı		recinipi	IVIC - Butte	rilly Piojec	١
						intrumetation A	pproval Required (N/A)		YES		NO 🗹					1101 5			
_	mation to be attache	_	7	l		I			1			⊣⊢.			OLIOPE DE	HOLD	5	PEOOL	VED (()
	er Copy of PID:			N/A		Nº No	800124-029-PID-0031-0)10	Rev.	1 IFC		N:	N º		SHORT DE	SCRIPTION		RESOL	VED (▼)
-	flodification Sheet:	YES		N/A		Nº No			Rev.										
	ment Vendor Dwg. :	YES		N/A		Nº No			Rev.										
	ment Dwg. :	YES _	<u> </u>	N/A	<u>₹</u>	Nº No			Rev.										
	ct By-Pass ⁽⁴⁾ : Approved Isometric:	YES _		N/A N/A		№ Rev.			Rev.	· B			_						
	oproved Isometric:	YES	<u></u>	N/A		Rev.				tion Date:									
SII A																			
					<u>A</u>	VERIFICAR /	TO BE CHECKED								" N/A " NO APLICA / NOT APPLICABLE	IFC	REV 0	REV 1	REV 2
	Revision By : (D) Designer / (LDG) Design Leader / (ST) Stress Specialist / (LST) Stress Leader / (SP) Supports Specialist / (LSP) Supports leader / (M) Materials / (SL) Spooler / (CHK) Issuer / (L) Discipline Lead												N/A APLI NOT		✓				
		(SP) Sup	pports Speci	ialist / ((LSP) Supports	s leader / (M) l	Materials / (SL) Sp	ooler / (Cl	HK) Issu	uer / (L) L	Discipline Le	ad			A PP	√	X ⁽¹⁾	1 st-Chk ⁽²⁾	2nd-Chk ⁽³⁾
						Revision By : (D) Designer / (LDG) Desig	ın Leader							•	Ву	: D	Ву:	LDG
	Nº de línea según P	PID y lista de lí	íneas / <i>Line Nbr.</i>	accordin	g to PID and line list	•										V		*	
ion	Datos de la línea se	egún lista de lír	ineas / Line data	accordin	a to line list											√		√	
mat						and Line Lint										<u> </u>			
Information	Clase de tubería se		<u> </u>															*	
SO	Vinculo E3D con Di	agrams (Proce	ess Unit, Temp (Operació	n, Numeracion TOD	AS válvulas manua	ales) / Link between E3D	and Diagram	s (Proces	ss Unit, Op 7	emp, ALL manu	al valves 1	Tagged	i)		V		V	
	Diámetro de la línea	a indicado en r	número de línea	en el caj	etin / <i>Line diameter i</i>	indicated in the line	number in the title block									V		*	
			endor válido para	a generar	isométrica IFC / Eq	uipment modelled a	according Vendor drawin	g valid for Iso	metric IFC	C generation					V				
ent	Código / Code: 2					. 8/-													
Equipment	Nombre de tubulado	uras según PII	D y plano Vendo	or / Name	of nozzle according	to PID and Vendor	r drawing								V				
Equ	Rating y diámetro d	e tubuladuras	según plano Ve	ndor / Ra	ting and diameter of	f nozzles according	to vendor drawing								V				
	Posición y elevación	n de tubuladur	ras según plano	Vendor /	Position and elevati	on of nozzles accor	rding to Vendor drawing	_			_		_	_	V				
						Revision By : (D) Designer / (LDG) Designer	ın Leader							. *	Ву	: D	Ву:	LDG
	Revision By : (D) Designer / (LDG) Design Leader Línea sin colisión (verificación incluyendo la nube de puntos) / Line is clash free (checked including points cloud)															1		₩	
	`				·		,	onto to!!	lines ::	aluad seed	nlomente -!! '	a final - '	racti-	for incres		▼		▼	
						accion tinal para e	misión / Process comme	nus to critical	ıırıes rece	eivea and im	uierrientea betore	ıınaı extra	action f	or issuance	V				
	Verificación contra l					ovietontes ·· -t !	nois do la isométrie e	ne ovtram -	lo línes :	CIIC rem-1	inclused	vacions -	v 000:	onadas /		✓		√	
							noja de la isométrica en la end of the line and its bra					aciones y	y coorde	cildud5 /		▼		₩	
	Verificación contra I	P&ID / Check	lso vs P&ID :															✓	
	Elementos en línea sequence, slope, flo						strumentos, cambios de	especificació	n, cumplin	miento de no	tas / in-line com	oonents in	ncluded,	, branch				•	
ug	Verificación contra I			aning, pipe	Class Dieans, Hole.	s accomplishment													
Design	Longitudes requerid	las de entrada	a y/o salida a equ			nes mínimas o máx	kimas requeridas, forma	ción de cond	ensados /	Required in	let and/or outlet l	engths to e	equipm	ents, minimum				V	
Line	or maximum distances and/or elevations, condensate generation															•			
-	Comentarios de STT à recipidos e implementados antes de extracción final para emisión / instrumentation comments received and implemented before final extraction for issuance												V						
Verificación contra Planos de Vendor o Hook-up Instrumentacion / Check Iso vs Instrument Vendor Drawings or Hook-up: Tamaño de las válvulas de control y de seguridad, instalación de acuerdo a hook-up / Size of control valves and safety valves, instrument installation according to hook-up											V								
Picajes según tabla de picajes correspondiente / Branch configuration according to correspondent branch table Venteos y drenajes de Procesos según requerimientos de PIDs y de puntos altos y bajos para prueba hidrostática y modelados según "assembly" correspondiente / Process vents and drains according PID											V								
Venteos y drenajes de Procesos según requerimientos de PIDs y de puntos altos y bajos para prueba hidrostática y modelados según "assembly" correspondiente / Process vents and drains according PID requirements and high and low points for hydrostatic test and modelled according proper assembly														V					
	Verificación de distancia mínima entre soldaduras / Check minimum distance between welds												√		√				
															√			<u> </u>	
	Notas explicativas a	adicionales inc	corporadas / Add	iitionai cia											V	_		_	
						, , ,	tress Specialist / (LST) S								ı	By:	ST	By:	LST
Stress	El cálculo de stress	disponible no	está pendiente	de revisió	on en curso / Availat	ole stress calculation	nn is not awaiting for revis	sion											
St	Los requisitos segú	n el cálculo de	e stress están ind	corporado	os (si son aplicables) / Stress calculation	on requirements have be	en added (if a	pplicable))									
					Rev	ision By : (SP) Sup	ports Specialist / (LSP)	Supports lead	er							Ву:	SP	Ву:	LSP
	La línea está soport	tada por comp	oleto y la lista de	soportes	está actualizada en	el exel extraído de	el E3D / Line is complete	ly supported a	nd suppo	ort list update	ed according file	from E3D							
	Concepto de soport	te y separación	n máxima entre	soportes	/ Support concept a	nd support spans													
ts							de Stress / Support requ	uirements acc	ording to	stress calcu	lation note are in	cluded and	nd adjus	sted jointly with	1				
Supports	stress specialist													-					
Sup	Numeración correct	ta de los sopoi	rtes / Supports o	correctly r	numbered														
	Código de soportes correctamente indicados (STD - SPC - COM - MRS - PRF) / Support code correctly indicated (STD - SPC - COM - MRS - PRF)																		
	Marcado de elemen	ntos soldados (de los soportes	en Iso Sp	ool preliminar corre	spondiente / Mark-	up of welded supports co	omponents in	the corres	spondent pre	eliminary Iso Spo	ol			N/A				
				<u> </u>		<u> </u>	sion By : (M) Materials			,						Ву	: M		
						tada en la Lista de	Lineas Críticas de Mater		metricas r	requieren V	erificacion exahu	stiva / The	e Line b	elongs to some	N/A				
	,						ics require exahustive ve		din 4- '	omet-1	oro lietl' '	2014				✓			
							materiales / All material								 	₩			
<u>s</u>							especiales de tubería (Ve Piping Material List (Verif							to en diseño si		V			
Materials	. ,					•		, identificatio	. mannuel,	, piping ues	gri iooalion Gilei	п арріїС	JUDIC)		 				
Ма	Nº de identificación	de válvulas m	nanuales (según	PID)/ Ide	entification number o	f manual valve (acc	cording to PID)									✓			
	Todas las juntas y p	pernos colocad	das según tipo re	equerido	(RF, FF, Bolts, Mac	nine Bolts) / All gas	kets and bolts placed ac	cording requi	red type (F	RF, FF, Bolt	s, Machine Bolts)			N/A				
	Extensión de volant	te de válvula n	modelada y reflej	ada en lis	sta de materiales de	la isométrica / Val	ves axis extension mode	lled and refle	cted in Iso	ometric BON			_		N/A				
	Extensión de volante de válvula modelada y reflejada en lista de materiales de la isométrica / Valves axis extension modelled and reflected in Isometric BOM Válvulas colocadas según PID y Piping Class / Valves placed according PID an Piping Class											✓							
	Revision By : (CHK) Issuer													By:	СНК				
							, , , , , , , , , , , , , , , , , , , ,									1st-C	•	2nd-0	.hk ⁽³⁾
																√ ·	ж х	✓	Х
	La isométrica verific	cada por Proce	esos (SPO) se c	orrespon	de a la última revisio	ón / The isometric v	verified by Process (SPC) correspond	to its las	t revision					V				
J	La isométrica verificada por Procesos (SPO) se corresponde a la última revisión / The isometric verified by Process (SPO) corresponds to its last revision La isométrica verificada por Instrumentación (SIT) se corresponde a la última revisión / The isometric verified by Instrumentation (SIT) corresponds to its last revision																		
Final Check																			
nal C		as notas a mano están incorporadas en las isométricas / The hand-made annotation is included a revisión de los documentos para la verificación siguen siendo las actuales. / Current revision of documents for checking are still the latest available.								 									
ΙĒ									 										
	El número de revisión y la fecha son correctos / The revision number and the date are correct Todos los comentarios se han revisado para se incluidos o descartados / All comments have been checked to be included or discarded										V								
											V								
	Holds resueltos o el	n su defecto B	By-Pass aprobad	lo / Holds	resolved or instead	By-Pass approved	1									V			
SIGNATURES (Name and date)										*									
		DE1 (12	FD.				I S	GNATUR	ے (Nan I	пе апа а	alej								
DESI	GN LEADER (LD)	REVIEWE	ED rrero at 2:22 pm,	Dec 11	2020		SUPPORTS LEADER	(LSP)	Ī					ISSUER	(CHK)	REVIEWED By oscar at 10:08 as	m, Dec 18. 2020		
		by Kuth Heri	1010 at 2:22 pm,	Dec 11, 2												, u. 10.00 al			
STRE	SS LEADER (LST)						MATERIALS	(M)	REVIEWE By Jose G. St		, Dec 14, 2020			DISCIPLINE	E LEAD (L)				
	MATERIALS (M) REVIEWED By Jose G. Suarez at 11:45 am, Dec 14, 2020 DISCIPLINE LEA																		

NOTES:

- [1] If "X" marqued, a "HOLD" note should be included in the Holds area for justification.
 [2] 1st checking round: Checker to place a (\$\struct\sigma\) or a (\$\mathbf{X}\) confirming or not Designer verification. A (\$\struct\sigma\) or a (\$\mathbf{X}\) should also be placed to confirm or reject any (\$\mathbf{X}\) mark placed by the Designer confirming or not the implicit HOLD.
 [3] 2nd checking round: Checker to place a (\$\struct\sigma\) to validate the points that were not confirmed in the 1st round and were corrected by respective Specialist.
 [4] If an isometric with HOLD is approved by IFC Leader for issuance, the correspondent By-Pass should be attached.





PT NO	N.S. (MM)	DESCRIPTION	IDENT	QTY
1	20	Pipes (Length), EN 10220, PE, EFW + 100% RT, -,/2MM EN 10217-7 Gr.X2CrNi19-11,	C1KV24Y3	11.4M
2	25 x 20	Conc Reducer, EN 10253-4 Type A, BW Ends, Welded + 100% RT, -,/2.3MM/2MM EN 10253-4 Gr.X2CrNi19-11,	C1NF9VR1	1
3	20	90° Elb LR, EN 10253-4 Type A, BW Ends, Welded + 100% RT, M.3D, Serie 4,/2MM EN 10253-4 Gr.X2CrNi19-11,	C1P0J0PG	8
4	20	45° Elb LR, EN 10253-4 Type A, BW Ends, Welded + 100% RT, M.3D, Serie 4,/2MM EN 10253-4 Gr.X2CrNi19-11,	C1P0J0P9	2

PIPING DPT.

ISSUER
CHECKED

By oscar at 10:07 am, Dec 18, 2020

PROCESS DESIGN AREA

0	11/12/20	SMA	RHE	OMC	IFC-ISSUED FOR CONSTRUCTION					
REV	DATE	DWN	CHK	APP	DESCRIPTION					

All dimensions to be checked in field prior to construction. Dimensions and routing shall be field adjusted, it is the piping contractors responsibility to check and verify all closing dimensions to equipment and make adjustments as required in field. All dimensions, elevations and coordinates are in millimeter unless noted otherwise. Fieldwelds and overlengths to be determined by piping contractor. Bolt holes to straddle horizontal and vertical centerline unless shown otherwise. Contractor will provide all necessary pipe supports.

, , , ,		•			
se. Contractor will provide all r	shown otherwise.	unless	centerline	vertical	horizontal and
TechnipFMC		ION	ON/LOCAT	SCRIPTI	PROJECT DE
	.D	KREFEL	ROJECT/k	ERFLY F	BUTT

PROJECT/KREFELD

LINE NUMBER

TRAIN SHEET RE

021921-20-PNW-10SS21-0132-ET


01 1 of 2

NOTES:

For pipes < dn50 supporting to be studied and defined by construction contractor before line fabrication and installation.

N 1027825 EL +106681

EXTRACTION DAY 11 DEC 2020 E3D NAME027A1-021921-20-PNW-10SS21-0132-ET_01



PT NO	N.S. (MM)	DESCRIPTION	IDENT	QTY
1	20	Pipes (Length), EN 10220, PE, EFW + 100% RT, -,/2MM EN 10217-7 Gr.X2CrNi19-11,	C1KV24Y3	17.2M
2	20	90° Elb LR, EN 10253-4 Type A, BW Ends, Welded + 100% RT, M.3D, Serie 4,/2MM EN 10253-4 Gr.X2CrNi19-11,	C1P0J0PG	8
3	20	45° Elb LR, EN 10253-4 Type A, BW Ends, Welded + 100% RT, M.3D, Serie 4,/2MM EN 10253-4 Gr.X2CrNi19-11,	C1P0J0P9	2
4	20	Bal BW,RB,SP,PN 63,BW Ends,Datasheet: 6006/2MM EN 10213 Gr.GX5CrNiMo19-11-2,	C3HDWU3R	1

MATERIAL LIST - ERECTION

PT NO	N.S. (MM)	DESCRIPTION	IDENT	QTY
5	20	021921A245 Hose Connection as per 30205-042-001000-001	C4102FN7	1

PIPING DPT. **ISSUER** By oscar at 10:07 am, Dec 18, 202

PROCESS DESIGN AREA

027A1

029

ı						
	0	11/12/20	SMA	RHE	OMC	IFC-ISSUED FOR CONSTRUCTION
	REV	DATE	DWN	CHK	APP	DESCRIPTION

All dimensions to be checked in field prior to construction. Dimensions and routing shall be field adjusted, it is the piping contractors responsibility to check and verify all closing dimensions to equipment and make adjustments as required in field. All dimensions, elevations and coordinates are in millimeter unless noted otherwise. Fieldwelds and overlengths to be determined by piping contractor. Bolt holes to straddle horizontal and vertical centerline unless shown otherwise. Contractor will provide all necessary pipe supports.

CONTRACTOR WITT	other wise.	SHOWH	uncess	LLITE	Center	lical	and ve	tzontat
Techr			ION	CAT	ON/L	RIPTI	DESCR	OJECT
		.D	KREFEL	CT/K	ROJE	LY F	JTTERI	ВІ

PROJECT/KREFELD	TechnipFMC	(Gáli	gill"	
LINE	7	ΓRΑΙΝ	SHEET	REV	
021921-20-PNW-10	SS21-0132-ET		01	2 of 2	0


For pipes < dn50 supporting to be studied and defined by construction contractor before line fabrication and installation.

REFERENCES / DOCUMENTS SYMBOLOGY LINE LIST 30201-042-001000-001 Insulated Pipe Insulated and Traced Pipe ISOMETRIC INDEX 30303-042-001000-200 PIPING SUPPORT 30207-042-001000-001

EXTRACTION DAY 11 DEC 2020


E3D NAME027A1-021921-20-PNW-10SS21-0132-ET_01







PT NO	N.S. (MM)	DESCRIPTION	IDENT	QTY
1	20	Pipes (Length), EN 10220, PE, EFW + 100% RT, -,/2MM EN 10217-7 Gr.X2CrNi19-11,	C1KV24Y3	11.4M
2	25 x 20	Conc Reducer, EN 10253-4 Type A, BW Ends, Welded + 100% RT, -,/2.3MM/2MM EN 10253-4 Gr.X2CrNi19-11,	C1NF9VR1	1
3	20	90° Elb LR, EN 10253-4 Type A, BW Ends, Welded + 100% RT, M.3D, Serie 4,/2MM EN 10253-4 Gr.X2CrNi19-11,	C1P0J0PG	8
4	20	45° Elb LR, EN 10253-4 Type A, BW Ends, Welded + 100% RT, M.3D, Serie 4,/2MM EN 10253-4 Gr.X2CrNi19-11,	C1P0J0P9	2



PROCESS DESIGN AREA

0	11/12/20	SMA	RHE	OMC	IFC-ISSUED FOR CONSTRUCTION
REV	DATE	DWN	CHK	APP	DESCRIPTION

All dimensions to be checked in field prior to construction. Dimensions and routing shall be field adjusted, it is the piping contractors responsibility to check and verify all closing dimensions to equipment and make adjustments as required in field. All dimensions, elevations and coordinates are in millimeter unless

noted otherwise. Fieldwelds and overlengths to be determine	ned by piping contractor. Bolt	noles to straddle
horizontal and vertical centerline unless shown otherwise	. Contractor will provide all n	ecessary pipe supports.
PROJECT DESCRIPTION/LOCATION	TechnipFMC	Carrello Car
BUTTERELY PROJECT/KREEFID		

LINE NUMBER

021921-20-PNW-10SS21-0132-ET

TRAIN


01

SHEET

of 2

NOTES: For pipes < dn50 supporting to be studied and defined by construction contractor before line fabrication and installation.


SPEC REFERENCES / DOCUMENTS 10SS21 SYMBOLOGY LINE LIST 30201-042-001000-001 Insulated Pipe Insulated and Traced Pipe ISOMETRIC INDEX 30303-042-001000-200 PIPING SUPPORT 30207-042-001000-001



PT NO	N.S. (MM)	DESCRIPTION	IDENT	QTY
1	20	Pipes (Length), EN 10220, PE, EFW + 100% RT, -,/2MM EN 10217-7 Gr.X2CrNi19-11,	C1KV24Y3	17.2N
2	20	90° Elb LR, EN 10253-4 Type A, BW Ends, Welded + 100% RT, M.3D, Serie 4,/2MM EN 10253-4 Gr.X2CrNi19-11,	C1P0J0PG	8
3	20	45° Elb LR, EN 10253-4 Type A, BW Ends, Welded + 100% RT, M.3D, Serie 4,/2MM EN 10253-4 Gr.X2CrNi19-11,	C1P0J0P9	2
4	20		C3HDWU3R	1

MATERIAL LIST - ERECTION

	PT NO	N.S. (MM)	DESCRIPTION	IDENT	QTY
l	5	20	021921A245 Hose Connection as per 30205-042-001000-001	C4102FN7	1



0	11/12/20	SMA	RHE	OMC	IFC-ISSUED FOR CONSTRUCTION	
REV	DATE	DWN	CHK	APP	DESCRIPTION	

All dimensions to be checked in field prior to construction. Dimensions and routing shall be field adjusted, it is the piping contractors responsibility to check and verify all closing dimensions to equipment and make adjustments as required in field. All dimensions, elevations and coordinates are in millimeter unless noted otherwise. Fieldwelds and overlengths to be determined by piping contractor. Bolt holes to straddle horizontal and vertical centerline unless shown otherwise. Contractor will provide all necessary pipe supports.

ROJECT	DESCRIPTION/LOCATION
D	LITTEDEL V. DDO JECT /VDEEELD

TechnipFMC Cárgilli TRAIN


BUTTERFLY PROJECT/KREFELD DESIGN AREA LINE NUMBER SHEET 021921-20-PNW-10SS21-0132-ET 029 027A1 01 2 of 2

NOTES:

For pipes < dn50 supporting to be studied and defined by construction contractor before line fabrication and installation.

SPEC REFERENCES / DOCUMENTS 10SS21 SYMBOLOGY LINE LIST 30201-042-001000-001 Insulated Pipe Insulated and Traced Pipe ISOMETRIC INDEX 30303-042-001000-200 PIPING SUPPORT 30207-042-001000-001






30207-042-001000-001

MATERIAL LIST - FABRICATION

PT NO	N.S. (MM)	DESCRIPTION	IDENT	QTY
1	20	Pipes (Length), EN 10220, PE, EFW + 100% RT, -,/2MM EN 10217-7 Gr.X2CrNi19-11,	C1KV24Y3	11.4
2	25 x 20	Conc Reducer, EN 10253-4 Type A, BW Ends, Welded + 100% ➡T, -,/2.3MM/2MM EN 10253-4 Gr.X2CrNi19-11,	C1NF9VR1	1
3	20	90° Elb LR, ÉN 10253-4 Type A, BW Ends, Welded + 100% RT, M.3D, Serie 4,/2MM EN 10253-4 Gr.X2CrNi19-11,	C1P0J0PG	8
4	20	45° Elb LR, EN 10253-4 Type A, BW Ends, Welded + 100% RT, M.3D, Serie 4,/2MM EN 10253-4 Gr.X2CrNi19-11,	C1P0J0P9	2





0	11/12/20	SMA	RHE	OMC	IFC-ISSUED FOR CONSTRUCTION
REV	DATE	DWN	CHK	APP	DESCRIPTION

All dimensions to be checked in field prior to construction. Dimensions and routing shall be field adjusted, it is the piping contractors responsibility to check and verify all closing dimensions to equipment and make adjustments as required in field. All dimensions, elevations and coordinates are in millimeter unless noted otherwise. Fieldwelds and overlengths to be determined by piping contractor. Bolt holes to straddle

	The contract of the contract o							
horizo	orizontal and vertical centerline unless shown otherwise. Contractor will provide all necessary pipe supports.							
PROJE		TION/LOCATION PROJECT/KREFELD	TechnipFMC	Gál	rgilli"	,		
PROCESS UNIT	DESIGN AREA	LINE N	NUMBER	TRAIN	SHEET	RI		

021921-20-PNW-10SS21-0132-ET

SPEC NOTES: REFERENCES / DOCUMENTS 10SS21


LINE LIST 30201-042-001000-001 For pipes < dn50 supporting to be studied and defined by construction contractor before line fabrication and installation. ISOMETRIC INDEX 30303-042-001000-200

PIPING SUPPORT

SYMBOLOGY Insulated Pipe Insulated and Traced Pipe

EL +106681


E3D NAME027A1-021921-20-PNW-10SS21-0132-ET_01 EXTRACTION DAY 11 DEC 2020



PT NO	N.S. (MM)	DESCRIPTION	IDENT	QTY
1	20	Pipes (Length), EN 10220, PE, EFW + 100% RT, -,/2MM EN 10217-7 Gr.X2CrNi19-11,	C1KV24Y3	17.2N
2	20	90° Elb LR, EN 10253-4 Type A, BW Ends, Welded + 100% RT, M.3D, Serie 4,/2MM EN 10253-4 Gr.X2CrNi19-11,	C1P0J0PG	8
3	20	45° Elb LR, EN 10253-4 Type A, BW Ends, Welded + 100% RT, M.3D, Serie 4,/2MM EN 10253-4 Gr.X2CrNi19-11,	C1P0J0P9	2
4	20	Bal BW,RB,SP,PN 63,BW Ends,Datasheet: 6006/2MM EN 10213 Gr.GX5CrNiMo19-11-2,	C3HDWU3R	1

MATERIAL LIST - ERECTION

PT NO	N.S. (MM)	DESCRIPTION	IDENT	QTY
5	20	021921A245 Hose Connection as per 30205-042-001000-001	C4102FN7	1





	0	11/12/20	SMA	RHE	OMC	IFC-ISSUED FOR CONSTRUCTION
	RFV	DATE	DWN	CHK	APP	DESCRIPTION

All dimensions to be checked in field prior to construction. Dimensions and routing shall be field adjusted, it is the piping contractors responsibility to check and verify all closing dimensions to equipment and make adjustments as required in field. All dimensions, elevations and coordinates are in millimeter unless noted otherwise. Fieldwelds and overlengths to be determined by piping contractor. Bolt holes to straddle horizontal and vertical centerline unless shown otherwise. Contractor will provide all necessary pipe supports.

PROJECT DESCRIPTION/LOCATION

TechnipFMC Cárgilli

BUTTERFLY PROJECT/KREFELD PROCESS DESIGN AREA LINE NUMBER TRAIN SHEET 021921-20-PNW-10SS21-0132-ET 029 027A1 01 2 of 2

NOTES:

For pipes < dn50 supporting to be studied and defined by construction contractor before line fabrication and installation.

SPEC REFERENCES / DOCUMENTS 10SS21 SYMBOLOGY LINE LIST 30201-042-001000-001 Insulated Pipe Insulated and Traced Pipe ISOMETRIC INDEX 30303-042-001000-200 PIPING SUPPORT 30207-042-001000-001

E3D NAME027A1-021921-20-PNW-10SS21-0132-ET_01

EXTRACTION DAY 11 DEC 2020