Risk valuation using ProActive workflows



Basics



Value At Risk (VaR)

One-day 95% VaR of \$1 million ⇔ 5% probability that the portfolio worst-case loss will exceed \$1 million over a one-day period

Monte Carlo (MC) simulations

$$\widetilde{X_n} = \frac{1}{n} \sum_{i=1}^n X_i \xrightarrow{n \to +\infty} \mathbb{E} X$$

 $\widetilde{X_n} = \frac{1}{n} \sum_{i=1}^{n} X_i \xrightarrow{n \to +\infty} \mathbb{E} X$ The Law of Large Numbers states for large n, the empirical average is very close to the expected value

Estimating the VaR using MC simulations

$$\mathbb{P}(L_t > x) = \frac{1}{nb_VaR} \sum_{i=1}^{nb_VaR} \mathbb{1}_{L_t^i > x} = 1 - \alpha$$

$$L_t \text{ the portfolio loss at } t$$

$$\alpha \text{ the VaR probability}$$


x the portfolio VaR

nb_VaR the number of MC simulations

Monte_Carlo_VaR_portfolio.xml



Estimates the Monte Carlo Value at Risk (MC VaR) of a portfolio. We use the geometric Brownian motion (GBM) method to simulate stock price paths, but more advanced assets can be integrated thanks to the Quantlib C++ lib.




Monte_Carlo_VaR_portfolio.xml



Estimate the number of MC simulations per replicated task. The tasks number does not necessary divide the total number of simulations

Using Quanlib, each replicated task proceses a subset of the MC simulations and deduces the PnL (profit and loss) of each simulated path (value at horizon of a simulation - value at start). On the task side, PnLs are saved into a dedicated file


This task gathers all the PnLs into a single array, sorts them, and retrieves the VaR at the VaR_index corresponding to (1 - confidenceRate) * nbMC. Finally, it generates the corresponding frequencies bar chart and exposes it (view/download)



Monte_Carlo_VaR_portfolio.xml




Deta	ils							
₹ T	asks	Visualization	Users Sessions Statis	stics Usage				Job Info Task Info Output Server Logs Preview
Tag		Q Filter	✓ Auto-refresh					
	ld 📤	Status	Name	Tag	Duration	Nodes	Executions N -	Remote Visualization
▶	0	Finished	Split_MC_simulations		1s 668ms	1	0/2	Remote visualization is disabled. Please toggle streaming in output view for a job in order to enable the remote visualization
>	1	Finished	simulate_ptf_PnLs		4s 800ms	1	0/2	
Þ	2	Finished	process_VaR		3s 66ms	1	0/2	Task Result
▶	3	Finished	simulate_ptf_PnLs*1	REPLICATE-Split_M	4s 562ms	1	0/2	Task process VaR (id: 2) from job MCVaR (id: 1)
\triangleright	4	Finished	simulate_ptf_PnLs*2	REPLICATE-Split_M	4s 246ms	1	0/2	
\triangleright	5	Finished	simulate_ptf_PnLs*3	REPLICATE-Split_M	4s 720ms	1	0/2	
\triangleright	6	Finished	simulate_ptf_PnLs*4	REPLICATE-Split_M	3s 6ms	1	0/2	Open in browser
								Save as file
1				111			<u> </u>	
<< Fir	st < Pre	evious	Page 1 of	1	Tasks	1-7	Next > Last >>	



Monte_Carlo_VaR_portfolio_Interactive_Control.xml



The interactive version of the Monte_Carlo_VaR_portfolio workflow allows the user to relaunch it to add more MC simulations for a more accurate VaR. The estimated VaR can be "refined incrementally."



The user will be asked to specify the new MC simulation number to be aggregated to the VaR estimation.



incremental_Monte_Carlo_VaR_each_portfolio_asset.xml



Estimates the incremental VaR (iVaR) for each asset of the portfolio. iVaR quantifies the risk a position (or sub-portfolio) is adding to a portfolio. For instance, the iVaR related to an asset Y, is the difference between the portfolio VaR with and without Y.

Simulation	<u> </u>	
nbMC	10000	The number of Monte Carlo simulations per VaR estimation.
nbTimeSteps	255	The number of time steps to the horizon.
horizon	1	The horizon in year fraction.
assets_params_file_path_from_dataspace	assets.txt	The relative path from the dataspace of the asset params file following the csv format.
assets_correlations_file_path_from_dataspace	assets_correlations.txt	The relative path from the dataspace of the asset correlations file.
VaR	107	
confidenceRate	0.99	The confidence level rate.
nbBins	50	The number of bins for the portfolio estimation distributions.
Parallelization		
nbTasksPerVaR	4	The number of ProActive replicated tasks per VaR estimation.
Display		
width_chart	1000	The width of the chart in pixels.
height_chart	500	The height of the chart in pixels.
	00	

incremental_Monte_Carlo_VaR_each_portfolio_asset.xml




Estimate the number of MC simulations per replicated task for each VaR (right branch and left branch). The tasks number must divide the total number of simulations

(left branch) A task submitting the Monte_Carlo_VaR_portfolio wkw by considering all assets specified by the user

(right branch) **1st level of replicated tasks:** a replicated task per asset (Y)


(right branch) Each replicated task instanciates an asset params files, by excluding an asset from the portfolio, ie setting to 0 the asset weight. Then each task submit the Monte_Carlo_VaR_portfolio wkw (2nd inner level of replicated tasks) with this instanciated asset params file as input.


Gather the portfolio VaR over all assets (left branch) and all partial VaRs (right branch). Compute and println the iVaR related to each asset (portfolio VaR estimated by the left branch - one portfolio VaR without the asset Y estimated by the right branch)











stress_testing_Monte_Carlo_value_portfolio.xml



Estimates the portfolio PnL (Profit and Loss) over stressed volatilities and risk free rates.

Simulation	86	
nb_MC_per_ptf_value	1000	The number of Monte Carlo simulations per portfolio estimation.
nb_time_steps	255	The number of time steps to the horizon.
stress_horizon	1	The stress horizon in year fraction.
assets_params_file_path_from_dataspace	assets.txt	The relative path from the dataspace of the asset params file following the csv format.
assets_correlations_file_path_from_dataspace	assets_correlations.txt	The relative path from the dataspace of the asset correlations file.
stressed_risk_free_rate_min_max_in_percent_and_steps	-10%,+10%,8	The min, max, step of the stressed risk free rate range.
stressed_volatility_min_max_in_percent_and_steps	-5%,+5%,8	The min, max, step of the stressed volatility rate range.
Parallelization		
nb_replicated_tasks	4	The number of ProActive replicated tasks which must divide the risk free rate step number x the volatility step number. These latter are deduced from stressed_risk_free_rate_min_max_in_percent_and_steps and stressed_volatility_min_max_in_percent_and_steps respectively.
Others		
DOCKER_ENABLED	TRUE O FALSE	If true, the workflow tasks will be executed inside a docker container

stress_testing_Monte_Carlo_value_portfolio.xml




Estimate the number of MC simulations per replicated task. The tasks number must divide the total number of simulations

Using Quanlib, each replicated task processes a subset of the MC simulations and deduces the PnL (profit and loss) of each simulated path. An expected PnL is estimated per risk free rate and volatility stressed percentage. On the task side, PnLs are saved into a dedicated file


Merge all stressed PnLs into a single csv file

Plot a 3D representation of the stressed PnLs



stress_testing_Monte_Carlo_value_portfolio.xml






Identically as the Monte_Carlo_VaR_portfolio workflow, an interactive version is available to add more MC simulations to each stressed portfolio estimation (see stress_testing_Monte_Carlo_value_portfolio_Interactive_Control).



REDUCTION BY SCENARIOS

Estimates a Mark-to-Future (MtF) cube of a bond portfolio. Each cell of the cube integrates the valuation of a bond at a specific time given a specific scenario. This can be easily extended thanks to the high maintenability of the implementation (C++ Quantlib for the pricing engine, inputs split in Java/Groovy, R for the cube/cubelet stats,..).





evaluation_date_start evaluation_date_start evaluation_frequency bisseeHy bisseeHy free discretization. The end date of the evaluation. The time discretization. The start of the shocked yield range. The start of the shocked yield range. The start of the shocked yield range. The end of the shocked yield range. The yield step of the shocked yield range. The yield step of the shocked yield range. The relative path from the dataspace of the bond params file following the tsv format. Parallelization nb_replicated_tasks nb_replicated_tasks rhb_replicated_tasks_per_cubelet The number of ProActive replicated tasks, each having in charge a cubelet, i.e. a subset of the instruments. Hardware Resources node_source_compute_intensive_exclusive node_source_compute_intensive_exclusive node_source_compute_intensive data_dir_path Attrip The path of the output files. The path of the output files.	Simulation		
evaluation_frequency shocked_yield_start shocked_yield_end shocked_yield_range. The price is the shocked yield range. The relative path from the dataspace of the bond params file following the tsv format. The relative path from the dataspace of the bond params file following the tsv format. The relative path from the dataspace of the bond params file following the tsv format. The number of ProActive replicated tasks, each having in charge a cubelet, i.e. a subset of the senarios. The number of ProActive replicated tasks, each having in charge a cubelet, i.e. a subset of the instruments. Hardware Resources node_source_compute_memory_intensive_exclusive node_source_compute_intensive Name of the targeted node source dedicated to compute intensive tasks. Name of the targeted node source dedicated to memory intensive tasks. Name of the targeted node source dedicated to memory intensive tasks.			The start date of the evalution.
shocked_yield_end shocked_yield_end shocked_yield_end shocked_yield_end shocked_yield_end shocked_yield_end shocked_yield_end shocked_yield_end shocked_yield_end shocked_yield_tarage. The yield step of the shocked yield range. The relative path from the dataspace of the bond params file following the tax format. Parallelization nb_replicated_tasks nb_replicated_tasks 2 The number of ProActive replicated tasks, each having in charge a cubelet, i.e. a subset of the senarios. The number of ProActive replicated tasks, each having in charge a cubelet, i.e. a subset of the instruments. Hardware Resources node_source_compute_memory_intensive_exclusive node_source_compute_intensive Name of the targeted node source dedicated to compute intensive tasks. Name of the targeted node source dedicated to memory intensive tasks. Others Trup	evaluation_date_end		The end date of the evalution.
shocked_yield_elate shocked_yield_delta shocked_yield_delta shocked_yield_delta shocked_yield_delta shocked_yield_delta shocked_yield_delta shocked_yield_delta shocked_yield_delta shocked_yield_range. The yield step of the shocked yield range. The relative path from the dataspace of the bond params file following the tsv format. Parallelization Inb_replicated_tasks Inb_replicated_tasks_per_cubelet The number of ProActive replicated tasks, each having in charge a cubelet, i.e. a subset of the senarios. The number of ProActive replicated tasks, each having in charge a cubelet, i.e. a subset of the instruments. Hardware Resources node_source_compute_intensive Indees ource_compute_intensive Name of the targeted node source dedicated to compute intensive tasks. Name of the targeted node source dedicated to memory intensive tasks. Name of the targeted node source dedicated to memory intensive tasks.	evaluation_frequency	biweekly	The time discretization.
shocked_yield_delta shocked_yield_delta bonds_params_file_path_from_dataspace bonds_bonds_params_file_path_from_dataspace bonds_txt The relative path from the dataspace of the bond params file following the tsv format. Parallelization nb_replicated_tasks nb_replicated_tasks_per_cubelet Parallelization 2 The number of ProActive replicated tasks, each having in charge a cubelet, i.e. a subset of the senarios. The number of ProActive replicated tasks, each having in charge a cubelet, i.e. a subset of the instruments. Hardware Resources node_source_compute_memory_intensive	shocked_yield_start	0	The start of the shocked yield range.
The yield step of the shocked yield range. Donds_params_file_path_from_dataspace	shocked_yield_end	0.1	The end of the shocked yield range.
The relative path from the dataspace of the bond params file following the tsv format. Parallelization Description	shocked_yield_delta	0.005	The yield step of the shocked yield range.
The number of ProActive replicated tasks, each having in charge a cubelet, i.e. a subset of the senarios. The number of ProActive replicated tasks, each having in charge a cubelet, i.e. a subset of the instruments. The number of ProActive replicated tasks, each having in charge a cubelet, i.e. a subset of the instruments. The number of ProActive replicated tasks, each having in charge a cubelet, i.e. a subset of the instruments. The number of ProActive replicated tasks, each having in charge a cubelet, i.e. a subset of the instruments. The number of ProActive replicated tasks, each having in charge a cubelet, i.e. a subset of the instruments. The number of ProActive replicated tasks, each having in charge a cubelet, i.e. a subset of the instruments. The number of ProActive replicated tasks, each having in charge a cubelet, i.e. a subset of the instruments. The number of ProActive replicated tasks, each having in charge a cubelet, i.e. a subset of the instruments. The number of ProActive replicated tasks, each having in charge a cubelet, i.e. a subset of the instruments. The number of ProActive replicated tasks, each having in charge a cubelet, i.e. a subset of the instruments. The number of ProActive replicated tasks, each having in charge a cubelet, i.e. a subset of the instruments. The number of ProActive replicated tasks, each having in charge a cubelet, i.e. a subset of the instruments. The number of ProActive replicated tasks, each having in charge a cubelet, i.e. a subset of the instruments.	bonds_params_file_path_from_dataspace	bonds.txt	The relative path from the dataspace of the bond params file following the tsv format.
The number of ProActive replicated tasks, each having in charge a cubelet, i.e. a subset of the instruments. Hardware Resources node_source_compute_memory_intensive_exclusive node_source_compute_intensive node_source_memory_intensive Name of the targeted node source dedicated to compute intensive tasks. Name of the targeted node source dedicated to memory intensive tasks. Others /tmp	Parallelization	·	
Hardware Resources node_source_compute_memory_intensive_exclusive node_source_compute_intensive node_source_memory_intensive Name of the targeted node source dedicated to compute intensive tasks. Name of the targeted node source dedicated to memory intensive tasks. Others /tmo	nb_replicated_tasks	2	The number of ProActive replicated tasks, each having in charge a cubelet, i.e. a subset of the senarios.
node_source_compute_memory_intensive_exclusive ○ TRUE ● FALSE Exclusive usage or not of the targeted node sources. node_source_compute_intensive Name of the targeted node source dedicated to compute intensive tasks. Name of the targeted node source dedicated to memory intensive tasks. Others /tmp	nb_replicated_tasks_per_cubelet	2	The number of ProActive replicated tasks, each having in charge a cubelet, i.e. a subset of the instruments.
node_source_compute_intensive node_source_memory_intensive Name of the targeted node source dedicated to compute intensive tasks. Name of the targeted node source dedicated to memory intensive tasks.	Hardware Resources		
node_source_memory_intensive Name of the targeted node source dedicated to memory intensive tasks. Others /tmp	node_source_compute_memory_intensive_exclusive	○ TRUE ● FALSE	Exclusive usage or not of the targeted node sources.
Others /tmp	node_source_compute_intensive		Name of the targeted node source dedicated to compute intensive tasks.
/tmp	node_source_memory_intensive		Name of the targeted node source dedicated to memory intensive tasks.
data_dir_path /tmp The path of the output files.	<u>Others</u>	-	
	data_dir_path	/tmp	The path of the output files.



Split the scenarios and bonds over the replicated tasks


1st level of replicated tasks: a replicated task per subset of scenarios

Each replicated task pull from the catalog and submit the cubelet simulation workflow

Compute the portfolio clean prices per scenario and evaluation date (cubelets)

Merge the portfolio clean prices into a single csv file (cube). Compute portfolio prices time series for each scenario and create a csv file. Compute correlations over scenarios and create a csv file + heat map png file

Allow user to visualize/download the png/csv zip files



Init parameters

2nd level of replicated tasks: a replicated task per subset of bonds

Using Quanlib, each replicated task estimates a subset of the portfolio clean prices (cubelet)

Merge cubelets (bonds -> portfolio) and create a csv file

