

ICPC Team Notebook

typedef unsigned long long ll;
Sorbonne Université
SWERC 2025

A curated reference of algorithms and data structures



November 16, 2025

Contents

1 Math	1
1.1 Fourier Transform	1
1.2 Linear Algebra	1
1.3 Matrix Operations	1
1.4 Number Theory	2
1.5 Useful NT Functions in Python	2
1.6 Useful NT Functions in c++	2
2 Data Structures	3
2.1 Fenwick Tree	3
2.2 RMQ	3
2.3 Segment Tree(s)	3
2.4 Trie	4
2.5 Union find	4
3 Graph Algorithms	4
3.1 2-SAT	4
3.2 Articulation Points and Bridges	5
3.3 Cycle detection	5
3.4 Euler paths	5
3.5 Hungarian	6
3.6 Iterative dfs	6
3.7 LCA	6
3.8 Max Bipartite Matching	6
3.9 Max Flow Min Cut	7
3.10 Min Cost Flow	7
3.11 Minimum Spanning Tree	8
3.12 Shortest Path	8
3.13 Strongly Connected Components	8
3.14 Toposort	9
4 Dynamic Programming	9
4.1 Coin Change	9
4.2 Convex Hull Trick	9
4.3 Kadane	9
4.4 Knapsack	9
4.5 Longest Increasing Subsequence	9
4.6 MinPathSum	10
4.7 TSP	10
5 Strings	10
5.1 Aho-Corasick	10
5.2 Knuth-Morris-Pratt	10
5.3 Manacher	11
5.4 SuffixArray	11
6 Arrays	11
6.1 Inversions	11
7 Utilities	12
7.1 STL	12

1 Math

1.1 Fourier Transform

FFT: in-place, invert=false for forward, true for inverse Input size must be power of two $O(n \log n)$

```
void fft(vector<complex<double>> &a, bool invert) {
    int n = a.size();
    for (int i = 1, j = 0; i < n; i++) {
        int bit = n >> 1;
        for (; j & bit; bit >>= 1)
```

```
        j ^= bit;
        j ^= bit;
        if (i < j) swap(a[i], a[j]);
    }
    for (int len = 2; len <= n; len <<= 1) {
        double ang = 2 * M_PI / len * (invert ? -1 : 1);
        complex<double> wlen(cos(ang), sin(ang));
        for (int i = 0; i < n; i += len) {
            complex<double> w(1);
            for (int j = 0; j < len / 2; j++) {
                complex<double> u = a[i + j];
                complex<double> v = a[i + j + len / 2] * w;
                a[i + j] = u + v;
                a[i + j + len / 2] = u - v;
                w *= wlen;
            }
        }
    }
    if (invert) {
        for (auto &x : a) x /= n;
    }
}
```

Multiply two polynomials, where $a[i]$ is the coefficient of x^i

```
vi multiply(vi &a, vi &b) {
    vector<complex<double>> fa(a.begin(), a.end()), fb(b.begin(), b.end());
    int n = 1; while (n < a.size() + b.size()) n <<= 1; // next power of 2
    fa.resize(n); fb.resize(n);
    fft(fa, false); fft(fb, false); // forward FFT
    for (int i = 0; i < n; i++) fa[i] *= fb[i]; // pointwise multiply
    fft(fa, true); // inverse FFT
    vi res(n);
    for (int i = 0; i < n; i++) res[i] = round(fa[i].real());
    return res;
}
```

1.2 Linear Algebra

Solve $Ax = b$ using Gaussian elimination $O(n^3)$

```
def solve_gauss(a, b):
    n = len(a)
    a = [row[:] + [b[i]] for i, row in enumerate(a)]
    for i in range(n):
        pivot_row = max(range(i, n), key=lambda r: abs(a[r][i]))
        if abs(a[pivot_row][i]) < 1e-12:
            return None
        a[i], a[pivot_row] = a[pivot_row], a[i]
        pivot = a[i][i]
        for j in range(i, n + 1):
            a[i][j] /= pivot
        for r in range(i + 1, n):
            factor = a[r][i]
            for c in range(i, n + 1):
                a[r][c] -= factor * a[i][c]

    x = [0] * n
    for i in range(n - 1, -1, -1):
        x[i] = a[i][n]
        for j in range(i + 1, n):
            x[i] -= a[i][j] * x[j]
    return x
```

Maximizes $c^T x$ s.t. $Ax \leq b, x \geq 0$

```
def simplex(A, b, c):
    m, n = len(A), len(c)
    tableau = []
```

```

for i in range(m):
    tableau.append(A[i][:] + [1 if j == i else 0 for j in range(m)] + [b[i]])
tableau.append([-c_j for c_j in c] + [0] * (m + 1))
basic = list(range(n, n + m))
while True:
    entering = -1
    for j in range(n + m):
        if tableau[-1][j] < -1e-12:
            if entering == -1 or tableau[-1][j] < tableau[-1][entering]:
                entering = j
    if entering == -1: # Optimal solution found
        break
    leaving = -1
    min_ratio = float('inf')
    for i in range(m):
        if tableau[i][entering] > 1e-12:
            ratio = tableau[i][-1] / tableau[i][entering]
            if ratio < min_ratio - 1e-12:
                min_ratio = ratio
                leaving = i
    if leaving == -1: # Unbounded problem
        return None, float('inf')
    pivot = tableau[leaving][entering]
    for j in range(n + m + 1):
        tableau[leaving][j] /= pivot
    for i in range(m + 1):
        if i != leaving:
            factor = tableau[i][entering]
            for j in range(n + m + 1):
                tableau[i][j] -= factor * tableau[leaving][j]
    basic[leaving] = entering
x = [0] * n
for i in range(m):
    if basic[i] < n:
        x[basic[i]] = tableau[i][-1]
return x, tableau[-1][-1]

```

1.3 Matrix Operations

Performs matrix multiplication in $O(n^3)$. Watch out for overflow.

```

matrix mult(const matrix &a, matrix &b) {
    int i, j, k, m = a.size(), n = a[0].size(), p = b[0].size();
    matrix res = matrix(m, vi(p, 0));
    for (i = 0; i < m; i++) for (j = 0; j < p; j++)
        for (k = 0; k < n; k++)
            res[i][j] += a[i][k] * b[k][j];
    return res;
}

```

Calculates a^p in $O(n^3 \log p)$. Watch out for overflow. Modifies matrix.

```

matrix pow(matrix &a, int p) {
    int l = a.size(), i;
    matrix b(l, vi(l, 0));
    for (i = 0; i < l; i++) b[i][i] = 1;
    while (p) {
        if (p & 1) {b = mult(b, a); p--;}
        a = mult(a, a);
        p >>= 1;
    }
    return b;
}

```

Gauss-Jordan on an augmented matrix, returns determinant, modifies matrix. $O(n^3)$

```

double gaussJordan(matrix &a, int &rank, int &augRank) {
    int n = a.size(), m = a[0].size() - 1; // n eqs, m vars

```

```

double det = 1.0; rank = 0;
for (int j = 0; j <= m; j++) {
    int pivotRow = -1;
    double maxVal = 0;
    for (int i = rank; i < n; i++)
        if (pivotRow < 0 || abs(a[i][j]) > maxVal) {
            maxVal = abs(a[i][j]);
            pivotRow = i;
        }
    if (maxVal > 1e-7) {
        double c = a[pivotRow][j];
        if (pivotRow != rank) det = -det;
        det *= c;
        for (int k = j; k <= m; k++) {
            swap(a[pivotRow][k], a[rank][k]);
            a[rank][k] /= c;
        }
        for (int i = rank + 1; i < n; i++) {
            c = a[i][j];
            for (int k = j; k <= m; k++)
                a[i][k] -= c * a[rank][k];
        }
        if (j < m) rank++;
    }
}
augRank = rank;
for (int i = rank; i < n; i++)
    if (abs(a[i][m]) > 1e-6) { augRank++; break; }
if (rank != n) det = 0;
return det;
}

```

Solve $Ax=b$. Input:[A—b] (augmented matrix) $O(n^3)$. Modifies Matrix.

```

void solve(matrix &a, vi &solution) {
    int n = a.size(), m = a[0].size() - 1;
    solution.assign(m, 0.0);
    for (int i = n - 1; i >= 0; i--) {
        double c = a[i][m];
        for (int j = i + 1; j < m; j++)
            c -= a[i][j] * solution[j];
        solution[i] = c;
    }
}

```

1.4 Number Theory

Linear diophantine equations: Let $a, b, c \in \mathbb{N}$. The equation $ax + by = c$ has integer solutions iff c is a multiple of $\gcd(a, b)$. If (x_0, y_0) is a solution for the equation (c.f. Extended Euclidean Algorithm), then all integer solutions are given by $(x_0 - b't, y_0 + a't)$ with $t \in \mathbb{N}, a' = \frac{a}{\gcd(a, b)}, b' = \frac{b}{\gcd(a, b)}$.

Chinese remainder theorem: Let $n_1, \dots, n_k \in \mathbb{N}$ pairwise coprime, and $b_1, \dots, b_k \in \mathbb{N}$. The system of linear congruencies $x \equiv b_i \pmod{n_i}$ for $1 \leq i \leq k$ has a unique solution $\pmod{\prod_{i=1}^k n_i}$, constructed as follows: Let $a_i = \frac{N}{n_i}$ and c_i its inverse $\pmod{n_i}$. Then, $x \equiv \sum_{i=1}^k a_i b_i c_i \pmod{\prod_{i=1}^k n_i}$

$\gcd(a, b) = \gcd(a, b \bmod a)$, $\text{lcm}(a, b) = \frac{ab}{\gcd(a, b)}$, $\gcd(a, b, c) = \gcd(\gcd(a, b), c)$, $\text{lcm}(a, b, c) = \text{lcm}(\text{lcm}(a, b), c)$

1.5 Useful NT Functions in Python

Sieve of Gries-Misra $O(n)$. Produces prime list and SPF array

```

def gries_misra(n):
    primes = []
    factor = [0] * n

```

```

for x in range(2, n):
    if not factor[x]:      # no factor found
        factor[x] = x     # meaning x is prime
        primes.append(x)

    for p in primes:      # loop over primes found so far
        if p > factor[x] or p * x >= n:
            break
        factor[p * x] = p # p is the smallest factor of p * x

return primes, factor

```

Returns (u,v) s.t. $au + bv = \gcd(a, b)$ in $O(\log a + \log b)$

```

def bezout(a, b):
    if b == 0:
        return (1, 0)
    u, v = bezout(b, a % b)
    return (v, u - (a // b) * v)

```

Inverse of a in $\mathbb{Z}_p$ in $O(\log a + \log p)$

```

def inv(a, p):
    return bezout(a, p)[0] % p

```

$\binom{n}{k} \bmod p$ in $O(k)$

```

def binom_modulo(n, k, p):
    prod = 1
    for i in range(k):
        prod = (prod * (n - i) * inv(i + 1, p)) % p
    return prod

```

Constructs an arithmetic expression tree. Input: tokens e.g. ["1", "+", "2"]

```

def arithm_expr_parse(tokens):
    vals, ops = [], []
    PRIO = {'+':1, '-':1, '*':2, '/':2, '(':0}
    for t in tokens:
        if t in PRIO:
            while ops and PRIO[ops[-1]] >= PRIO[t] and t != '(':
                vals.append((vals.pop(-2), ops.pop(), vals.pop()))
                ops.append(t)
            elif t == ')':
                while ops[-1] != '(':
                    vals.append((vals.pop(-2), ops.pop(), vals.pop()))
                ops.pop()
            else:
                vals.append(int(t) if t.isdigit() else t)
        while ops:
            vals.append((vals.pop(-2), ops.pop(), vals.pop()))
    return vals[0]

```

1.6 Useful NT Functions in c++

Sieve of Eratosthenes: $O(n \log \log n)$ sieve[i] = 0 if i prime, spf otherwise for fast fact

```

vi sieve(int n){
    vi sieve(n,0);
    for(int i = 2; i*i < n ; i++)
        if(!sieve[i])
            for(int j = i*i ; j < n ; j += i)
                if(!sieve[j]) sieve[j] = i;
    return sieve;
}

```

Fast exponentiation $O(\log b)$: fast $a^b \bmod p$.

```

int modular_exp(int a, int b, int p){
    int res = 1;
    while(b > 0){
        if(b & 1) res = (1LL * a * res) % p;
        b = b >> 1;
    }
}

```

```

        a = (1LL * a * a) % p;
    }
    return res;
}

```

Euler's φ : Number of ints $\leq n$ coprime to n .

```

int phi(int n, vi& primes) {
    int res = n;
    for (int p : primes) {
        if (1LL * p * p > n) break;
        if (n % p == 0) {
            while (n % p == 0) n /= p;
            res -= res / p;
        }
    }
    if (n > 1) res -= res / n;
    return res;
}

```

Extended Euclidean Algorithm Solves $ax + by = \gcd(a, b)$.

```

ll eea(ll a, ll b, ll& x, ll& y) {
    ll xx = y = 0, yy = x = 1;
    while (b) {
        ll q = a / b, t = b; b = a%b; a = t;
        t = xx; xx = x - q*xx; x = t;
        t = yy; yy = y - q*yy; y = t;
    }
    return a; // Returns gcd(a,b)
}

```

2 Data Structures

2.1 Fenwick Tree

Point update, prefix and range sum, $O(\log n)$, $O(n)$ build

```

struct Fenwick {
    int n; vector<ll> t; //using long long, int might overflow.
    Fenwick(vector<ll>& a): n(a.size()), t(n+1,0) {
        for(int i = 1; i <= n; i++) { // Builds tree from array in O(n)
            t[i] += a[i-1];
            int p = i+(i&-i);
            if(p<=n) t[p] += t[i];
        }
    }
    void add(int i, long long v){
        for(; i<=n; i+=i&-i) t[i] += v;
    }
    long long sum(int i){
        long long r=0;
        for(; i>0 ; i -= i&-i) r += t[i];
        return r;
    }
    long long sum(int l, int r){ return sum(r)-sum(l-1); }
};

```

2.2 RMQ

Preprocess an array in $O(n \log n)$ to answer range minimum queries in $O(1)$

```

struct RMQ {
    vvi jmp;
    RMQ(const vi& V) { // Python: depth = N.bit_length()
        int N = V.size(), depth = 32 - __builtin_clz(N);
        jmp.assign(depth, V);
        for(int i = 0; i < depth-1; ++i)

```

```

        for(int j = 0; j < N; ++j)
            jmp[i+1][j] = min(jmp[i][j],
                               jmp[i][min(N-1, j + (1<<i))]);
    } // Returns min{V[a], V[a+1], ..., V[b-1]}
    int query(int a, int b) {
        if(b <= a) return INT_MAX;
        int dep = 31 - __builtin_clz(b - a); // python: (b-a).bit_length() - 1
        return min(jmp[dep][a], jmp[dep][b - (1<<dep)]);
    }
};

```

2.3 Segment Tree(s)

Regular seg tree: point update, range sum query, $O(\log n)$

```

struct SegTree {
    int n; vector<ll> t;
    SegTree(vi &a): n(a.size()), t(4*n) { build(a,1,0,n); }
    void build(vi &a,int v,int l,int r){
        if(r-l == 1){ t[v]=a[l]; return; }
        int m = (l+r)/2;
        build(a, 2*v, l, m); build(a, 2*v+1, m, r);
        t[v] = t[2*v] + t[2*v+1];
    }
    ll sum_aux(int v,int l,int r,int ql,int qr){
        if(qr <= l || r <= ql) return 0;
        if(ql <= l && r <= qr) return t[v];
        int m = (l+r)/2;
        return sum_aux(2*v, l,m,ql,qr) + sum_aux(2*v+1, m,r,ql,qr);
    }
    ll sum(int ql,int qr){ return sum_aux(1,0,n,ql,qr); }
    void upd_aux(int v,int l,int r,int pos,ll val){
        if(r-l==1){ t[v]=val; return; }
        int m = (l+r)/2;
        if(pos<m) upd_aux(2*v,l,m,pos,val);
        else upd_aux(2*v+1,m,r,pos,val);
        t[v]=t[2*v]+t[2*v+1];
    }
    void upd(int pos,ll val){ upd_aux(1,0,n,pos,val); }
};

```

Lazy SegTree: range add, range sum query, $O(\log n)$

```

struct LazySegTree {
    int n; vector<ll> t, lazy;
    LazySegTree(vi &a):n(a.size()),t(4*n),lazy(4*n){build(a,1,0,n);}
    void build(vi &a,int v,int l,int r){
        if(r-l == 1){ t[v]=a[l]; return; }
        int m = (l+r)/2;
        build(a,2*v,l,m); build(a,2*v+1,m,r);
        t[v] = t[2*v]+t[2*v+1];
    }
    void push(int v,int l,int r){
        if(lazy[v]==0) return;
        t[v] += lazy[v]*(r-l);
        if(r-l>1){
            lazy[2*v] += lazy[v];
            lazy[2*v+1] += lazy[v];
        }
        lazy[v]=0;
    }
    void upd_aux(int v,int l,int r,int ql,int qr,ll val){
        push(v,l,r);
        if(qr<=l || r<=ql) return;
        if(ql<=l && r<=qr){
            lazy[v] += val; push(v,l,r);
            return;
        }
    }
};

```

```

    }
    int m = (l+r)/2;
    upd_aux(2*v, l,m,ql,qr,val);
    upd_aux(2*v+1, m,r,ql,qr,val);
    t[v] = t[2*v] + t[2*v+1];
}
ll sum_aux(int v,int l,int r,int ql,int qr){
    push(v,l,r);
    if(qr<=l || r<=ql) return 0;
    if(ql<=l && r<=qr) return t[v];
    int m = (l+r)/2;
    return sum_aux(2*v, l,m,ql,qr) + sum_aux(2*v+1, m,r,ql,qr);
}
void upd(int ql,int qr,ll val){ upd_aux(1,0,n,ql,qr,val); }
ll sum(int ql,int qr){ return sum_aux(1,0,n,ql,qr); }
};

```

Iterative SegTree: point update, range sum query, $O(\log n)$

```

struct IterSegTree {
    int n; vector<ll> t;
    IterSegTree(vi &a): n(a.size()), t(2*n) {
        for(int i=0;i<n;i++) t[n+i]=a[i];
        for(int i=n-1;i>0;i--) t[i]=t[i<<1]+t[i<<1|1];
    }
    void upd(int pos,ll val){
        pos+=n; t[pos]=val;
        for(pos>>=1; pos>0; pos>>=1) t[pos]=t[pos<<1]+t[pos<<1|1];
    }
    ll sum(int l,int r){
        ll res=0;
        for(l+=n,r+=n;l<r;l>>=1,r>>=1){
            if(l&1) res+=t[l++];
            if(r&1) res+=t[--r];
        }
        return res;
    }
};

```

2.4 Trie

Prefix tree: stores strings, insert/find in $O(|s|)$; handles lowercase letters a-z

```

struct Node{
    int next[26]; bool isEnd=false;
    Node(){fill(begin(next), end(next), -1);}
};
struct Trie{
    vector<Node> t;
    Trie() {t.emplace_back();}
    void insert(string s){
        int cur = 0;
        for (auto c : s){
            if (t[cur].next[c-'a'] == -1){
                t.emplace_back(); // Adds new node
                t[cur].next[c-'a'] = t.size() - 1;
            }
            cur = t[cur].next[c-'a'];
        }
        t[cur].isEnd = true;
    }
    bool find(string s){
        int cur = 0;
        for (auto c : s){
            if (t[cur].next[c-'a'] == -1) return false;
        }
    }
};

```

```

    cur = t[cur].next[c-'a'];
}
return t[cur].isEnd;
}
};

```

2.5 Union find

Complexity: effectively $O(1)$

```

struct union_find{
    vector<int> rank, parent;
    union_find(int n){
        rank.resize(n, 0); parent.resize(n);
        for (int i = 0; i < n; i++) parent[i] = i;
    }
    int find(int i){
        int root = parent[i];
        if (parent[root] != root) return parent[i] = find(root);
        return root;
    }
    void unite(int x, int y) {
        int xRoot = find(x);
        int yRoot = find(y);
        if (xRoot == yRoot) return;
        if (rank[xRoot] < rank[yRoot]) parent[xRoot] = yRoot;
        else if (rank[yRoot] < rank[xRoot]) parent[yRoot] = xRoot;
        else{
            parent[yRoot] = xRoot;
            rank[xRoot]++;
        }
    }
};

```

3 Graph Algorithms

3.1 2-SAT

Check if n variables satisfy $(x_i \vee x_j) \wedge (\neg x_k \vee x_l) \wedge \dots$

```

struct TwoSAT {
    int n; SCC g; // c.f. strongly connected components
    TwoSAT(int vars): n(vars), g(2*vars) {}
    int var(int i){ return i; }
    int neg(int i){ return i+n; }
    void add_clause(int a, bool a_val, int b, bool b_val){
        int u = a_val ? var(a) : neg(a);
        int v = b_val ? var(b) : neg(b);
        g.add_edge(u^1, v); //  $\neg a \rightarrow b$ .  $\wedge$  bitwise XOR, same in python
        g.add_edge(v^1, u); //  $\neg b \rightarrow a$ 
    }
    bool satisfiable(vi& ans){
        g.kosaraju();
        ans.assign(n,0);
        for(int i=0;i<n;i++){
            if(g.scc[var(i)] == g.scc[neg(i)]) return false;
            ans[i] = g.scc[var(i)] > g.scc[neg(i)];
        }
        return true;
    }
};

```

3.2 Articulation Points and Bridges

$O(V + E)$

AP = vertices whose removal increases # of connected components.

Bridge = edges whose removal increases # of connected components.

```

void tarjan(int u, vvi &adj, vi &vis, vi &disc, vi &low,
            int &time, int p, vi &isAP, set<pii> &bridges) {
    vis[u] = 1;
    disc[u] = low[u] = ++time;
    int children = 0;
    for (int v : adj[u]) {
        if (v == p) continue;
        if (!vis[v]) {
            children++;
            tarjan(v, adj, vis, disc, low, time, u, isAP, bridges);
            low[u] = min(low[u], low[v]);
            if (low[v] > disc[u]) // Bridge
                bridges.insert({min(u, v), max(u, v)});
            if (p != -1 && low[v] >= disc[u])
                isAP[u] = 1; // Articulation Point
        }
        else low[u] = min(low[u], disc[v]);
    }
    if (p == -1 && children > 1)
        isAP[u] = 1;
}

pair<vi, set<pii>> findAPandBridges(int V, vvi &adj) {
    vi disc(V), low(V), vis(V), isAP(V); // Initialize with 0s
    set<pii> bridges;
    int time = 0;
    for (int i = 0; i < V; i++)
        if (!vis[i])
            tarjan(i, adj, vis, disc, low, time, -1, isAP, bridges);
    return {isAP, bridges};
}

```

3.3 Cycle detection

Returns a cycle in a directed graph, or empty if none exists. $O(n + m)$

```

vi dfs_cycle(const vvi &adj) {
    int n = adj.size();
    vi color(n, 0), path;
    vi cycle;
    function<bool(int)> dfs = [&](int v) {
        color[v] = 1; path.push_back(v);
        for (int u : adj[v]) {
            if (color[u] == 0 && dfs(u)) return true;
            else if (color[u] == 1) {
                auto it = find(path.begin(), path.end(), u);
                cycle.assign(it, path.end());
                return true;
            }
        }
        path.pop_back(); color[v] = 2;
        return false;
    };
    for (int i = 0; i < n; i++)
        if (color[i] == 0 && dfs(i)) break;
    return cycle;
}

```

Check if undirected graph contains a cycle in $O(m)$.

```

bool dsu_cycle(int n, vvi &edges) {
    union_find uf(n); //c.f. union find
    for (auto &e : edges) {
        if (uf.find(e[0]) == uf.find(e[1])) return true;
        uf.unite(e[0], e[1]);
    }
}

```

```

}
return false;
}

```

Tortoise & Hare: finds start of cycle in a functional graph (-1 if none). $O(n)$

```

int floyd_cycle(int start, vi& nxt){
    int tort=start, hare=start;
    do {
        if(hare==-1 || nxt[hare]==-1) return -1;
        tort = nxt[tort];
        hare = nxt[nxt[hare]];
    } while(tort!=hare);
    tort=start;
    while(tort!=hare){
        tort=nxt[tort]; hare=nxt[hare];
    }
    return tort;
}

```

3.4 Euler paths

Euler Path/Circuits:

Undirected:

- Circuit: all vertices even degree and connected.
- Path: exactly 2 odd-degree vertices and connected; start at one of them.
- Trick: to use circuit function for path, add dummy edge between odd vertices, find circuit, remove dummy.

Directed:

- Circuit: strongly connected, $\text{indegree}[v] == \text{outdegree}[v] \forall v$.
- Path: one vertex with $\text{out}-\text{in}=1$ (start), one with $\text{in}-\text{out}=1$ (end), rest balanced.
- Trick: add dummy edge $\text{end} \rightarrow \text{start}$, find circuit, rotate to remove dummy.

Find Euler path in directed graph. $O(E)$ MODIFIES THE GRAPH!!!

```

vi euler_directed(vvi &adj, int start=0) {
    vi path; stack<int> st; st.push(start);
    while(!st.empty()) {
        int v = st.top();
        if(!adj[v].empty()) {
            int u = adj[v].back(); adj[v].pop_back();
            st.push(u);
        } else {
            path.push_back(v);
            st.pop();
        }
    }
    reverse(path.begin(), path.end());
    return path; // size = E+1 if valid Euler tour
}

```

Input: $\text{adj}[u][i] = v, \text{id}$, $\text{adj}[v][j] = u, \text{id}$ if u and v adjacent (same id for both edges).

```

vi euler_undirected(int n, vector<vpi>& adj) {
    vi used, path; stack<int> st; st.push(0);
    int m=0; for (auto &v:adj) m += v.size(); used.assign(m/2,0);
    while(!st.empty()){
        int v=st.top();
        while(!adj[v].empty() && used[adj[v].back().second])
            adj[v].pop_back();
        if(adj[v].empty()){
            path.push_back(v);
            st.pop();
        } else {
            auto e=adj[v].back(); adj[v].pop_back();
            used[e.second]=1;
            st.push(e.first);
        }
    }
}

```

```

reverse(path.begin(), path.end());
return path;
}

```

3.5 Hungarian

Min cost assignment $O(n^3)$. Input cost matrix, output (min cost, assignment)

```

pair<int, vi> hungarian(const vvi &a) {
    int n = a.size(), m = a[0].size();
    vi u(n + 1), v(m + 1), p(m + 1), way(m + 1);
    for (int i = 1; i <= n; i++) {
        p[0] = i;
        vi minv(m + 1, 1e9); // INF constant
        vector<bool> used(m + 1, false);
        int j0 = 0;
        do {
            used[j0] = true;
            int i0 = p[j0], delta = 1e9, j1 = 0;
            for (int j = 1; j <= m; j++) if (!used[j]) {
                int cur = a[i0 - 1][j - 1] - u[i0] - v[j];
                if (cur < minv[j]) minv[j] = cur, way[j] = j0;
                if (minv[j] < delta) delta = minv[j], j1 = j;
            }
            for (int j = 0; j <= m; j++) {
                if (used[j]) u[p[j]] += delta, v[j] -= delta;
                else minv[j] -= delta;
            }
            j0 = j1;
        } while (p[j0] != 0);
        do {
            int j1 = way[j0];
            p[j0] = p[j1];
            j0 = j1;
        } while (j0);
    }
    vi match(n);
    for (int j = 1; j <= m; j++) if (p[j]) match[p[j] - 1] = j - 1;
    return {-v[0], match};
}

```

3.6 Iterative dfs

Iterative depth-first search

```

void dfs_iter(int start, vvi& adj, vi &output, vi& visited) {
    stack<int> st; st.push(start); visited[start] = 1;
    while (!st.empty()) {
        int v = st.top(); bool done = true;
        for (auto u : adj[v]) {
            if (!visited[u]) {
                visited[u] = 1; st.push(u);
                done = false; break;
            }
        }
        if (done) {
            st.pop(); output.push_back(v);
        }
    }
}

```

3.7 LCA

```

struct LCA {
    int n; vvi adj;
}

```

```

vi depth, first, euler;
RMQ rmq; // c.f. RMQ structure.
LCA(int _n) : n(_n), adj(n), depth(n), first(n), rmq(vi()) {}
void add_edge(int u, int v) { adj[u].push_back(v); adj[v].push_back(u); }
void dfs(int v, int p, int d) {
    first[v] = euler.size();
    depth[v] = d;
    euler.push_back(v);
    for(int u: adj[v]) if(u != p) {
        dfs(u, v, d+1);
        euler.push_back(v);
    }
}
void build(int root=0) {
    euler.clear();
    dfs(root, -1, 0);
    vi D(euler.size());
    for(int i=0; i<euler.size(); i++) D[i]=depth[euler[i]];
    rmq = RMQ(D);
} // dist(a,b) = depth[a] + depth[b] - 2 * depth[lca];
int query(int a, int b) {
    int l = first[a], r = first[b];
    if(l>r) swap(l,r);
    return euler[rmq.query(l,r+1)];
}
};

```

3.8 Max Bipartite Matching

König's theorem: In a bipartite graph, the number of edges in a maximum matching equals the number of vertices in a minimum vertex cover.

Hopcroft–Karp $O(E\sqrt{V})$ left $[0..nL-1]$, right $[0..nR-1]$ adj from left to right.

```

int nL, nR;
vector<vi>adj;
vi dist, matchL, matchR;
bool bfs() {
    queue<int> q;
    dist.assign(nL, -1);
    for (int u = 0; u < nL; ++u)
        if (matchL[u] == -1) dist[u] = 0, q.push(u);
    bool found = 0;
    while (!q.empty()) {
        int u = q.front(); q.pop();
        for (int v : adj[u]) {
            int mu = matchR[v];
            if (mu == -1) found = 1;
            else if (dist[mu] == -1) dist[mu] = dist[u] + 1, q.push(mu);
        }
    }
    return found;
}
bool dfs(int u) {
    for (int v : adj[u]) {
        int mu = matchR[v];
        if (mu == -1 || (dist[mu] == dist[u] + 1 && dfs(mu))) {
            matchL[u] = v; matchR[v] = u;
            return 1;
        }
    }
    dist[u] = -1;
    return 0;
}
int hopcroftKarp() {
    matchL.assign(nL, -1);

```

```

matchR.assign(nR, -1);
int matching = 0;
while (bfs())
    for (int u = 0; u < nL; ++u)
        if (matchL[u] == -1 && dfs(u))
            ++matching;
return matching;
}

```

3.9 Max Flow Min Cut

Dinic's max flow $O(V^2E)$, $O(E\sqrt{V})$ for bipartite/unit. Edges from reachable nodes after flow form a min cut.

```

struct FlowEdge {
    int v, u;
    long long cap, flow = 0;
    FlowEdge(int v, int u, long long cap) : v(v), u(u), cap(cap) {}
};

struct Dinic {
    const long long flow_inf = 1e18;
    vector<FlowEdge> edges;
    vector<vi> adj;
    int n, m = 0;
    int s, t; // source, target
    vi level, ptr;
    queue<int> q;
    Dinic(int n, int s, int t) : n(n), s(s), t(t) {
        adj.resize(n); level.resize(n); ptr.resize(n);
    }
    void add_edge(int v, int u, long long cap) {
        edges.emplace_back(v, u, cap);
        edges.emplace_back(u, v, 0);
        adj[v].push_back(m);
        adj[u].push_back(m + 1);
        m += 2;
    }
    bool bfs() {
        while (!q.empty()) {
            int v = q.front(); q.pop();
            for (int id : adj[v]) {
                if (edges[id].cap == edges[id].flow) continue;
                if (level[edges[id].u] != -1) continue;
                level[edges[id].u] = level[v] + 1;
                q.push(edges[id].u);
            }
        }
        return level[t] != -1;
    }
    long long dfs(int v, long long pushed) {
        if (pushed == 0) return 0;
        if (v == t) return pushed;
        for (int& cid = ptr[v]; cid < (int)adj[v].size(); cid++) {
            int id = adj[v][cid]; int u = edges[id].u;
            if (level[v] + 1 != level[u]) continue;
            long long tr = dfs(u, min(pushed, edges[id].cap - edges[id].flow));
            if (tr == 0) continue;
            edges[id].flow += tr;
            edges[id ^ 1].flow -= tr;
            return tr;
        }
        return 0;
    }
    long long flow() {

```



```

    long long f = 0;
    while (true) {
        fill(level.begin(), level.end(), -1);
        level[s] = 0; q.push(s);
        if (!bfs()) break;
        fill(ptr.begin(), ptr.end(), 0);
        while (long long pushed = dfs(s, flow_inf))
            f += pushed;
    }
    return f;
}

vector<pii> min_cut_edges() {
    vector<bool> vis(n, false);
    queue<int> q;
    q.push(s); vis[s] = true;
    while (!q.empty()) {
        int v = q.front(); q.pop();
        for (int id : adj[v]) {
            auto &e = edges[id];
            if (!vis[e.u] && e.cap > e.flow) {
                vis[e.u] = true;
                q.push(e.u);
            }
        }
    }
    vector<pii> cut;
    for (auto &e : edges) {
        if (vis[e.v] && !vis[e.u] && e.cap > 0) {
            cut.push_back({e.v, e.u});
        }
    }
    return cut;
}
};

```

3.10 Min Cost Flow

Finds min cost to send up to F flow (set F=INF for MCMF) $O(FE \log V)$. Handles neg costs (no neg cycles).

```

struct MCF {
    struct E { int v, rev, cap; ll cost; };
    int n; vector<vector<E>> g;
    MCF(int n): n(n), g(n) {}
    void addEdge(int u, int v, int cap, ll cost){
        g[u].push_back({v, (int)g[v].size(), cap, cost});
        g[v].push_back({u, (int)g[u].size()-1, 0, -cost});
    }
    pair<ll, ll> minCostFlow(int s, int t, int maxf){
        ll flow=0, cost=0; vll pot(n), dist(n); vi pv(n), pe(n);
        while(flow<maxf){
            fill(dist.begin(), dist.end(), LLONG_MAX);
            priority_queue<pii, vector<pii>, greater<>> pq;
            dist[s]=0; pq.push({0, s});
            while(!pq.empty()){
                auto [d, u]=pq.top(); pq.pop();
                if(d!=dist[u]) continue;
                for(int i=0; i<(int)g[u].size(); i++){
                    E &e=g[u][i]; if(!e.cap) continue;
                    ll nd=d+e.cost+pot[u]-pot[e.v];
                    if(nd<dist[e.v]){
                        dist[e.v]=nd; pv[e.v]=u; pe[e.v]=i;
                        pq.push({nd, e.v});
                    }
                }
            }
        }
    }
};

```

```

    }
    if(dist[t]==LLONG_MAX) break;
    for(int i=0; i<n; i++) if(dist[i]<LLONG_MAX) pot[i]+=dist[i];
    int add=maxf-flow;
    for(int v=t; v!=s; v=pv[v])
        add=min(add, g[pv[v]][pe[v]].cap);
    for(int v=t; v!=s; v=pv[v]){
        E &e=g[pv[v]][pe[v]];
        e.cap-=add; g[v][e.rev].cap+=add;
        cost+=add*e.cost;
    }
    flow+=add;
}
return {flow, cost};
}
};

```

3.11 Minimum Spanning Tree

Kruskal $O(E \log E)$ edges list of {u,v,weight}

```

int kruskal(int V, vvi &edges) {
    sort(edges.begin(), edges.end(), [](auto a, auto b){return a[2]<b[2];});
    union_find uf(V);
    int cost = 0, count = 0;
    for (auto &e : edges) {
        if (uf.find(e[0]) != uf.find(e[1])) {
            uf.unite(e[0], e[1]);
            cost += e[2];
            if (++count == V - 1) break;
        }
    }
    return cost;
}

```

Prim's $O((E + V) \log V)$ adj[u] list of (v,weight) adjacent to u.

```

int prim(int V, vector<vpi> &adj) {
    priority_queue<pii, vector<pii>, greater<pii>> q;
    vector<bool> vis(V, false);
    q.push({0, 0});
    int res = 0;
    while(!q.empty()){
        auto [w, u] = q.top(); q.pop();
        if(vis[u]) continue;
        res += w;
        vis[u] = true;
        for(auto v : adj[u]){
            if(!vis[v.first]){
                q.push({v.second, v.first});
                //weight, vertex
            }
        }
    }
    return res;
}

```

3.12 Shortest Path

Find shortest paths from src (no negative weights). $O((V+E) \log V)$

```

vi dijkstra(const vector<vector<pii>> &adj, int src) {
    vi dist(adj.size(), INT_MAX);
    priority_queue<pii, vector<pii>, greater<pii>> q;
    dist[src] = 0; q.push({0, src});
    while (!q.empty()) {
        auto [d, u] = q.top(); q.pop();
    }
}

```

```

    if (d != dist[u]) continue;
    for (auto [v, w] : adj[u]) {
        if (d+w < dist[v]) {
            dist[v] = d+w;
            q.push({d+w, v});
        }
    }
}
return dist;
}
}

```

$O(VE)$ Shortest Path+neg edges; BFS from nodes with dist $-\infty$ for all neg-cycle reachable.

```

vi bellmanFord(int n, vvi& edges, int src) {
    vector<int> dist(n, INT_MAX);
    dist[src] = 0;
    for (int i = 0; i < n; i++) {
        for (auto edge : edges) {
            int u = edge[0]; int v = edge[1]; int wt = edge[2];
            if (dist[u] != INT_MAX && dist[u] + wt < dist[v]) {
                if (i == n - 1) return {-1};
                dist[v] = dist[u] + wt;
            }
        }
    }
    return dist;
}
}

```

All-pairs shortest paths (neg edges ok, no neg cycles) $O(V^3)$ $graph[i][i] = 0$, $graph[i][j] = w$ if edge $i \rightarrow j$ else INT_MAX

```

vector<vi> floydWarshall(vector<vi> graph) {
    int V = graph.size();
    auto dist = graph;
    for (int k = 0; k < V; ++k)
        for (int i = 0; i < V; ++i)
            for (int j = 0; j < V; ++j)
                if (dist[i][k] < INT_MAX && dist[k][j] < INT_MAX)
                    dist[i][j] = min(dist[i][j], dist[i][k] + dist[k][j]);

    return dist;
}

```

3.13 Strongly Connected Components

Kosaraju SCC $O(n+m)$

```

struct SCC {
    int n, ordn = 0, scc_cnt = 0;
    vvi adj, adjt; vi vis, ord, scc;
    SCC(int n): n(n), adj(n), adjt(n), vis(n,0), ord(n), scc(n) {}
    void add_edge(int u, int v){ adj[u].push_back(v); adjt[v].push_back(u); }
    void dfs(int u){
        vis[u]=1;
        for(int v:adj[u]) if(!vis[v]) dfs(v);
        ord[ordn++]=u;
    }
    void dfst(int u){
        scc[u]=scc_cnt; vis[u]=0; // SCCs IDs are in reverse topological order.
        for(int v:adjt[u]) if(vis[v]) dfst(v);
    }
    void kosaraju(){
        for(int i=0;i<n;i++) if(!vis[i]) dfs(i);
        for(int i=ordn-1;i>=0;i--) if(vis[ord[i]]){ scc_cnt++; dfst(ord[i]); }
    }
};

```

3.14 Toposort

TopoSort via DFS $O(V + E)$.

```

void dfs(int u, vector<vi> &adj, vi &vis, vi &res) {
    vis[u] = 1;
    for (int v : adj[u])
        if (!vis[v])
            dfs(v, adj, vis, res);
    res.push_back(u);
}

vi toposort(vector<vi> &adj) {
    int n = adj.size();
    vi vis(n, 0), res;
    for (int i = 0; i < n; i++)
        if (!vis[i]) dfs(i, adj, vis, res);
    reverse(res.begin(), res.end());
    return res;
}

```

4 Dynamic Programming

4.1 Coin Change

Given coins $c_1, \dots, c_k$ and a sum S :

Min coins to make S : DP Formula: $dp[x]$: min coins to make x , $dp[0] = 0$. $dp[x] = \min_{c_i \leq x} (dp[x - c_i] + 1)$. Ans = $dp[S]$.

Number of ways to make S : DP formula: $dp[x]$: #ways to make x , $dp[0] = 1$. $dp[x] = \sum_{c_i \leq x} dp[x - c_i]$. Ans = $dp[S]$.

Number of ways to make S , $O(n \times \text{sum})$

```

def count(coins, s):
    n = len(coins) ; dp = [0] * (s + 1) ; dp[0] = 1
    for i in range(n):
        for j in range(coins[i], s + 1):
            dp[j] += dp[j - coins[i]]
    return dp[s]

```

4.2 Convex Hull Trick

Maintains lines $y = m \cdot x + b$, supports add(m,b) and query(x) for max y at given x. Works in $O(\log n)$ per operation using a multiset and integer intersections.

```

struct Line {
    mutable ll m, b, p;
    bool operator<(const Line& o) const { return m < o.m; }
    bool operator<(ll x) const { return p < x; }
};

struct LineContainer : multiset<Line, less<>> {
    const ll inf = LLONG_MAX;
    ll div(ll a, ll b) {
        return a / b - ((a ^ b) < 0 && a % b);
    }
    bool isect(iterator x, iterator y) {
        if (y == end()) { x->p = inf; return false; }
        if (x->m == y->m) x->p = x->b > y->b ? inf : -inf;
        else x->p = div(y->b - x->b, x->m - y->m);
        return x->p >= y->p;
    }
    void add(ll m, ll b) {
        auto z = insert({m, b, 0}), y = z++, x = y;
        while (isect(y, z)) z = erase(z);
        if (x != begin() && isect(--x, y)) isect(x, y = erase(y));
        while ((y = x) != begin() && (--x)->p >= y->p) isect(x, erase(y));
    }
    ll query(ll x) {
        assert(!empty());

```

```

    auto l = *lower_bound(x);
    return l.m * x + l.b;
}
};

```

4.3 Kadane

Given an array $a_1, \dots, a_n$, find $\max_{1 \leq i \leq j \leq n} \sum_{k=i}^j a_k$

DP formula: dp_i : max sum of subarray ending at i , $dp_i = \max(a_i, dp_{i-1} + a_i)$, $Ans = \max_i dp_i$.
Kadane 1D $O(n)$

```

def kadane1D(arr):
    maxSum = arr[0] ; DP = arr[0]
    for i in range(1, len(arr)):
        DP = max(DP + arr[i], arr[i])
        maxSum = max(maxSum, DP)
    return maxSum

```

2D-version : For $r_1 \leq r_2$: $colSum[c] = \sum_{r=r_1}^{r_2} A_{r,c}$, $maxSum = \max(maxSum, Kadane1D(colSum))$.

Kadane 2D $O(n^3)$

```

def kadane2D(mat):
    rows = len(mat) ; cols = len(mat[0]) ; maxSum = float('-inf') ; temp = [0] * rows
    for left in range(cols):
        temp = [0] * rows
        for right in range(left, cols):
            for row in range(rows):
                temp[row] += mat[row][right]
            sumValue = kadane1D(temp)
            maxSum = max(maxSum, sumValue)
    return maxSum

```

4.4 Knapsack

n items, each with value v_i and weight w_i . Max total weight W . DP formula: $dp[i][j]$ max value using i items, where max total weight is j . $dp[i][w] = \max(dp[i-1][w], dp[i-1][w-w_i] + v_i)$.
Space optimized version $O(n \times W)$

```

def knapsack(W, val, wt):
    dp = [0] * (W + 1)
    for i in range(1, len(wt) + 1):
        for j in range(W, wt[i-1] - 1, -1):
            dp[j] = max(dp[j], dp[j - wt[i-1]] + val[i-1])
    return dp[W]

```

4.5 Longest Increasing Subsequence

ℓ_i : LIS length ending at i . DP formula : $\ell_i = 1 + \max_{1 \leq j < i \atop a_j < a_i} \ell_j$ (or 1 if none). $Ans = \max_i \ell_i$.

Predecessor $p_i = \arg \max_{1 \leq j < i \atop a_j < a_i} \ell_j$.

$O(n^2)$

```

def LIS(arr):
    n = len(arr) ; lis = [1] * n
    for i in range(1, n):
        for prev in range(0, i):
            if arr[i] > arr[prev]:
                lis[i] = max(lis[i], lis[prev] + 1)
    return max(lis)

```

Note that $O(n \log n)$ is possible with BS

```

def LIS_BS(arr):
    n = len(arr) ; ans = [] ; ans.append(arr[0])
    for i in range(1, n):
        if arr[i] > ans[-1]:
            ans.append(arr[i])
        else:

```

```

low = 0
high = len(ans) - 1
while low < high:
    mid = low + (high - low) // 2
    if ans[mid] < arr[i]:
        low = mid + 1
    else:
        high = mid
ans[low] = arr[i]
return len(ans)

```

4.6 MinPathSum

Given a grid with non negative ints, where you can only move right/down finds the min sum path from top-left to bottom-right.

$O(n \times m)$ Modifies grid.

```

11 minPathSum(vvi &grid){
    for (int i = 0; i < grid.size(); i++){
        for (int j = 0; j < grid[0].size(); j++){
            if (i == 0 && j == 0) continue;
            if (i == 0) grid[i][j] += grid[i][j-1];
            else if (j == 0) grid[i][j] += grid[i-1][j];
            else grid[i][j] += min(grid[i-1][j], grid[i][j-1]);
        }
    }
    return grid[grid.size()-1][grid[0].size()-1];
}

```

4.7 TSP

Traveling Salesman Problem $O(n^2 2^n)$ DP formula: $dp[S][i]$: min cost to start at 0, visit all $v \in S$, end at i . $dp[\{0\}][0] = 0$. $dp[S][i] = \min_{j \in S \setminus \{i\}} dp[S \setminus \{i\}][j] + w_{j,i}$. $Ans = \min_i dp[V][i] + w_{i,0}$.

```

int tsp(int n, vvi& dist) {
    int mask_limit = 1 << n;
    vvi dp(mask_limit, vi(n, INT_MAX));
    dp[1][0] = 0;
    for (int mask = 1; mask < mask_limit; mask++) {
        for (int last = 0; last < n; last++) {
            if (dp[mask][last] == INT_MAX) continue;
            for (int next = 0; next < n; next++) {
                if (mask & (1 << next)) continue;
                int new_mask = mask | (1 << next);
                dp[new_mask][next] = min(dp[new_mask][next],
                                         dp[mask][last] + dist[last][next]);
            }
        }
    }
    int ans = INT_MAX;
    for (int last = 1; last < n; last++) {
        if (dp[mask_limit-1][last] != INT_MAX && dist[last][0] != INT_MAX) {
            ans = min(ans, dp[mask_limit-1][last] + dist[last][0]);
        }
    }
    return ans;
}

```

5 Strings

5.1 Aho-Corasick

Finds the occurrences of a set of patterns in a text simultaneously $O(n + m + matches)$, where $n = \text{len}(\text{text})$, $m = \text{total pattern length}$.

```

class TrieNode:
    def __init__(self):
        self.children = {}
        self.output = []
        self.fail = None
def build_automaton(keywords):
    root = TrieNode()
    for keyword in keywords:
        node = root
        for char in keyword:
            node = node.children.setdefault(char, TrieNode())
            node.output.append(keyword)
    queue = deque()
    for node in root.children.values():
        node.fail = root
        queue.append(node)
    while queue:
        current = queue.popleft()
        for ch, nxt in current.children.items():
            queue.append(nxt)
            f = current.fail
            while f and ch not in f.children:
                f = f.fail
            nxt.fail = f.children.get(ch, root)
            nxt.output += nxt.fail.output
    return root
def search_text(text, keywords):
    root = build_automaton(keywords)
    res = {kw: [] for kw in keywords}
    node = root
    for i, ch in enumerate(text):
        while node and ch not in node.children:
            node = node.fail
        if not node:
            node = root
            continue
        node = node.children[ch]
        for kw in node.output:
            res[kw].append(i - len(kw) + 1)
    return res

```

5.2 Knuth-Morris-Pratt

Search for a pattern within a text in $O(n + m)$, where n is the size of the text and m the length of the pattern. Length of the longest proper prefix which is also a suffix of the substring ending at that position.

```

def constructLps(pat, lps):
    len_ = 0 ; m = len(pat) ; lps[0] = 0 ; i = 1
    while i < m:
        if pat[i] == pat[len_]:
            len_ += 1
            lps[i] = len_
            i += 1
        else:
            if len_ != 0:
                len_ = lps[len_ - 1]
            else:
                lps[i] = 0
                i += 1
    def search(pat, txt):
        n = len(txt) ; m = len(pat) ; lps = [0] * m ; res = []
        constructLps(pat, lps)
        i = 0 ; j = 0
        while i < n:

```

```

        if txt[i] == pat[j]:
            i += 1 # If characters match, move both pointers forward
            j += 1
            if j == m: #found
                res.append(i - j)
                j = lps[j - 1] # Use LPS to skip unnecessary comparisons
            else: # mismatch
                if j != 0:
                    j = lps[j - 1] # Use LPS to skip unnecessary comparisons
                else:
                    i += 1
    return res

```

5.3 Manacher

Longest palindromic substring $O(n)$. Max of P corresponds to len(LPS)

```

def manacher(s):
    T = '#' + '#'.join(s) + '#' # handle even-length, remember to remove after
    n = len(T)
    P = [0]*n # P[i] = radius of palindrome centered at i
    C = R = 0 # current center, right boundary
    for i in range(n):
        mirr = 2*C - i
        if i < R: P[i] = min(R-i, P[mirr]) # use symmetry
        while i+P[i]+1 < n and i-P[i]-1 >= 0 and T[i+P[i]+1] == T[i-P[i]-1]:
            P[i] += 1 # attempt to expand palindrome at i
        if i + P[i] > R: # update center and right boundary
            C, R = i, i + P[i]

```

5.4 SuffixArray

SuffixArray i.e. starting positions of suffixes in lexicographic order. $O(n \log^2 n)$

```

def build_sa(s):
    n = len(s)
    sa = list(range(n))
    rank = [ord(ch) for ch in s] # initial ranks by 1 char
    k = 1
    while k < n: # sort by first k chars
        sa.sort(key=lambda x: (rank[x], rank[x+k] if x+k < n else -1))
        temp = [0]*n
        temp[sa[0]] = 0
        for i in range(1, n):
            prev = sa[i-1]
            cur = sa[i]
            prev_key = (rank[prev], rank[prev+k] if prev+k < n else -1)
            cur_key = (rank[cur], rank[cur+k] if cur+k < n else -1)
            temp[cur] = temp[prev] + (cur_key > prev_key)
        rank = temp
        if rank[sa[-1]] == n-1: break # all ranks distinct
        k <= 1
    return sa

```

Longest Common Prefix between suffixes $sa[i]$ and $sa[i+1]$ $O(n)$

```

def build_lcp(s, sa):
    n = len(s)
    rank = [0]*n
    for i in range(n): rank[sa[i]] = i
    lcp = [0]*n
    k = 0
    for i in range(n):
        if rank[i] == n-1: k = 0; continue
        j = sa[rank[i] + 1]
        while i+k < n and j+k < n and s[i+k] == s[j+k]:

```

```

    k += 1
    lcp[rank[i]] = k
    if k: k -= 1
return lcp

```

Longest Repeated Substring = max LCP over all adjacent suffixes.

```

def lrs(s):
    sa = build_sa(s)
    lcp = build_lcp(s, sa)
    idx = lcp.index(max(lcp))
    return (lcp[idx], idx) # (length, position in SA)

```

Finds all occurrences of pat in s via binary search on the SA. Returns [L, R]: all SA positions where suffix starts with pat.

```

def search(s, pat, sa):
    n, m = len(s), len(pat)
    l, r = 0, n-1
    while l <= r:
        mid = (l+r)//2
        if s[sa[mid]:sa[mid]+m] < pat: l = mid+1
        else: r = mid-1
    start = l
    l, r = 0, n-1
    while l <= r:
        mid = (l+r)//2
        if s[sa[mid]:sa[mid]+m] <= pat: l = mid+1
        else: r = mid-1
    return (start, r) if start <= r else (-1, -1)

```

Longest Common Substring between two strings. Build SA/LCP on s1#s2\$, then the LCS occurs between adjacent suffixes coming from different strings.

```

def lcs(s1, s2):
    s = s1 + '#' + s2 + '$'
    sa = build_sa(s)
    lcp = build_lcp(s, sa)
    idx, max_len = 0, 0
    for i in range(1, len(s)):
        a = sa[i] < len(s1)
        b = sa[i-1] < len(s1)
        if a != b and lcp[i] > max_len:
            max_len, idx = lcp[i], i

```

```

return (max_len, idx)

```

6 Arrays

6.1 Inversions

Count pairs where order flips between arrays. $O(n \log n)$

```

11 inversions(vi& a, vi& b) {
    int n = a.size();
    unordered_map<int,int> pos;
    for (int i = 0; i < n; i++) pos[b[i]] = i + 1;
    Fenwick t(n); // C.f. Fenwick tree
    ll inv = 0;
    for (int i = 0; i < n; i++) {
        inv += i - t.sum(pos[a[i]]);
        t.add(pos[a[i]], 1);
    }
    return inv;
}

```

7 Utilities

7.1 STL

```

int main()
{

```

Lambda functions

```

    int a;
    auto f = [](){}; // empty capture: no outer variables, only parameters +
    ↪ globals
    auto f = [=](int x){cout <<a;}; // capture all outer variables by value
    auto f = [&](int x){a=2;}; // capture all outer variables by reference

```

Sort using custom function

```

vector<pair<int,int>> P = {{1,2},{3,0},{2,5}};
sort(P.begin(), P.end(), [](auto &a, auto &b){ return a.second < b.second; });
}

```