

Fantasy Sports API

Introduction to Fantasy Sports API

The Fantasy Sports APIs provide URIs used to access fantasy sports data. Currently the APIs support retrieval of Fantasy Football, Baseball, Basketball, and Hockey data including game, league, team, and player information. The APIs are based on a RESTful model. Therefore, resources like game, league, team, player etc. and collections like games, leagues, teams, players form the building blocks for these APIs. Each resource is identified by a resource ID, and a collection is identified by its scope, specified in the URI.

Historically, Yahoo! has provided two full draft and trade style fantasy football and baseball [games](#) – a free version, and a plus version (which contains more features and content). With the 2010 seasons, the Free and Plus versions of Football and Baseball have merged. Each game is comprised of many “[leagues](#)”, which typically contain 8-12 [teams](#), which are managed by one or more [users](#). At the beginning of a league’s season, professional athletes (“[players](#)”) are uniquely assigned or chosen through a draft to each team. The players that are not chosen or assigned are available to be acquired via a free-agent or waiver wire process (a “[transaction](#)”). These teams compete against each other based on statistics from real-world competitions based on categories like touchdowns, yards gained, batting average and ERA. Many fantasy sport rules can be set and changed within a league; for instance, the roster positions, statistics used to score, scoring modifiers, and game style are configurable.

The game structure means that a lot of fantasy data is relevant only in the context of a particular league and team. For instance, without the league’s scoring rules, the statistics compiled by a player in a real-life competition are not meaningful to a particular league. Three rushing touchdowns by a running back is irrelevant to a league that only considers defensive players. Many leagues are private – the information about them is only available to users that are members.

Getting Started

OAuth

If you’re going to use the Fantasy Sports APIs, you’re going to have to get a bit familiar with OAuth. OAuth is the authentication mechanism for these services that allows users to grant you permission to make requests on their behalf. Many other Yahoo! services use OAuth, and thus all of the underlying details are explained in exhaustive detail in our [primary OAuth documentation](#). Of particular interest is the [OAuth Authorization Flow](#), which explains where each request is made and where the user needs to get involved.

Registering Your Application

To work with OAuth and Yahoo! services, you also must register your application with the Yahoo! Developer Network. When you register your application, you define a scope of Yahoo! services that your application will need access to, as well as the basic descriptive information that will be presented to users of your application when they're asked to grant you permissions. You will be given a consumer key and secret value that will need to be fed into OAuth requests that you generate. You should be sure to keep these values secret, as anyone with access to them could masquerade as your application.

To create a new OAuth application to use with the Fantasy Sports APIs, you should go through the [New API Key flow](#) on YDN. Be sure to specify that you need access to private user data, and select either Read or Read/Write access for Fantasy Sports.

PHP Sample Code

Basic OAuth Library Use

While everyone will have their favorite language to use when writing applications using the Fantasy Sports APIs, hopefully this PHP example will still serve as a useful reference. It tries to do several interesting things: keeping track of (and potentially refreshing) access tokens for future reuse, facilitating the interactive user authentication flow, and actually making a request based on any tokens retrieved. In order to use this code, you must have the [default PHP OAuth extension](#) installed, and you will need to fill in your own consumer key and secret where specified. You should then be able to execute the PHP script from the command line.

```
<?php
// **** POTENTIAL CONFIGURATION STARTS HERE ****

// NOTE: If you don't have the OAuth extension hooked into PHP, you may need
// to include it here.

// MODIFY: Insert whichever URL you'd like to try below. By default, the
// following URL will try to pull out the NFL teams for the logged-in user
$url =
'https://fantasysports.yahooapis.com/fantasy/v2/users;use_login=1/games;game_keys=nfl/teams';
$scope = 'test';

// MODIFY: Insert your own consumer key and secret here!
$consumer_data = array();
$consumer_data['test']['key'] = '<INSERT CONSUMER KEY HERE>;'
```

developer

```
// **** MAIN PROGRAM START HERE ****
```

```
$consumer_key = $consumer_data[$scope]['key'];  
$consumer_secret = $consumer_data[$scope]['secret'];
```

```
// By default, try to store token information in /tmp folder
```

```
$token_file_name = '/tmp/oauth_data_token_storage_' . $consumer_key . '.out';
```

```
$access_token = NULL;  
$access_secret = NULL;  
$access_session = NULL;  
$access_verifier = NULL;  
$store_access_token_data = false;
```

```
if( file_exists( $token_file_name ) &&  
    $tok_fh = fopen( $token_file_name, 'r' ) ) {
```

```
    $invalid_file = false;
```

```
    // Get first line: access token
```

```
    $access_token = fgets( $tok_fh );
```

```
    if( $access_token ) {
```

```
        // Get next line: access secret
```

```
        $access_secret = fgets( $tok_fh );
```

```
        if( $access_secret ) {
```

```
            // Get next line: access session handle
```

```
            $access_session = fgets( $tok_fh );
```

```
            if( ! $access_session ) {
```

```
                $invalid_file = true;
```

```
            }
```

```
        } else {
```

```
            $invalid_file = true;
```

```
        }
```

```
    } else {
```

```
        $invalid_file = true;
```

```
    }
```

```
if( $invalid_file ) {
```

```
    print "File did not seem to be formatted correctly -- needs 3 lines with access  
token, secret, and session handle.\n";
```

```
    $access_token = NULL;
```

```
    $access_secret = NULL;
```

```
    $access_session = NULL;
```

```
    } else {
```

```
        print "Got access token information!\n";
```

```
        $access_token = rtrim( $access_token );
```

developer

```
    print " Token: ${access_token}\n";
    print " Secret: ${access_secret}\n";
    print " Session Handle: ${access_session}\n\n";
}

// Done with file, close it up
fclose( $tok_fh );

} else {
    print "Couldn't open ${token_file_name}, assuming we need to get a new request
token.\n";
}

// 1. See if we have a stored access token/secret/session. If so, try to use
// that token.
if( $access_token ) {

    $o = new OAuth( $consumer_key, $consumer_secret,
                    OAUTH_SIG_METHOD_HMACSHA1, OAUTH_AUTH_TYPE_URI );
    $o->enableDebug();

    $auth_failure = false;

    // Try to make request using stored token
    try {
        $o->setToken( $access_token, $access_secret );
        if( $o->fetch( $url ) ) {
            print "Got data from API:\n\n";
            print $o->getLastResponse() . "\n\n";

            print "Successful!\n";
            exit;
        } else {
            print "Couldn't fetch\n";
        }
    } catch( OAuthException $e ) {
        print 'Error: ' . $e->getMessage() . "\n";
        print 'Error Code: ' . $e->getCode() . "\n";
        print 'Response: ' . $e->lastResponse . "\n";

        if( $e->getCode() == 401 ) {
            $auth_failure = true;
        }
    }
}

// 2. If we get an auth error, try to refresh the token using the session.
```

developer

```

        $response = $o->getAccessToken( 'https://api.login.yahoo.com/oauth/v2/get_token',
$access_session, $access_verifier );
    } catch( OAuthException $e ) {
        print 'Error: ' . $e->getMessage() . "\n";
        print 'Response: ' . $e->lastResponse . "\n";

        $response = NULL;
    }

    print_r( $response );

    if( $response ) {
        $access_token = $response['oauth_token'];
        $access_secret = $response['oauth_token_secret'];
        $access_session = $response['oauth_session_handle'];
        $store_access_token_data = true;

        print "Was able to refresh access token:\n";
        print " Token: ${access_token}\n";
        print " Secret: ${access_secret}\n";
        print " Session Handle: ${access_session}\n\n";

    } else {

        $access_token = NULL;
        $access_secret = NULL;
        $access_session = NULL;
        print "Unable to refresh access token, will need to request a new one.\n";
    }
}
}
}

```

// 3. If none of that worked, send the user to get a new token

```

if( ! $access_token ) {

    print "Better try to get a new access token.\n";
    $o = new OAuth( $consumer_key, $consumer_secret,
                    OAUTH_SIG_METHOD_HMACSHA1, OAUTH_AUTH_TYPE_URI );
    $o->enableDebug();

    $request_token = NULL;

    try {
        $response = $o->getRequestToken(
            "https://api.login.yahoo.com/oauth/v2/get_request_token", 'oob' );
        $request_token = $response['oauth_token'];
        $request_secret = $response['oauth_token_secret'];
    }
}

```

developer

```

} catch( OAuthException $e ) {
    print $e->getMessage() . "\n";
}

// Wait for input, then try to use it to get a new access token.
if( $request_token && $request_secret ) {
    print "Type the verifier and hit enter...\n";
    $verifier = fgets( STDIN );
    $verifier = rtrim( $verifier );

    print "Here's the verifier you gave us: ${verifier}\n";

    try {
        $o->setToken( $request_token, $request_secret );
        $response = $o->getAccessToken( 'https://api.login.yahoo.com/oauth/v2/get_token',
NULL, $verifier );

        print "Got it!\n";
        $access_token = $response['oauth_token'];
        $access_secret = $response['oauth_token_secret'];
        $access_session = $response['oauth_session_handle'];
        $store_access_token_data = true;
        print " Token: ${access_token}\n";
        print " Secret: ${access_secret}\n";
        print " Session Handle: ${access_session}\n\n";

    } catch( OAuthException $e ) {
        print 'Error: ' . $e->getMessage() . "\n";
        print 'Response: ' . $e->lastResponse . "\n";
        print "Shoot, couldn't get the access token. :(\n";
    }
}

if( $access_token ) {

    // Try to make request using stored token
    try {
        $o->setToken( $access_token, $access_secret );
        if( $o->fetch( $url ) ) {
            print "Got data from API:\n\n";
            print $o->getLastResponse() . "\n\n";

            print "Successful!\n";

```

developer

```

    } catch( OAuthException $e ) {
        print 'Error: ' . $e->getMessage() . "\n";
        print 'Error Code: ' . $e->getCode() . "\n";
        print 'Response: ' . $e->lastResponse . "\n";
    }
}

// 4. Rewrite token information if necessary
if( $store_access_token_data ) {

    print "Looks like we need to store access token data! Doing that now.\n";

    $tok_fh = fopen( $token_file_name, 'w' );
    if( $tok_fh ) {
        fwrite( $tok_fh, "${access_token}\n" );
        fwrite( $tok_fh, "${access_secret}\n" );
        fwrite( $tok_fh, "${access_session}\n" );

        fclose( $tok_fh );
    } else {
        print "Hm, couldn't open file to write back access token information.\n";
    }
}
?>

```

Full OAuth Flow without Libraries

If the PHP library described above doesn't fit your needs, you may feel like implementing the flow yourself. It's mildly tricky and you may run into common issues like not sorting the parameters correctly, or not encoding the various parts of the URL at the right time. The following script is an example of doing absolutely everything from scratch, and may be a useful guide for you.

```

<?php
// **** POTENTIAL CONFIGURATION STARTS HERE ****

// MODIFY: Insert your own consumer key and secret here!
$consumer_data = array();
$consumer_data['test']['key']    = '<INSERT CONSUMER KEY HERE>';
$consumer_data['test']['secret'] = '<INSERT CONSUMER SECRET HERE>';

// **** HELPER FUNCTIONS START HERE ****

////////////////////////////////////
// FUNCTION _make_signed_request
/// @brief Helper function to make a signed OAuth request. Only allows GET

```

developer

```

///
/// @param[in] $consumer_key      Application consumer key
/// @param[in] $consumer_secret   Application consumer secret
/// @param[in] $token              Token (request or access token)
/// @param[in] $token_secret      Token secret
/// @param[in] $signature_method  'PLAINTEXT' or 'HMAC-SHA1'
/// @param[in] $url                URL to make request to
/// @param[in] $params             Array of key=>val for params. Don't
///                                urlencode ahead of time, we'll do that here.
///
////////////////////////////////////
function _make_signed_request( $consumer_key, $consumer_secret, $token, $token_secret,
$signature_method, $url, $params = array() ) {

    // Only support GET in this function
    $method = 'GET';

    $signature_method = strtoupper( $signature_method );
    if( $signature_method != 'PLAINTEXT' && $signature_method != 'HMAC-SHA1' ) {
        print "Invalid signature method: ${signature_method}\n";
        return false;
    }

    $oauth_nonce = rand( 0, 999999 );
    $oauth_timestamp = time();
    $oauth_version = '1.0';

    $params['oauth_consumer_key'] = $consumer_key;
    $params['oauth_nonce'] = $oauth_nonce;
    $params['oauth_signature_method'] = $signature_method;
    $params['oauth_timestamp'] = $oauth_timestamp;
    $params['oauth_version'] = $oauth_version;

    if( $token ) {
        $params['oauth_token'] = $token;
    }
    if( ! $token_secret ) {
        $token_secret = '';
    }

    // Params need to be sorted by key
    ksort( $params, SORT_STRING );

    // Urlencode params and generate param string
    $param_list = array();
    foreach( $params as $key => $value ) {
        $param_list[] = urlencode( $key ) . '=' . urlencode( $value );
    }
    $param_string = join( '&', $param_list );

```


developer

```

    urlencode( $param_string );

    // Generate secret
    $secret = urlencode( $consumer_secret ) . '&' . urlencode( $token_secret );
    if( $signature_method == 'PLAINTEXT' ) {
        $signature = $secret;
    } else if( $signature_method == 'HMAC-SHA1' ) {
        $signature = base64_encode( hash_hmac( 'sha1', $base_string, $secret, true ) );
    }

    // Append signature
    $param_string .= '&oauth_signature=' . urlencode( $signature );
    $final_url = $url . '?' . $param_string;

    // Make curl call
    $ch = curl_init();
    curl_setopt( $ch, CURLOPT_URL, $final_url );
    curl_setopt( $ch, CURLOPT_AUTOREFERER, 1 );
    curl_setopt( $ch, CURLOPT_RETURNTRANSFER, 1 );
    curl_setopt( $ch, CURLOPT_FOLLOWLOCATION, 0 );
    curl_setopt( $ch, CURLOPT_SSL_VERIFYPEER, 0 );
    curl_setopt( $ch, CURLOPT_SSL_VERIFYHOST, 0 );

    $timeout = 2; // seconds
    curl_setopt( $ch, CURLOPT_TIMEOUT, $timeout );
    curl_setopt( $ch, CURLOPT_CONNECTTIMEOUT, $timeout );

    $contents = curl_exec($ch);
    $ret_code = curl_getinfo( $ch, CURLINFO_HTTP_CODE );
    $errno = curl_errno($ch);
    $error_str = curl_error($ch);

    if( $errno || $error_str ) {
        //print "Error: ${error_str} (${errno})\n";
    }

    //print "Response code: ${ret_code}\n";
    //print "Contents:\n${contents}\n\n";

    curl_close($ch);

    $data = array(
        'return_code' => $ret_code,
        'contents'    => $contents,
        'error_str'   => $error_str,
        'errno'       => $errno
    );

```

developer

```

////////////////////////////////////
// FUNCTION oauth_response_to_array
/// @brief Break up the oauth response data into an associate array
////////////////////////////////////
function oauth_response_to_array( $response ) {
    $data = array();
    foreach( explode( '&', $response ) as $param ) {
        $parts = explode( '=', $param );
        if( count( $parts ) == 2 ) {
            $data[urldecode($parts[0])] = urldecode($parts[1]);
        }
    }
    return $data;
}

////////////////////////////////////
// FUNCTION get_request_token
/// @brief Get a request token for a given application.
////////////////////////////////////
function get_request_token( $consumer_key, $consumer_secret ) {

    $url = 'https://api.login.yahoo.com/oauth/v2/get_request_token';
    $signature_method = 'plaintext';

    $token = NULL;
    $token_secret = NULL;

    // Add in the lang pref and callback
    $xoauth_lang_pref = 'en-us';
    $oauth_callback = 'oob'; // Set OOB for ease of use -- could be a URL

    $params = array( 'xoauth_lang_pref' => $xoauth_lang_pref,
                     'oauth_callback'   => $oauth_callback );

    // Make the signed request without any token
    $response_data = _make_signed_request( $consumer_key, $consumer_secret, $token,
    $token_secret, $signature_method, $url, $params );

    if( $response_data && $response_data['return_code'] == 200 ) {

        $contents = $response_data['contents'];
        $data = oauth_response_to_array( $contents );

        //print_r( $data );

        return $data;
    }
}

```

developer

```

}

////////////////////////////////////
// FUNCTION get_access_token
/// @brief Get an access token for a certain user and a certain application,
///         based on the request token and verifier
////////////////////////////////////
function get_access_token( $consumer_key, $consumer_secret, $request_token,
    $request_token_secret, $verifier ) {

    $url = 'https://api.login.yahoo.com/oauth/v2/get_token';
    $signature_method = 'plaintext';

    // Add in the oauth verifier
    $params = array( 'oauth_verifier' => $verifier );

    // Make the signed request using the request_token data
    $response_data = _make_signed_request( $consumer_key, $consumer_secret,
    $request_token, $request_token_secret, $signature_method, $url, $params );

    if( $response_data && $response_data['return_code'] == 200 ) {

        $contents = $response_data['contents'];
        $data = oauth_response_to_array( $contents );

        //print_r( $data );

        return $data;
    }

    return false;
}

////////////////////////////////////
// FUNCTION make_request
/// @brief Make an actual request to the fantasy API.
////////////////////////////////////
function make_request( $consumer_key, $consumer_secret, $access_token,
    $access_token_secret, $url ) {

    $signature_method = 'hmac-sha1';

    // Make the signed request to fantasy API
    $response_data = _make_signed_request( $consumer_key, $consumer_secret, $access_token,
    $access_token_secret, $signature_method, $url );

```

developer

```
// **** MAIN PROGRAM STARTS HERE ****

$consumer_key = $consumer_data['test']['key'];
$consumer_secret = $consumer_data['test']['secret'];

// 1. Get Request Token
$request_token_data = get_request_token( $consumer_key, $consumer_secret );

if( ! $request_token_data ) {
    print "Could not retrieve request token data\n";
    exit;
}

$request_token = $request_token_data['oauth_token'];
$request_token_secret = $request_token_data['oauth_token_secret'];
$auth_url = $request_token_data['xoauth_request_auth_url'];

// 2. Direct user to Yahoo! for authorization (retrieve verifier)
print "Hey! Go to this URL and tell us the verifier you get at the end.\n";
print ' ' . $auth_url . "\n\n";

print "Type the verifier and hit enter...\n";
$verifier = fgets( STDIN );

print "Here's the verifier you gave us: ${verifier}\n";

// 3. Get Access Token
$access_token_data =
    get_access_token( $consumer_key, $consumer_secret, $request_token,
        $request_token_secret, $verifier );

if( ! $access_token_data ) {
    print "Could not get access token\n";
    exit;
}

$access_token = $access_token_data['oauth_token'];
$access_token_secret = $access_token_data['oauth_token_secret'];

// 4. Make request using Access Token
$base_url = 'https://fantasysports.yahooapis.com/';
if( isset( $argv[1] ) ) {
    $request_uri = $argv[1];
} else {
    $request_uri = 'fantasy/v2/game/nfl';
}
```

developer

```

$request_data = make_request( $consumer_key, $consumer_secret, $access_token,
$access_token_secret, $request_url );

if( ! $request_data ) {
    print "Request failed\n";
}

$return_code = $request_data['return_code'];
$contents = $request_data['contents'];

print "Return code: ${return_code}\n";
print "Contents:\n${contents}\n\n";

print "Successful\n";

?>

```

PUTs and POSTs

The default PHP OAuth extension does not support any methods aside from GET (as far as I can tell), but we do have write operations as part of the Fantasy API that you might want to make use of. The easiest solution would be to find a library that does support PUTs and POSTs (and DELETes), but failing that, you can check out this quick sample code that will execute a PUT or POST given an access token (see earlier scripts for how to retrieve an access token).

```

<?php
////////////////////////////////////////////////////////////////////////////////////////////////////////////////////////////////
//  FUNCTION make_write_request
/// @brief Make a write (PUT/POST) request
///
/// @param[out] $auth_failure    Sets variable to true on 401 HTTP code (auth)
/// @param[in]   $consumer_key   Application consumer key
/// @param[in]   $consumer_secret Application consumer secret
/// @param[in]   $access_token   Access token for user/application
/// @param[in]   $access_secret  Access token secret for user/application
/// @param[in]   $method         PUT or POST
/// @param[in]   $url            URL to PUT/POST against
/// @param[in]   $infile         Filename specifying data to PUT/POST
////////////////////////////////////////////////////////////////////////////////////////////////////////////////////////////////
function make_write_request( &$auth_failure, $consumer_key, $consumer_secret,
$access_token, $access_secret, $method, $url, $infile ) {

    // Make sure we can open the infile
    $in_fh = NULL;

```

developer

```
$input_data = '';
while( $line = fgets( $in_fh ) ) {
    $input_data .= $line;
}

} else {
    print "Cannot open infile: ${infile}\n";
    return false;
}

$auth_failure = false;
$response_success = false;

$oauth_consumer_key = $consumer_key;
$oauth_consumer_secret = $consumer_secret;
$oauth_token = $access_token;
$oauth_token_secret = $access_secret;

$oauth_signature_method = 'HMAC-SHA1';
$oauth_nonce = rand( 0, 999999 );
$oauth_timestamp = time();
$oauth_version = "1.0";

$params = array(
    'oauth_consumer_key'    => $oauth_consumer_key,
    'oauth_nonce'           => $oauth_nonce,
    'oauth_signature_method' => $oauth_signature_method,
    'oauth_timestamp'       => $oauth_timestamp,
    'oauth_token'           => $oauth_token,
    'oauth_version'         => $oauth_version,
);

// Params need to be sorted by key
ksort( $params, SORT_STRING );

// Urlencode params and generate param string
$params_list = array();
foreach( $params as $key => $value ) {
    $params_list[] = urlencode( $key ) . '=' . urlencode( $value );
}
$params_string = join( '&', $params_list );

// Generate base string (needed for SHA1)
$base_string = urlencode( $method ) . '&' . urlencode( $url ) . '&' .
    urlencode( $params_string );

// Generate secret and signature
```

developer

```

        urlencode( $auth_data );
    }

    // Append signature
    $final_url = $url . '?' . $param_string . '&oauth_signature=' . urlencode( $signature );
};

// Make the curl call
$ch = curl_init();
curl_setopt( $ch, CURLOPT_HTTPHEADER, array( 'Content-type: application/xml' ) );
if( $method == 'POST' ) {
    curl_setopt( $ch, CURLOPT_POST, 1 );
    curl_setopt( $ch, CURLOPT_POSTFIELDS, $input_data );
} else if( $method == 'PUT' ) {

    fseek( $in_fh, 0 );

    curl_setopt( $ch, CURLOPT_PUT, 1 );
    curl_setopt( $ch, CURLOPT_INFILE, $in_fh );
    curl_setopt( $ch, CURLOPT_INFILESIZE, strlen( $input_data ) );

}
curl_setopt( $ch, CURLOPT_URL, $final_url );
curl_setopt( $ch, CURLOPT_RETURNTRANSFER, true );

$ycw_result = curl_exec( $ch );
$ret_code = curl_getinfo( $ch, CURLINFO_HTTP_CODE );

fclose( $in_fh );

curl_close( $ch );

if( $ret_code == 401 ) {
    $auth_failure = true;
} else {
    $response_success = true;
}

print "Return code: ${ret_code}\n";
print "Response from API:\n";
print_r( $ycw_result );

return $response_success;
}
?>

```

Making Public Requests

developer

down to making a request without setting an access token through the default PHP OAuth library, or effectively using your consumer key/secret as the token.

```
<?php
$consumer_key = '<INSERT CONSUMER KEY HERE>';
$consumer_secret = '<INSERT CONSUMER SECRET HERE>';

$o = new OAuth( $consumer_key, $consumer_secret,
                OAUTH_SIG_METHOD_HMACSHA1,
                OAUTH_AUTH_TYPE_URI );

$url = 'https://fantasysports.yahooapis.com/fantasy/v2/game/nfl';

try {
    if( $o->fetch( $url ) ) {

        print $o->getLastResponse();

        print "Successful fetch\n";
    } else {
        print "Couldn't fetch\n";
    }
} catch( OAuthException $e ) {
    print 'Error: ' . $e->getMessage() . "\n";
    print 'Response: ' . $e->lastResponse . "\n";
}
?>
```

Resources and Collections

Introduction

The primary building blocks of the Fantasy Sports APIs are Resources and Collections. Resources typically describe chunks of data that can be identified by a unique key. Collections are simply wrappers that contain similar resources. So, for instance, if we need to retrieve data about a single league, we might ask for a [League Resource](#) and provide a single [league key](#). However, if we wanted data across several leagues, we would ask for a [Leagues Collection](#) and provide multiple league keys.

The format for requesting a Resource will typically look like:

```
https://fantasysports.yahooapis.com/fantasy/v2/{resource}/{resource_key}
```


developer

```
https://fantasysports.yahooapis.com/fantasy/v2/{collection};{resource}_keys={resource_key1},{resource_key2}
```

Collections

As mentioned, Collections are simply groups of Resources. If you care about particular Resources within a Collection, you can apply filters to the Collection to narrow the results. The most common type of filtering is by `key`. For instance, if you'd like to see two particular players, you could ask for them directly:

```
/fantasy/v2/?player_keys={player_key2}
```

Some Collections support more complex filters. Within a game, for example, you might ask for only the players that play a certain position. You could also request only the particular user who is currently logged in:

```
/fantasy/v2/?use_login=1
```

Sub-Resources

Resources will typically define a list of valid Sub-Resources. These are Resources and Collections that can live within the scope of the parent Resource. For instance, a fantasy league in the Football draft and trade games can contain up to 20 fantasy teams; therefore, the [League Resource](#) can have a [Teams Collection](#) as a sub-resource. As a general rule of thumb, if you can possibly have multiple of one Resource contained within another Resource, then you'll have a Collection of the first Resource as a sub-resource of the second Resource. You would only have a singular Resource as a sub-resource of another Resource if it would only make sense to ever ask for one instance of that Resource.

The scope of a sub-resource is typically defined by the parent Resource; for instance, if you're viewing a [Players Collection](#) as a sub-resource of a particular [League](#), then you would expect to only see Players that are eligible within that League. Further filters could then be applied to this already narrowed list.

Having sub-resources allows you to chain together Resources and Collections to provide more data, and the URI you request directly specifies how the chaining works. For instance, if you wanted to take a particular logged in user, see which games he had played, and then get the league information within those games, you might construct a request like:

```
/fantasy/v2/?use_login=1//
```

This would present you with a [Users Collection](#), a single [User Resource](#) for the logged in user, a [Games Collection](#) for that user, potentially multiple [Game Resources](#) for each game the user is playing, a [Leagues](#)

developer

When you specify a sub-resource beneath a Collection, you're really saying that you'd like to see that sub-resource appended beneath each Resource within the Collection. Therefore, the sub-resources available to a Collection will be equivalent to the sub-resources available to the corresponding Resource.

If you ever need to branch off other sub-resources outside of your main resource chain, you can use the `out` parameter, which will let you specify one level of extra sub-resources to pull in. At the moment, you cannot pass any parameters along to these `out` sub-resources, aside from any data that might get passed by default. This typically means that you can't chain other resources off of sub-resources specified by the `out` parameter.

As an example, if you wanted to view a league's settings along with two teams in particular in a league, you might construct a URI like:

```
/fantasy/v2//;out=settings/;team_keys=,{team_key2}
```

Parameters

Parameters can be provided to Resources and Collections as semicolon-delimited key-value pairs. These should be placed after the Resource or Collection name in the URI; in the case of entry-point Resources like [Games](#), [Leagues](#), [Teams](#), and [Players](#), the parameters belong after the `resource_key`.

```
/fantasy/v2/{resource}/{resource_key};{key}={value};{key}={value}/{collection};{key}={value};{key}={value}/{collection};{key}={value}/{resource};{key}={value}
```

Resource keys, `out` parameters, and other filters are just specific types of parameters that can be applied to various Resources or Collections.

Game resource

Description

With the Game API, you can obtain the fantasy game related information, like the fantasy game name, the Yahoo! game code, and season.

To refer to a Game resource, you'll need to provide a `game_key`, which will either be a `game_id` or `game_code`. The `game_id` is a unique ID identifying a given fantasy game for a given season. For instance, the `game_id` for the Free NFL draft and trade fantasy game for the 2009 season is `222`, while the `game_id` for the Plus version is `223`. A `game_code` generally identifies a game, independent of season, and, when used as a `game_key`, will typically return the current season of that game. For instance, the `game_code` for the Free NFL game is `nf1`, and the `game_code` for the Plus game is `pnf1`;

developer

combined into a single code. Next year, the `game_code nfl` will point to the new `game_id` for the 2011 version of the NFL game. Thus, if you always want the current season of a game, the `game_code` should be used as a `game_key`.

Below is a list of game IDs for most of our seasons of each game. If you're looking for a current game ID that's not listed in the table below, as mentioned above, you can request game information by `game_code`. For example:

- **YQL:** `select * from fantasysports.games where game_key='nfl';`
- **API:** `https://fantasysports.yahooapis.com/fantasy/v2/game/nfl`

Game IDs Table

Season	nfl game ID	pnfl game ID	mlb game ID	pm1b game ID	nba game ID	nhl game ID
2001	57	58	12	—	16	15
2002	49	62	39	44	67	64
2003	79	78	74	73	95	94
2004	101	102	98	99	112	111
2005	124	125	113	114	131	130
2006	153	154	147	148	165	164
2007	175	176	171	172	187	186
2008	199	200	195	196	211	210
2009	222	223	215	216	234	233
2010	242	—	238	—	249	248
2011	257	—	253	—	265	263
2012	273	—	268	—	304	303

HTTP Operations Supported

- GET

developer

Any sub-resource under a game is extracted using a URI like:

```
https://fantasysports.yahooapis.com/fantasy/v2/game/
```

Multiple sub-resources can be extracted from game in the same URI using a format like:

```
https://fantasysports.yahooapis.com/fantasy/v2/game/;out=,{sub_resource_2}
```

Game key format

{game_code} or {game_id}

Example: pnfl or 223

Note

If you specify a game_code as the game_key , we'll translate that to the corresponding game_id upon parsing the URI. Therefore, any game_code s will be converted to game_id s in any keys returned by the Fantasy Sports APIs in the response XML.

Sub-resources

Default sub-resource: metadata

Sample XML

```
https://fantasysports.yahooapis.com/fantasy/v2/game/nfl
```

```
<?xml version="1.0" encoding="UTF-8"?>
<fantasy_content xml:lang="en-US"
yahoo:uri="http://fantasysports.yahooapis.com/fantasy/v2/game/nfl"
xmlns:yahoo="http://www.yahooapis.com/v1/base.rng" time="30.575037002563ms"
copyright="Data provided by Yahoo! and STATS, LLC"
xmlns="http://fantasysports.yahooapis.com/fantasy/v2/base.rng">
  <game>
    <game_key>257</game_key>
    <game_id>257</game_id>
    <name>Football</name>
    <code>nfl</code>
```

```
</game>  
</fantasy_content>
```

Games collection

Description

With the Games API, you can obtain information from a collection of games simultaneously. Each element beneath the Games Collection will be a [Game Resource](#)

HTTP Operations Supported

- GET

URIs

Any [sub-resource](#) valid for a game is a valid sub-resource under the games collection.

Any sub-resource for a collection of games is extracted using a URI like:

```
/games/{sub_resource}
```

OR

```
/games;game_keys={game_key1},{game_key2}/{sub_resource}
```

Multiple sub-resources can be extracted from games in the same URI using a format like:

```
/games;out={sub_resource_1},{sub_resource_2}
```

OR

```
/games;game_keys={game_key1},{game_key2};out={sub_resource_1},{sub_resource_2}
```

Filters

developer

instance, if you wanted only the 2011 version of the nfl game, you might filter by `seasons=2011` and `game_codes=nfl`.

Filter parameter	Filter parameter values	Usage
<code>is_available</code>	<code>1</code> to only show games currently in season	<code>/games;is_available=1</code>
<code>game_types</code>	<code>full</code> <code>pickem-team</code> <code>pickem-group</code> <code>pickem-team-list</code>	<code>/games;game_types=full,pickem-team</code>
<code>game_codes</code>	Any valid game codes	<code>/games;game_codes=nfl,mlb</code>
<code>seasons</code>	Any valid seasons	<code>/games;seasons=2011,2012</code>

Sub-resources

In addition to the [sub-resources](#) valid for a game resource, the following are valid sub-resources for a games collection.

League resource

Description

When users join a Fantasy Football, Baseball, Basketball, or Hockey draft and trade game, they are organized into leagues with a limited number of friends or other Yahoo! users, with each user managing a [Team](#). With the League API, you can obtain the league related information, like the league name, the number of teams, the draft status, et cetera. Leagues only exist in the context of a particular [Game](#), although you can request a League Resource as the base of your URI by using the global `''''`. A particular user can only retrieve data for private leagues of which they are a member, or for public leagues.

HTTP Operations Supported

- GET

URIs

`https://fantasysports.yahooapis.com/fantasy/v2/league/`

developer

<https://fantasysports.yahooapis.com/fantasy/v2/league/>

Multiple sub-resources can be extracted from league in the same URI using a format like:

https://fantasysports.yahooapis.com/fantasy/v2/league/;out=,{sub_resource_2}

League key format

.l.{league_id}

Example: pnfl.1.431 or 223.1.431

Note

The separator between the game_key and league_id is a lower case L (not the number 1).

Sub-resources

Default sub-resource: metadata

Sample XML

<https://fantasysports.yahooapis.com/fantasy/v2/league/223.1.431>

```
<?xml version="1.0" encoding="UTF-8"?>
<fantasy_content xml:lang="en-US"
yahoo:uri="http://fantasysports.yahooapis.com/fantasy/v2/league/223.1.431"
xmlns:yahoo="http://www.yahooapis.com/v1/base.rng" time="181.80584907532ms"
copyright="Data provided by Yahoo! and STATS, LLC"
xmlns="http://fantasysports.yahooapis.com/fantasy/v2/base.rng">
  <league>
    <league_key>223.1.431</league_key>
    <league_id>431</league_id>
    <name>Y! Friends and Family League</name>
    <url>https://football.fantasysports.yahoo.com/archive/pnfl/2009/431</url>
    <draft_status>postdraft</draft_status>
    <num_teams>14</num_teams>
    <edit_key>17</edit_key>
    <weekly_deadline/>
    <league_update_timestamp>1262595518</league_update_timestamp>
    <scoring_type>head</scoring_type>
```

developer

```
</is_finished>1</is_finished>
</league>
</fantasy_content>
```

<https://fantasysports.yahooapis.com/fantasy/v2/league/223.1.431/settings>

```
<?xml version="1.0" encoding="UTF-8"?>
<fantasy_content xmlns:yahoo="http://www.yahooapis.com/v1/base.rng"
xmlns="http://fantasysports.yahooapis.com/fantasy/v2/base.rng" xml:lang="en-US"
yahoo:uri="http://fantasysports.yahooapis.com/fantasy/v2/league/223.1.431/settings"
time="86.472988128662ms" copyright="Data provided by Yahoo! and STATS, LLC">
  <league>
    <league_key>223.1.431</league_key>
    <league_id>431</league_id>
    <name>Y! Friends and Family League</name>
    <url>https://football.fantasysports.yahoo.com/archive/pnfl/2009/431</url>
    <draft_status>postdraft</draft_status>
    <num_teams>14</num_teams>
    <edit_key>17</edit_key>
    <weekly_deadline/>
    <league_update_timestamp>1262595518</league_update_timestamp>
    <scoring_type>head</scoring_type>
    <current_week>16</current_week>
    <start_week>1</start_week>
    <end_week>16</end_week>
    <is_finished>1</is_finished>
    <settings>
      <draft_type>live</draft_type>
      <scoring_type>head</scoring_type>
      <uses_playoff>1</uses_playoff>
      <playoff_start_week>14</playoff_start_week>
      <uses_playoff_reseeding>0</uses_playoff_reseeding>
      <uses_lock_eliminated_teams>0</uses_lock_eliminated_teams>
      <uses_faab>1</uses_faab>
      <trade_end_date>2009-11-27</trade_end_date>
      <trade_ratify_type>commish</trade_ratify_type>
      <trade_reject_time>0</trade_reject_time>
      <roster_positions>
        <roster_position>
          <position>QB</position>
          <count>1</count>
        </roster_position>
        <roster_position>
          <position>WR</position>
          <count>3</count>
        </roster_position>
```


developer

```

</roster_position>
<roster_position>
  <position>TE</position>
  <count>1</count>
</roster_position>
<roster_position>
  <position>W/R/T</position>
  <count>1</count>
</roster_position>
<roster_position>
  <position>K</position>
  <count>1</count>
</roster_position>
<roster_position>
  <position>DEF</position>
  <count>1</count>
</roster_position>
<roster_position>
  <position>BN</position>
  <count>4</count>
</roster_position>
</roster_positions>
<stat_categories>
  <stats>
    <stat>
      <stat_id>4</stat_id>
      <enabled>1</enabled>
      <name>Passing Yards</name>
      <display_name>Pass Yds</display_name>
      <sort_order>1</sort_order>
      <position_type>0</position_type>
    </stat>
    <stat>
      <stat_id>5</stat_id>
      <enabled>1</enabled>
      <name>Passing Touchdowns</name>
      <display_name>Pass TD</display_name>
      <sort_order>1</sort_order>
      <position_type>0</position_type>
    </stat>
    <stat>
      <stat_id>6</stat_id>
      <enabled>1</enabled>
      <name>Interceptions</name>
      <display_name>Int</display_name>
      <sort_order>0</sort_order>
      <position_type>0</position_type>

```

developer

```
<stat_id>9</stat_id>
<enabled>1</enabled>
<name>Rushing Yards</name>
<display_name>Rush Yds</display_name>
<sort_order>1</sort_order>
<position_type>0</position_type>
</stat>
<stat>
  <stat_id>10</stat_id>
  <enabled>1</enabled>
  <name>Rushing Touchdowns</name>
  <display_name>Rush TD</display_name>
  <sort_order>1</sort_order>
  <position_type>0</position_type>
</stat>
<stat>
  <stat_id>11</stat_id>
  <enabled>1</enabled>
  <name>Receptions</name>
  <display_name>Rec</display_name>
  <sort_order>1</sort_order>
  <position_type>0</position_type>
</stat>
<stat>
  <stat_id>12</stat_id>
  <enabled>1</enabled>
  <name>Reception Yards</name>
  <display_name>Rec Yds</display_name>
  <sort_order>1</sort_order>
  <position_type>0</position_type>
</stat>
<stat>
  <stat_id>13</stat_id>
  <enabled>1</enabled>
  <name>Reception Touchdowns</name>
  <display_name>Rec TD</display_name>
  <sort_order>1</sort_order>
  <position_type>0</position_type>
</stat>
<stat>
  <stat_id>15</stat_id>
  <enabled>1</enabled>
  <name>Return Touchdowns</name>
  <display_name>Ret TD</display_name>
  <sort_order>1</sort_order>
  <position_type>0</position_type>
</stat>
<stat>
```

developer

```

    <display_name>2-PT</display_name>
    <sort_order>1</sort_order>
    <position_type>0</position_type>
  </stat>
  <stat>
    <stat_id>18</stat_id>
    <enabled>1</enabled>
    <name>Fumbles Lost</name>
    <display_name>Fum Lost</display_name>
    <sort_order>0</sort_order>
    <position_type>0</position_type>
  </stat>
  <stat>
    <stat_id>57</stat_id>
    <enabled>1</enabled>
    <name>Offensive Fumble Return TD</name>
    <display_name>Fum Ret TD</display_name>
    <sort_order>1</sort_order>
    <position_type>0</position_type>
  </stat>
  <stat>
    <stat_id>19</stat_id>
    <enabled>1</enabled>
    <name>Field Goals 0-19 Yards</name>
    <display_name>FG 0-19</display_name>
    <sort_order>1</sort_order>
    <position_type>K</position_type>
  </stat>
  <stat>
    <stat_id>20</stat_id>
    <enabled>1</enabled>
    <name>Field Goals 20-29 Yards</name>
    <display_name>FG 20-29</display_name>
    <sort_order>1</sort_order>
    <position_type>K</position_type>
  </stat>
  <stat>
    <stat_id>21</stat_id>
    <enabled>1</enabled>
    <name>Field Goals 30-39 Yards</name>
    <display_name>FG 30-39</display_name>
    <sort_order>1</sort_order>
    <position_type>K</position_type>
  </stat>
  <stat>
    <stat_id>22</stat_id>
    <enabled>1</enabled>

```

developer

```
</stat>
  <position_type>K</position_type>
</stat>
<stat>
  <stat_id>23</stat_id>
  <enabled>1</enabled>
  <name>Field Goals 50+ Yards</name>
  <display_name>FG 50+</display_name>
  <sort_order>1</sort_order>
  <position_type>K</position_type>
</stat>
<stat>
  <stat_id>24</stat_id>
  <enabled>1</enabled>
  <name>Field Goals Missed 0-19 Yards</name>
  <display_name>FGM 0-19</display_name>
  <sort_order>0</sort_order>
  <position_type>K</position_type>
</stat>
<stat>
  <stat_id>25</stat_id>
  <enabled>1</enabled>
  <name>Field Goals Missed 20-29 Yards</name>
  <display_name>FGM 20-29</display_name>
  <sort_order>0</sort_order>
  <position_type>K</position_type>
</stat>
<stat>
  <stat_id>29</stat_id>
  <enabled>1</enabled>
  <name>Point After Attempt Made</name>
  <display_name>PAT Made</display_name>
  <sort_order>1</sort_order>
  <position_type>K</position_type>
</stat>
<stat>
  <stat_id>30</stat_id>
  <enabled>1</enabled>
  <name>Point After Attempt Missed</name>
  <display_name>PAT Miss</display_name>
  <sort_order>0</sort_order>
  <position_type>K</position_type>
</stat>
<stat>
  <stat_id>31</stat_id>
  <enabled>1</enabled>
  <name>Points Allowed</name>
  <display_name>Pts Allow</display_name>
```

developer

```

</stat>
<stat>
  <stat_id>32</stat_id>
  <enabled>1</enabled>
  <name>Sack</name>
  <display_name>Sack</display_name>
  <sort_order>1</sort_order>
  <position_type>DT</position_type>
</stat>
<stat>
  <stat_id>33</stat_id>
  <enabled>1</enabled>
  <name>Interception</name>
  <display_name>Int</display_name>
  <sort_order>1</sort_order>
  <position_type>DT</position_type>
</stat>
<stat>
  <stat_id>34</stat_id>
  <enabled>1</enabled>
  <name>Fumble Recovery</name>
  <display_name>Fum Rec</display_name>
  <sort_order>1</sort_order>
  <position_type>DT</position_type>
</stat>
<stat>
  <stat_id>35</stat_id>
  <enabled>1</enabled>
  <name>Touchdown</name>
  <display_name>TD</display_name>
  <sort_order>1</sort_order>
  <position_type>DT</position_type>
</stat>
<stat>
  <stat_id>36</stat_id>
  <enabled>1</enabled>
  <name>Safety</name>
  <display_name>Safe</display_name>
  <sort_order>1</sort_order>
  <position_type>DT</position_type>
</stat>
<stat>
  <stat_id>37</stat_id>
  <enabled>1</enabled>
  <name>Block Kick</name>
  <display_name>Blk Kick</display_name>
  <sort_order>1</sort_order>

```

developer

```
<stat_id>50</stat_id>
<enabled>1</enabled>
<name>Points Allowed 0 points</name>
<display_name>Pts Allow 0</display_name>
<sort_order>1</sort_order>
<position_type>DT</position_type>
</stat>
<stat>
  <stat_id>51</stat_id>
  <enabled>1</enabled>
  <name>Points Allowed 1-6 points</name>
  <display_name>Pts Allow 1-6</display_name>
  <sort_order>1</sort_order>
  <position_type>DT</position_type>
</stat>
<stat>
  <stat_id>52</stat_id>
  <enabled>1</enabled>
  <name>Points Allowed 7-13 points</name>
  <display_name>Pts Allow 7-13</display_name>
  <sort_order>1</sort_order>
  <position_type>DT</position_type>
</stat>
<stat>
  <stat_id>53</stat_id>
  <enabled>1</enabled>
  <name>Points Allowed 14-20 points</name>
  <display_name>Pts Allow 14-20</display_name>
  <sort_order>1</sort_order>
  <position_type>DT</position_type>
</stat>
<stat>
  <stat_id>54</stat_id>
  <enabled>1</enabled>
  <name>Points Allowed 21-27 points</name>
  <display_name>Pts Allow 21-27</display_name>
  <sort_order>1</sort_order>
  <position_type>DT</position_type>
</stat>
<stat>
  <stat_id>55</stat_id>
  <enabled>1</enabled>
  <name>Points Allowed 28-34 points</name>
  <display_name>Pts Allow 28-34</display_name>
  <sort_order>1</sort_order>
  <position_type>DT</position_type>
</stat>
```

developer

```

</stat>
</stats>
</stat_categories>
<stat_modifiers>
  <stats>
    <stat>
      <stat_id>4</stat_id>
      <value>0.04</value>
    </stat>
    <stat>
      <stat_id>5</stat_id>
      <value>4</value>
    </stat>
    <stat>
      <stat_id>6</stat_id>
      <value>-1</value>
    </stat>
    <stat>
      <stat_id>9</stat_id>
      <value>0.1</value>
    </stat>
    <stat>
      <stat_id>10</stat_id>
      <value>6</value>
    </stat>
    <stat>
      <stat_id>11</stat_id>
      <value>.75</value>
    </stat>
    <stat>
      <stat_id>12</stat_id>
      <value>0.1</value>
    </stat>
    <stat>
      <stat_id>13</stat_id>
      <value>6</value>
    </stat>
    <stat>
      <stat_id>15</stat_id>
      <value>6</value>
    </stat>
    <stat>
      <stat_id>16</stat_id>

```

developer

```
</stat>
  <stat_id>18</stat_id>
  <value>-1</value>
</stat>
<stat>
  <stat_id>57</stat_id>
  <value>6</value>
</stat>
<stat>
  <stat_id>19</stat_id>
  <value>3</value>
</stat>
<stat>
  <stat_id>20</stat_id>
  <value>3</value>
</stat>
<stat>
  <stat_id>21</stat_id>
  <value>3</value>
</stat>
<stat>
  <stat_id>22</stat_id>
  <value>4</value>
</stat>
<stat>
  <stat_id>23</stat_id>
  <value>5</value>
</stat>
<stat>
  <stat_id>24</stat_id>
  <value>-3</value>
</stat>
<stat>
  <stat_id>25</stat_id>
  <value>-1</value>
</stat>
<stat>
  <stat_id>29</stat_id>
  <value>1</value>
</stat>
<stat>
  <stat_id>30</stat_id>
  <value>-.5</value>
</stat>
<stat>
  <stat_id>32</stat_id>
  <value>1</value>
</stat>
```


developer

```
</stat>
<stat>
  <stat_id>34</stat_id>
  <value>2</value>
</stat>
<stat>
  <stat_id>35</stat_id>
  <value>6</value>
</stat>
<stat>
  <stat_id>36</stat_id>
  <value>2</value>
</stat>
<stat>
  <stat_id>37</stat_id>
  <value>2</value>
</stat>
<stat>
  <stat_id>50</stat_id>
  <value>10</value>
</stat>
<stat>
  <stat_id>51</stat_id>
  <value>7</value>
</stat>
<stat>
  <stat_id>52</stat_id>
  <value>4</value>
</stat>
<stat>
  <stat_id>53</stat_id>
  <value>1</value>
</stat>
<stat>
  <stat_id>54</stat_id>
  <value>0</value>
</stat>
<stat>
  <stat_id>55</stat_id>
  <value>-1</value>
</stat>
<stat>
  <stat_id>56</stat_id>
  <value>-4</value>
</stat>
</stats>
</stat_modifiers>
```

developer

```

    <name>Family</name>
  </division>
  <division>
    <division_id>2</division_id>
    <name>Friends</name>
  </division>
</divisions>
</settings>
</league>
</fantasy_content>

```

<https://fantasysports.yahooapis.com/fantasy/v2/league/223.1.431/standings>

```

<?xml version="1.0" encoding="UTF-8"?>
<fantasy_content xmlns:yahoo="http://www.yahooapis.com/v1/base.rng"
xmlns="http://fantasysports.yahooapis.com/fantasy/v2/base.rng" xml:lang="en-US"
yahoo:uri="http://fantasysports.yahooapis.com/fantasy/v2/league/223.1.431/standings"
time="201.46489143372ms" copyright="Data provided by Yahoo! and STATS, LLC">
  <league>
    <league_key>223.1.431</league_key>
    <league_id>431</league_id>
    <name>Y! Friends and Family League</name>
    <url>https://football.fantasysports.yahoo.com/archive/pnfl/2009/431</url>
    <draft_status>postdraft</draft_status>
    <num_teams>14</num_teams>
    <edit_key>17</edit_key>
    <weekly_deadline/>
    <league_update_timestamp>1262595518</league_update_timestamp>
    <scoring_type>head</scoring_type>
    <current_week>16</current_week>
    <start_week>1</start_week>
    <end_week>16</end_week>
    <is_finished>1</is_finished>
    <standings>
      <teams count="14">
        <team>
          <team_key>223.1.431.t.10</team_key>
          <team_id>10</team_id>
          <name>Gehlken</name>
          <url>https://football.fantasysports.yahoo.com/archive/pnfl/2009/431/10</url>
          <team_logos>
            <team_logo>
              <size>medium</size>

            <url>https://a323.yahoofs.com/coreid/4b978f0ci2432zws140sp2/imXqmYo8cq3NxEftQB4wgAs-/6/t
n48.jpeg?ciA8DVOBMH.UXGXk</url>

```

developer

```

</faab_balance>0</faab_balance>
<clinched_playoffs>1</clinched_playoffs>
<managers>
  <manager>
    <manager_id>5</manager_id>
    <nickname>-- hidden --</nickname>
    <guid>4LAITFUXFASDNAXFWUOHWNU3BY</guid>
  </manager>
</managers>
<team_points>
  <coverage_type>season</coverage_type>
  <season>2009</season>
  <total>1682.33</total>
</team_points>
<team_standings>
  <rank>1</rank>
  <outcome_totals>
    <wins>9</wins>
    <losses>4</losses>
    <ties>0</ties>
    <percentage>.692</percentage>
  </outcome_totals>
  <divisional_outcome_totals>
    <wins>5</wins>
    <losses>1</losses>
    <ties>0</ties>
  </divisional_outcome_totals>
</team_standings>
</team>
<team>
  <team_key>223.1.431.t.5</team_key>
  <team_id>5</team_id>
  <name>RotoExperts</name>
  <url>https://football.fantasysports.yahoo.com/archive/pnfl/2009/431/5</url>
  <team_logos>
    <team_logo>
      <size>medium</size>

<url>https://a323.yahoofs.com/coreid/49be42a6i26e5zul3re3/d2x_9_UweKP95SJZ_Hwnk2R1/2/tn4
8.jpg?ciA8DVOBIRa6b7wq</url>
    </team_logo>
  </team_logos>
  <division_id>2</division_id>
  <faab_balance>1</faab_balance>
  <clinched_playoffs>1</clinched_playoffs>
  <managers>
    <manager>

```

developer

```

    </manager>
  </managers>
  <team_points>
    <coverage_type>season</coverage_type>
    <season>2009</season>
    <total>1764.09</total>
  </team_points>
  <team_standings>
    <rank>2</rank>
    <outcome_totals>
      <wins>9</wins>
      <losses>4</losses>
      <ties>0</ties>
      <percentage>.692</percentage>
    </outcome_totals>
    <divisional_outcome_totals>
      <wins>4</wins>
      <losses>2</losses>
      <ties>0</ties>
    </divisional_outcome_totals>
  </team_standings>
</team>
<team>
  <team_key>223.1.431.t.8</team_key>
  <team_id>8</team_id>
  <name>Y! - Pianowski</name>
  <url>https://football.fantasysports.yahoo.com/archive/pnfl/2009/431/8</url>
  <team_logos>
    <team_logo>
      <size>medium</size>
      <url>https://l.yimg.com/a/i/us/sp/fn/default/full/nfl/icon_10_48.gif</url>
    </team_logo>
  </team_logos>
  <division_id>1</division_id>
  <faab_balance>0</faab_balance>
  <clinched_playoffs>1</clinched_playoffs>
  <managers>
    <manager>
      <manager_id>6</manager_id>
      <nickname>-- hidden --</nickname>
      <guid>WMKEJTV3VUJA4VZWQ25027W43M</guid>
    </manager>
  </managers>
  <team_points>
    <coverage_type>season</coverage_type>
    <season>2009</season>
    <total>1569.48</total>

```

developer

```

</team_standings>
</team>
<team>
  <team_key>223.1.431.t.12</team_key>
  <team_id>12</team_id>
  <name>Y! - Behrens</name>
  <url>https://football.fantasysports.yahoo.com/archive/pnfl/2009/431/12</url>
  <team_logos>
    <team_logo>
      <size>medium</size>
      <url>https://lookup.avatars.yahoo.com/images?
        yid=abehrens53&size=medium&type=jpg&pty=3000</url>
    </team_logo>
  </team_logos>
  <division_id>1</division_id>
  <faab_balance>0</faab_balance>
  <clinched_playoffs>1</clinched_playoffs>
  <managers>
    <manager>
      <manager_id>3</manager_id>
      <nickname>-- hidden --</nickname>
      <guid>E2KS77CDQPACRTSBCYP0FFW6AI</guid>
    </manager>
  </managers>
  <team_points>
    <coverage_type>season</coverage_type>
    <season>2009</season>
    <total>1652.27</total>
  </team_points>
  <team_standings>
    <rank>4</rank>
    <outcome_totals>
      <wins>8</wins>
      <losses>5</losses>
      <ties>0</ties>
      <percentage>.615</percentage>
    </outcome_totals>
    <divisional_outcome_totals>
      <wins>4</wins>
      <losses>2</losses>
      <ties>0</ties>
    </divisional_outcome_totals>
  </team_standings>
</team>

```

developer

```

        <losses>1</losses>
        <ties>0</ties>
    </divisional_outcome_totals>
</team_standings>
</team>
<team>
    <team_key>223.1.431.t.4</team_key>
    <team_id>4</team_id>
    <name>Salfino-Comcast/NESN</name>
    <url>https://football.fantasysports.yahoo.com/archive/pnfl/2009/431/4</url>
    <team_logos>
        <team_logo>
            <size>medium</size>

<url>https://a323.yahoofs.com/coreid/4d8a517fi1b71zul1re3/ypdMGIA8cbVafvybuj2J.Jg-/2/tn4
8.jpg?ciA8DVOB5bipYD0R</url>
        </team_logo>
    </team_logos>
    <division_id>2</division_id>
    <faab_balance>0</faab_balance>
    <clinched_playoffs>1</clinched_playoffs>
    <managers>
        <manager>
            <manager_id>9</manager_id>
            <nickname>-- hidden --</nickname>
            <guid>PDLVXDDVXK2FRDI3FHRSS74F2U</guid>
        </manager>
    </managers>
    <team_points>
        <coverage_type>season</coverage_type>
        <season>2009</season>
        <total>1621.98</total>
    </team_points>
    <team_standings>
        <rank>5</rank>
        <outcome_totals>
            <wins>7</wins>
            <losses>6</losses>
            <ties>0</ties>
            <percentage>.538</percentage>
        </outcome_totals>
        <divisional_outcome_totals>
            <wins>3</wins>
            <losses>3</losses>
            <ties>0</ties>
        </divisional_outcome_totals>
    </team_standings>

```

developer

```

<team_key>223.1.431.t.1</team_key>
<team_id>11</team_id>
<name>FantasyGuru.com-Hans</name>
<url>https://football.fantasysports.yahoo.com/archive/pnfl/2009/431/11</url>
<team_logos>
  <team_logo>
    <size>medium</size>
    <url>https://lookup.avatars.yahoo.com/images?
    yid=fantasygurudotcom&amp;size=medium&amp;type=jpg&amp;pty=3000</url>
  </team_logo>
</team_logos>
<division_id>2</division_id>
<faab_balance>1</faab_balance>
<clinched_playoffs>1</clinched_playoffs>
<managers>
  <manager>
    <manager_id>4</manager_id>
    <nickname>-- hidden --</nickname>
    <guid>B7IJFDI5UUTN3AQ2F7ZEA4BDU4</guid>
  </manager>
</managers>
<team_points>
  <coverage_type>season</coverage_type>
  <season>2009</season>
  <total>1469.00</total>
</team_points>
<team_standings>
  <rank>6</rank>
  <outcome_totals>
    <wins>7</wins>
    <losses>6</losses>
    <ties>0</ties>
    <percentage>.538</percentage>
  </outcome_totals>
  <divisional_outcome_totals>
    <wins>2</wins>
    <losses>4</losses>
    <ties>0</ties>
  </divisional_outcome_totals>
</team_standings>
</team>
<team>
  <team_key>223.1.431.t.1</team_key>
  <team_id>1</team_id>
  <name>PFW - Blunda</name>
  <url>https://football.fantasysports.yahoo.com/archive/pnfl/2009/431/1</url>
  <team_logos>
    <team_logo>

```

developer

```

</team_logos>
<division_id>2</division_id>
<faab_balance>22</faab_balance>
<managers>
  <manager>
    <manager_id>13</manager_id>
    <nickname>-- hidden --</nickname>
    <guid>XNAXQZRDZPJ3RVFMY7ZTSWEFLU</guid>
  </manager>
</managers>
<team_points>
  <coverage_type>season</coverage_type>
  <season>2009</season>
  <total>1461.71</total>
</team_points>
<team_standings>
  <rank>7</rank>
  <outcome_totals>
    <wins>7</wins>
    <losses>6</losses>
    <ties>0</ties>
    <percentage>.538</percentage>
  </outcome_totals>
  <divisional_outcome_totals>
    <wins>3</wins>
    <losses>3</losses>
    <ties>0</ties>
  </divisional_outcome_totals>
</team_standings>
</team>
<team>
  <team_key>223.1.431.t.2</team_key>
  <team_id>2</team_id>
  <name>Y! - Evans</name>
  <url>https://football.fantasysports.yahoo.com/archive/pnf1/2009/431/2</url>
  <team_logos>
    <team_logo>
      <size>medium</size>

<url>https://a323.yahoofs.com/coreid/4a68b2d6i2663zul3re3/HYebAP0zcqEPfMp3gOK8Mmbv/4/tn4
8.jpg?ciA8DVOBzMjxdtsK</url>
    </team_logo>
  </team_logos>
  <division_id>1</division_id>
  <faab_balance>35</faab_balance>
  <managers>
    <manager>

```


developer

```

    </manager>
  </managers>
  <team_points>
    <coverage_type>season</coverage_type>
    <season>2009</season>
    <total>1512.53</total>
  </team_points>
  <team_standings>
    <rank>8</rank>
    <outcome_totals>
      <wins>6</wins>
      <losses>7</losses>
      <ties>0</ties>
      <percentage>.462</percentage>
    </outcome_totals>
    <divisional_outcome_totals>
      <wins>2</wins>
      <losses>4</losses>
      <ties>0</ties>
    </divisional_outcome_totals>
  </team_standings>
</team>
<team>
  <team_key>223.1.431.t.13</team_key>
  <team_id>13</team_id>
  <name>Erickson - RotoWire</name>
  <url>https://football.fantasysports.yahoo.com/archive/pnfl/2009/431/13</url>
  <team_logos>
    <team_logo>
      <size>medium</size>
      <url>https://lookup.avatars.yahoo.com/images?
yid=jeff_rotonews&size=medium&type=jpg&pty=3000</url>
    </team_logo>
  </team_logos>
  <division_id>2</division_id>
  <faab_balance>17</faab_balance>
  <managers>
    <manager>
      <manager_id>11</manager_id>
      <nickname>-- hidden --</nickname>
      <guid>SB4Y5HVVUKMCTKZFQCXHIZ222E</guid>
    </manager>
  </managers>
  <team_points>
    <coverage_type>season</coverage_type>
    <season>2009</season>
    <total>1484.56</total>

```

developer

```

</team_standings>
</team>
<team>
  <team_key>223.1.431.t.9</team_key>
  <team_id>9</team_id>
  <name>Y! - Funston</name>
  <url>https://football.fantasysports.yahoo.com/archive/pnfl/2009/431/9</url>
  <team_logos>
    <team_logo>
      <size>medium</size>
      <url>https://lookup.avatars.yahoo.com/images?
yid=brandoanf1&size=medium&type=jpg&pty=3000</url>
    </team_logo>
  </team_logos>
  <division_id>1</division_id>
  <faab_balance>10</faab_balance>
  <managers>
    <manager>
      <manager_id>1</manager_id>
      <nickname>-- hidden --</nickname>
      <guid>3H7IQ3F2742K20DHSJK5YXL23E</guid>
      <is_commissioner>1</is_commissioner>
    </manager>
  </managers>
  <team_points>
    <coverage_type>season</coverage_type>
    <season>2009</season>
    <total>1430.24</total>
  </team_points>
  <team_standings>
    <rank>10</rank>
    <outcome_totals>
      <wins>6</wins>
      <losses>7</losses>
      <ties>0</ties>
      <percentage>.462</percentage>

```

developer

```

        <losses>4</losses>
        <ties>0</ties>
    </divisional_outcome_totals>
</team_standings>
</team>
<team>
    <team_key>223.1.431.t.7</team_key>
    <team_id>7</team_id>
    <name>RotoWire_Liss</name>
    <url>https://football.fantasysports.yahoo.com/archive/pnfl/2009/431/7</url>
    <team_logos>
        <team_logo>
            <size>medium</size>
            <url>https://l.yimg.com/a/i/us/sp/fn/default/full/nfl/icon_10_48.gif</url>
        </team_logo>
    </team_logos>
    <division_id>2</division_id>
    <faab_balance>68</faab_balance>
    <managers>
        <manager>
            <manager_id>7</manager_id>
            <nickname>-- hidden --</nickname>
            <guid>4BDB5LIG3IFVROH7SRBX44LBZM</guid>
        </manager>
    </managers>
    <team_points>
        <coverage_type>season</coverage_type>
        <season>2009</season>
        <total>1424.56</total>
    </team_points>
    <team_standings>
        <rank>11</rank>
        <outcome_totals>
            <wins>6</wins>
            <losses>7</losses>
            <ties>0</ties>
            <percentage>.462</percentage>
        </outcome_totals>
        <divisional_outcome_totals>
            <wins>3</wins>
            <losses>3</losses>
            <ties>0</ties>
        </divisional_outcome_totals>
    </team_standings>
</team>
<team>
    <team_key>223.1.431.t.3</team_key>

```

developer

```

<team_logos>
  <team_logo>
    <size>medium</size>
    <url>https://l.yimg.com/a/i/us/sp/fn/default/full/nfl/icon_05_48.gif</url>
  </team_logo>
</team_logos>
<division_id>2</division_id>
<faab_balance>0</faab_balance>
<managers>
  <manager>
    <manager_id>10</manager_id>
    <nickname>-- hidden --</nickname>
    <guid>4A5KVYHC7ZSEGOBFHFS05Q64VA</guid>
  </manager>
</managers>
<team_points>
  <coverage_type>season</coverage_type>
  <season>2009</season>
  <total>1366.89</total>
</team_points>
<team_standings>
  <rank>12</rank>
  <outcome_totals>
    <wins>6</wins>
    <losses>7</losses>
    <ties>0</ties>
    <percentage>.462</percentage>
  </outcome_totals>
  <divisional_outcome_totals>
    <wins>3</wins>
    <losses>3</losses>
    <ties>0</ties>
  </divisional_outcome_totals>
</team_standings>
</team>
<team>
  <team_key>223.1.431.t.6</team_key>
  <team_id>6</team_id>
  <name>Y! - Romig</name>
  <url>https://football.fantasysports.yahoo.com/archive/pnfl/2009/431/6</url>
  <team_logos>
    <team_logo>
      <size>medium</size>
      <url>https://a323.yahoofs.com/coreid/49b954dci229az/IJtbcRQjdKtd_DMoStSK/103/tn48.jpg?ciA8DVOB2wQ2Fk4F</url>
    </team_logo>

```

developer

```

</team_key>223.1.431.t.14</team_key>
<managers>
  <manager>
    <manager_id>2</manager_id>
    <nickname>-- hidden --</nickname>
    <guid>FS5M5LOFJRKVJNRIWG36ZUF7IQ</guid>
  </manager>
</managers>
<team_points>
  <coverage_type>season</coverage_type>
  <season>2009</season>
  <total>1370.16</total>
</team_points>
<team_standings>
  <rank>13</rank>
  <outcome_totals>
    <wins>5</wins>
    <losses>8</losses>
    <ties>0</ties>
    <percentage>.385</percentage>
  </outcome_totals>
  <divisional_outcome_totals>
    <wins>2</wins>
    <losses>4</losses>
    <ties>0</ties>
  </divisional_outcome_totals>
</team_standings>
</team>
<team>
  <team_key>223.1.431.t.14</team_key>
  <team_id>14</team_id>
  <name>Y! - Chase</name>
  <url>https://football.fantasysports.yahoo.com/archive/pnfl/2009/431/14</url>
  <team_logos>
    <team_logo>
      <size>medium</size>
    </team_logo>
  </team_logos>
  <division_id>1</division_id>
  <faab_balance>92</faab_balance>
  <managers>
    <manager>
      <manager_id>14</manager_id>
      <nickname>-- hidden --</nickname>
      <guid>7CSOKBMM74MGFMSWHWJMM4FBQ4</guid>
    </manager>
  </managers>
  <url>https://a323.yahoofs.com/coreid/4a7a23a5icfazul2re3/2fIcrk8yc7QS3j_ei4PULEbpFA-
  -/1/tn48.jpg?ciA8DV0BcEQk3vWZ</url>
  </team_logo>
</team_logos>
<division_id>1</division_id>
<faab_balance>92</faab_balance>
<managers>
  <manager>
    <manager_id>14</manager_id>
    <nickname>-- hidden --</nickname>
    <guid>7CSOKBMM74MGFMSWHWJMM4FBQ4</guid>
  </manager>
</managers>

```

developer

```

<team_points>
  <coverage_type>season</coverage_type>
  <season>2009</season>
  <total>1237.47</total>
</team_points>
<team_standings>
  <rank>14</rank>
  <outcome_totals>
    <wins>1</wins>
    <losses>12</losses>
    <ties>0</ties>
    <percentage>.077</percentage>
  </outcome_totals>
  <divisional_outcome_totals>
    <wins>1</wins>
    <losses>5</losses>
    <ties>0</ties>
  </divisional_outcome_totals>
</team_standings>
</team>
</teams>
</standings>
</league>
</fantasy_content>

```

<https://fantasysports.yahooapis.com/fantasy/v2/league/223.1.431/scoreboard>

```

<?xml version="1.0" encoding="UTF-8"?>
<fantasy_content xmlns:yahoo="http://www.yahooapis.com/v1/base.rng"
xmlns="http://fantasysports.yahooapis.com/fantasy/v2/base.rng" xml:lang="en-US"
yahoo:uri="http://fantasysports.yahooapis.com/fantasy/v2/league/223.1.431/scoreboard"
time="148.71311187744ms" copyright="Data provided by Yahoo! and STATS, LLC">
  <league>
    <league_key>223.1.431</league_key>
    <league_id>431</league_id>
    <name>Y! Friends and Family League</name>
    <url>https://football.fantasysports.yahoo.com/archive/pnfl/2009/431</url>
    <draft_status>postdraft</draft_status>
    <num_teams>14</num_teams>
    <edit_key>17</edit_key>
    <weekly_deadline/>
    <league_update_timestamp>1262595518</league_update_timestamp>
    <scoring_type>head</scoring_type>
    <current_week>16</current_week>
    <start_week>1</start_week>
    <end_week>16</end_week>
    <is_finished>1</is_finished>
  </league>

```

developer

```

<matchup>
  <week>16</week>
  <status>postevent</status>
  <is_tied>0</is_tied>
  <winner_team_key>223.1.431.t.10</winner_team_key>
  <teams count="2">
    <team>
      <team_key>223.1.431.t.5</team_key>
      <team_id>5</team_id>
      <name>RotoExperts</name>

    <url>https://football.fantasysports.yahoo.com/archive/pnfl/2009/431/5</url>
    <team_logos>
      <team_logo>
        <size>medium</size>

    <url>https://a323.yahoofs.com/coreid/49be42a6i26e5zul3re3/d2x_9_UweKP95SJZ_Hwnk2R1/2/tn4
    8.jpg?ciA8DVOBIRa6b7wq</url>
      </team_logo>
    </team_logos>
    <division_id>2</division_id>
    <faab_balance>1</faab_balance>
    <clinched_playoffs>1</clinched_playoffs>
    <managers>
      <manager>
        <manager_id>12</manager_id>
        <nickname>-- hidden --</nickname>
        <guid>RW3ELDFMOFTES2EUAWQVCPN7E</guid>
      </manager>
    </managers>
    <team_points>
      <coverage_type>week</coverage_type>
      <week>16</week>
      <total>135.22</total>
    </team_points>
    <team_projected_points>
      <coverage_type>week</coverage_type>
      <week>16</week>
      <total>142.81</total>
    </team_projected_points>
  </team>
  <team>
    <team_key>223.1.431.t.10</team_key>
    <team_id>10</team_id>
    <name>Gehlken</name>

    <url>https://football.fantasysports.yahoo.com/archive/pnfl/2009/431/10</url>

```

developer

```
<url>https://a323.yahoofs.com/coreid/4b978f0ci2432zws140sp2/imXqmYo8cq3NxEFtQB4wgAs-/6/t
n48.jpeg?ciA8DVOBMH.UXGXk</url>
```

```
    </team_logo>
  </team_logos>
  <division_id>1</division_id>
  <faab_balance>0</faab_balance>
  <clinched_playoffs>1</clinched_playoffs>
  <managers>
    <manager>
      <manager_id>5</manager_id>
      <nickname>-- hidden --</nickname>
      <guid>4LAITFUXFASDNAXFWUOHWNU3BY</guid>
    </manager>
  </managers>
  <team_points>
    <coverage_type>week</coverage_type>
    <week>16</week>
    <total>137.86</total>
  </team_points>
  <team_projected_points>
    <coverage_type>week</coverage_type>
    <week>16</week>
    <total>133.57</total>
  </team_projected_points>
</team>
</teams>
</matchup>
<matchup>
  <week>16</week>
  <status>postevent</status>
  <is_tied>0</is_tied>
  <winner_team_key>223.1.431.t.8</winner_team_key>
  <teams count="2">
    <team>
      <team_key>223.1.431.t.8</team_key>
      <team_id>8</team_id>
      <name>Y! - Pianowski</name>
```

```
<url>https://football.fantasysports.yahoo.com/archive/pnfl/2009/431/8</url>
  <team_logos>
    <team_logo>
      <size>medium</size>
```

```
<url>https://l.yimg.com/a/i/us/sp/fn/default/full/nfl/icon_10_48.gif</url>
  </team_logo>
</team_logos>
```


<https://developer.yahoo.com/fantasysports/guide/> 49/9

```
</team_projected_points>
</team>
</teams>
</matchup>
</matchups>
</scoreboard>
</league>
</fantasy_content>
```

Leagues collection

Description

With the Leagues API, you can obtain information from a collection of leagues simultaneously. Each element beneath the Leagues Collection will be a [League Resource](#)

HTTP Operations Supported

- GET

URIs

Any [sub-resource](#) valid for a league is a valid sub-resource under the leagues collection.

Any sub-resource for a collection of leagues is extracted using a URI like:

```
/leagues/{sub_resource}
```

OR

```
/leagues;league_keys={league_key1},{league_key2}/{sub_resource}
```

Multiple sub-resources can be extracted from leagues in the same URI using a format like:

```
/leagues;out={sub_resource_1},{sub_resource_2}
```

OR

```
/leagues;league_keys={league_key1},{league_key2};out={sub_resource_1},{sub_resource_2}
```

Description

The Team APIs allow you to retrieve information about a team within our fantasy games. The team is the basic unit for keeping track of a roster of players, and can be managed by either one or two managers (the second manager being called a co-manager). With the Team APIs, you can obtain team-related information, like the team name, managers, logos, stats and points, and rosters for particular weeks. Teams only exist in the context of a particular [League](#), although you can request a Team Resource as the base of your URI by using the global `team`. A particular user can only retrieve data about a team if that team is part of a private league of which the user is a member, or if it's in a public league.

HTTP Operations Supported

- GET

URIs

`https://fantasysports.yahooapis.com/fantasy/v2/team/`

Any sub-resource under a team is extracted using a URI like:

`https://fantasysports.yahooapis.com/fantasy/v2/team/`

Multiple sub-resources can be extracted from team in the same URI using a format like:

`https://fantasysports.yahooapis.com/fantasy/v2/team/?out=,{sub_resource_2}`

Team key format

`.l.{league_id}.t.{team_id}`

Example: `pnf1.1.431.t.1` or `223.1.431.t.1`

Sub-resources

Default sub-resource: `metadata`

developer

```
<?xml version="1.0" encoding="UTF-8"?>
<fantasy_content xmlns:yahoo="http://www.yahooapis.com/v1/base.rng"
xmlns="http://fantasysports.yahooapis.com/fantasy/v2/base.rng" xml:lang="en-US"
yahoo:uri="http://fantasysports.yahooapis.com/fantasy/v2/team/223.1.431.t.1"
time="426.26690864563ms" copyright="Data provided by Yahoo! and STATS, LLC">
  <team>
    <team_key>223.1.431.t.1</team_key>
    <team_id>1</team_id>
    <name>PFW - Blunda</name>
    <url>https://football.fantasysports.yahoo.com/archive/pnfl/2009/431/1</url>
    <team_logos>
      <team_logo>
        <size>medium</size>
        <url>https://l.yimg.com/a/i/us/sp/fn/default/full/nfl/icon_01_48.gif</url>
      </team_logo>
    </team_logos>
    <division_id>2</division_id>
    <faab_balance>22</faab_balance>
    <managers>
      <manager>
        <manager_id>13</manager_id>
        <nickname>Michael Blunda</nickname>
        <guid>XNAXQZRDZPJ3RVFMY7ZTSWEFLU</guid>
      </manager>
    </managers>
  </team>
</fantasy_content>
```

<https://fantasysports.yahooapis.com/fantasy/v2/team/223.1.431.t.1/matchups;weeks=1,5> - team's matchups for weeks 1 and 5 in a NFL H2H league

```
<?xml version="1.0" encoding="UTF-8"?>
<fantasy_content xmlns:yahoo="http://www.yahooapis.com/v1/base.rng"
xmlns="http://fantasysports.yahooapis.com/fantasy/v2/base.rng" xml:lang="en-US"
yahoo:uri="http://fantasysports.yahooapis.com/fantasy/v2/team/223.1.431.t.1/matchups;weeks=1,5"
time="576.54285430908ms" copyright="Data provided by Yahoo! and STATS, LLC">
  <team>
    <team_key>223.1.431.t.1</team_key>
    <team_id>1</team_id>
    <name>PFW - Blunda</name>
    <url>https://football.fantasysports.yahoo.com/archive/pnfl/2009/431/1</url>
    <team_logos>
      <team_logo>
        <size>medium</size>
```

developer

```

</team_logos>
<division_id>2</division_id>
<faab_balance>22</faab_balance>
<managers>
  <manager>
    <manager_id>13</manager_id>
    <nickname>Michael Blunda</nickname>
    <guid>XNAXQZRDZPJ3RVFMY7ZTSWEFLU</guid>
  </manager>
</managers>
<matchups count="2">
  <matchup>
    <week>1</week>
    <status>postevent</status>
    <is_tied>0</is_tied>
    <winner_team_key>223.1.431.t.1</winner_team_key>
    <teams count="2">
      <team>
        <team_key>223.1.431.t.1</team_key>
        <team_id>1</team_id>
        <name>PFW - Blunda</name>
        <url>https://football.fantasysports.yahoo.com/archive/pnfl/2009/431/1</url>
        <team_logos>
          <team_logo>
            <size>medium</size>

<url>https://l.yimg.com/a/i/us/sp/fn/default/full/nfl/icon_01_48.gif</url>
          </team_logo>
        </team_logos>
      </team>
    </teams>
  </matchup>
</matchups>
<division_id>2</division_id>
<faab_balance>22</faab_balance>
<managers>
  <manager>
    <manager_id>13</manager_id>
    <nickname>Michael Blunda</nickname>
    <guid>XNAXQZRDZPJ3RVFMY7ZTSWEFLU</guid>
  </manager>
</managers>
<team_points>
  <coverage_type>week</coverage_type>
  <week>1</week>
  <total>117.88</total>
</team_points>
<team_projected_points>
  <coverage_type>week</coverage_type>
  <week>1</week>
  <total>107.94</total>
</team_projected_points>

```

developer

```

<team_key>223.1.431.t.1</team_key>
<team_id>5</team_id>
<name>RotoExperts</name>
<url>https://football.fantasysports.yahoo.com/archive/pnfl/2009/431/5</url>
<team_logos>
  <team_logo>
    <size>medium</size>

<url>https://a323.yahoofs.com/coreid/49be42a6i26e5zul3re3/d2x_9_UweKP95SJZ_Hwnk2R1/2/tn4
8.jpg?ciA8DVOBIRa6b7wq</url>
  </team_logo>
</team_logos>
<division_id>2</division_id>
<faab_balance>1</faab_balance>
<clinched_playoffs>1</clinched_playoffs>
<managers>
  <manager>
    <manager_id>12</manager_id>
    <nickname>Scott</nickname>
    <guid>RW3ELDFM0FTES2EUAWQVCPN7E</guid>
  </manager>
</managers>
<team_points>
  <coverage_type>week</coverage_type>
  <week>1</week>
  <total>103.82</total>
</team_points>
<team_projected_points>
  <coverage_type>week</coverage_type>
  <week>1</week>
  <total>110.41</total>
</team_projected_points>
</team>
</teams>
</matchup>
<matchup>
  <week>5</week>
  <status>postevent</status>
  <is_tied>0</is_tied>
  <winner_team_key>223.1.431.t.1</winner_team_key>
  <teams count="2">
    <team>
      <team_key>223.1.431.t.1</team_key>
      <team_id>1</team_id>
      <name>PFW - Blunda</name>
      <url>https://football.fantasysports.yahoo.com/archive/pnfl/2009/431/1</url>
      <team_logos>
        <team_logo>

```

developer

```

    </team_logo>
  </team_logos>
  <division_id>2</division_id>
  <faab_balance>22</faab_balance>
  <managers>
    <manager>
      <manager_id>13</manager_id>
      <nickname>Michael Blunda</nickname>
      <guid>XNAXQZRDZPJ3RVFMY7ZTSWEFLU</guid>
    </manager>
  </managers>
  <team_points>
    <coverage_type>week</coverage_type>
    <week>5</week>
    <total>140.00</total>
  </team_points>
  <team_projected_points>
    <coverage_type>week</coverage_type>
    <week>5</week>
    <total>110.85</total>
  </team_projected_points>
</team>
<team>
  <team_key>223.1.431.t.7</team_key>
  <team_id>7</team_id>
  <name>RotoWire_Liss</name>
  <url>https://football.fantasysports.yahoo.com/archive/pnfl/2009/431/7</url>
  <team_logos>
    <team_logo>
      <size>medium</size>

<url>https://l.yimg.com/a/i/us/sp/fn/default/full/nfl/icon_10_48.gif</url>
    </team_logo>
  </team_logos>
  <division_id>2</division_id>
  <faab_balance>68</faab_balance>
  <managers>
    <manager>
      <manager_id>7</manager_id>
      <nickname>RotoWire_Liss</nickname>
      <guid>4BDB5LIG3IFVROH7SRBX44LBZM</guid>
    </manager>
  </managers>
  <team_points>
    <coverage_type>week</coverage_type>
    <week>5</week>
    <total>86.47</total>

```

developer

```

    </coverage_type>
    <week>5</week>
    <total>88.14</total>
  </team_projected_points>
</team>
</teams>
</matchup>
</matchups>
</team>
</fantasy_content>

```

<https://fantasysports.yahooapis.com/fantasy/v2/team/223.1.431.t.1/stats?type=season> - team's season stats in a NFL H2H league

```

<?xml version="1.0" encoding="UTF-8"?>
<fantasy_content xmlns:yahoo="http://www.yahooapis.com/v1/base.rng"
xmlns="http://fantasysports.yahooapis.com/fantasy/v2/base.rng" xml:lang="en-US"
yahoo:uri="http://fantasysports.yahooapis.com/fantasy/v2/team/223.1.431.t.1/stats?type=s
eason" time="129.66799736023ms" copyright="Data provided by Yahoo! and STATS, LLC">
  <team>
    <team_key>223.1.431.t.1</team_key>
    <team_id>1</team_id>
    <name>PFW - Blunda</name>
    <url>https://football.fantasysports.yahoo.com/archive/pnfl/2009/431/1</url>
    <team_logos>
      <team_logo>
        <size>medium</size>
        <url>https://l.yimg.com/a/i/us/sp/fn/default/full/nfl/icon_01_48.gif</url>
      </team_logo>
    </team_logos>
    <division_id>2</division_id>
    <faab_balance>22</faab_balance>
    <managers>
      <manager>
        <manager_id>13</manager_id>
        <nickname>Michael Blunda</nickname>
        <guid>XNAXQZRDZPJ3RVFMY7ZTSWEFLU</guid>
      </manager>
    </managers>
    <team_points>
      <coverage_type>season</coverage_type>
      <season>2009</season>
      <total>1461.71</total>
    </team_points>
  </team>
</fantasy_content>

```


developer

```
<?xml version="1.0" encoding="UTF-8"?>
<fantasy_content xmlns:yahoo="http://www.yahooapis.com/v1/base.rng"
xmlns="http://fantasysports.yahooapis.com/fantasy/v2/base.rng" xml:lang="en-US"
yahoo:uri="http://fantasysports.yahooapis.com/fantasy/v2/team/253.l.102614.t.10/stats;date=2011-07-06;type=date" time="68.986892700195ms" copyright="Data provided by Yahoo! and STATS, LLC">
  <team>
    <team_key>253.l.102614.t.10</team_key>
    <team_id>10</team_id>
    <name>Matt Dzaman</name>
    <url>https://baseball.fantasysports.yahoo.com/b1/102614/10</url>
    <team_logos>
      <team_logo>
        <size>medium</size>
        <url>https://l.yimg.com/a/i/us/sp/fn/mlb/gr/icon_12_2.gif</url>
      </team_logo>
    </team_logos>
    <managers>
      <manager>
        <manager_id>10</manager_id>
        <nickname>smock514</nickname>
        <guid>VZVEVUCLSJAHS73FMJ4BYFIKU</guid>
        <exposed_yahoo_id>1</exposed_yahoo_id>
      </manager>
    </managers>
    <team_stats>
      <coverage_type>date</coverage_type>
      <date>2011-07-06</date>
      <stats>
        <stat>
          <stat_id>60</stat_id>
          <value>13/31</value>
        </stat>
        <stat>
          <stat_id>7</stat_id>
          <value>9</value>
        </stat>
        <stat>
          <stat_id>12</stat_id>
          <value>3</value>
        </stat>
        <stat>
          <stat_id>13</stat_id>
          <value>11</value>
        </stat>
        <stat>
```

```

</stats>
</team_stats>
</team>
</fantasy_content>

```

Roster resource

Description

Players on a team are organized into rosters corresponding to certain weeks, in NFL, or certain dates, in MLB, NBA, and NHL. Each player on a roster will be assigned a position if they're in the starting lineup, or will be on the bench. You can only receive credit for stats accumulated by players in your starting lineup.

You can use this API to edit your lineup by PUT ting up new positions for the players on a roster. You can also add/drop players from your roster by `POST` ing new transactions `<#transactions-collection-POST>`__` to the league's transactions collection.

developer

- GET
- PUT <#roster-resource-PUT>`__

URIs

<https://fantasysports.yahooapis.com/fantasy/v2/team//roster>

Any sub-resource under a roster is extracted using a URI like:

<https://fantasysports.yahooapis.com/fantasy/v2/team//roster/>

For NFL, you can specify a week parameter to retrieve a specific week – otherwise it will default to the current roster

<https://fantasysports.yahooapis.com/fantasy/v2/team//roster;week=10>

For MLB, NHL, or NBA, you can specify a date parameter to retrieve a specific date – otherwise it will default to today's roster.

<https://fantasysports.yahooapis.com/fantasy/v2/team//roster;date=2011-05-01>

Sub-resources

Default sub-resource: players

Sample XML

<https://fantasysports.yahooapis.com/fantasy/v2/team/253.1.102614.t.10/roster/players>

```
<?xml version="1.0" encoding="UTF-8"?>
<fantasy_content xmlns:yahoo="http://www.yahooapis.com/v1/base.rng"
xmlns="http://fantasysports.yahooapis.com/fantasy/v2/base.rng" xml:lang="en-US"
yahoo:uri="http://fantasysports.yahooapis.com/fantasy/v2/team/253.1.102614.t.10/roster/p
layers" time="110.02206802368ms" copyright="Data provided by Yahoo! and STATS, LLC">
  <team>
    <team_key>253.1.102614.t.10</team_key>
    <team_id>10</team_id>
    <name>Matt Dzaman</name>
    <url>https://baseball.fantasysports.yahoo.com/b1/102614/10</url>
    <team_logos>
```

developer

```

</team_logo>
</team_logos>
<managers>
  <manager>
    <manager_id>10</manager_id>
    <nickname>Sean Montgomery</nickname>
    <guid>VZVEVUCLSJAHSM73FMJ4BYFIKU</guid>
    <is_current_login>1</is_current_login>
  </manager>
</managers>
<roster>
  <coverage_type>date</coverage_type>
  <date>2011-07-22</date>
  <players count="22">
    <player>
      <player_key>253.p.7569</player_key>
      <player_id>7569</player_id>
      <name>
        <full>Brian McCann</full>
        <first>Brian</first>
        <last>McCann</last>
        <ascii_first>Brian</ascii_first>
        <ascii_last>McCann</ascii_last>
      </name>
      <editorial_player_key>mlb.p.7569</editorial_player_key>
      <editorial_team_key>mlb.t.15</editorial_team_key>
      <editorial_team_full_name>Atlanta Braves</editorial_team_full_name>
      <editorial_team_abbr>Atl</editorial_team_abbr>
      <uniform_number>16</uniform_number>
      <display_position>C</display_position>
      <image_url>https://l.yimg.com/a/i/us/sp/v/mlb/players_1/20110503x/7569.jpg?
x=46& y=60& xc=1& yc=1& wc=164& hc=215& q=100& sig=eYxVIp_jg4DlEZmI
gv6idg--</image_url>
      <is_undroppable>0</is_undroppable>
      <position_type>B</position_type>
      <eligible_positions>
        <position>C</position>
        <position>Util</position>
      </eligible_positions>
      <has_player_notes>1</has_player_notes>
      <selected_position>
        <coverage_type>date</coverage_type>
        <date>2011-07-22</date>
        <position>C</position>
      </selected_position>
      <starting_status>
        <coverage_type>date</coverage_type>

```

developer

```

</player>
<player>
  <player_key>253.p.7054</player_key>
  <player_id>7054</player_id>
  <name>
    <full>Adrian Gonzalez</full>
    <first>Adrian</first>
    <last>Gonzalez</last>
    <ascii_first>Adrian</ascii_first>
    <ascii_last>Gonzalez</ascii_last>
  </name>
  <editorial_player_key>mlb.p.7054</editorial_player_key>
  <editorial_team_key>mlb.t.2</editorial_team_key>
  <editorial_team_full_name>Boston Red Sox</editorial_team_full_name>
  <editorial_team_abbr>Bos</editorial_team_abbr>
  <uniform_number>28</uniform_number>
  <display_position>1B</display_position>
  <image_url>https://l.yimg.com/a/i/us/sp/v/mlb/players_1/20110503x/7054.jpg?
x=46& y=60& xc=1& yc=1& wc=164& hc=215& q=100& sig=54B0DgSe4P3NxShT
jtIt9g--</image_url>
  <is_undroppable>0</is_undroppable>
  <position_type>B</position_type>
  <eligible_positions>
    <position>1B</position>
    <position>Util</position>
  </eligible_positions>
  <has_player_notes>1</has_player_notes>
  <selected_position>
    <coverage_type>date</coverage_type>
    <date>2011-07-22</date>
    <position>1B</position>
  </selected_position>
  <starting_status>
    <coverage_type>date</coverage_type>
    <date>2011-07-22</date>
    <is_starting>1</is_starting>
  </starting_status>
</player>
<player>
  <player_key>253.p.7746</player_key>
  <player_id>7746</player_id>
  <name>
    <full>Howie Kendrick</full>
    <first>Howie</first>
    <last>Kendrick</last>
    <ascii_first>Howie</ascii_first>
    <ascii_last>Kendrick</ascii_last>

```

developer

```

</editorial_team_key>
<editorial_team_full_name>Los Angeles Angels</editorial_team_full_name>
<editorial_team_abbr>LAA</editorial_team_abbr>
<uniform_number>47</uniform_number>
<display_position>1B,2B,OF</display_position>
<image_url>https://l.yimg.com/a/i/us/sp/v/mlb/players_1/20110503x/7746.jpg?
x=46& y=60& xc=1& yc=1& wc=164& hc=215& q=100& sig=001i1gf0s6RgisJQ
jmdipQ--</image_url>
<is_undroppable>0</is_undroppable>
<position_type>B</position_type>
<eligible_positions>
  <position>1B</position>
  <position>2B</position>
  <position>OF</position>
  <position>Util</position>
</eligible_positions>
<has_player_notes>1</has_player_notes>
<has_recent_player_notes>1</has_recent_player_notes>
<selected_position>
  <coverage_type>date</coverage_type>
  <date>2011-07-22</date>
  <position>2B</position>
</selected_position>
<starting_status>
  <coverage_type>date</coverage_type>
  <date>2011-07-22</date>
  <is_starting>0</is_starting>
</starting_status>
</player>
<player>
  <player_key>253.p.7737</player_key>
  <player_id>7737</player_id>
  <name>
    <full>Martin Prado</full>
    <first>Martin</first>
    <last>Prado</last>
    <ascii_first>Martin</ascii_first>
    <ascii_last>Prado</ascii_last>
  </name>
  <editorial_player_key>mlb.p.7737</editorial_player_key>
  <editorial_team_key>mlb.t.15</editorial_team_key>
  <editorial_team_full_name>Atlanta Braves</editorial_team_full_name>
  <editorial_team_abbr>Atl</editorial_team_abbr>
  <uniform_number>14</uniform_number>
  <display_position>2B,3B,OF</display_position>
  <image_url>https://l.yimg.com/a/i/us/sp/v/mlb/players_1/20110503x/7737.jpg?
x=46& y=60& xc=1& yc=1& wc=164& hc=215& q=100& sig=WPYI1x062JwsL8Qt
urlmJw--</image_url>

```

developer

```

</eligible_positions>
  <position>2B</position>
  <position>3B</position>
  <position>OF</position>
  <position>Util</position>
</eligible_positions>
<has_player_notes>1</has_player_notes>
<selected_position>
  <coverage_type>date</coverage_type>
  <date>2011-07-22</date>
  <position>3B</position>
</selected_position>
<starting_status>
  <coverage_type>date</coverage_type>
  <date>2011-07-22</date>
  <is_starting>1</is_starting>
</starting_status>
</player>
<player>
  <player_key>253.p.7744</player_key>
  <player_id>7744</player_id>
  <name>
    <full>Erick Aybar</full>
    <first>Erick</first>
    <last>Aybar</last>
    <ascii_first>Erick</ascii_first>
    <ascii_last>Aybar</ascii_last>
  </name>
  <editorial_player_key>mlb.p.7744</editorial_player_key>
  <editorial_team_key>mlb.t.3</editorial_team_key>
  <editorial_team_full_name>Los Angeles Angels</editorial_team_full_name>
  <editorial_team_abbr>LAA</editorial_team_abbr>
  <uniform_number>2</uniform_number>
  <display_position>SS</display_position>
  <image_url>https://l.yimg.com/a/i/us/sp/v/mlb/players_1/20110503x/7744.jpg?
x=46& y=60& xc=1& yc=1& wc=164& hc=215& q=100& sig=qHzsNyGFtGYxlpMx
tysSPQ--</image_url>
  <is_undroppable>0</is_undroppable>
  <position_type>B</position_type>
  <eligible_positions>
    <position>SS</position>
    <position>Util</position>
  </eligible_positions>
  <selected_position>
    <coverage_type>date</coverage_type>
    <date>2011-07-22</date>
    <position>SS</position>
  </selected_position>

```

developer

```

    </is_starting>1</is_starting>
  </starting_status>
</player>
<player>
  <player_key>253.p.7977</player_key>
  <player_id>7977</player_id>
  <name>
    <full>Andrew McCutchen</full>
    <first>Andrew</first>
    <last>McCutchen</last>
    <ascii_first>Andrew</ascii_first>
    <ascii_last>McCutchen</ascii_last>
  </name>
  <editorial_player_key>mlb.p.7977</editorial_player_key>
  <editorial_team_key>mlb.t.23</editorial_team_key>
  <editorial_team_full_name>Pittsburgh Pirates</editorial_team_full_name>
  <editorial_team_abbr>Pit</editorial_team_abbr>
  <uniform_number>22</uniform_number>
  <display_position>OF</display_position>
  <image_url>https://l.yimg.com/a/p/sp/tools/med/2011/05/ipt/1304541420.jpg?
x=46&y=60&xc=1&yc=1&wc=164&hc=215&q=100&sig=61GeaeZwqXZWY2IT
0X62Zg--</image_url>
  <is_undroppable>0</is_undroppable>
  <position_type>B</position_type>
  <eligible_positions>
    <position>OF</position>
    <position>Util</position>
  </eligible_positions>
  <has_player_notes>1</has_player_notes>
  <selected_position>
    <coverage_type>date</coverage_type>
    <date>2011-07-22</date>
    <position>OF</position>
  </selected_position>
</player>
<player>
  <player_key>253.p.7104</player_key>
  <player_id>7104</player_id>
  <name>
    <full>Shane Victorino</full>
    <first>Shane</first>
    <last>Victorino</last>
    <ascii_first>Shane</ascii_first>
    <ascii_last>Victorino</ascii_last>
  </name>
  <editorial_player_key>mlb.p.7104</editorial_player_key>
  <editorial_team_key>mlb.t.22</editorial_team_key>

```


developer

```

</player>
<display_position>OF</display_position>
<image_url>https://l.yimg.com/a/i/us/sp/v/mlb/players_1/20110503x/7104.jpg?
x=46&y=60&x=1&y=1&wc=164&hc=215&q=100&sig=QE9iNVRK5VCHq650
WQii4g--</image_url>
<is_undroppable>0</is_undroppable>
<position_type>B</position_type>
<eligible_positions>
  <position>OF</position>
  <position>Util</position>
</eligible_positions>
<has_player_notes>1</has_player_notes>
<selected_position>
  <coverage_type>date</coverage_type>
  <date>2011-07-22</date>
  <position>OF</position>
</selected_position>
<starting_status>
  <coverage_type>date</coverage_type>
  <date>2011-07-22</date>
  <is_starting>1</is_starting>
</starting_status>
</player>
<player>
  <player_key>253.p.8239</player_key>
  <player_id>8239</player_id>
  <name>
    <full>Matt Joyce</full>
    <first>Matt</first>
    <last>Joyce</last>
    <ascii_first>Matt</ascii_first>
    <ascii_last>Joyce</ascii_last>
  </name>
  <editorial_player_key>mlb.p.8239</editorial_player_key>
  <editorial_team_key>mlb.t.30</editorial_team_key>
  <editorial_team_full_name>Tampa Bay Rays</editorial_team_full_name>
  <editorial_team_abbr>TB</editorial_team_abbr>
  <uniform_number>20</uniform_number>
  <display_position>OF</display_position>
  <image_url>https://l.yimg.com/a/i/us/sp/v/mlb/players_1/20110503x/8239.jpg?
x=46&y=60&x=1&y=1&wc=164&hc=215&q=100&sig=ZIY1Z9IryxkYXVsS
sodRfQ--</image_url>
  <is_undroppable>0</is_undroppable>
  <position_type>B</position_type>
  <eligible_positions>
    <position>OF</position>
    <position>Util</position>
  </eligible_positions>

```

developer

```

    </coverage_type>date
    <date>2011-07-22</date>
    <position>OF</position>
  </selected_position>
</player>
<player>
  <player_key>253.p.8857</player_key>
  <player_id>8857</player_id>
  <name>
    <full>Eric Hosmer</full>
    <first>Eric</first>
    <last>Hosmer</last>
    <ascii_first>Eric</ascii_first>
    <ascii_last>Hosmer</ascii_last>
  </name>
  <editorial_player_key>mlb.p.8857</editorial_player_key>
  <editorial_team_key>mlb.t.7</editorial_team_key>
  <editorial_team_full_name>Kansas City Royals</editorial_team_full_name>
  <editorial_team_abbr>KC</editorial_team_abbr>
  <uniform_number>35</uniform_number>
  <display_position>1B</display_position>
  <image_url>https://l.yimg.com/a/i/us/sp/v/mlb/players_1/20110706/8857.jpg?
x=46& y=60& xc=1& yc=1& wc=164& hc=215& q=100& sig=h5CchQfLoumJ6xXR
YqQNOw--</image_url>
  <is_undroppable>0</is_undroppable>
  <position_type>B</position_type>
  <eligible_positions>
    <position>1B</position>
    <position>Util</position>
  </eligible_positions>
  <selected_position>
    <coverage_type>date</coverage_type>
    <date>2011-07-22</date>
    <position>Util</position>
  </selected_position>
</player>
<player>
  <player_key>253.p.8171</player_key>
  <player_id>8171</player_id>
  <name>
    <full>Jay Bruce</full>
    <first>Jay</first>
    <last>Bruce</last>
    <ascii_first>Jay</ascii_first>
    <ascii_last>Bruce</ascii_last>
  </name>
  <editorial_player_key>mlb.p.8171</editorial_player_key>
  <editorial_team_key>mlb.t.17</editorial_team_key>

```

developer

```

</display_position>OF</display_position>
<image_url>https://l.yimg.com/a/i/us/sp/v/mlb/players_1/20110503x/8171.jpg?
x=46&y=60&xc=1&yc=1&wc=164&hc=215&q=100&sig=icy.cvuP8XXvyrQK
m7m3HA--</image_url>
<is_undroppable>0</is_undroppable>
<position_type>B</position_type>
<eligible_positions>
  <position>OF</position>
  <position>Util</position>
</eligible_positions>
<has_player_notes>1</has_player_notes>
<has_recent_player_notes>1</has_recent_player_notes>
<selected_position>
  <coverage_type>date</coverage_type>
  <date>2011-07-22</date>
  <position>BN</position>
</selected_position>
<starting_status>
  <coverage_type>date</coverage_type>
  <date>2011-07-22</date>
  <is_starting>0</is_starting>
</starting_status>
</player>
<player>
  <player_key>253.p.8401</player_key>
  <player_id>8401</player_id>
  <name>
    <full>Elvis Andrus</full>
    <first>Elvis</first>
    <last>Andrus</last>
    <ascii_first>Elvis</ascii_first>
    <ascii_last>Andrus</ascii_last>
  </name>
  <editorial_player_key>mlb.p.8401</editorial_player_key>
  <editorial_team_key>mlb.t.13</editorial_team_key>
  <editorial_team_full_name>Texas Rangers</editorial_team_full_name>
  <editorial_team_abbr>Tex</editorial_team_abbr>
  <uniform_number>1</uniform_number>
  <display_position>SS</display_position>
  <image_url>https://l.yimg.com/a/i/us/sp/v/mlb/players_1/20110503x/8401.jpg?
x=46&y=60&xc=1&yc=1&wc=164&hc=215&q=100&sig=HIAp3xabHCwOw.hJ
pkbd1w--</image_url>
  <is_undroppable>0</is_undroppable>
  <position_type>B</position_type>
  <eligible_positions>
    <position>SS</position>
    <position>Util</position>

```

developer

```

</selected_position>
  <coverage_type>date</coverage_type>
  <date>2011-07-22</date>
  <position>BN</position>
</selected_position>
<starting_status>
  <coverage_type>date</coverage_type>
  <date>2011-07-22</date>
  <is_starting>1</is_starting>
</starting_status>
</player>
<player>
  <player_key>253.p.7926</player_key>
  <player_id>7926</player_id>
  <name>
    <full>Yovani Gallardo</full>
    <first>Yovani</first>
    <last>Gallardo</last>
    <ascii_first>Yovani</ascii_first>
    <ascii_last>Gallardo</ascii_last>
  </name>
  <editorial_player_key>mlb.p.7926</editorial_player_key>
  <editorial_team_key>mlb.t.8</editorial_team_key>
  <editorial_team_full_name>Milwaukee Brewers</editorial_team_full_name>
  <editorial_team_abbr>Mil</editorial_team_abbr>
  <uniform_number>49</uniform_number>
  <display_position>SP</display_position>
  <image_url>https://l.yimg.com/a/i/us/sp/v/mlb/players_1/20110503x/7926.jpg?
x=46& y=60& xc=1& yc=1& wc=164& hc=215& q=100& sig=1lRXgDptEQng1WvY
IB3vDQ--</image_url>
  <is_undroppable>0</is_undroppable>
  <position_type>P</position_type>
  <eligible_positions>
    <position>SP</position>
    <position>P</position>
  </eligible_positions>
  <has_player_notes>1</has_player_notes>
  <selected_position>
    <coverage_type>date</coverage_type>
    <date>2011-07-22</date>
    <position>SP</position>
  </selected_position>
</player>
<player>
  <player_key>253.p.7172</player_key>
  <player_id>7172</player_id>
  <name>

```

developer

```

<ascii_first>Dan</ascii_first>
<ascii_last>Haren</ascii_last>
</name>
<editorial_player_key>mlb.p.7172</editorial_player_key>
<editorial_team_key>mlb.t.3</editorial_team_key>
<editorial_team_full_name>Los Angeles Angels</editorial_team_full_name>
<editorial_team_abbr>LAA</editorial_team_abbr>
<uniform_number>24</uniform_number>
<display_position>SP</display_position>
<image_url>https://l.yimg.com/a/i/us/sp/v/mlb/players_1/20110503x/7172.jpg?
x=46&y=60&xc=1&yc=1&wc=164&hc=215&q=100&sig=fnc4Dr.qGpHVMt8t
W4phOQ--</image_url>
<is_undroppable>0</is_undroppable>
<position_type>P</position_type>
<eligible_positions>
  <position>SP</position>
  <position>P</position>
</eligible_positions>
<has_player_notes>1</has_player_notes>
<selected_position>
  <coverage_type>date</coverage_type>
  <date>2011-07-22</date>
  <position>SP</position>
</selected_position>
</player>
<player>
  <player_key>253.p.6210</player_key>
  <player_id>6210</player_id>
  <name>
    <full>Kyle Farnsworth</full>
    <first>Kyle</first>
    <last>Farnsworth</last>
    <ascii_first>Kyle</ascii_first>
    <ascii_last>Farnsworth</ascii_last>
  </name>
  <editorial_player_key>mlb.p.6210</editorial_player_key>
  <editorial_team_key>mlb.t.30</editorial_team_key>
  <editorial_team_full_name>Tampa Bay Rays</editorial_team_full_name>
  <editorial_team_abbr>TB</editorial_team_abbr>
  <uniform_number>43</uniform_number>
  <display_position>RP</display_position>
  <image_url>https://l.yimg.com/a/i/us/sp/v/mlb/players_1/20110503x/6210.jpg?
x=46&y=60&xc=1&yc=1&wc=164&hc=215&q=100&sig=kJYLFUywfddzSTtT
Q5MupQ--</image_url>
  <is_undroppable>0</is_undroppable>
  <position_type>P</position_type>
  <eligible_positions>

```

developer

```

</eligible_positions>
<has_player_notes>1</has_player_notes>
<selected_position>
  <coverage_type>date</coverage_type>
  <date>2011-07-22</date>
  <position>RP</position>
</selected_position>
</player>
<player>
  <player_key>253.p.8929</player_key>
  <player_id>8929</player_id>
  <name>
    <full>Javy Guerra</full>
    <first>Javy</first>
    <last>Guerra</last>
    <ascii_first>Javy</ascii_first>
    <ascii_last>Guerra</ascii_last>
  </name>
  <editorial_player_key>mlb.p.8929</editorial_player_key>
  <editorial_team_key>mlb.t.19</editorial_team_key>
  <editorial_team_full_name>Los Angeles Dodgers</editorial_team_full_name>
  <editorial_team_abbr>LAD</editorial_team_abbr>
  <uniform_number>54</uniform_number>
  <display_position>RP</display_position>
  <image_url>https://l.yimg.com/a/i/us/sp/v/blank_player2.gif?
x=46&y=60&xc=1&yc=1&wc=164&hc=215&q=100&sig=8G0MjQyD1AdYbnv.
fd2Wog--</image_url>
  <is_undroppable>0</is_undroppable>
  <position_type>P</position_type>
  <eligible_positions>
    <position>RP</position>
    <position>P</position>
  </eligible_positions>
  <selected_position>
    <coverage_type>date</coverage_type>
    <date>2011-07-22</date>
    <position>RP</position>
  </selected_position>
</player>
<player>
  <player_key>253.p.7279</player_key>
  <player_id>7279</player_id>
  <name>
    <full>Jesse Crain</full>
    <first>Jesse</first>
    <last>Crain</last>
    <ascii_first>Jesse</ascii_first>
    <ascii_last>Crain</ascii_last>

```

developer

```

</editorial_team_key>
<editorial_team_full_name>Chicago White Sox</editorial_team_full_name>
<editorial_team_abbr>CWS</editorial_team_abbr>
<uniform_number>26</uniform_number>
<display_position>RP</display_position>
<image_url>https://l.yimg.com/a/i/us/sp/v/mlb/players_1/20110503x/7279.jpg?
x=46& y=60& xc=1& yc=1& wc=164& hc=215& q=100& sig=Xx9Emr_lBK3smmAB
r7f0cg--</image_url>
<is_undroppable>0</is_undroppable>
<position_type>P</position_type>
<eligible_positions>
  <position>RP</position>
  <position>P</position>
</eligible_positions>
<selected_position>
  <coverage_type>date</coverage_type>
  <date>2011-07-22</date>
  <position>P</position>
</selected_position>
</player>
<player>
  <player_key>253.p.8193</player_key>
  <player_id>8193</player_id>
  <name>
    <full>Max Scherzer</full>
    <first>Max</first>
    <last>Scherzer</last>
    <ascii_first>Max</ascii_first>
    <ascii_last>Scherzer</ascii_last>
  </name>
  <editorial_player_key>mlb.p.8193</editorial_player_key>
  <editorial_team_key>mlb.t.6</editorial_team_key>
  <editorial_team_full_name>Detroit Tigers</editorial_team_full_name>
  <editorial_team_abbr>Det</editorial_team_abbr>
  <uniform_number>37</uniform_number>
  <display_position>SP</display_position>
  <image_url>https://l.yimg.com/a/i/us/sp/v/mlb/players_1/20110503x/8193.jpg?
x=46& y=60& xc=1& yc=1& wc=164& hc=215& q=100& sig=lcgNVFPn0gpchY5f
Cbb6nw--</image_url>
  <is_undroppable>0</is_undroppable>
  <position_type>P</position_type>
  <eligible_positions>
    <position>SP</position>
    <position>P</position>
  </eligible_positions>
  <has_player_notes>1</has_player_notes>
  <selected_position>
    <coverage_type>date</coverage_type>

```

developer

```

</selected_position>
  <starting_status>
    <coverage_type>date</coverage_type>
    <date>2011-07-22</date>
    <is_starting>1</is_starting>
  </starting_status>
</player>
<player>
  <player_key>253.p.8099</player_key>
  <player_id>8099</player_id>
  <name>
    <full>Ian Kennedy</full>
    <first>Ian</first>
    <last>Kennedy</last>
    <ascii_first>Ian</ascii_first>
    <ascii_last>Kennedy</ascii_last>
  </name>
  <editorial_player_key>mlb.p.8099</editorial_player_key>
  <editorial_team_key>mlb.t.29</editorial_team_key>
  <editorial_team_full_name>Arizona Diamondbacks</editorial_team_full_name>
  <editorial_team_abbr>Ari</editorial_team_abbr>
  <uniform_number>31</uniform_number>
  <display_position>SP</display_position>
  <image_url>https://l.yimg.com/a/i/us/sp/v/mlb/players_1/20110503x/8099.jpg?
x=46& y=60& x=1& y=1& wc=164& hc=215& q=100& sig=TjXYM8e9wtrcLfRh
DnCMKQ--</image_url>
  <is_undroppable>0</is_undroppable>
  <position_type>P</position_type>
  <eligible_positions>
    <position>SP</position>
    <position>P</position>
  </eligible_positions>
  <has_player_notes>1</has_player_notes>
  <has_recent_player_notes>1</has_recent_player_notes>
  <selected_position>
    <coverage_type>date</coverage_type>
    <date>2011-07-22</date>
    <position>P</position>
  </selected_position>
</player>
<player>
  <player_key>253.p.8179</player_key>
  <player_id>8179</player_id>
  <name>
    <full>Gio Gonzalez</full>
    <first>Gio</first>
    <last>Gonzalez</last>
    <ascii_first>Gio</ascii_first>

```


developer

```

</editorial_player_key>
<editorial_team_key>mlb.t.11</editorial_team_key>
<editorial_team_full_name>Oakland Athletics</editorial_team_full_name>
<editorial_team_abbr>Oak</editorial_team_abbr>
<uniform_number>47</uniform_number>
<display_position>SP</display_position>
<image_url>https://l.yimg.com/a/i/us/sp/v/mlb/players_1/20110503x/8179.jpg?
x=46&y=60&xc=1&yc=1&wc=164&hc=215&q=100&sig=Wg7KqIjVG4zwo0zn
BbEViw--</image_url>
<is_undroppable>0</is_undroppable>
<position_type>P</position_type>
<eligible_positions>
  <position>SP</position>
  <position>P</position>
</eligible_positions>
<has_player_notes>1</has_player_notes>
<selected_position>
  <coverage_type>date</coverage_type>
  <date>2011-07-22</date>
  <position>BN</position>
</selected_position>
</player>
<player>
  <player_key>253.p.8759</player_key>
  <player_id>8759</player_id>
  <name>
    <full>Michael Pineda</full>
    <first>Michael</first>
    <last>Pineda</last>
    <ascii_first>Michael</ascii_first>
    <ascii_last>Pineda</ascii_last>
  </name>
  <editorial_player_key>mlb.p.8759</editorial_player_key>
  <editorial_team_key>mlb.t.12</editorial_team_key>
  <editorial_team_full_name>Seattle Mariners</editorial_team_full_name>
  <editorial_team_abbr>Sea</editorial_team_abbr>
  <uniform_number>36</uniform_number>
  <display_position>SP</display_position>
  <image_url>https://l.yimg.com/a/i/us/sp/v/mlb/players_1/20110503x/8759.jpg?
x=46&y=60&xc=1&yc=1&wc=164&hc=215&q=100&sig=31SmIDWcet4v3AVA
OGrY2g--</image_url>
  <is_undroppable>0</is_undroppable>
  <position_type>P</position_type>
  <eligible_positions>
    <position>SP</position>
    <position>P</position>
  </eligible_positions>
  <selected_position>

```

developer

```

    </selected_position>
  </player>
  <player>
    <player_key>253.p.6571</player_key>
    <player_id>6571</player_id>
    <name>
      <full>Ryan Vogelsong</full>
      <first>Ryan</first>
      <last>Vogelsong</last>
      <ascii_first>Ryan</ascii_first>
      <ascii_last>Vogelsong</ascii_last>
    </name>
    <editorial_player_key>mlb.p.6571</editorial_player_key>
    <editorial_team_key>mlb.t.26</editorial_team_key>
    <editorial_team_full_name>San Francisco Giants</editorial_team_full_name>
    <editorial_team_abbr>SF</editorial_team_abbr>
    <uniform_number>32</uniform_number>
    <display_position>SP,RP</display_position>
    <image_url>https://l.yimg.com/a/i/us/sp/v/mlb/players_1/20110706/6571.jpg?
x=46&y=60&xc=1&yc=1&wc=164&hc=215&q=100&sig=bdeeFeFntdasbz_0
xzXCGA--</image_url>
    <is_undroppable>0</is_undroppable>
    <position_type>P</position_type>
    <eligible_positions>
      <position>SP</position>
      <position>RP</position>
      <position>P</position>
    </eligible_positions>
    <has_player_notes>1</has_player_notes>
    <selected_position>
      <coverage_type>date</coverage_type>
      <date>2011-07-22</date>
      <position>BN</position>
    </selected_position>
  </player>
  <player>
    <player_key>253.p.7382</player_key>
    <player_id>7382</player_id>
    <name>
      <full>David Wright</full>
      <first>David</first>
      <last>Wright</last>
      <ascii_first>David</ascii_first>
      <ascii_last>Wright</ascii_last>
    </name>
    <status>DL</status>
    <on_disabled_list>1</on_disabled_list>

```

developer

```

</editorial_team_abbrev>
<editorial_team_abbrev>NYM</editorial_team_abbrev>
<uniform_number>5</uniform_number>
<display_position>3B</display_position>
<image_url>https://l.yimg.com/a/i/us/sp/v/mlb/players_1/20110503x/7382.jpg?
x=46&y=60&xc=1&yc=1&wc=164&hc=215&q=100&sig=QNOFMSgR6NuPxUwD
MUSM1w--</image_url>
<is_undroppable>0</is_undroppable>
<position_type>B</position_type>
<eligible_positions>
  <position>3B</position>
  <position>Util</position>
  <position>DL</position>
</eligible_positions>
<has_player_notes>1</has_player_notes>
<has_recent_player_notes>1</has_recent_player_notes>
<selected_position>
  <coverage_type>date</coverage_type>
  <date>2011-07-22</date>
  <position>DL</position>
</selected_position>
<starting_status>
  <coverage_type>date</coverage_type>
  <date>2011-07-22</date>
  <is_starting>1</is_starting>
</starting_status>
</player>
</players>
</roster>
</team>
</fantasy_content>

```

PUT

Using PUT , you may modify a subset of players on the roster for a particular day, specifically in terms of changing their position or whether they're in the starting lineup. The URL for PUT ting to a Roster resource is:

<https://fantasysports.yahooapis.com/fantasy/v2/team//roster>

You may move as many players as you like in your input XML – any players whose position you do not change will stay in the same position they were previously. If you try to move players in an invalid way, you will receive an error and no changes will be made.

NFL:

```
<?xml version="1.0"?>
<fantasy_content>
  <roster>
    <coverage_type>week</coverage_type>
    <week>13</week>

    <players>
      <player>
        <player_key>242.p.8332</player_key>
        <position>WR</position>
      </player>
      <player>
        <player_key>242.p.1423</player_key>
        <position>BN</position>
      </player>
    </players>
  </roster>
</fantasy_content>
```

MLB, NBA, or NHL:

```
<?xml version="1.0"?>
<fantasy_content>
  <roster>
    <coverage_type>date</coverage_type>
    <date>2011-05-01</date>

    <players>
      <player>
        <player_key>253.p.8332</player_key>
        <position>1B</position>
      </player>
      <player>
        <player_key>253.p.1423</player_key>
        <position>BN</position>
      </player>
    </players>
  </roster>
</fantasy_content>
```

Teams collection

developer

collection is qualified in the URI by a particular league to obtain information about teams within the league, or by a particular user (and optionally, a game) to obtain information about the teams owned by the user. Each element beneath the Teams Collection will be a [Team Resource](#)

HTTP Operations Supported

- GET

URIs

Any [sub-resource](#) valid for a team is a valid sub-resource under the teams collection.

Any sub-resource for a collection of teams is extracted using a URI like:

```
/teams/{sub_resource}
```

OR

```
/teams;team_keys={team_key1},{team_key2}/{sub_resource}
```

Multiple sub-resources can be extracted from teams in the same URI using a format like:

```
/teams;out={sub_resource_1},{sub_resource_2}
```

OR

```
/teams;team_keys={team_key1},{team_key2};out={sub_resource_1},{sub_resource_2}
```

Player resource

Description

With the Player API, you can obtain the player (athlete) related information, such as their name, professional team, and eligible positions. The player is identified in the context of a particular game, and can be requested as the base of your URI by using the global `""`.

HTTP Operations Supported

URIs

`https://fantasysports.yahooapis.com/fantasy/v2/player/`

Any sub-resource under a player is extracted using a URI like:

`https://fantasysports.yahooapis.com/fantasy/v2/player/`

Multiple sub-resources can be extracted from player in the same URI using a format like:

`https://fantasysports.yahooapis.com/fantasy/v2/player/;out=,{sub_resource_2}`

Player key format

`.p.{player_id}`

Example: pnfl.p.5479 or 223.p.5479

Sub-resources

Default sub-resource: metadata

Sample XML

`https://fantasysports.yahooapis.com/fantasy/v2/league/223.1.431/players;player_keys=223.p.5479`

- Player in a NFL league context

```
<?xml version="1.0" encoding="UTF-8"?>
<fantasy_content xmlns:yahoo="http://www.yahooapis.com/v1/base.rng"
xmlns="http://fantasysports.yahooapis.com/fantasy/v2/base.rng" xml:lang="en-US"
yahoo:uri="http://fantasysports.yahooapis.com/fantasy/v2/league/223.1.431/players;player_keys=223.p.5479" time="508.72206687927ms" copyright="Data provided by Yahoo! and STATS, LLC">
  <league>
    <league_key>223.1.431</league_key>
    <league_id>431</league_id>
    <name>Y! Friends and Family League</name>
    <url>https://football.fantasysports.yahoo.com/archive/pnfl/2009/431</url>
    <password>liss</password>
```

developer

```

<weekly_deadline/>
<league_update_timestamp>1262595518</league_update_timestamp>
<scoring_type>head</scoring_type>
<current_week>16</current_week>
<start_week>1</start_week>
<end_week>16</end_week>
<is_finished>1</is_finished>
<players count="1">
  <player>
    <player_key>223.p.5479</player_key>
    <player_id>5479</player_id>
    <name>
      <full>Drew Brees</full>
      <first>Drew</first>
      <last>Brees</last>
      <ascii_first>Drew</ascii_first>
      <ascii_last>Brees</ascii_last>
    </name>
    <status>P</status>
    <editorial_player_key>nfl.p.5479</editorial_player_key>
    <editorial_team_key>nfl.t.18</editorial_team_key>
    <editorial_team_full_name>New Orleans Saints</editorial_team_full_name>
    <editorial_team_abbr>NO</editorial_team_abbr>
    <bye_weeks>
      <week>5</week>
    </bye_weeks>
    <uniform_number>9</uniform_number>
    <display_position>QB</display_position>

    <image_url>https://l.yimg.com/a/i/us/sp/v/nfl/players_1/headshots/20100903/5479.jpg?
x=46& y=60& x=1& y=1& w=164& h=215& q=100& sig=LTUFmLVwQ.kvKzbh
SsG94w--</image_url>
    <is_undroppable>0</is_undroppable>
    <position_type>0</position_type>
    <eligible_positions>
      <position>QB</position>
    </eligible_positions>
  </player>
</players>
</league>
</fantasy_content>

```

https://fantasysports.yahooapis.com/fantasy/v2/league/223.1.431/players;player_keys=223.p.5479/stats
 - Player season stats in a NFL league context

developer

```

xmlns="http://fantasysports.yahooapis.com/fantasy/v2/base.rng" xml:lang="en-US"
yahoo:uri="http://fantasysports.yahooapis.com/fantasy/v2/league/223.1.431/players;player
_keys=223.p.5479/stats" time="3140.1500701904ms" copyright="Data provided by Yahoo! and
STATS, LLC">
  <league>
    <league_key>223.1.431</league_key>
    <league_id>431</league_id>
    <name>Y! Friends and Family League</name>
    <url>https://football.fantasysports.yahoo.com/archive/pnfl/2009/431</url>
    <password>liss</password>
    <draft_status>postdraft</draft_status>
    <num_teams>14</num_teams>
    <edit_key>17</edit_key>
    <weekly_deadline/>
    <league_update_timestamp>1262595518</league_update_timestamp>
    <scoring_type>head</scoring_type>
    <current_week>16</current_week>
    <start_week>1</start_week>
    <end_week>16</end_week>
    <is_finished>1</is_finished>
    <players count="1">
      <player>
        <player_key>223.p.5479</player_key>
        <player_id>5479</player_id>
        <name>
          <full>Drew Brees</full>
          <first>Drew</first>
          <last>Brees</last>
          <ascii_first>Drew</ascii_first>
          <ascii_last>Brees</ascii_last>
        </name>
        <status>P</status>
        <editorial_player_key>nfl.p.5479</editorial_player_key>
        <editorial_team_key>nfl.t.18</editorial_team_key>
        <editorial_team_full_name>New Orleans Saints</editorial_team_full_name>
        <editorial_team_abbr>NO</editorial_team_abbr>
        <bye_weeks>
          <week>5</week>
        </bye_weeks>
        <uniform_number>9</uniform_number>
        <display_position>QB</display_position>

        <image_url>https://l.yimg.com/a/i/us/sp/v/nfl/players_1/headshots/20100903/5479.jpg?
x=46& y=60& xc=1& yc=1& wc=164& hc=215& q=100& sig=LTUFmLVwQ.kvKzbh
SsG94w--</image_url>
        <is_undroppable>0</is_undroppable>
        <position_type>0</position_type>

```


developer

```
</stats>  
<player_stats>  
  <coverage_type>season</coverage_type>  
  <season>2009</season>  
  <stats>  
    <stat>  
      <stat_id>4</stat_id>  
      <value>4388</value>  
    </stat>  
    <stat>  
      <stat_id>5</stat_id>  
      <value>34</value>  
    </stat>  
    <stat>  
      <stat_id>6</stat_id>  
      <value>11</value>  
    </stat>  
    <stat>  
      <stat_id>9</stat_id>  
      <value>33</value>  
    </stat>  
    <stat>  
      <stat_id>10</stat_id>  
      <value>2</value>  
    </stat>  
    <stat>  
      <stat_id>11</stat_id>  
      <value>1</value>  
    </stat>  
    <stat>  
      <stat_id>12</stat_id>  
      <value>-4</value>  
    </stat>  
    <stat>  
      <stat_id>13</stat_id>  
      <value>0</value>  
    </stat>  
    <stat>  
      <stat_id>15</stat_id>  
      <value>0</value>  
    </stat>  
    <stat>  
      <stat_id>16</stat_id>  
      <value>0</value>  
    </stat>  
    <stat>  
      <stat_id>18</stat_id>  
      <value>6</value>
```

```

    <value>0</value>
  </stat>
</stats>
</player_stats>
<player_points>
  <coverage_type>season</coverage_type>
  <season>2009</season>
  <total>310.17</total>
</player_points>
</player>
</players>
</league>
</fantasy_content>

```

Players collection

Description

With the Players API, you can obtain information from a collection of players simultaneously. To obtain general players information, the players collection can be qualified in the URI by a particular game, league or team. To obtain specific league or team related information, the players collection is qualified by the relevant league or team. Each element beneath the Players Collection will be a [Player Resource](#)

HTTP Operations Supported

- GET

URIs

Any [sub-resource](#) valid for a player is a valid sub-resource under the players collection.

Any sub-resource for a collection of players is extracted using a URI like:

```
/players/{sub_resource}
```

OR

```
/players;player_keys={player_key1},{player_key2}/{sub_resource}
```

Multiple sub-resources can be extracted from players in the same URI using a format like:

OR

```
/players;player_keys={player_key1},{player_key2};out={sub_resource_1},{sub_resource_2}
```

Filters

The players collection can have filters such as the following to obtain a subset of a players collection that satisfy the filtering condition. The filters can be combined to obtain a more restricted list of players.

Filter parameter	Filter parameter values	Usage
position	Valid player positions	<code>/players;position=QB</code>
		Note
		Applied only in a league's context
status	A (all available players)	<code>/players;status=A</code>
	FA (free agents only)	Note
	W (waivers only)	Applied only in a league's context
	T (all taken players)	
	K (keepers only)	
search	player name	<code>/players;search=smith</code>
		Note
sort	{stat_id}	Applied only in a league's context
		<code>/players;sort=60</code>
		Note
		Applied only in a league's context
	OR (overall rank)	
	AR (actual rank)	

developer

sort_type		
	season	/players;sort_type=season
	date (baseball, basketball, and hockey only)	Note Applied only in a league's context
	week (football only)	
	lastweek (baseball, basketball, and hockey only)	
	lastmonth	
sort_season		
	year	/players;sort_type=season;sort_season=2010
		Note Applied only in a league's context
sort_date (baseball, basketball, and hockey only)		
	YYYY-MM-DD	/players;sort_type=date;sort_date=2010-02-01
		Note Applied only in a league's context
sort_week (football only)		
	week	/players;sort_type=week;sort_week=10
		Note Applied only in a league's context
start		
	Any integer 0 or greater	/players;start=25
count		
	Any integer greater than 0	/players;count=5

Description

With the Transaction API, you can obtain information about transactions (adds, drops, trades, and league settings changes) performed on a league. A transaction is identified in the context of a particular league, although you can request a particular Transaction Resource as the base of your URI by using the global `transaction`.

You can also `PUT` to the API to perform operations like editing waiver priorities or FAAB bids, or modifying the state of pending trades. You can also cancel pending transactions by `DELETE` ing them.

Keep in mind, if you don't have the `transaction` for a waiver claim or pending trade, the only way to discover these transactions is to filter the league [Transactions collection](#) by a particular type (`waiver` or `pending_trade`) and by a particular `team`. Pending transactions will not show up if you simply ask for all of the transactions in the league, because they can only be seen by certain teams.

HTTP Operations Supported

- `GET`
- `PUT <#transaction-resource-PUT>`__`
- `DELETE <#transaction-resource-DELETE>`__`

URIs

`https://fantasysports.yahooapis.com/fantasy/v2/transaction/`

Any sub-resource under a transaction is extracted using a URI like:

`https://fantasysports.yahooapis.com/fantasy/v2/transaction/`

Multiple sub-resources can be extracted from transaction in the same URI using a format like:

`https://fantasysports.yahooapis.com/fantasy/v2/transaction/;out=,{sub_resource_2}`

Transaction key format

Completed transactions: `.l.{league_id}.tr.{transaction_id}`

developer

waiver claims: .l.{league_id}.w.c.{claim_id}

Example: 257.1.193.w.c.2_6390

Pending trades: .l.{league_id}.pt.{pending_trade_id}

Example: 257.1.193.pt.1

Sub-resources

Default sub-resources: metadata, players

Sample XML

<https://fantasysports.yahooapis.com/fantasy/v2/transaction/257.1.193.tr.2> - Completed add/drop transaction

```
<?xml version="1.0" encoding="UTF-8"?>
<fantasy_content xmlns:yahoo="http://www.yahooapis.com/v1/base.rng"
xmlns="http://fantasysports.yahooapis.com/fantasy/v2/base.rng" xml:lang="en-US"
yahoo:uri="http://fantasysports.yahooapis.com/fantasy/v2/transaction/257.1.193.tr.2"
time="51.784038543701ms" copyright="Data provided by Yahoo! and STATS, LLC">
  <transaction>
    <transaction_key>257.1.193.tr.2</transaction_key>
    <transaction_id>2</transaction_id>
    <type>add/drop</type>
    <status>successful</status>
    <timestamp>1310694660</timestamp>
    <players count="2">
      <player>
        <player_key>257.p.7847</player_key>
        <player_id>7847</player_id>
        <name>
          <full>Owen Daniels</full>
          <first>Owen</first>
          <last>Daniels</last>
          <ascii_first>Owen</ascii_first>
          <ascii_last>Daniels</ascii_last>
        </name>
        <transaction_data>
          <type>add</type>
          <source_type>freeagents</source_type>
          <destination_type>team</destination_type>
        </transaction_data>
      </player>
    </players>
  </transaction>
</fantasy_content>
```

developer

```

<player>
  <player_key>257.p.6390</player_key>
  <player_id>6390</player_id>
  <name>
    <full>Anquan Boldin</full>
    <first>Anquan</first>
    <last>Boldin</last>
    <ascii_first>Anquan</ascii_first>
    <ascii_last>Boldin</ascii_last>
  </name>
  <transaction_data>
    <type>drop</type>
    <source_type>team</source_type>
    <source_team_key>257.l.193.t.1</source_team_key>
    <destination_type>waivers</destination_type>
  </transaction_data>
</player>
</players>
</transaction>
</fantasy_content>

```

https://fantasysports.yahooapis.com/fantasy/v2/transaction/257.l.193.w.c.2_6390 - Waiver claim transaction

```

<?xml version="1.0" encoding="UTF-8"?>
<fantasy_content xmlns:yahoo="http://www.yahooapis.com/v1/base.rng"
xmlns="http://fantasysports.yahooapis.com/fantasy/v2/base.rng" xml:lang="en-US"
yahoo:uri="http://fantasysports.yahooapis.com/fantasy/v2/transaction/257.l.193.w.c.2_6390"
time="30.953884124756ms" copyright="Data provided by Yahoo! and STATS, LLC">
  <transaction>
    <transaction_key>257.l.193.w.c.2_6390</transaction_key>
    <type>waiver</type>
    <status>pending</status>
    <waiver_player_key>257.p.6390</waiver_player_key>
    <waiver_team_key>257.l.193.t.2</waiver_team_key>
    <waiver_date>2011-07-17</waiver_date>
    <waiver_priority>1</waiver_priority>
    <players count="2">
      <player>
        <player_key>257.p.6390</player_key>
        <player_id>6390</player_id>
        <name>
          <full>Anquan Boldin</full>
          <first>Anquan</first>
          <last>Boldin</last>
          <ascii_first>Anquan</ascii_first>

```

developer

```

        <type>add</type>
        <source_type>waivers</source_type>
        <destination_type>team</destination_type>
        <destination_team_key>257.1.193.t.2</destination_team_key>
    </transaction_data>
</player>
<player>
    <player_key>257.p.8266</player_key>
    <player_id>8266</player_id>
    <name>
        <full>Marshawn Lynch</full>
        <first>Marshawn</first>
        <last>Lynch</last>
        <ascii_first>Marshawn</ascii_first>
        <ascii_last>Lynch</ascii_last>
    </name>
    <transaction_data>
        <type>drop</type>
        <source_type>team</source_type>
        <source_team_key>257.1.193.t.2</source_team_key>
        <destination_type>waivers</destination_type>
    </transaction_data>
</player>
</players>
</transaction>
</fantasy_content>

```

<https://fantasysports.yahooapis.com/fantasy/v2/transaction/257.1.193.pt.1> - Pending trade transaction

```

<?xml version="1.0" encoding="UTF-8"?>
<fantasy_content xmlns:yahoo="http://www.yahooapis.com/v1/base.rng"
xmlns="http://fantasysports.yahooapis.com/fantasy/v2/base.rng" xml:lang="en-US"
yahoo:uri="http://fantasysports.yahooapis.com/fantasy/v2/transaction/257.1.193.pt.1"
time="45.558929443359ms" copyright="Data provided by Yahoo! and STATS, LLC">
    <transaction>
        <transaction_key>257.1.193.pt.1</transaction_key>
        <type>pending_trade</type>
        <status>proposed</status>
        <trader_team_key>257.1.193.t.2</trader_team_key>
        <tradee_team_key>257.1.193.t.1</tradee_team_key>
        <trade_proposed_time>1310694832</trade_proposed_time>
        <trade_note>This is a great trade, fo' shizzle.</trade_note>
        <players count="2">
            <player>
                <player_key>257.p.8261</player_key>

```


developer

```

<first>Adrian</first>
<last>Peterson</last>
<ascii_first>Adrian</ascii_first>
<ascii_last>Peterson</ascii_last>
</name>
<transaction_data>
  <type>pending_trade</type>
  <source_type>team</source_type>
  <source_team_key>257.1.193.t.2</source_team_key>
  <destination_type>team</destination_type>
  <destination_team_key>257.1.193.t.1</destination_team_key>
</transaction_data>
</player>
<player>
  <player_key>257.p.9527</player_key>
  <player_id>9527</player_id>
  <name>
    <full>Arian Foster</full>
    <first>Arian</first>
    <last>Foster</last>
    <ascii_first>Arian</ascii_first>
    <ascii_last>Foster</ascii_last>
  </name>
  <transaction_data>
    <type>pending_trade</type>
    <source_type>team</source_type>
    <source_team_key>257.1.193.t.1</source_team_key>
    <destination_type>team</destination_type>
    <destination_team_key>257.1.193.t.2</destination_team_key>
  </transaction_data>
</player>
</players>
</transaction>
</fantasy_content>

```

PUT

Using PUT , you may edit the waiver priority or FAAB bid for any of your pending waiver claims. You can also accept or reject trades that have been proposed to you, and allow or vote against trades if your league settings allow it. The URL for PUT ting to a Transaction resource is:

<https://fantasysports.yahooapis.com/fantasy/v2/transaction/>

You can only PUT to Transactions of the types `waiver` or `pending_trade` .

developer

collection for all waivers for a certain team, you can edit the waiver priority or FAAB bid. The input XML should look like:

```
<?xml version='1.0'?>
<fantasy_content>
  <transaction>
    <transaction_key>248.1.55438.w.c.2_6093</transaction_key>
    <type>waiver</type>
    <waiver_priority>1</waiver_priority>
    <faab_bid>20</faab_bid>
  </transaction>
</fantasy_content>
```

Accepting Trades

Once you have the `transaction_key` for a pending trade that has been proposed to you, which you can get by asking the transactions collection for all pending trades for your team, you can choose to accept it. The input XML should look like:

```
<?xml version='1.0'?>
<fantasy_content>
  <transaction>
    <transaction_key>248.1.55438.pt.11</transaction_key>
    <type>pending_trade</type>
    <action>accept</action>
    <trade_note>Dude, that is a totally fair trade.</trade_note>
  </transaction>
</fantasy_content>
```

Rejecting Trades

To reject a pending trade proposed to you, the input XML should look like:

```
<?xml version='1.0'?>
<fantasy_content>
  <transaction>
    <transaction_key>248.1.55438.pt.11</transaction_key>
    <type>pending_trade</type>
    <action>reject</action>
    <trade_note>No way!</trade_note>
  </transaction>
</fantasy_content>
```

Allowing/Disallowing Trades

developer

has the commissioner approve trades, you can choose to allow or disallow the trade. The input XML should look like:

```
<?xml version='1.0'?>
<fantasy_content>
  <transaction>
    <transaction_key>248.1.55438.pt.11</transaction_key>
    <type>pending_trade</type>
    <action>allow</action>
  </transaction>
</fantasy_content>
```

Or

```
<?xml version='1.0'?>
<fantasy_content>
  <transaction>
    <transaction_key>248.1.55438.pt.11</transaction_key>
    <type>pending_trade</type>
    <action>disallow</action>
  </transaction>
</fantasy_content>
```

Voting Against Trades

If there are accepted trades in your league waiting to be processed, which you can get by asking the transactions collection for all pending trades for your team, and you're a manager in a league that allows managers to vote against trades, you can choose to vote against the trade. The input XML should look like:

```
<?xml version='1.0'?>
<fantasy_content>
  <transaction>
    <transaction_key>248.1.55438.pt.11</transaction_key>
    <type>pending_trade</type>
    <action>vote_against</action>
    <voter_team_key>248.1.55438.t.2</voter_team_key>
  </transaction>
</fantasy_content>
```

DELETE

`https://fantasysports.yahooapis.com/fantasy/v2/transaction/`

You can only `DELETE` transactions of the types `waiver` or `pending_trade` if the pending trade has not yet been accepted.

Transactions collection

Description

With the Transactions API, you can obtain information via `GET` from a collection of transactions simultaneously. The transactions collection is qualified in the URI by a particular league. Each element beneath the Transactions Collection will be a [Transaction Resource](#)

You can also `POST` to the API to perform operations like adding and/or dropping players to/from a team and proposing trades.

HTTP Operations Supported

- `GET`
- `POST` [<#transactions-collection-POST>](#) `__`

URIs

Any [sub-resource](#) valid for a transaction is a valid sub-resource under the transactions collection.

Any sub-resource for a collection of transactions is extracted using a URI like:

```
/transactions/{sub_resource}
```

OR

```
/transactions;transaction_keys={transaction_key1},{transaction_key2}/{sub_resource}
```

Multiple sub-resources can be extracted from transactions in the same URI using a format like:

```
/transactions;out={sub_resource_1},{sub_resource_2}
```

OR

Filters

The transactions collection can have filters such as the following to obtain a subset of a transactions collection that satisfy the filtering condition. These filters can be combined to obtain a more restricted list of transactions.

Filter parameter	Filter parameter values	Usage
type	add,drop,commish,trade	/transactions?type=add
types	Any valid types	/transactions?types=add,trade
team_key	A team_key within the league	/transactions?team_key=257.1.193.t.1
type with team_key	waiver,pending_trade	You can only use these options when also providing the team_key, ie /transactions?team_key=257.1.193.t.1;type=waiver
count	Any integer greater than 0	/transactions;count=5

POST

Using POST , players can be added and/or dropped from a team, or trades can be proposed. The URI for POST ing to transactions collection is:

<https://fantasysports.yahooapis.com/fantasy/v2/league//transactions>

Adding/Dropping Players

The input XML format for a POST request to the transactions API for adding a player is:

```
<fantasy_content>
  <transaction>
    <type>add</type>
    <player>
      <player_key>{player_key}</player_key>
    <transaction_data>
      <type>add</type>
      <destination_team_key>{team_key}</destination_team_key>
```

developer

```
</fantasy_content>
```

The input XML format for a POST request to the transactions API for dropping a player is:

```
<fantasy_content>
  <transaction>
    <type>drop</type>
    <player>
      <player_key>{player_key}</player_key>
      <transaction_data>
        <type>drop</type>
        <source_team_key>{team_key}</source_team_key>
      </transaction_data>
    </player>
  </transaction>
</fantasy_content>
```

The input XML format for a POST request to the transactions API for replacing one player with another player in a team is:

```
<fantasy_content>
  <transaction>
    <type>add/drop</type>
    <players>
      <player>
        <player_key>{player_key}</player_key>
        <transaction_data>
          <type>add</type>
          <destination_team_key>{team_key}</destination_team_key>
        </transaction_data>
      </player>
      <player>
        <player_key>{player_key}</player_key>
        <transaction_data>
          <type>drop</type>
          <source_team_key>{team_key}</source_team_key>
        </transaction_data>
      </player>
    </players>
  </transaction>
</fantasy_content>
```

You may also add players that are currently on waivers – the players will not be immediately added to your team, but rather, you will be returned back a waiver claim that will be processed at some point in the

developer

If you are placing a waiver claim in a league that uses FAAB, you may add that to the XML that you POST :

```
<?xml version='1.0'?>
<fantasy_content>
  <transaction>
    <type>add/drop</type>
    <faab_bid>25</faab_bid>
    <players>
      <player>
        <player_key>238.p.5484</player_key>
        <transaction_data>
          <type>add</type>
          <destination_team_key>238.l.627060.t.6</destination_team_key>
        </transaction_data>
      </player>
      <player>
        <player_key>238.p.6327</player_key>
        <transaction_data>
          <type>drop</type>
          <destination_team_key>238.l.627060.t.6</destination_team_key>
        </transaction_data>
      </player>
    </players>
  </transaction>
</fantasy_content>
```

Once you have a waiver claim transaction, you may also [edit the waiver priority or FAAB bid](#), or [cancel](#) the waiver entirely.

Proposing Trades

The input XML format for a POST request to the transactions API for proposing a trade is:

```
<?xml version='1.0'?>
<fantasy_content>
  <transaction>
    <type>pending_trade</type>
    <trader_team_key>248.l.55438.t.11</trader_team_key>
    <tradee_team_key>248.l.55438.t.4</tradee_team_key>
    <trade_note>Yo yo yo yo yo!!!</trade_note>
    <players>
      <player>
        <player_key>248.p.4130</player_key>
        <transaction_data>
          <type>pending_trade</type>
```

developer

```

    </player>
    <player>
      <player_key>248.p.2415</player_key>
      <transaction_data>
        <type>pending_trade</type>
        <source_team_key>248.l.55438.t.4</source_team_key>
        <destination_team_key>248.l.55438.t.11</destination_team_key>
      </transaction_data>
    </player>
  </players>
</transaction>
</fantasy_content>

```

Once you have a pending trade transaction, you may [accept](#), [reject](#), [allow/disallow](#), or [vote against](#) the trade (depending on which role you have in the league). You may also [cancel](#) the trade.

User resource

Description

With the User API, you can retrieve fantasy information for a particular Yahoo! user. Most usefully, you can see which games a user is playing, and which leagues they belong to and teams that they own within those games. Because you can currently only view user information for the logged in user, you would generally want to use the [Users collection](#), passing along the `use_login` flag, instead of trying to request a User resource directly from the URI.

HTTP Operations Supported

- GET

URIs

It is generally recommended that you instead use the [Users collection](#), passing along the `use_login` flag.

Sub-resources

Default sub-resource: N/A

Users collection

developer

beneath the Users Collection will be a [User Resource](#)

HTTP Operations Supported

- GET

URIs

Any [sub-resource](#) valid for a user is a valid sub-resource under the users collection.

Any sub-resource for a collection of users is extracted using a URI like:

```
/users;use_login=1/{sub_resource}
```

Multiple sub-resources can be extracted from users in the same URI using a format like:

```
/users;use_login=1;out={sub_resource_1},{sub_resource_2}
```

```
/users;field={field_name1},{field_name2}
```

Support



Brands



© 2025 Yahoo. All rights reserved.