
TCP Reset Attacks

- CEG 6430/4430 Cyber Network Security
- Junjie Zhang
- junjie.zhang@wright.edu
- Wright State University

TCP Packet Header



How to Close TCP Connections?

- The "Civilized" Approach: FIN
 - A sends B a FIN and B replies A with an ACK
 - The A-to-B connection is closed but the B-to-A one is open
 - B sends A a FIN and A replies B with an ACK
 - The B-to-A connection is closed
- The "Non-Civilized"/"Emergency" Approach: RST
 - Either A or B sends a single TCP RST packet to the other side
 - Immediately breaks the connection.

RST Can Be Helpful

- No time to do FIN
- A system receives an SYN-ACK packet without sending a SYN packet
 - The server is likely under an SYN flood attack
 - The system can send the server an RST packet to close the halfopen connection

TCP RST Attack


An attacker, say Eve, wants to spoof an RST packet to discrupt an TCP connection between Alice and Bob. This RST packet has to be *correct*:

- Correct Src & Dst IPs
- Correct Src & Dst Ports
- Correct Sequence Number
 - The sequence number matches the one expected by the receiver.

TCP RST Attack

- Eve is off-the-path: Eve cannot observe packets exchanged between Alice and Bob
 - It is very challenging to launch TCP RST Attack in this case.
- Eve is in-the-path: Eve can observe packets exchanged between Alice and Bob
 - It is much easier to launch such attack since
 - IPs and Ports are readily available from the observed packets.
 - Correct sequence numbers can now be predicted (but the race-condition challenge is still there)

TCP RST Attack



TCP RST Attack Using netwox 78

In console 1, connect to bender using ssh

ssh w077jxz@bender.cs.wright.edu

In console 2, launch TCP reset attack against this ssh session. 120 is my IP address and 150 is bender's IP address

sudo netwox 78 -d eth0 --filter "tcp and src host 172.20.135.210 and dst host 130.108.5.150"

[w077jxz@head ~]\$ tclient_loop: send disconnect: Broken pipe