EE4001 Mechanical

EE4001 Study Questions - ED Chapter 2

- 1. A 10 kg mass is hung from the tip of a lever. The lever is 1 m long and is at a 60° angle to the ground. Calculate the holding torque required to keep the lever from turning. [Ans. 49.05 Nm] **2003A,B**
- 2. Given that a solid metal cylinder has radius $r_I = 10$ cm, length l = 20 cm, and material density $\rho = 10 \times 10^3$ kg m⁻³, calculate its moment of inertia. [Ans. 0.314 kg m²] **2003A**
- 3. If the moment of inertia of a solid cylinder is $\frac{\pi}{2}\rho l r^4$, what is the moment of inertia of a hollow cylinder of inner radius r_I and outer radius r_O ? **2004**
- 4. A motor is rigidly coupled to a load and each structure has an inertia of 0.05 kgm². Calculate the required electromagnetic torque and peak power if the speed is to increase linearly from rest to 600 rpm in 10 s. [Ans. 0.628 Nm, 39.5 W] **2004**
- 5. An electric vehicle has the following attributes: drag co-efficient $C_{\rm W}=0.2$, vehicle cross section $A=3~{\rm m}^2$. Use density of air $\rho_{\rm air}=1.202~{\rm kg~m}^{-3}$. Instantaneously at a vehicle speed of 36 km/hr, calculate the aerodynamic drag when driving into a 3.6 km/hr headwind. [Ans. 43.96 N] **2003A**

6. An electric vehicle has the following attributes: mass M = 500 kg, wheel diameter $d_{\rm W} = 1$ m, gear ratio from rotor to drive axle n = 10, and a nominal gear efficiency of 95%. The vehicle is required to accelerate from 0 to 36 km/hr in 10 s on a flat road surface under calm wind conditions. Neglecting load forces, instantaneously at 36 km/hr calculate the

EE4001 Mechanical

electromagnetic torque, rotor speed, and horse power of the electric motor to achieve this acceleration. [Ans. 26.3 Nm, 1910 rpm, 7.06 hp] **2004**

- 7. A vehicle experiences a drag force of 400 N at 36 km/h. If the wheel diameter is 0.6 m. Calculate the torque required at the axle to overcome the drag. [Ans. 120 Nm] **2003A,B**
- 8. At highway speed, the power generated by car engines is mostly used to overcome aerodynamic drag, and thus the fuel consumption is nearly proportional to the drag force on a level road. Determine the percentage increase in fuel consumption of a car per unit time when a person who normally drives at 55 mph now starts driving at 70 mph. Calculate the approximate percentage increase in energy consumption to travel a 55 mile distance at a constant speed of 70 mph compared to 55 mph. [Ans. 106 %, 62 %,] **2003A**, **2004**

- 9. What are the principal load forces associated with a moving vehicle? **2002A**
- 10. What are some of the advantages of using a gearing system in an application?
- 11. Sketch a plot of torque vs. speed for a squared-power load. **2003B**
- 12. A motor developing a torque $T_{\rm EM}$ is coupled with a shaft of torsional coefficient K to a structure of load torque $T_{\rm L}$ and each structure has an inertia J. Sketch the analogous electrical circuit. **2004**