

Installation Guide

Firstly, download Apache solr v7.5.0 binary release and unzip it. Then through the command prompt, navigate inside solr-7.5.0/bin folder as shown in the picture below by using your own path to that folder. After that, write the command 'solr start' and Apache solr should start on port 8983.

```
Microsoft Windows [Version 10.0.17134.471]
(c) 2018 Microsoft Corporation. All rights reserved.

C:\Users\akyri>cd desktop\solr-7.5.0\bin

C:\Users\akyri\Desktop\solr-7.5.0\bin>solr start
INFO - 2018-12-14 17:17:17.554; org.apache.solr.util.configuration.SSLCredentialProviderFactory; Processing SSL Credential Provider chain: env;sysprop
Waiting up to 30 to see Solr running on port 8983
Started Solr server on port 8983. Happy searching!

C:\Users\akyri\Desktop\solr-7.5.0\bin>
```

Figure 1. Starting apache solr from cmd.

Then, create four folders named edam, swo, biotools and hybrid under solr-7.5.0/server/solr directory. You will need to copy and paste all the files and folders that exist under solr-7.5.0\server\solr\configsets_default\conf directory to all four folders created previously as shown to the example figure below. Do that for edam, swo, biotools and hybrid folders.





Figure 2. Example of the EDAM folder.


After completing that step, navigate to localhost:8983 through a browser. You will need to create four new cores with the names and instanceDirs edam, swo, biotools and hybrid respectively as shown in the example figure below.



The screenshot shows the Solr Core Admin interface. On the left is a sidebar with navigation links: Dashboard, Logging, Core Admin (highlighted), Java Properties, Thread Dump, and a Core Selector dropdown. The main panel displays the 'Add Core' dialog box. At the top of the dialog are buttons for '+ Add Core', 'Unload', and 'Rename'. Below these are input fields for 'name' (edam), 'instanceDir' (edam), 'dataDir' (data), 'config' (solrconfig.xml), and 'schema' (schema.xml). A message icon indicates that 'instanceDir' and 'dataDir' must exist before creating the core. At the bottom of the dialog are 'Add Core' and 'Cancel' buttons.

Figure 3. Example of creating EDAM core in apache solr.

For all three cores, you will need to upload the given json files, EDAMSolr.json, swoSolr.json, biotoolsSolr.json and hybridSolr.json for each core respectively as shown in the example figure.



The screenshot shows the Solr Core Admin interface with the 'edam' core selected in the sidebar. The main panel displays the 'Upload Document' form. It includes fields for 'Request-Handler (qt)' (set to /update), 'Document Type' (File Upload), and 'Document(s)' (with a 'Choose File' button and 'EDAMSolr.json' listed). Below these are fields for 'Extracting Req. Handler Params', 'Commit Within' (1000), and 'Overwrite' (true). A 'Submit Document' button is at the bottom.

Figure 4. figure of uploading the edam json file in apache solr's EDAM core.

The last step to finish with the Apache solr configuration, is to open solrconfig.xml file for all four cores that is located under solr-7.5.0\server\solr\edam, solr-7.5.0\server\solr\swo, solr-7.5.0\server\solr\biotools and solr-7.5.0\server\solr\hybrid respectively. You will need to add the line ‘<str name="fl">*,score</str>’ in the /select requestHandler as shown in the figure below.

```

687     queries across multiple shards
688     -->
689     <requestHandler name="/select" class="solr.SearchHandler">
690     <!-- default values for query parameters can be specified, these
691          will be overridden by parameters in the request
692     -->
693     <lst name="defaults">
694     <str name="echoParams">explicit</str>
695     <str name="fl">*,score</str>
696     <int name="rows">10</int>
697     <!-- Default search field
698     <str name="df">text</str>
699     -->
700     <!-- Change from JSON to XML format (the default prior to Solr 7.0)
701     <str name="wt">xml</str>
702     -->
703     </lst>

```

Figure 5. Apache solr cores' configuration.

After completing those steps, Apache solr is set and ready. The next step is to download and install pgAdmin software. After installing it, create a new database named ontosearch and run the sql script given in the file OntoSearchDB.sql. After running that script, you should have two tables created in the ontosearch database with the names solrresultsedam and solrresultsswo like shown in the figure below.




Figure 6. PGadmin3 ontosearch database.

After the database is set, download and install XAMPP Control Panel. Download MySQL and Tomcat service through XAMPP, if you haven't downloaded it already during installation.

Next, open the given file config.xml and set your database name, username and password.




Figure 7. confix.xml file

Move the given files OntoSearch.war and config.xml under xampp/tomcat/webapps (xampp folder can typically be found in C://)




Figure 8. webapps folder.

The final step is to start MySQL and Tomcat in XAMPP.




Figure 9. XAMPP Control Panel.

Congratulations

The web-app should start under <http://localhost:8080/OntoSearch/>.