Tutorial 5: Relational Algebra

CS3402 Database Systems

Question 1

Consider the two tables T1 and T2 shown below; show the results of the following operations.

a)
$$T1 \times T2$$

b) T1
$$\bowtie_{T1.P=T2.A}$$
 T2

c) T1
$$\bowtie_{T1.Q=T2.B}$$
 T2

d) T1
$$\bowtie_{T1.R>T2.R}$$
 T2

11		
Р	Q	R
10	a	5
15	b	8
25	а	6

Α	В	R
10	b	6
25	С	3
10	b	5

Question 1(a) (Answer) (1/3)

> T1	×T2	-			
Р	Q	R1	Α	В	R2
10	а	5	10	b	6
10	a	5	25	С	3
10	а	5	10	b	5
15	b	8	10	b	6
15	b	8	25	С	3
15	b	8	10	b	5
25	а	6	10	b	6
25	а	6	25	С	3
25	а	6	10	b	5

T1			T2		
Р	Q	R	Α	В	R
10	а	5	10	b	6
15	b	8	25	С	3
25	а	6	10	b	5

Question 1(a) (Answer) (2/3)

> T1	×T2				
Р	Q	R1	Α	В	R2
10	a	5	10	b	6
10	a	5	25	С	3
10	а	5	10	b	5
15	b	8	10	b	6
15	b	8	25	С	3
15	b	8	10	b	5
25	а	6	10	b	6
25	а	6	25	С	3
25	а	6	10	b	5

T1				T2		
Р	Q	R		Α	В	R
10	а	5		10	b	6
15	b	8	\leftarrow	25	С	3
25	а	6		10	b	5

Question 1(a) (Answer) (3/3)

> T1	×T2				
Р	Q	R1	Α	В	R2
10	a	5	10	b	6
10	a	5	25	С	3
10	a	5	10	b	5
15	b	8	10	b	6
15	b	8	25	С	3
15	b	8	10	b	5
25	а	6	10	b	6
25	a	6	25	С	3

T1			T2		
Р	Q	R	Α	В	R
10	а	5	10	b	6
15	b	8	25	С	3
25	а	6	10	b	5

Question 1(b) (Answer) (1/9)



Р	Q	R1	Α	В	R2
10	а	5	10	b	6
10	а	5	10	b	5
25	a	6	25	С	3

÷	,
	4
ш	L

Р	Q	R
10	а	5
15	В	8
25	Α	6

T2

Α	В	R
10	b	6
25	С	3
10	b	5

Question 1(b) (Answer) (2/9)

 \succ T1 $\bowtie_{T1.P=T2.A}$ T2

Р	Q	R1	Α	В	R2
10	a	5	10	b	6
10	a	5	10	b	5
25	а	6	25	С	3

T1

Р	Q	R
10	а	5
15	b	8
25	а	6

T2

Α	В	R
10	b	6
25	С	3
10	b	5

Question 1(b) (Answer) (3/9)



Р	Q	R
10	а	5
15	b	8
25	а	6

1 4		
А	В	R
10	b	6
25	С	3
10	b	5

Question 1(b) (Answer) (4/9)



Р	Q	R1	Α	В	R2
10	a	5	10	b	6
10	a	5	10	b	5
25	а	6	25	С	3

11		
Р	Q	R
10	а	5
15	b	8
25	а	6


Α	В	R
10	b	6
25	С	3
10	b	5

Question 1(b) (Answer) (5/9)



Р	Q	R1	Α	В	R2
10	a	5	10	b	6
10	a	5	10	b	5
25	а	6	25	С	3

Р	Q	R
10	a	5
15	b	8
25	а	6




Question 1(b) (Answer) (6/9)



Р	Q	R1	Α	В	R2
10	а	5	10	b	6
10	a	5	10	b	5
25	а	6	25	С	3

11		
Р	Q	R
10	a	5

10	a	5
15	b	8
25	а	6



Question 1(b) (Answer) (7/9)





А	В	R
10	b	6
25	С	3
10	b	5

Question 1(b) (Answer) (8/9)



Р	Q	R
10	а	5
15	b	8
25	а	6

Α	В	R
10	b	6
25	С	3
10	b	5

Question 1(b) (Answer) (9/9)



Р	Q	R1	Α	В	R2
10	a	5	10	b	6
10	a	5	10	b	5
25	a	6	25	С	3


T1


Р	Q	R
10	a	5
15	b	8
25	а	6

T2


Α	В	R
10	b	6
25	С	3
10	b	5

Question 1(c) (Answer)







Question 1(d) (Answer) (1/3)



Question 1(d) (Answer) (2/3)




Question 1(d) (Answer) (3/3)




Question 1(e) (Answer) (1/2)






Question 1(e) (Answer) (2/2)





Question 2 (1/2)

Consider the COMPANY relational schema shown below; specify the following queries in relational algebra.




Question 2 (2/2)

- a) Find the Ssn (social security number) of all employees who are not supervisors
- b) Find the Ssn of all employees who either work in department 5 or directly supervise an employee who works in department 5
- c) List the names and numbers of all departments locating in 'Houston'
- d) List the first names of all employees who have a dependent with the same first name as themselves
- e) Retrieve the salary of all employees in department 5 who work more than 10 hours on the project named 'ProjectX'


Question 2(a) (Answer)

- Find the Ssn (social security number) of all employees who are not supervisors
- $\succ \pi_{ssn}$ (EMPLOYEE) $\blacksquare \pi_{Super\ ssn}$ (EMPLOYEE)




Question 2(b) (Answer)

- Find the Ssn of all employees who either work in department 5 or directly supervise an employee who works in department 5
- $\succ \pi_{Ssn} (\sigma_{Dno=5} (\text{EMPLOYEE})) \cup \pi_{Super_ssn} (\sigma_{Dno=5} (\text{EMPLOYEE}))$




Question 2(c) (Answer)

- > List the names and numbers of all departments locating in 'Houston'
- $\rightarrow \pi_{Dname,Dnumber} (\sigma_{Dlocation='Houston'} (DEPARTMENT*DEPT_LOCATIONS))$



Question 2(d) (Answer)

- List the first names of all employees who have a dependent with the same first name (i.e., dependent_name) as themselves
- $\succ \pi_{Fname}$ (EMPLOYEE) $\bowtie_{Ssn=Essn}$ AND $_{Fname=Dependent_name}$ (DEPENDENT))



Question 2(e) (Answer)

- Retrieve the salary of all employees in department 5 who work more than 10 hours on the project named 'ProjectX'
- \triangleright WORK5_10 \leftarrow WORKS_ON $\bowtie_{Pnumber=Pno}$ AND $p_{num=5}$ AND $p_{num=5}$ PROJECT
- $\triangleright (PROJECTX5_10) \leftarrow \sigma_{Pname=ProjectX}, (WORK5_10)$
- $ho \pi_{Salary}$ (PROJECTX5_10) $\bowtie_{Essn=Ssn}$ EMPLOYEE)

