

High-dimensional sampling and volume computation

Vissarion Fisikopoulos

Dept. of Informatics & Telecommunications, University of Athens




Pireaus, 28/01/2020

Our problem

Given P a convex body in \mathbb{R}^d compute the volume of P .

Some elementary polytopes (simplex, cube) have simple determinantal formulas.



$$\begin{vmatrix} 1 & 2 & 1 \\ 3 & 6 & 1 \\ 6 & 1 & 1 \end{vmatrix} / 2! = 11$$

$$\begin{vmatrix} 2 & 5 \\ 4 & 0 \end{vmatrix} = 20$$


Convex bodies

H-polytope : $P = \{x \mid Ax \leq b, A \in \mathbb{R}^{q \times d}, b \in \mathbb{R}^q\}$

V-polytope : P is the convex hull of a set of points in \mathbb{R}^d

Z-polytope : Minkowski sum of segments (projections of d -cubes)

LMI : $P = A_0 + y_1 A_1 + y_2 A_2 + \cdots + y_m A_m \succeq 0$,
where A_i : symmetric matrices, $B \succeq 0$: B is positive
semidefinite




First thoughts for volume computation

- ▶ Triangulation (or sign decomposition) methods – exponential size in d

First thoughts for volume computation

- ▶ Triangulation (or sign decomposition) methods – exponential size in d
- ▶ Sampling/rejections techniques (sample from bounding box) fail in high dimensions



volume(unit cube) = 1
volume(unit ball) $\sim (c/d)^{d/2}$
–drops exponentially with d

Volume computation is hard!

- ▶ #P-hard for V-, H-, Z-polytopes [DyerFrieze'88]
- ▶ no deterministic poly-time algorithm can compute the volume with less than exponential relative error (oracle model) [Elekes'86]
- ▶ open problem if V-polytope and H-polytope representations available

Randomized algorithms


Volume algorithms parts

1. **M**ultiphase **M**onte **C**arlo (MMC)
e.g. Sequence of balls, Annealing of functions
2. Sampling via geometric random walks
e.g. grid-walk, ball-walk, hit-and-run, billiard walk

Notes:

- ▶ MMC (1) at each phase solves a sampling problem (2)
- ▶ geometric random walks are (most of the times) Markov chains where each "event" is a d -dimensional point
- ▶ Algorithmic complexity is polynomial in d [Dyer, Frieze, Kannan'91]

Multiphase Monte Carlo



- Sequence of convex bodies $C_1 \supseteq \dots \supseteq C_m$ intersecting P , then:





$$\text{vol}(P) = \text{vol}(P_m) \frac{\text{vol}(P_{m-1})}{\text{vol}(P_m)} \dots \frac{\text{vol}(P_1)}{\text{vol}(P_2)} \frac{\text{vol}(P)}{\text{vol}(P_1)}$$

where $P_i = C_i \cap P$ for $i = 1, \dots, m$.


- Estimate ratios by sampling.

Four random walks


- ▶ Ball walk
- ▶ Random directions hit and run (rdhr)
- ▶ Coordinate directions hit and run (cdhr)
- ▶ Billiard walk




Ball walk




Ball walk




Ball walk




Ball walk




Ball walk




Random directions hit and run




Random directions hit and run




Random directions hit and run




Coordinate directions hit and run




Coordinate directions hit and run




Coordinate directions hit and run




Coordinate directions hit and run




Billiard walk




Billiard walk




Billiard walk



Billiard walk



Billiard walk



State-of-the-art

Theory:

Authors-Year	Complexity (oracle steps)	Algorithm
[Dyer, Frieze, Kannan'91]	$O^*(d^{23})$	Seq. of balls + grid walk
[Kannan, Lovasz, Simonovits'97]	$O^*(d^5)$	Seq. of balls + ball walk + isotropy
[Lovasz, Vempala'03]	$O^*(d^4)$	Annealing + hit-and-run
[Cousins, Vempala'15]	$O^*(d^3)$	Gaussian cooling (* well-rounded)
[Lee, Vempala'18]	$O^*(Fd^{\frac{2}{3}})$	Hamiltonian walk (** H-polytopes)

State-of-the-art

Theory:

Authors-Year	Complexity (oracle steps)	Algorithm
[Dyer, Frieze, Kannan'91]	$O^*(d^{23})$	Seq. of balls + grid walk
[Kannan, Lovasz, Simonovits'97]	$O^*(d^5)$	Seq. of balls + ball walk + isotropy
[Lovasz, Vempala'03]	$O^*(d^4)$	Annealing + hit-and-run
[Cousins, Vempala'15]	$O^*(d^3)$	Gaussian cooling (* well-rounded)
[Lee, Vempala'18]	$O^*(Fd^{\frac{2}{3}})$	Hamiltonian walk (** H-polytopes)

Software:

1. [Emiris, F'14] Sequence of balls + coordinate hit-and-run
2. [Cousins, Vempala'16] Gaussian cooling + hit-and-run
3. [Chalikis, Emiris, F'20] Convex body annealing + billiard walk

State-of-the-art

Theory:

Authors-Year	Complexity (oracle steps)	Algorithm
[Dyer, Frieze, Kannan'91]	$O^*(d^{23})$	Seq. of balls + grid walk
[Kannan, Lovasz, Simonovits'97]	$O^*(d^5)$	Seq. of balls + ball walk + isotropy
[Lovasz, Vempala'03]	$O^*(d^4)$	Annealing + hit-and-run
[Cousins, Vempala'15]	$O^*(d^3)$	Gaussian cooling (* well-rounded)
[Lee, Vempala'18]	$O^*(Fd^{\frac{2}{3}})$	Hamiltonian walk (** H-polytopes)

Software:


1. [Emiris, F'14] Sequence of balls + coordinate hit-and-run
2. [Cousins, Vempala'16] Gaussian cooling + hit-and-run
3. [Chalikis, Emiris, F'20] Convex body annealing + billiard walk

Notes:

- ▶ (2) is (theory + practice) faster than (1)
- ▶ (1),(2) efficient only for H-polytopes
- ▶ (3) efficient also for V-,Z-polytope, non-linear convex bodies
- ▶ C++ implementation of (2) $\times 10$ faster than original (MATLAB)

Performance


H-polytopes



Sequence Of Balls (SOB), Cooling Gaussians (CG), Cooling Balls (CB)

Performance



Z-polytopes



Applications

Biogeography & engineering

- ▶ Volume of **zonotopes** is used to test methods for order reduction which is important in several areas: autonomous driving, human-robot collaboration and smart grids [Althoff et al.]
- ▶ Volumes of **intersections of polytopes** are used in bio-geography to compute biodiversity and related measures e.g. [Barnagaud, Kissling, Tsirogiannis, F, Villeger, Sekercioglu'17]



Applications

Combinatorics & Machine Learning

- ▶ Volume can be used for **counting linear extensions** of a partially ordered set. This arises in sorting [Peczarski 2004], sequence analysis [Mannila et al.2000], convex rank tests [Morton et al.2009], preference reasoning [Lukasiewicz et al.2014], partial order plans [Muise et al.2016], learning graphical models [Niinimäki et al. 2016] See also [Talvitie et al.AAI'2018]
- ▶ e.g. elements a, b, c
partial order $a < c$
3 linear extensions: abc, acb, bac

Applications

Computing integrals for AI

- ▶ In Weighted Model Integration (WMI), given is a SMT formula and a weight function, then we want to compute the weight of the SMT formula.
- ▶ e.g. SMT formula:


$$(A \ \& \ (X > 20) \mid (X > 30)) \ \& \ (X < 40)$$

Boolean formula + comparison operations. Let X has a weight function of $w(X) = X^2$ and $w(A) = 0.3$.

- ▶ WMI answers the question of the weight of this formula i.e. integration of a weight function over convex sets.
- ▶ [\[P.Z.D. Martires et al.2019\]](#)

Applications in finance

When is the next financial crisis?



Cales, Chalkis, Emiris, Fisikopoulos - Practical volume computation of structured convex bodies, and an application to modeling portfolio dependencies and financial crises, SoCG 2018

VolEsti package: sampling and volume estimation

https://github.com/GeomScale/volume_approximation

- ▶ C++, R-interface, python bindings (limited)
- ▶ open source, LGPL3
- ▶ since 2014, CGAL (not any more), Eigen, LPSolve, Boost
- ▶ 3 volume algorithms, 4 sampling algorithms
- ▶ design: mix of obj oriented + templates
- ▶ C++11 dependence (mostly C++03)
- ▶ main developers: Vissarion Fisikopoulos, Tolis Chalkis

VolEsti package

- ▶ R package on CRAN
<https://cran.r-project.org/package=volesti>
- ▶ Documentation
https://github.com/GeomScale/volume_approximation/blob/develop/README.md

How to contribute (github account is needed):

- ▶ first star and fork the repo :D
- ▶ then follow the [contribution tutorial](#)

VolEsti on Google Summer of Code 2020

- ▶ Applying this year as an organization for GSoC 2020.
- ▶ See this [wiki](#) for more details.
- ▶ Tentative plan:
 - ▶ MCMC integration
 - ▶ sampling for structural biology
 - ▶ randomized algorithms for convex optimization
 - ▶ sampling in higher dimensions (reach the thousands)
- ▶ Communication channels: [gitter](#),
geomscale-gsoc@googlegroups.com

VolEsti tutorial

https://vissarion.github.io/tutorials/volesti_tutorial_pydata.html

CRAN mode (recommended!)

- ▶ in Rstudio install CRAN package "volesti"
- ▶ follow this https://github.com/GeomScale/volume_approximation/blob/tutorial/tutorials/volesti_tutorial.Rmd

develop mode

- ▶ `git clone git@github.com:GeomScale/volume_approximation.git`
- ▶ `git checkout tutorial`
- ▶ in Rstudio open R-proj/volesti.Rproj and then click build source Package and then Install and Restart in Build tab at the menu bar.
- ▶ follow this https://github.com/GeomScale/volume_approximation/blob/tutorial/tutorials/volesti_tutorial_1_1_0.Rmd