

Package ‘volesti’

August 8, 2018

Type Package

License GPL (>= 2)

Title Volume approximation using VolEsti and CV algorithms.

Description Package provides C++ code and a Rcpp interface for volume approximation. The main function takes as input a H-polytope or a V-polytope and apply VolEsti or CV algorithm.

Maintainer Fisikopoulos Vissarion <vissarion.fysikopoulos@oracle.com>, Chalkis Apostolos <tolis.chal@gmail.com>

Version 1.0

Date 2018-08-08

BugReports https://github.com/vissarion/volume_approximation/issues

SystemRequirements C++11

Depends Rcpp (>= 0.12.17), RcppEigen, lpSolveAPI, BH

Imports Rcpp (>= 0.12.17)

LinkingTo Rcpp, RcppEigen, BH

RoxygenNote 6.0.1

Author Fisikopoulos Vissarion [cph, cre, aut],
Chalkis Apostolos [cph, ctb, aut] (Contribution and development, as
part of Google Summer of Code 2018 program)

R topics documented:

CheBall	2
demoVolume	2
ineToMatrix	3
modifyMat	3
volume	4

Index	6
-------	---

CheBall	<i>Compute the Chebychev ball of a H-polytope, $P:= Ax \leq b$</i>
---------	---

Description

Compute the Chebychev ball of a H-polytope, $P:= Ax \leq b$

Usage

CheBall(A, b)

Arguments

A	the matrix of the H-polytope
b	the vector with the constants of the hyperplanes

Value

The Chebychev center of the Polytope discribed by the matrix A and the vector b

Examples

CheBall(A,b)

demoVolume	<i>Run some experiments</i>
------------	-----------------------------

Description

Run volesti or CV algorithm to approximate the volume of some cubes, simplices, skinny_cubes, cross polytopes, birkhoff polytopes.

Usage

demoVolume(algo)

Value

Print the computed volumes and the total time

Examples

```
#test volesti
demoVolume("volesti")
#test CV
demoVolume("CV")
```

ineToMatrix	<i>function to get a ine file and return matrix A in ine format for VolEsti()</i>
-------------	---

Description

function to get a ine file and return matrix A in ine format for VolEsti()

Usage

```
ineToMatrix(P)
```

Arguments

P	It is in format, read.cs('path/to/file.ine'). The ine file describes the H-polytope
---	---

Value

The numerical matrix in ine format of read.cs('path/to/file.ine')

Examples

```
ineToMatrix(read.cs('path/to/data/cube40.ine'))
```

modifyMat	<i>takes a numerical matrix in ine format and return numerical matrix A and vector b: $Ax \leq b$</i>
-----------	--

Description

takes a numerical matrix in ine format and return numerical matrix A and vector b: $Ax \leq b$

Usage

```
modifyMat(A)
```

Arguments

A	the numerical matrix in ine format of the H-polytope
---	--

Value

numerical matrix A and vector b: $Ax \leq b$

Examples

```
modifyMat(A)
```

volume	<i>The main R function for volume approximation of a convex H-Polytope</i>
--------	--

Description

The main R function for volume approximation of a convex H-Polytope

Usage

```
volume(Inputs)
```

Arguments

<code>list("argument"=value)</code>	A list that includes all the parameters of the algorithm
<code>path</code>	The path to an in or ext file that describes the H-polytope. If path is given then "matrix" and "vector" inputs are not needed
<code>matrix</code>	The matrix A of the polytope. If it is in in format then the input "vector" is not needed
<code>vector</code>	The vector b that contains the constants of the hyperplanes
<code>Walk_length</code>	Optional. Declare the number of the steps for the random walk, default is $10+d/10$
<code>error</code>	Optional. Declare the goal for the approximation error. Default is 1 for volesti and 0.2 for CV.
<code>Chebychev</code>	Optional. A d+1 vector that contains the chebychev center in the first d coordinates and the radius of the chebychev ball in the last coordinate
<code>annealing</code>	Optional. A boolean parameter to use CV algorithm. Default value is false.
<code>win_len</code>	Optional. The size of the window for the ratios' approximation in CV algorithm. Default value is $win_len=4*(dimension^2)+500$
<code>C</code>	Optional. a constant for the upper bound of variance/mean ² in schedule annealing
<code>N</code>	optional. The number of points we sample in each step of schedule annealing in CV algorithm. Default value is $N=500*C+(dimension^2)/2$
<code>ratio</code>	Optional. parameter of schedule annealing, larger ratio means larger steps in schedule annealing. Default value is $ratio=1-1/dimension$
<code>frac</code>	Optional. the fraction of the total error to spend in the first gaussian. Default value is $frac=0.1$
<code>ball_walk</code>	Optional. Boolean parameter to use ball walk, only for CV algorithm. Default value is False
<code>delta</code>	Optional. The radius for the ball walk
<code>verbose</code>	Optional. A boolean parameter for printing. Default is False
<code>vpoly</code>	A boolean parameter, has to be true when a V-polytope is given as input

coordinate	Optional. A boolean parameter for the hit-and-run. True for Coordinate Directions HnR, false for Random Directions HnR. Default value is True
rounding	Optional. A boolean parameter to activate the rounding option. Default value is False
test	Optional. A boolean parameter. Declare if the current execution is a test or not. Default value is False

Value

The approximation of the volume of an H-polytope

Examples

```
VolEsti(list("path"="/path/to/ine/file", "verbose"=TRUE))
```

Index

CheBall, [2](#)

demoVolume, [2](#)

ineToMatrix, [3](#)

modifyMat, [3](#)

volume, [4](#)