Reference Number
162155

Version DRAFT

HSE Report

Fire Risk Assessment

Prepared for

(demo) Test Company on behalf of Landlord 2

Visit Date
8th July 2022

Site Address
Building 4
Building Lane
Buildsmouth
PO15 7AH

Consultant
Tom Stallard
Head of Fire Services
MIFSM CFPA.Dip

Ligtas

Cardiff Head Office: Axys House, Parc Natgarw, Cardiff, CF15 7TW
Tel: 02922 800 000 Email: enquiries@ligtas.co.uk Web: www.ligtas.co.uk

Table of Contents

1. Summary 1
2. Competent Persons 3
3. Introduction 4
4. Terms and Definitions 5
4.1. Fire Safety Order 5
4.2. Fire Safety Arrangements 5
4.3. Standards/Approved Codes of Practices and European Norms 6
5. Premises Details 8
5.1. On-site Contacts 8
5.2. Clients Nominated Responsible Person(s) For Fire Safety 8
5.3. Location of Premises 8
5.4. Owner 8
5.5. Managing Agent 8
5.6. Description of Undertakings 8
5.7. Construction Details 9
5.8. Building Classification 10
5.9. Fire Evacuation Policy 10
5.10. Utilities 11
5.11. Usage 12
5.12. Enforcement 12
5.13. Employed Staff on Site 12
5.14. Persons at Risk 13
6. Limitations of Report 15
7. Resume of the brief 16
8. Fire Risk Assessment 17
9. Risk Assessment and Action Plan 19
9.1. Fire Safety Management 19
9.2. Site Security 20
9.3. Electrical Matters 21
9.4. Deliberate or Malicious Ignition 22
9.5. Training (Fire) 23
9.6. Fire Protection Systems - Fire Alarm 24
9.7. Compartmentation 25
9.8. Fire Extinguishers 27
9.9. Hose Reels 28
9.10. Smoke Control Systems 29

Draft

9.11. Dry/Wet Riser 30
9.12. Sprinkler System 31
9.13. Gaseous Suppression Systems 32
9.14. Fire Hydrants 33
9.15. Emergency Procedures 34
9.16. Means of Escape 35
9.17. Emergency Lighting 37
9.18. Highly Flammable Liquids 38
9.19. Liquefied Petroleum Gas 39
9.20. General Fire Safety 40
9.21. Grainger PLC - Fire Safety Management 41
10. Tenant(s) Monitoring 42

Draft

1. Summary

This is the introduction to the report and should contain where the fire risk assessment was done, when it was done, the weather conditions at the time, who you have met on site, and details of the debrief given

Where people are named in the report, their full name and job title should be stated.

The template text is:

On 8th July 2022 between [00:00] and [00:00], a Fire Risk Assessment was carried out in the areas under the control of the client in Building 4, Buildsmouth, PO15 7AH. Weather conditions at the time of the visit were [XXX].

This assessment was commissioned by (demo) Test Company, on behalf of Landlord 2, to assist them in fulfilling their duties under relevant fire safety legislation.

[XXX] was [available / not available] to accompany the consultant during the inspection. Following the assessment a [verbal / written] debrief was carried out and issued.

A site inspection and audit of relevant records of examination, testing and maintenance work was carried out. Any inaccessible areas during this assessment are detailed within the limitations section of this report.

This risk assessment is intended to be a working document that can be used to guide future action aimed at improving compliance and maintaining fire safety standards. Following this risk assessment measures must be taken to implement effective, preventative and protective control measures to reduce the risks identified, as well as maintaining ongoing 'general' fire precautions.

Any fire risk assessment must be reviewed by the responsible person regularly so as to keep it up to date, there is no definition of regularly but annually is generally accepted to be best practice.

Draft

Risk Assessment Findings

The following risks were identified during the assessment:

Priority	Number of Risks (X)	Risk Rating (Y)	Risk Score (X x Y)
High	2	3	6
Medium	1	2	2
Low	1	1	1
		Total Risk Score	9

High Risk Action(s) requiring immediate attention are as follows:

- Once you have completed the writing of the report, click the 'populate with template' button above this section to bring any high risk actions though to the front of the report.

Draft

2. Competent Persons

Ligtas Fire Safety Consultants have been appointed by (demo) Test Company to assist them in the carrying out of their duties under fire safety legislation, specifically in carrying out a fire safety risk assessment in accordance with their duties under the Regulatory Reform (Fire Safety) Order 2005 hereafter referred to as the 'Fire Safety Order'.

Draft

3. Introduction

On 8th July 2022, a Fire Risk Assessment was carried out on all areas of Building 4, Building Lane, Buildsmouth for which the client has responsibility, and a report prepared. The aims of the Fire Risk Assessment are:

- To assist the 'Responsible Person' as defined in the Fire Safety Order to identify general fire precautions, which are to be taken 'so far as is reasonably practicable' to ensure the safety of his employees, the safety of relevant persons and to ensure the premises are safe.

- To assist the Responsible Person in meeting the general fire precautions requirements for the building/area under their control.

- To identify any practices or conditions which could pose significant risks from fire to persons occupying the building.

- To identify any practices or conditions which could pose significant risks to the building, the environment and persons in the immediate vicinity of the building.

- To assist the client in meeting their requirements to ensure compliance with the Fire Safety Order and other fire related issues throughout the building.

- To assess the adequacy of current fire safety measures against the risks posed, using current standards, legislation and recognised codes of practice and to recommend improvements where required.

The Fire Risk Assessment must be reviewed by the Responsible Person regularly so as to keep it up to date and accurate and particularly if:

- There is reason to believe a significant change in the structure or use of the building.

- There is a significant change in relation to the special, technical or organisational measures.

- Changes have taken place that have not been notified and approved by the relevant enforcing body or Fire Authority where an 'Alterations' notice is in force.

- There is reason to believe that an occupant is operating in breach of fire safety legislation.

- Where changes to an assessment are required as a result of any such review, the Responsible Person must make them.

- As soon as practicable after the assessments made or reviewed, the Responsible Person must record the information.

The information to be recorded must include the significant findings of the assessment, including the measures, which will or have been taken by the Responsible Person pursuant to the Fire Safety Order and any group of persons identified by the assessment as being especially at risk.

Draft

4. Terms and Definitions

4.1. Fire Safety Order

The Regulatory Reform (Fire Safety) Order 2005 came into force on 1st October 2006 and extends to England and Wales only.

The Fire Safety Order specifies:

- The requirement for the nomination of a Responsible Person with regard to fire safety;
- The general fire precautions needed to be taken;
- The fire risk assessment requirements;
- Principles of fire prevention to be applied;
- Fire safety arrangements;
- The need to eliminate or reduce the risks from dangerous substances;
- Fire fighting and detection requirements;
- The requirements for emergency routes and exits;
- Procedures for serious and imminent danger and danger areas;
- Additional emergency measures in respect of dangerous substances;
- The fire protection maintenance requirements;
- Safety assistance and competency of persons used by the responsible person to carry out preventive and protective measures;
- Provision of information to employees;
- Training requirements for employees;
- The need for cooperation and coordination between responsible persons;
- Employees general duties at work;
- Enforcement notices and offences.

Draft

4.2. Fire Safety Arrangements

The responsible person must make and give effect to such arrangements as are appropriate, having regard to the size, nature of activities for the effective planning, organisation, control, monitoring and review of preventative and protective measures.

Planning
Adopting a systematic approach that identifies priorities and sets objectives. This assessment facilitates this process and wherever possible risks should be eliminated by the careful design and selection of facilities, equipment and processes or minimised by the use of physical control measures.

Organisation
Putting in place the necessary structure with the aim of ensuring that there is a progressive improvement in fire safety performance.

Control
Ensuring that the decisions for promoting fire safety are being implemented as planned.

Monitoring and review
Like quality, progressive improvement in fire safety can only be achieved through the constant development of policies, approaches to implementation and techniques of risk control.

Preventative and protective measures
Measures, which have been identified by the Responsible Person in consequence of a risk assessment as the general precautions he needs to take to comply with the requirements of the Order.

Draft

4.3. Standards/Approved Codes of Practices and European Norms

In this report reference may be made to the Category of Automatic Fire Detection installed or recommended to be installed in premises. These categories are taken from BS 5839-1 and the coverage they entail is summarised below.

System documentation, including any purchase specification, tender document, design proposal, submission to enforcing authorities or insurers for approval and the certificate issued by the designers, installers or commissioners, should clearly identify the system Category as well as, where appropriate, the areas to be protected and any specific proposals for the type(s) of detector to be used.

Category M requires manual call points on all exits as well as corridors where persons are not expected to walk more than 45m to operate one.

Category L5 is designed for buildings that have a particular risk identified which warrants some special attention. For example if there is an area of high risk which is considered worthy of having some automatic detection but a manual system is also needed, then it will be termed as L5/M.

Category L4 provides detection within the escape routes only; All escape stairways, all corridors and any other areas that form part of the common escape routes. NOTE - Main access and egress stairways normally form part of escape routes, and should be treated as escape stairways.

Category L3 covers the same areas as an L4 category and in addition all rooms leading onto the escape route. The reasoning behind this is to alert people of the danger prior to full smoke logging of the corridor so they can escape safely.

Category L2 is a further enhancement of protection with all the areas covered by an L3 category as well as all high-risk areas such as boiler rooms etc.

Category L1 provides the highest possible enhancement of life safety. In an L1 system automatic fire detectors protect all areas of the building. An L1 system might be appropriate where there is a significant number of occupants at risk in the event of fire (e.g. hospitals and certain residential care premises) or in which throughout the building structural fire precautions are not of as high a standard as normally required for that type of building.

For greater detail in the type, exact location and positioning of detectors as part of these systems reference must be made to BS 5839-1.

Draft

5. Premises Details

5.1. On-site Contacts

This section should list the site contact for the building

5.2. Clients Nominated Responsible Person(s) For Fire Safety

For Fire Risk Assessment - Competent and Responsible Persons should be detailed here

If working in Scotland, then the term is Duty Holder, and in Northern Ireland the term is Appropriate Person

5.3. Location of Premises

Building 4
Building Lane
Buildsmouth
PO15 7AH

5.4. Owner

Landlord 2

5.5. Managing Agent

(demo) Test Company
The Road 1
The Town
Merseyside
CH60 1UX

5.6. Description of Undertakings

Describe what the building is used for, ideal with a recognized purpose group i.e. commercial, industrial, office, retail, leisure. If residential specify what sort of residential it is e.g. general needs, supported living, HMO, boarding house.

If it is a general needs block of flat you will need to state if it was purpose built as a general needs block of flats or has been converted. If its been converted when it has been converted must be established and stated.

State if the entire building, specific area of the building or common areas are being assessed. If it is common areas details of what the common areas are should be stated, e.g. stairwells, access corridors, plant rooms, riser cupboards and reception areas.

Draft

5.7. Construction Details

This section is to describe the construction materials used in the building, this should include primary and secondary construction. It should also include the floor area for the building and the building height. The template text is:

Roof: Flat and accessed via an internal door situated at the top of the staircase. Satellite dishes, water tanks, and tenant air-conditioning units are sited on the roof with edge protection provided to the rear and a brick wall to the front of the property.

Floors: Appear to be concrete.

Ceilings: Appear to be plasterboard.

Walls: Brick/block and plaster and assumed stud partition separating the flats.

External Cladding: Visually from the ground floor, the external walls appear to be brick and block.

Internal Staircase: One internal wooden staircase which is carpeted spirals around the lift shaft serving all floors in the property.

External Staircase: A metal staircase situated at the rear of the building service all floor levels of the property.

Windows: Single glaze in a metal casing. Reinforced windows situated on the internal staircase can be opened for ventilation purposes.

Balconies: External metal balconies form part of the metal evacuation staircase at the rear of the property. No balconies at the front of the property.

Building Size: XXXXX sq. Ft

******* DELETE THIS GUIDANCE calculating building height - measure from the ground floor (the level the FRS will access the building on) to the floor slab of the highest occupied floor, excluding rooftop plant rooms, i.e. 4 storey building (ground - 3rd), with the third floor being an occupied floor, will be 3.2m x 3 (G + 1 + 2) *********

Based on RICS guidance that a storey is any floor or part of a floor of a building visible above ground level, including the ground floor, whether used for residential, commercial, parking, or other use. It does not include basements or mezzanine levels. Where a building has multiple levels, the highest number of floors in the building should be used for applying the criteria.

Based on nationally described space standards for dwellings having 2.5m floor-to-ceiling height. An assumption of 0.7m between the ceiling and floors has been made. Please take note that this calculation is for new buildings and older buildings could have some slight variation.

Draft

Number of Storeys (ground floor and above): XXX

Estimated Building Height: [XXX} ([X] floors x 3.2m). The building height for the purposes of the relevant fire safety legislation is to the floor slab of the upper most occupied floor.

5.8. Building Classification

Each building should be classified, while the template text reflects building with or without two or more domestic dwellings if there is a single domestic dwelling that should also be identified.

The template text is:

This building contains two or more domestic premises. Based on the height and the number of storeys of the building, when measured and counted in accordance with relevant national benchmark guidance, the building is classed as a:

High Rise Residential Building (18 meters in height + or 7 or more storeys) / Medium Rise Residential Building (11 - 17.9 meters in height) / Low Rise Residential Building (Below 11 meters in height) *** Delete as applicable***

This fire risk assessment incorporates the relevant legislative requirements of the country in which the building is located based on the classification of the building, unless otherwise noted.

***** OR ******

This building does not contain two or more domestic premises and therefore is classed as commercial building.

This fire risk assessment incorporates the relevant legislative requirements of the country in which the building is located based on the classification of the building, unless otherwise noted.

****OR*****

This property is a mixed-use building containing, two or more Residential dwellings, as well as [Retail/ Assembly / Industrial / Commercial / Office] units *** DELETE IN SQUARE BRACKETS AS APPLICABLE**** .

The residential elements of the building are of the following building classification:

High Rise Residential Building (18 meters in height + or 7 or more storeys) / Medium Rise Residential Building (11 - 17.9 meters in height) / Low Rise Residential Building (Below 11 meters in height)

This fire risk assessment incorporates the relevant legislative requirements of the country in which the building is located based on the classification of the building, unless otherwise noted.

5.9. Fire Evacuation Policy

Draft

This section is to describe the evacuation strategy that is in place, or lack of one in place. Not the strategy that should be in place, the strategy that is in place at the time of assessment.

The template text is:

Article 15 of the Regulatory Reform (Fire Safety) Order 2005 requires that the Responsible Person for a building must establish, and implement, appropriate procedures to be followed in the event of a fire.

Evacuation Policy - Stay Put / Simultaneous Progressive Horizontal / Phased Unknown ***Delete as applicable***

Based on the information gathered and observations made, within the scope and limitations of this report, it appear that the building adopts a stay put evacuation policy. It appears that this evacuation policy is viable for this building. Rationale for this statement, and any actions required to support the effectiveness of this policy will be detailed in the relevant areas of section 9 of this report.

Based on the information gathered and observations made, within the scope and limitations of this report, it appear that the building adopts a simultaneous evacuation policy. It appears that this evacuation policy is viable for this building. Rationale for this statement, and any actions required to support the effectiveness of this policy will be detailed in the relevant areas of section 9 of this report.

Based on the information gathered and observations made, within the scope and limitations of this report, it was unclear what evacuation procedures have been put in place by the responsible person. Actions to implement a suitable evacuation policy will be detailed in the relevant areas of section 9 of this report.

Based on the information gathered and observations made, within the scope and limitations of this report, it appears that the building adopts a [stay put / simultaneous / progressive horizontal / phased] evacuation policy. This does not appear to be the correct evacuation procedure for the building. Rationale for this, and the actions the client should undertake to implement the correct evacuation, are detailed in the relevant areas of section 9 of this report.

Based on the information gathered and observations made, within the scope and limitations of this report, it appear that the building adopts a progressive horizontal evacuation policy. It appears that this evacuation policy is viable for this building. Rationale for this statement, and any actions required to support the effectiveness of this policy will be detailed in the relevant areas of section 9 of this report.

Based on the information gathered and observations made, within the scope and limitations of this report, it appear that the building adopts a phased evacuation policy. It appears that this evacuation policy is viable for this building. Rationale for this statement, and any actions required to support the effectiveness of this policy will be detailed in the relevant areas of section 9 of this report.

5.10. Utilities

This section is to describe the utility supplies to the building, this should include the template text as well as any other utilities in the building:

Draft

The template text is:

No gas supply or gas fired plant was observed.

The electrical intake is located to a cupboard under the stairs up to the entrance. A variety of different ages and conditions of electrical installation run through the building, some which are disused.

The water supply is not used for fire fighting purposes.

5.11. Usage

Ground Floor	Each floor should have an individual entry. This should include a description of all areas of the building, even if out side of the control of our client

5.12. Enforcement

This section details any fires within the recent past of the building as well as any interactions with the Fire and Rescue Services.

The template text is:

No known history of fires at this building.

There are no reported visits from the Fire Safety Officer. It is not known if crews from the local watch have visited for the purpose of site familiarisation.

No matters known to be outstanding and no enforcement notices have been issued in respect of the building.

5.13. Employed Staff on Site

This section is to detail the persons employed to work on the site by our client.

The template text is:

The Building Manager , the , is responsible for managing the building daily. They [are/are not] based on site and have working hours of XXX. ***OR*** They are not based on site but conduct visits to the site on an XXX basis.

XXX employees of the client are employed to work on the property, with up to XXX present at any given time. Working hours are typically between XXX and XXX on XXX days.

Alongside XXX, contracts are arranged for security, reception, cleaning, and plant maintenance staff to work on-site daily.

Draft

*** RESIDENTIAL CARE PROPERTIES***

XXX staff members work during the day shift, which is typically considered to be between XXX and XXX.

XXX staff members work during the night shift, which is regarded as occurring between XXX and XXX.

5.14. Persons at Risk

This section should identify all Relevant Persons. This includes anyone directly employed by the client, anyone within the clients areas of the building, any persons in other areas of the building; either other tenants of multi occupied commercial building or residents in residential areas of the same building.

The template text for this section is:

*** COMMERCIAL***

Persons at risk within the building include the client's employees, the tenants' employees, visiting contractors, visitors to the tenanted areas, and members of the public.

There were no disabled persons reported as working in the building that are the client's responsibility.

No children or young persons are employed at the premises that are the client's responsibility.

There may be individuals or groups at high risk of fire within the building, particularly members of the public. No information was available at the time of the visit to determine the demographics of these individuals; however, it should be considered that there may be children or individuals within the building with mobility or hearing impairments that could affect their ability to evacuate the premises or raise an alarm in the event of a fire. ***OR*** No individuals or groups are at high fire risk within the building.

There is no sleeping accommodation within the building. ***OR*** There is sleeping accommodation within the building [though not within the areas under the control of the client]

The risk to relevant persons in the building is [trivial/tolerable/moderate/substantial/intolerable].

The risk to relevant persons in the vicinity of the building is [trivial/tolerable/moderate/substantial/intolerable].

Occupancy for the building is thought to be up to approximately XXXX persons at any one time.

*** RESIDENTIAL***

Persons at risk within the building include the client's employees, residents, residents' visitors, employees of the commercial units, visiting contractors, and members of the public.

Draft

No disabled persons were reported as working in the building.

No children or young persons are employed at the premises that are the client's responsibility.

There may be individuals or groups at high risk of fire within the building, specifically residents and visitors. No information was available at the time of the visit to determine the demographics of the residents; however, it should be noted that there may be children or individuals with mobility impairments, hearing impairments, and so on, which could affect their ability to evacuate the premises or raise an alarm in the event of a fire.

There is sleeping accommodation within the building.

The risk to relevant persons in the building is [trivial/tolerable/moderate/substantial/intolerable].

The risk to relevant persons in the vicinity of the building is [trivial/tolerable/moderate/substantial/intolerable].

It is believed that around XXX people reside in the building, based on an estimated two persons per flat and XXX flats within the building. The number of contractors and visitors also varies.

Draft

6. Limitations of Report

This assessment addresses the requirements of the Fire Safety Order and identifies the measures required to comply.

The assessment covers:

- All areas, which to any degree are under the control of the client.

- All areas accessed, which are under the control of tenants, where the landlord has to any degree control. The assessment does not constitute a Risk Assessment of the tenant's areas. Responsibility for the carrying out of such a risk assessment lies with the nominated responsible person on behalf of the tenant.

It is recommended that this assessment is reviewed at least annually and is supplemented by regular general fire precautions.

Whilst our Fire Safety Consultants make every reasonable effort to access all areas of the premises for which the client is responsible, there may be some areas that are inaccessible or are difficult to access due to the fabric of the building and to do so would cause unnecessary damage.

The following survey specific areas were not accessed during the survey because they were either locked, not reasonably accessible for reasons of health and safety, outside of the scope of the works requested or where excessive damage would be have been done to access the areas: Any areas not accessed during the survey due to these considerations are outlined below:

- This section should list all areas of the building that you did not assess and the reason for not assessing it. In residential buildings this should include which flats you accessed and which flats you attempted to gain access to

The Fire Risk Assessment is based on a combination of observations made by the Consultant at the time of the survey as well as information provided by representatives of the client. All such information is accepted in good faith as being factual, accurate and a valid representation of the client's views. Any changes to the occupancy, use or other circumstances of the premises will require that a review of the assessment be carried out.

The checking of the integrity of fire compartmentation within floor and ceiling voids is outside the scope of this report. Compartmentation will be visually assessed, as far as is possible, in all other accessible areas of the premises.

The electrical and mechanical worthiness of all plant and equipment is outside the scope of this report although the servicing and maintenance of such items may be commented upon as well as the design and coverage of installed systems.

Draft

7. Resume of the brief

The **'Existing control measures/Remarks'** section of the Action Plan provides a general description of the standard of fire safety and the current control measures implemented on site. Specific fire safety issues are detailed under the relevant subject headings within this section of the report.

Having considered the potential risks in terms of the worst possible outcome, the persons likely to be affected and the probability of an incident occurring; and taking account of the existing control measures, the report identifies the actions required to be taken to reduce such risks to a minimum.

The report identifies any failures to comply with legislative requirements and gives brief, but specific, advice on the action to be taken. All statutory provisions relevant to the client and their undertaking are considered. Codes of Practice, Guidance Notes, British Standards and best practice are also considered and recommendations made. In each case the action is denoted as **(L)** legal requirement or **(R)** recommendation.

The requirements within the action plan are then further prioritised as follows: Low **(L)**, Medium **(M)** or High **(H)**, having considered the potential risks, the probability of an incident occurring and the existing means of control.

In each case the requirements are prioritised as follows:

H	A serious breach of the fire legislation and/or affecting the adequacy of risk control features as determined by the risk assessment. Risks or issues which may result in legal action against the responsible persons. (Immediate attention required)
M	A lesser breach of the fire safety legislation or inadequate control measures as identified by the risk assessment. (Recommended timescale for completion within 3 months)
L	Poor practices or features that, whilst not presenting an immediate increased risk to life safety, may affect overall fire safety. Also includes provision of practices and features that are favourable, but over and above the minimum adequate standards as defined by fire safety legislation and/or risk assessment. (Recommended timescale for completion within 6 months)

The above are given only as a guide to assist implementation and allocation of resources, although it is recommended that work be carried out as soon as reasonably practicable.

Draft

8. Fire Risk Assessment

The following simple risk level estimator is based on a commonly used risk level estimator:

Potential consequences of fire **Likelihood of fire**	Slight harm	Moderate harm	Extreme harm
Low	Trivial risk	Tolerable risk	Moderate risk
Medium	Tolerable risk	Moderate risk	Substantial risk
High	Moderate risk	Substantial risk	Intolerable risk

Taking into account the fire prevention measures observed at the time of this risk assessment, it is considered that the hazard from fire (likelihood of fire) at these premise is:

Low ☐ **Medium** ☒ **High** ☐

In this context, a definition of the above terms is as follows:

Low: Unusually low likelihood of fire as a result of negligible potential sources of ignition.

Medium: Normal fire hazards (e.g. potential ignition sources) for this type of occupancy, with fire hazards generally subject to appropriate controls (other than minor shortcomings)

High: Lack of adequate controls applied to one or more significant fire hazards, such as to result in significant increase in likelihood of fire.

Taking into account the nature of the premises and the occupants, as well as the fire protection and procedural arrangements observed at the time of this fire risk assessment, it is considered that the consequences for life safety in the event of fire would be:

Slight harm ☐ **Moderate harm** ☒ **Extreme harm** ☐

In this context, a definition of the above terms is as follows:

Slight harm: Outbreak of fire unlikely to result in serious injury or death of any occupant (other than an occupant sleeping in a room in which a fire occurs).

Moderate harm: Outbreak of fire could foreseeably result in injury (including serious injury) of one or more occupants, but is unlikely to result in multiple fatalities.

Extreme harm: Significant potential for serious injury or death of one or more occupants.

Accordingly, it is considered that the risk to life from fire at these premises is:

Trivial ☐ **Tolerable** ☐ **Moderate** ☒ **Substantial** ☐ **Intolerable** ☐

A suitable risk-based control plan should involve effort and urgency that are proportional to risk. The following risk-based control plan is based on one advocated for general health and safety risks:

Draft

Risk level	Action and timescale
Trivial	No action is required, and no detailed records need be kept.
Tolerable	No major additional controls required. However, there might be a need for improvements that involve minor or limited cost.
Moderate	It is essential that efforts are made to reduce the risk. Risk reduction measures should be implemented within a defined time period. Where moderate risk is associated with consequences that constitute extreme harm, further assessment might be required to establish more precisely the likelihood of harm as a basis for determining the priority for improved control measures.
Substantial	Considerable resources might have to be allocated to reduce the risk. If the building is unoccupied, it should not be occupied until the risk has been reduced. If the building is occupied, urgent action should be taken.
Intolerable	Building (or relevant area) should not be occupied until the risk is reduced.

Note that, although the purpose of this section is to place the fire risk in context, the above approach to risk assessment is subjective and for guidance only. All hazards and deficiencies identified in this report should be addressed by implementing all recommendations contained in the following action plan. The fire risk assessment should be repeated regularly.

Draft

9. Risk Assessment and Action Plan

This section of the report identifies the necessary steps to be taken to reduce specific or inherent risks to a minimum & comply with the duties under the relevant fire safety legislation, regulation, approved code of practice, british standard or best practice. This may involve, drafting of safe working procedures, training of staff, installation and or maintenance of equipment or systems etc.

This section of the report is a working document, giving an indication of the time period expected for compliance, a section for allocating responsibility for compliance and a section to be signed on completion. Where offences have been highlighted in the tenant's areas, it is the owner's responsibility to ensure that the tenant completes the remedial work required.

Any examples of safety signage identified in this section are to be used for guidance purposes only. Alternative signage, as identified in The Health and Safety (Safety Signs and Signals) regulations 1996 may be used.

9.1. Fire Safety Management

Existing Controls and Observations

This sections covers the fire safety management arrangements for the building and should detail all reasonably foreseeable findings.

Item Description	Action Required	L/R	Priority Rating	Freq	Photograph	Progress / Completion Notes
Building Fire Strategy / Fire strategy	Any actions raised in the action plan should have suitable photographs provide as evidence of what was observed, where practicable	L	Medium	-		

Draft

9.2. Site Security

Existing Controls and Observations

This section should detail the site security arrangements in place to reduce the risk of unauthorised access to the building.

Item Description	Action Required	L/R	Priority Rating	Freq	Photograph	Progress / Completion Notes
No action is required at present.						

Draft

9.3. Electrical Matters

Existing Controls and Observations

This section should detail all potential sources of ignition posed by electricity in the building and the control measures in place to reduce the risk. It should detail all reasonably foreseeable findings.

There were no Personal Electrical Transport devices (E-scooters, E-bikes, E-unicycles) observed in the areas of the building under the control of the client.

Item Description	Action Required	L/R	Priority Rating	Freq	Photograph	Progress / Completion Notes
Electrical testing / Examination and testing of electrical installation	Ensure that the electrical installation is subject to an electrical installation condition inspection by a competent person and a suitable record held on site, or made readily available for inspection. Ensure that the work identified in the observations and recommendations for action section of the report are completed. Electrical installation condition inspection should be carried out at least once in every five year period, or as recommended by an NICEIC, or equivalent, contractor and any necessary maintenance work carried out.	L	High	5y		
Electrical room / Electric shock poster	Provide an electric shock poster to be displayed in the electrical room. For example: 	L	High	-		
Portable electrical equipment / Portable electrical equipment testing	Ensure that a competent person carries out a periodic inspection and test of the electrical safety of portable electrical appliances. All equipment should be labelled, with its reference no. and location and test results should be held on site or made readily available for inspection. New equipment should be marked with an installation date in order to ascertain when the first inspection is due.	L	Low	1y		

Draft

9.4. Deliberate or Malicious Ignition

Existing Controls and Observations

This section should detail the control measures in place to reduce the risk posed by arson.

Item Description	Action Required	L/R	Priority Rating	Freq	Photograph	Progress / Completion Notes
No action is required at present.						

Draft

9.5. Training (Fire)

Existing Controls and Observations

This section should detail the fire safety training arrangement in place for competent persons, fire wardens, and all staff employed to work in the building by the client.

Item Description	Action Required	L/R	Priority Rating	Freq	Photograph	Progress / Completion Notes
No action is required at present.						

Draft

9.6. Fire Protection Systems - Fire Alarm

Existing Controls and Observations

This section covers provision of fire detection and alarm within the building. It should detail where the fire alarm control panel and any repeater panel locations, where you have observed fire detection and if the level of detection is suitable or not for the use of the building or area of the building. It should detail the operations, cause and effect, of the system and the current operational state of the system. Any PAVA systems and any other systems interfaced with the fire alarm system should be detailed.

The template text for the description is:

The building is provided with an [addressable ***OR*** conventional] fire alarm system, with the fire alarm control panel located XXX and repeater panels located XXX

There is no delay between the detection of fire and the activation of the system's audible and visual warning devices. ***OR*** There is a XXX minute delay between the detection of fire and the activation of the system's audible and visual warning devices. The fire alarm system is programmed for a 'double knock' staff alarm. Activation of a single smoke detector will alert the staff to investigate the cause of the activation. If staff do not reset the system within XXX minutes, a second smoke detector activates, or a manual call point is operated, or a heat detector activates, the system's audible and visual warning devices will be engaged.

Design, installation, commissioning, verification or handover certificates [were / were not] available to view. These certificates should [either be found, or new copies provided by the original installers of the fire alarm system and] be kept as they detail the system specification, system category and any agreed variations from the British Standard.

Due to the location of the existing automatic fire detectors, it would indicate that a category [L1/2/3/4/5/M], as described in British Standard 5839:1 2025, with automatic fire detection located [DESCRIPTION OF LOCATIONS WHERE AUTOMATIC FIRE DETECTION WAS OBSERVED], has been installed in the [building/areas under the control of the client]. This provision of automatic fire detection [is/isn't] acceptable for the occupancy of the building and the activities carried out in the premises.

Item Description	Action Required	L/R	Priority Rating	Freq	Photograph	Progress / Completion Notes
No action is required at present.						

Draft

9.7. Compartmentation

Existing Controls and Observations

This section should detail where you have observed fire compartmentation within the building, or area of the building, as well as its condition. It should cover maintenance requirements for fire doors to.

The template text for the description is this:

COMMERCIAL

Fire compartmentation seems to be provided in XXX. Furthermore, fire compartmentation appears to be present around areas of special fire risk, such as XXX. On the assessment date, no fire strategy documents or as-built drawings were available for review to confirm this. As required by relevant legislation, fire doors are located within the fire compartmentation lines.

OR

Fire compartmentation for compartment size or protection of escape routes is not required. No areas of special fire risk require enclosing in fire-resisting construction. At the time of assessment, no fire strategy documents or as-built drawings were available for review to confirm this. There is no requirement for internal fire doors.

RESIDENTIAL

Fire compartmentation seems to be provided in XXX. Furthermore, fire compartmentation appears to be present around areas of special fire risk, such as XXX. On the assessment date, no fire strategy documents or as-built drawings were available for review to confirm this. As required by relevant legislation, fire doors are located within the fire compartmentation lines.

Effective compartmentation is fundamental in ensuring adequate fire safety in blocks of flats. Therefore, it is vital that floors and walls are in good condition and that no openings allow the uncontrolled spread of fire and smoke. To support the evacuation policy, ongoing monitoring of compartmentation is recommended, and any breaches should be inspected by a third-party accredited contractor, with remedial works conducted as necessary.

Draft

Item Description	Action Required	L/R	Priority Rating	Freq	Photograph	Progress / Completion Notes
No action is required at present.						

Draft

9.8. Fire Extinguishers

Existing Controls and Observations

This section covers the provision and maintenance of fire extinguishers in the areas under the control of the client

The template text for the description is this:

Fire extinguishers are provided to the client's areas of the premises and responsibility for servicing and maintenance lies with the client.

Tenants must assess and make adequate provision for the risks in their areas.

**** OR FOR RESIDENTIAL*****

Fire Extinguishers are not provided in the common areas of the building. However, they are provided in plant areas for use by contractors and staff of the client.

Fire extinguishers should only be used by those trained in its use. It is not considered appropriate or practicable for residents in a block of flats to receive such training. In addition, if a fire occurs in a flat, the provision of fire extinguishing appliances in the common parts might encourage the occupants of the flat to enter the common parts to obtain an appliance and return to their flat to fight the fire. Such a procedure is inappropriate.

Item Description	Action Required	L/R	Priority Rating	Freq	Photograph	Progress / Completion Notes
No action is required at present.						

Draft

9.9. Hose Reels

Existing Controls and Observations

This section covers the provision and maintenance of fire hose reel in the areas under the control of the client. The description should cover the location and use of the hose reels.

If there are none on site then the 'Not Applicable' box should be ticked and template text will be provided to use if appropriate

Item Description	Action Required	L/R	Priority Rating	Freq	Photograph	Progress / Completion Notes
No action is required at present.						

Draft

9.10. Smoke Control Systems

Existing Controls and Observations

This section should cover the provision of all smoke control systems, Automatic Opening Vents, Positive Pressure Systems, Mechanical Smoke Extractions, Permanently Open Vents. It it should provide details of the systems, where equipment is located, and how it functions. It should also detail any maintenance requirements

If there are none on site then the 'Not Applicable' box should be ticked and template text will be provided to use if appropriate

Item Description	Action Required	L/R	Priority Rating	Freq	Photograph	Progress / Completion Notes
No action is required at present.						

Draft

9.11. Dry/Wet Riser

Existing Controls and Observations

This section covers any dry and/or wet rising and/or falling mains. It should detail the location of breaching inlets and outlets within the building as well as all maintenance.

If there are none on site then the 'Not Applicable' box should be ticked and template text will be provided to use if appropriate

Item Description	Action Required	L/R	Priority Rating	Freq	Photograph	Progress / Completion Notes
No action is required at present.						

Draft

9.12. Sprinkler System

Existing Controls and Observations

This section covers automatic water fire suppression systems, sprinklers. This include where sprinkler heads were obserevd, the type of pumps, if the system is wet/dry, how the system is fed (tank, towns main, or tank with towns mains), as well as all maintenance requirements.

If there are none on site then the 'Not Applicable' box should be ticked and template text will be provided to use if appropriate

Item Description	Action Required	L/R	Priority Rating	Freq	Photograph	Progress / Completion Notes
No action is required at present.						

Draft

9.13. Gaseous Suppression Systems

Existing Controls and Observations

This section should cover all other automatic fire suppression system, such as gaseous fire suppression system and wet chemical suppression systems. This should detail the areas protected by these systems, their methods of operations and safe working practices, as well as the type of suppression agent used. The location of storage cylinders or tanks should be detailed. All maintenance requirements should be detailed to.

If there are none on site then the 'Not Applicable' box should be ticked and template text will be provided to use if appropriate

Item Description	Action Required	L/R	Priority Rating	Freq	Photograph	Progress / Completion Notes
No action is required at present.						

Draft

9.14. Fire Hydrants

Existing Controls and Observations

This section should cover the location of private fire hydrants as well as the maintenance of them.

If there are none under the control of the client then the 'Not Applicable' box should be ticked and template text will be provided to use if appropriate

Item Description	Action Required	L/R	Priority Rating	Freq	Photograph	Progress / Completion Notes
No action is required at present.						

Draft

9.15. Emergency Procedures

Existing Controls and Observations

This section covers the evacuation procedures and plans in place for emergencies. This should state the evacuation procedure in place and where appropriate the assembly point.

In a residential building in England the provision of fire safety information required under the Fire Safety (England) Regulations must be covered, and where the building is within scope Residential PEEPs must be covered.

Item Description	Action Required	L/R	Priority Rating	Freq	Photograph	Progress / Completion Notes
No action is required at present.						

Draft

9.16. Means of Escape

Existing Controls and Observations

This section covers the means of escape in the building, and where you are assessing an area of a building it should comment on how the means of escape in the areas of assessment interacts with the other means of escape in the building.

This section should detail all horizontal and vertical means of escape. All staircases should be described, the type (protected/accommodation/external) and what floors they serve.

It should also describe the amount of final fire exits, and if they are on multiple floors what floors they are on.

The template text for the description is:

In the buildings current configuration, there are XXX protected staircases that serve the XXX floors. These stairs discharge to a [final fire exit / to a protected route from the foot of the stairway enclosure leading to a final exit / to two exits from the stairway, each giving access to a final exit via routes that are separated from each other by fire-resisting construction].

There are XXX accommodation staircases serving XXX floors within the building.

There are XXX external escape staircases from the building, serving XXX floors.

The internal protected escape routes generally contain no flammable materials or ignition sources. No items are stored or used in this area, and no heat sources other than basic electrical fittings exist.

The protected escape routes are to an acceptable standard, having the following:

- Automatic fire detection installed
- Emergency lighting installed
- Escape signage
- Break glass units installed

Draft

- Fire action notices at break glass units
- Escape routes are unobstructed

There are XXX final fire exits from the building. The number and arrangement of final fire exits [are/are not] suitable for the risks presented by the premises and the activities conducted there.

Item Description	Action Required	L/R	Priority Rating	Freq	Photograph	Progress / Completion Notes
No action is required at present.						

Draft

9.17. Emergency Lighting

Existing Controls and Observations

This section covers emergency lighting, it should describe where emergency lighting was observed and what type of units are fitted. all maintenance requirements should be detailed to

Self-contained and combined emergency lighting units are provided [DESCRIPTION OF LOCATIONS WHERE EMERGENCY LIGHTING WAS OBSERVED].

These are generally of the [maintained / non-maintained type].

On visual inspection, the provision [does/does not] appear to meet the requirements of BS5266-1. A lighting level test under emergency conditions was not conducted as part of the fire risk assessment process, so it could not be confirmed whether the luminaire locations would meet the minimum lighting level required by British Standard 5266. At the next system service, the emergency lighting engineer should verify that the lighting levels under emergency conditions meet the requirements of British Standard 5266.

Design, installation or commissioning certificates [were/were not] available to view.

Item Description	Action Required	L/R	Priority Rating	Freq	Photograph	Progress / Completion Notes
No action is required at present.						

Draft

9.18. Highly Flammable Liquids

Existing Controls and Observations

The storage arrangements for all flammable liquids should be detailed here, if present on site. If there are none on site then the 'Not Applicable' box should be ticked and template text will be provided to use if appropriate

Item Description	Action Required	L/R	Priority Rating	Freq	Photograph	Progress / Completion Notes
No action is required at present.						

Draft

9.19. Liquefied Petroleum Gas

Existing Controls and Observations

The storage arrangements for all compressed gas cylinders should be detailed here. they types of gas and what they are used for should be detailed to

If there are none on site then the 'Not Applicable' box should be ticked and template text will be provided to use if appropriate

Item Description	Action Required	L/R	Priority Rating	Freq	Photograph	Progress / Completion Notes
No action is required at present.						

Draft

9.20. General Fire Safety

Existing Controls and Observations

all other reasonably foreseeable fire safety matters should be detailed here.

Item Description	Action Required	L/R	Priority Rating	Freq	Photograph	Progress / Completion Notes
No action is required at present.						

Draft

9.21. Grainger PLC - Fire Safety Management

Existing Controls and Observations

This section is for Grainger PLC HRRB buildings only - please refer to the guidance for this to complete this section.

Grainger PLC has asked Ligtas to assess several items relating to their compliance with the Building Safety Act as part of the Fire Risk Assessment for their buildings. While these items fall outside the scope of the relevant fire safety legislation under which the fire risk assessment was conducted, they are included here at Grainger PLC's request.

Item Description	Action Required	L/R	Priority Rating	Freq	Photograph	Progress / Completion Notes
No action is required at present.						

Draft

10. Tenant(s) Monitoring

Tenant	Existing Control Measure / Remarks	Action Required	L/R	Photo Ref	Priority Rating	To be Completed by	Completed
dghggtfb	78 people are employed on site by the tenant. A Responsible Person has been nominated. A fire risk assessment has been carried out on 90/98/98776 and a copy made available.	Ensure regular fire safety training is carried out for all members of staff. Ensure the staff with specific responsibilities for fire safety management receive additional training commensurate with their role, i.e. Fire Wardens.	L		Medium		
		Ensure fire wardens are nominated and receive formal training to allow them to undertake their roles and responsibilities during incidents.	L		Medium		

Draft

Tenant	Existing Control Measure / Remarks	Action Required	L/R	Photo Ref	Priority Rating	To be Completed by	Completed
fsdhjfhs	[XXXX] people are employed on site by the tenant. Fire detection is provided to the demised area.	Ensure that a fire risk assessment is carried out and record significant findings. Where 5 or more staff are employed, a copy of the risk assessment must be retained on site for inspection by the enforcing authorities.	L		Medium		

Draft

Tenant	Existing Control Measure / Remarks	Action Required	L/R	Photo Ref	Priority Rating	To be Completed by	Completed
Ground floor shop unit	[XXXX] people are employed on site by the tenant. A Responsible Person has been nominated. A fire risk assessment has been carried out on XX/XX/XXXX and a copy made available. Regular fire safety training for staff has been carried out. Fire detection is provided to the demised area. All fire extinguishers are wall mounted or otherwise secured. Means of escape are maintained free from obstruction.	Ensure that the electrical installation has been thoroughly tested and examined by a competent person and that a suitable record is held on site. Ensure that the work identified during the thorough examination is completed. Thorough examinations and tests should be done at least once in every five year period, or as recommended by a NICEIC contractor and any necessary maintenance work carried out.	L		Medium		
		Provide fire action notices in the prescribed form and ensure that required information is completed.	L		Medium		
		Ensure that the emergency lighting units receive a monthly flick test and an annual duration test in accordance with BS 5266 and that records are retained on site.	L		Medium		

Draft

Ligtas
Safety Beyond Compliance

At Ligtas, we empower organisations with expert Fire Safety, Health & Safety, Legionella Risk Management and training solutions, ensuring compliance, reducing risk, and protecting people. Our consultancy and training services are tailored to your organisation's needs, providing actionable insights and practical solutions.

Our Services

- Fire Safety
- Health & Safety Compliance
- Legionella Risk Management
- Training

www.ligtas.co.uk
02922 800000
enquiries@ligtas.co.uk