

# CS372 Operating System

## Lab 3

### Part I Producer and consumer (multithread)

- Implement the code from Figures 4.13, 4.14, 4.15

```
import java.util.Date;

public class Factory
{
    public static void main(String args[]) {
        // create the message queue
        Channel<Date> queue = new MessageQueue<Date>();

        // Create the producer and consumer threads and pass
        // each thread a reference to the MessageQueue object.
        Thread producer = new Thread(new Producer(queue));
        Thread consumer = new Thread(new Consumer(queue));

        // start the threads
        producer.start();
        consumer.start();
    }
}
```

**Figure 4.13** The Factory class.

```

import java.util.Date;

class Producer implements Runnable
{
    private Channel<Date> queue;

    public Producer(Channel<Date> queue) {
        this.queue = queue;
    }

    public void run() {
        Date message;

        while (true) {
            // nap for awhile
            SleepUtilities.nap();

            // produce an item and enter it into the buffer
            message = new Date();
            System.out.println("Producer produced " + message);
            queue.send(message);
        }
    }
}

```

**Figure 4.14** Producer thread.

```

import java.util.Date;

class Consumer implements Runnable
{
    private Channel<Date> queue;

    public Consumer(Channel<Date> queue) {
        this.queue = queue;
    }

    public void run() {
        Date message;

        while (true) {
            // nap for awhile
            SleepUtilities.nap();

            // consume an item from the buffer
            message = queue.receive();

            if (message != null)
                System.out.println("Consumer consumed " + message);
        }
    }
}

```

**Figure 4.15** Consumer thread.

## Part II Producer and consumer (semaphore)

- Implement the code from Figures 6.9 – 6.14

```

public class BoundedBuffer<E> implements Buffer<E>
{
    private static final int BUFFER_SIZE = 5;
    private E[] buffer;
    private int in, out;
    private Semaphore mutex;
    private Semaphore empty;
    private Semaphore full;

    public BoundedBuffer() {
        // buffer is initially empty
        in = 0;
        out = 0;
        mutex = new Semaphore(1);
        empty = new Semaphore(BUFFER_SIZE);
        full = new Semaphore(0);

        buffer = (E[]) new Object[BUFFER_SIZE];
    }

    public void insert(E item) {
        // Figure 6.10
    }

    public E remove() {
        // Figure 6.11
    }
}

```

**Figure 6.9** Solution to the bounded-buffer problem using semaphores.

```
// Producers call this method
public void insert(E item) {
    empty.acquire();
    mutex.acquire();

    // add an item to the buffer
    buffer[in] = item;
    in = (in + 1) % BUFFER_SIZE;

    mutex.release();
    full.release();
}
```

**Figure 6.10** The insert() method.

```
// Consumers call this method
public E remove() {
    E item;

    full.acquire();
    mutex.acquire();

    // remove an item from the buffer
    item = buffer[out];
    out = (out + 1) % BUFFER_SIZE;

    mutex.release();
    empty.release();

    return item;
}
```

**Figure 6.11** The remove() method.

```
import java.util.Date;

public class Producer implements Runnable
{
    private Buffer<Date> buffer;

    public Producer(Buffer<Date> buffer) {
        this.buffer = buffer;
    }

    public void run() {
        Date message;

        while (true) {
            // nap for awhile
            SleepUtilities.nap();

            // produce an item & enter it into the buffer
            message = new Date();
            buffer.insert(message);
        }
    }
}
```

---

**Figure 6.12** The producer.

```

import java.util.Date;

public class Consumer implements Runnable
{
    private Buffer<Date> buffer;

    public Consumer(Buffer<Date> buffer) {
        this.buffer = buffer;
    }

    public void run() {
        Date message;

        while (true) {
            // nap for awhile
            SleepUtilities.nap();

            // consume an item from the buffer
            message = (Date)buffer.remove();
        }
    }
}

```

**Figure 6.13** The consumer.

```

import java.util.Date;

public class Factory
{
    public static void main(String args[]) {
        Buffer<Date> buffer = new BoundedBuffer<Date>();

        // Create the producer and consumer threads
        Thread producer = new Thread(new Producer(buffer));
        Thread consumer = new Thread(new Consumer(buffer));

        producer.start();
        consumer.start();
    }
}

```

**Figure 6.14** The Factory class.



## **Part III GUI –Revise Part II**

- Add two attributes to the Bounded Buffer Class, producerSleep and consumerSleep, to set the sleep time of producer and consumer.
- Create with get() and set() methods for each.
- Build a GUI that monitors the number of items in the Bounded Buffer and allows the user to change the sleep times for each of the producer and consumer.

## **Part V Turn in your lab**

Zip (1) the source code of Part I, Part II, and Part III and (2) a screen dump of the running of Part I, Part II, and Part III. Turn in the zipped file to Moodle before the deadline.