


Data Analysis and Integration

OLAP operations

Data warehousing


- Star schema



Data warehousing

- Sales by customer country


```
select country, sum(linetotal) as sales  
from fact_order natural join dim_customer  
group by country;
```



Data warehousing

- Sales by product line and year


```
select productline, year, sum(linetotal) as sales  
from fact_order natural join dim_product natural join dim_time  
group by productline, year;
```



Data warehousing

- Sales by customer country, product line and year

```
select country, productline, year, sum(linetotal) as sales
from fact_order natural join dim_customer natural join dim_product
      natural join dim_time
group by country, productline, year;
```



Dimension levels

- Each **dimension** can have different **levels**
 - customer (city; country)
 - product (productline; productvendor)
 - time (year; quarter; month)

Drill-down

- Going from a higher to a lower level is called **drill-down**
 - e.g. sales by customer country → sales by customer city

```
select country, sum(linetotal) as sales  
from fact_order natural join dim_customer  
group by country;
```



```
select city, sum(linetotal) as sales  
from fact_order natural join dim_customer  
group by city;
```



Drill-down

- Going from a higher to a lower level is called **drill-down**
 - e.g. sales by customer country → sales by customer city

```
select country, sum(linetotal) as sales  
from fact_order natural join dim_customer  
group by country;
```



```
select country, city, sum(linetotal) as sales  
from fact_order natural join dim_customer  
group by country, city;
```



Drill-down

- Going from a higher to a lower level is called **drill-down**
 - e.g. sales by customer country → sales by customer city

country	sales
Australia	630638
Austria	202089
Belgium	108485
Canada	224085
Denmark	245582
Finland	329472
France	1111022
Germany	220354
Hong Kong	48766
Ireland	57788
Italy	403696
Japan	188212
...	...

21 rows in set (0.02 sec)

country	city	sales
Australia	Chatswood	151631
Australia	Glen Waverly	64621
Australia	Melbourne	200845
Australia	North Sydney	154070
Australia	South Brisbane	59471
Austria	Graz	52218
Austria	Salzburg	149871
Belgium	Bruxelles	75037
Belgium	Charleroi	33448
Canada	Montréal	74224
Canada	Tsawassen	74665
Canada	Vancouver	75196
...

81 rows in set (0.03 sec)

Drill-down

- Another example of **drill-down**
 - e.g. sales by year → sales by month

```
select year, sum(linetotal) as sales  
from fact_order natural join dim_time  
group by year;
```



```
select year, month, sum(linetotal) as sales  
from fact_order natural join dim_time  
group by year, month;
```

Drill-down

- Another example of **drill-down**
 - e.g. sales by year → sales by month

year	sales
2003	4312435
2004	4987780
2005	1980850

3 rows in set (0.02 sec)

year	month	sales
2003	1	764883
2003	2	140920
2003	3	174467
2003	4	201557
2003	5	192785
2003	6	170533
2003	7	225638
2003	8	197822
2003	9	263836
2003	10	589773
2003	11	1086757
2003	12	303464
2004	1	316662
2004	2	318663
...

29 rows in set (0.01 sec)

Roll-up

- Going from a lower to a higher level is called **roll-up**
 - e.g. sales by customer city → sales by customer country

```
select country, city, sum(linetotal) as sales  
from fact_order natural join dim_customer  
group by country, city;
```



```
select country, sum(linetotal) as sales  
from fact_order natural join dim_customer  
group by country;
```

Roll-up

- Going from a lower to a higher level is called **roll-up**
 - e.g. sales by customer city → sales by customer country

country	city	sales
Australia	Chatswood	151631
Australia	Glen Waverly	64621
Australia	Melbourne	200845
Australia	North Sydney	154070
Australia	South Brisbane	59471
Austria	Graz	52218
Austria	Salzburg	149871
Belgium	Bruxelles	75037
Belgium	Charleroi	33448
Canada	Montréal	74224
Canada	Tsawassen	74665
Canada	Vancouver	75196
...

81 rows in set (0.03 sec)

country	sales
Australia	630638
Austria	202089
Belgium	108485
Canada	224085
Denmark	245582
Finland	329472
France	1111022
Germany	220354
Hong Kong	48766
Ireland	57788
Italy	403696
Japan	188212
...	...

21 rows in set (0.02 sec)

Roll-up

- Another example of **roll-up**
 - e.g. sales by month → sales by year

```
select year, month, sum(linetotal) as sales  
from fact_order natural join dim_time  
group by year, month;
```



```
select year, sum(linetotal) as sales  
from fact_order natural join dim_time  
group by year;
```

Roll-up


- Another example of **roll-up**
 - e.g. sales by month → sales by year

year	month	sales
2003	1	764883
2003	2	140920
2003	3	174467
2003	4	201557
2003	5	192785
2003	6	170533
2003	7	225638
2003	8	197822
2003	9	263836
2003	10	589773
2003	11	1086757
2003	12	303464
2004	1	316662
2004	2	318663
...

29 rows in set (0.01 sec)

year	sales
2003	4312435
2004	4987780
2005	1980850

3 rows in set (0.02 sec)



Slice

- Selecting a particular value of dimension level is a **slice**
 - e.g. sales by product line in 2003

```
select productline, year, sum(linetotal) as sales  
from fact_order natural join dim_product natural join dim_time  
group by productline, year;
```



```
select productline, year, sum(linetotal) as sales  
from fact_order natural join dim_product natural join dim_time  
group by productline, year  
having year = 2003;
```



Slice

- Selecting a particular value of dimension level is a **slice**
 - e.g. sales by product line in 2003

```
select productline, year, sum(linetotal) as sales  
from fact_order natural join dim_product natural join dim_time  
group by productline, year;
```



```
select productline, year, sum(linetotal) as sales  
from fact_order natural join dim_product natural join dim_time  
where year = 2003  
group by productline, year;
```



Slice

- Selecting a particular value of dimension level is a **slice**
 - e.g. sales by product line in 2003

productline	year	sales
Classic Cars	2003	1513998
Classic Cars	2004	1837904
Classic Cars	2005	738587
Motorcycles	2003	397392
Motorcycles	2004	590632
Motorcycles	2005	286327
Planes	2003	347924
Planes	2004	529129
Planes	2005	200077
Ships	2003	244652
Ships	2004	375498
Ships	2005	128219
Trains	2003	72857
Trains	2004	124885
Trains	2005	36920
...

21 rows in set (0.04 sec)



productline	year	sales
Classic Cars	2003	1513998
Motorcycles	2003	397392
Planes	2003	347924
Ships	2003	244652
Trains	2003	72857
Trucks and Buses	2003	420523
Vintage Cars	2003	1315089

7 rows in set (0.01 sec)

Dice

- Applying multiple slicing conditions is called a **dice**
 - e.g. sales of Motorcycles in 2003 and 2004

```
select productline, year, sum(linetotal) as sales  
from fact_order natural join dim_product natural join dim_time  
group by productline, year;
```



```
select productline, year, sum(linetotal) as sales  
from fact_order natural join dim_product natural join dim_time  
where productline = 'Motorcycles' and year in (2003, 2004)  
group by productline, year;
```

Dice

- Applying multiple slicing conditions is called a **dice**
 - e.g. sales of Motorcycles in 2003 and 2004

productline	year	sales
Classic Cars	2003	1513998
Classic Cars	2004	1837904
Classic Cars	2005	738587
Motorcycles	2003	397392
Motorcycles	2004	590632
Motorcycles	2005	286327
Planes	2003	347924
Planes	2004	529129
Planes	2005	200077
Ships	2003	244652
Ships	2004	375498
Ships	2005	128219
Trains	2003	72857
Trains	2004	124885
Trains	2005	36920
...

21 rows in set (0.04 sec)



productline	year	sales
Motorcycles	2003	397392
Motorcycles	2004	590632

2 rows in set (0.01 sec)

Pivot

- Changing the order of dimensions is called **pivot**
 - e.g. sales by product line, year → sales by year, product line

```
select productline, year, sum(linetotal) as sales  
from fact_order natural join dim_product natural join dim_time  
group by productline, year;
```



```
select year, productline, sum(linetotal) as sales  
from fact_order natural join dim_product natural join dim_time  
group by year, productline;
```

Pivot

- Changing the order of dimensions is called **pivot**
 - e.g. sales by product line, year → sales by year, product line

productline	year	sales
Classic Cars	2003	1513998
Classic Cars	2004	1837904
Classic Cars	2005	738587
Motorcycles	2003	397392
Motorcycles	2004	590632
Motorcycles	2005	286327
Planes	2003	347924
Planes	2004	529129
Planes	2005	200077
Ships	2003	244652
Ships	2004	375498
Ships	2005	128219
Trains	2003	72857
Trains	2004	124885
Trains	2005	36920
...

21 rows in set (0.04 sec)



year	productline	sales
2003	Classic Cars	1513998
2003	Motorcycles	397392
2003	Planes	347924
2003	Ships	244652
2003	Trains	72857
2003	Trucks and Buses	420523
2003	Vintage Cars	1315089
2004	Classic Cars	1837904
2004	Motorcycles	590632
2004	Planes	529129
2004	Ships	375498
2004	Trains	124885
2004	Trucks and Buses	532024
2004	Vintage Cars	997708
2005	Classic Cars	738587
...


21 rows in set (0.04 sec)

OLAP operations

- Typical analytical operations
 - **drill-down** and **roll-up** between levels
 - **slice** and **dice** to select particular values
 - **pivot** to rotate dimensions
 - etc.


Multidimensional model

- Data can be viewed as a **cube**



Hierarchies

- Each **dimension** has multiple **levels (hierarchy)**



OLAP operations

- Drill-down to month

Time (Quarter)	Customer (City)				Product (Category)			
	Köln	Berlin	Lyon	Paris	Produce	Seafood	Beverages	Condiments
Q1	21	10	18	35	35	33	25	14
Q2	27	14	11	30	30	14	23	17
Q3	26	12	35	32	32	12	20	18
Q4	14	20	47	31	31	10	33	18

Time (Month)	Customer (City)				Product (Category)			
	Köln	Berlin	Lyon	Paris	Produce	Seafood	Beverages	Condiments
Jan	7	2	6	20	20	10	10	3
Feb	8	4	8	8	8	9	7	...
Mar	6	4	4	7	7	8
...
Dec	4	4	16	7	7	5	14	8

OLAP operations

- **Roll-up** to country

Time (Quarter)	Customer (City)				Product (Category)			
	Köln	Berlin	Lyon	Paris	Produce	Seafood	Beverages	Condiments
Q1	21	10	18	35	35	33	25	14
Q2	27	14	11	30	30	23	20	17
Q3	26	12	35	32	32	12	33	18
Q4	14	20	47	31	31	10	33	18

Time (Quarter)	Customer (Country)		Product (Category)			
	Germany	France	Produce	Seafood	Beverages	Condiments
Q1	33	30	42	68	68	39
Q2	39	26	41	44	44	37
Q3	30	22	46	44	44	51
Q4	25	29	49	41	41	51

OLAP operations

- **Slice** on city (Paris)

Customer (City)

Time (Quarter)

	Köln	24	18	28	14
	Berlin	33	25	23	25
	Lyon	12	20	24	33
	Paris	21	10	18	35
Q1		21	10	18	35
Q2		27	14	11	30
Q3		26	12	35	32
Q4		14	20	47	31
			Produce	Seafood	
			Beverages	Condiments	
			Product (Category)		

Time (Quarter)

Q1	21	10	18	35
Q2	27	14	11	30
Q3	26	12	35	32
Q4	14	20	47	31
		Produce	Seafood	
		Beverages	Condiments	
		Product (Category)		

OLAP operations

- **Dice** on city {Paris, Lyon} and quarter {Q1, Q2}

		Customer (City)							
		Köln	Berlin	Lyon	Paris				
Time (Quarter)	Q1	21	10	18	35	35	33	25	14
	Q2	27	14	11	30	30	14	20	17
	Q3	26	12	35	32	32	12	33	18
	Q4	14	20	47	31	31	10	33	18
		Produce		Seafood		Beverages		Condiments	

Product (Category)

		Customer (City)							
		Lyon	Paris	Q1	Q2				
Time (Quarter)	Q1	21	10	18	35	35	14	20	17
	Q2	27	14	11	30	30	12	33	18
		Produce		Seafood		Beverages		Condiments	

Product (Category)

OLAP operations

- **Pivot** (rotate) dimensions

Customer (City)

Time (Quarter)

Product (Category)

	Produce	Seafood	Beverages	Condiments
Köln	24	18	28	14
Berlin	33	25	23	25
Lyon	12	20	24	33
Paris	21	10	18	35
Q1	21	10	18	35
Q2	27	14	11	30
Q3	26	12	35	32
Q4	14	20	47	31

Product (Category)

Customer (City)

Time (Quarter)

	Q1	Q2	Q3	Q4
Seafood	35	30	32	31
Condiments	18	11	35	47
Produce	10	14	12	20
Beverages	21	27	26	14
Paris	21	27	26	14
Lyon	12	14	11	13
Berlin	33	28	35	32
Köln	24	23	25	18

Other OLAP operations

- Sort by product category

Time (Quarter)	Customer (City)	Product (Category)			
		Produce	Seafood	Beverages	Condiments
	Köln	24	18	28	14
	Berlin	33	25	23	25
Time (Quarter)	Lyon	12	20	24	33
	Paris	21	10	18	35
	Q1	21	10	18	35
	Q2	27	14	11	30
Time (Quarter)	Q3	26	12	35	32
	Q4	14	20	47	31

Time (Quarter)	Customer (City)	Product (Category)			
		Condiments	Seafood	Beverages	Produce
	Köln	24	28	18	14
	Berlin	33	23	25	25
Time (Quarter)	Lyon	12	24	20	33
	Paris	21	18	10	35
	Q1	21	18	10	35
	Q2	27	11	14	30
Time (Quarter)	Q3	26	35	12	32
	Q4	14	47	20	31

Other OLAP operations

- Cube for 2012 vs. cube for 2011 (previous year)

3D cube visualization for 2012 data. The dimensions are Customer (City), Time (Quarter), and Product (Category). The data is as follows:

Time (Quarter)	Customer (City)	Product (Category)			
		Beverages	Condiments	Produce	Seafood
Q1	Köln	21	10	18	35
	Berlin	27	14	11	30
	Lyon	26	12	35	32
	Paris	14	20	47	31
Q2	Köln	33	25	23	25
	Berlin	12	20	24	33
	Lyon	21	10	18	35
	Paris	27	14	11	30
Q3	Köln	24	18	28	14
	Berlin	33	25	23	25
	Lyon	12	20	24	33
	Paris	21	10	18	35
Q4	Köln	20	22	24	16
	Berlin	30	22	21	26
	Lyon	14	18	22	28
	Paris	19	12	31	28

3D cube visualization for 2011 data. The dimensions are Customer (City), Time (Quarter), and Product (Category). The data is as follows:

Time (Quarter)	Customer (City)	Product (Category)			
		Beverages	Condiments	Produce	Seafood
Q1	Köln	19	12	31	28
	Berlin	30	12	10	29
	Lyon	28	11	31	28
	Paris	12	22	45	29
Q2	Köln	20	22	24	16
	Berlin	30	22	21	26
	Lyon	14	18	22	28
	Paris	19	12	31	28
Q3	Köln	24	18	28	14
	Berlin	33	25	23	25
	Lyon	12	20	24	33
	Paris	21	10	18	35
Q4	Köln	21	10	18	35
	Berlin	27	14	11	30
	Lyon	26	12	35	32
	Paris	14	20	47	31

Other OLAP operations

- Drill-across 2011 and 2012

Time (Quarter)	Customer (City)	2011				2012			
		Produce		Seafood		Beverages		Condiments	
		Q1	Q2	Q3	Q4	Q1	Q2	Q3	Q4
		Köln	Berlin	Lyon	Paris	Köln	Berlin	Lyon	Paris
		19	12	31	28	28	16	21	18

Time (Quarter)	Customer (City)	2011				2012			
		Produce		Seafood		Beverages		Condiments	
		Q1	Q2	Q3	Q4	Q1	Q2	Q3	Q4
		Köln	Berlin	Lyon	Paris	Köln	Berlin	Lyon	Paris
		21	10	18	35	35	14	23	17

Time (Quarter)	Customer (City)	2011				2012			
		Produce		Seafood		Beverages		Condiments	
		Q1	Q2	Q3	Q4	Q1	Q2	Q3	Q4
		Köln	Berlin	Lyon	Paris	Köln	Berlin	Lyon	Paris
		19	12	31	28	28	16	21	18

Other OLAP operations

- Percentage change between 2011 and 2012

Time (Quarter)	Customer (City)	2011				2012			
		Produce		Seafood		Beverages		Condiments	
		Q1	Q2	Q3	Q4	Q1	Q2	Q3	Q4
		Köln	Berlin	Lyon	Paris	Köln	Berlin	Lyon	Paris
		19	12	31	28	28	16	21	19

Time (Quarter)	Customer (City)	2011				2012			
		Produce		Seafood		Beverages		Condiments	
		Q1	Q2	Q3	Q4	Q1	Q2	Q3	Q4
		Köln	Berlin	Lyon	Paris	Köln	Berlin	Lyon	Paris
		21	10	18	35	35	14	11	30

Time (Quarter)	Customer (City)	2011				2012			
		Produce		Seafood		Beverages		Condiments	
		Q1	Q2	Q3	Q4	Q1	Q2	Q3	Q4
		Köln	Berlin	Lyon	Paris	Köln	Berlin	Lyon	Paris
		11	-17	-42	25	25	18	10	0

Data warehousing

- What is a data warehouse?
 - a data warehouse is a relational database that stores historical data in a convenient schema for multidimensional analysis using OLAP operations


Data warehousing

- A data warehouse stores **facts**

**customer 128 bought 26 units of product 33
on date 2003-01-09 for a price of 3770.00**

Data warehousing

- Facts have associated **measures**



Data warehousing

- **Facts** define the possible analysis dimensions
 - customer c bought product p (2D)
 - customer c bought product p on date d (3D)
 - customer c bought product p on date d in store s (4D)
 - customer c bought product p on date d in store s using payment method m (5D)
 - m may be 'cash', 'credit card', etc.
 - customer c bought product p on date d in store s using payment method m through sales representative e (6D)
 - e is an employee number
 - etc.

Data warehousing

- **Measures** define the quantity being analyzed
 - sales
 - quantity sold
 - sales amount
 - production
 - quantity produced
 - production cost
 - logistics
 - distance traveled
 - transported weight
 - etc.

Data warehousing

- **Facts** can be **grouped** by dimensions
 - examples
 - by customer (1D)
 - by product (1D)
 - by time (1D)
 - by customer and product (2D)
 - by customer and time (2D)
 - by product and time (2D)
 - by customer, product and time (3D)

Data warehousing

- As **facts** are **grouped**, their **measures** are **aggregated**
 - examples
 - sales amount by customer (1D)
 - sales amount by product (1D)
 - sales amount by time (1D)
 - sales amount by customer and product (2D)
 - sales amount by customer and time (2D)
 - sales amount by product and time (2D)
 - sales amount by customer, product and time (3D)

Data warehousing

- **Measures** are **aggregated** at a certain **level** of detail
 - examples
 - sales amount by customer country
 - sales amount by customer city
 - sales amount by customer country and product line
 - sales amount by customer city and product vendor
 - sales amount by customer country, product line and year
 - sales amount by customer city, product vendor and month

Data warehousing

- **Levels** are organized into **hierarchies**
 - examples
 - country, state, city
 - year, month, day
- A **dimension** can have one or more **hierarchies**
 - example: time dimension
 - year, month, day (for calendar year, from Jan to Dec)
 - year, semester, period (for school year, from Sep to Aug)