

Quarkus and Observability

Observability is the ability to watch the state of a system/application based on some external outputs.

These are the four important concepts to have observability correctly implemented:

- Monitoring/Metrics (Prometheus)
- Visualization (Grafana)
- Distributed tracing (Jaeger)
- Log aggregation (Sentry, GELF)

This cheat sheet covers the integrations you can find in the form of extensions for Quarkus to implement observability.

CREATING THE PROJECT

```
mvn "io.quarkus:quarkus-maven-plugin:1.4.2.Final:create" \
  -DprojectId="org.acme" \
  -DprojectArtifactId="greeting" \
  -DprojectVersion="1.0-SNAPSHOT" \
  -DclassName="org.acme.GreetingResource" \
  -Dpath="/hello"
```

Tip You can generate the project in <https://code.quarkus.io/>

CREATING THE PROJECT

Quarkus can utilize the MicroProfile Metrics spec to provide metrics support.

```
./mvnw quarkus:add-extension -
  Dextensions="io.quarkus:quarkus-smallrye-metrics"
```

The metrics can be provided in JSON or OpenMetrics format.

When the extension is present in the classpath, an endpoint is added automatically to /metrics providing default metrics. To add custom metrics, MicroProfile Metrics spec provides the next annotations:

@Timed / Tracks the duration of a call.

@SimplyTimed / Tracks the duration of a call without mean and distribution calculations.

@Metered / Tracks the frequency of invocations.

@Counted / Counts number of invocations.

@Gauge / Samples the value of the annotated object.

@ConcurrentGauge / Gauge to count parallel invocations.

@Metric / Used to inject a metric. Valid types are **Meter**, **Timer**, **Counter**, **Histogram**. **Gauge** type can only be produced in methods or fields.

```
@GET
//...
@Timed(name = "checksTimer",
unit = MetricUnits.MILLISECONDS)
public String hello() {}

@Counted(name = "countWelcome")
public String hello() {}
```

@Gauge annotation returning a measure as a gauge.

```
@Gauge(name = "hottestSauce", unit = MetricUnits.NONE)
public Long hottestSauce() {}
```

Injecting a histogram using **@Metric**.

```
@Metric(name = "histogram")
Histogram histogram;
```

Metrics can be configured in **application.properties** with the next properties:

quarkus.smallrye-metrics.path
The path to the metrics handler, defaults to /metrics.

quarkus.smallrye-metrics.extensions.enabled
If metrics are enabled or not, defaults to true.

quarkus.smallrye-metrics.micrometer.compatibility
Applies Micrometer compatibility mode, defaults to false.

You can apply metric annotations via CDI stereotypes:

```
@Stereotype
@Retention(RetentionPolicy.RUNTIME)
@Target({ ElementType.TYPE, ElementType.METHOD,
  ElementType.FIELD })
@Timed(name = "checksTimer", unit =
  MetricUnits.MILLISECONDS)
public @interface TimedMilliseconds {
}
```

Metrics in Quarkus also integrates with other extensions:

```
quarkus.smallrye-metrics.path
    If enabled Hibernate metrics are exposed under vendor scope.
```

```
quarkus.mongodb.metrics.enabled
    If enabled MongoDB metrics are exposed under vendor scope.
```

DISTRIBUTED TRACING

Quarkus can utilize the [MicroProfile OpenTracing](#) spec to provide tracing support.

```
./mvnw quarkus:add-extension -
Dextensions="io.quarkus:quarkus-smallrye-opentracing"
```

All the requests sent to any endpoint are traced automatically.

This extension includes OpenTracing and Jaeger tracer support.

Jaeger tracer has multiple configuration properties, but a typical example is:

```
application.properties
quarkus.jaeger.service-name=my-service
quarkus.jaeger.sampler-type=const
quarkus.jaeger.sampler-param=1
quarkus.jaeger.endpoint=http://localhost:14268/api/traces
```

`@Traced(false)` annotation can be used to disable tracing at class or method level.

`io.opentracing.Tracer` interface can be injected into a class to manipulate the information that is traced.

```
@Inject
Tracer tracer;

tracer.activeSpan().setBaggageItem("key", "value");
```

You can disable the Jaeger extension by using `quarkus.jaeger.enabled` property.

You can log the `traceId`, `spanId` and sampled tracing information in the Quarkus logging system by configuring the log format:

```
quarkus.log.console.format=%d{HH:mm:ss} %-5p
traceId=%X{traceId}, spanId=%X{spanId},
sampled=%X{sampled} [%c{2.}] (%t) %s%e%n
```

Tracing in Quarkus also integrates with other extensions:

JDBC Tracer

Adds a span for each JDBC queries.

```
<dependency>
  <groupId>io.opentracing.contrib</groupId>
  <artifactId>opentracing-jdbc</artifactId>
</dependency>
```

Configure JDBC driver apart from tracing properties seen before:

```
# add ':tracing' to your database URL
quarkus.datasource.url
=jdbc:tracing:postgresql://localhost:5432/mydatabase
quarkus.datasource.driver
=io.opentracing.contrib.jdbc.TracingDriver
quarkus.hibernate-orm.dialect
=org.hibernate.dialect.PostgreSQLDialect
```

AWS XRay

If you are building native images, and want to use AWS X-Ray Tracing with your lambda you will need to include `quarkus-amazon-lambda-xray` as a dependency in your pom.

LOG AGGREGATION

Sentry

Quarkus integrates with [Sentry](#) for logging errors into an error monitoring system.

```
./mvnw quarkus:add-extension -Dextensions="quarkus-
logging-sentry"
```

As an example if you want to send all errors occurring in the package `org.example` to Sentry with DSN <https://abcd@sentry.io/1234>, you should configure it in the following way:

```
application.properties
quarkus.log.sentry=true
quarkus.log.sentry.dsn=https://abcd@sentry.io/1234
quarkus.log.sentry.level=ERROR
quarkus.log.sentry.in-app-packages=org.example
```

Full list of configuration properties for Sentry are:

`quarkus.log.sentry.enable` / Enables the Sentry logging extension, defaults to false.

`quarkus.log.sentry.dsn` / The DSN where events are sent.

`quarkus.log.sentry.level` / The log level, defaults to WARN.

`quarkus.log.sentry.in-app-packages` / Configures application package prefixes.

`quarkus.log.sentry.environment` / Sets the environment value.

`quarkus.log.sentry.release` / Sets the release value.

GELF format

You can configure the output logging to be in GELF format instead of plain text.

```
./mvnw quarkus:add-extension -Dextensions="quarkus-
logging-gelf"
```

`quarkus.log.handler.gelf.enabled` / Enables GELF logging handler, defaults to false.

`quarkus.log.handler.gelf.host` / The Hostname/IP of Logstash/Graylog. Prepend tcp: for using TCP protocol, defaults to udp:localhost.

`quarkus.log.handler.gelf.port` / The port, defaults to 12201.

`quarkus.log.handler.gelf.version` / The GELF version, defaults to 1.1.

`quarkus.log.handler.gelf.extract-stack-trace` / Posts Stack-Trace to StackTrace field, defaults to true.

`quarkus.log.handler.gelf.stack-trace-throwable-reference` / Gets the cause level to stack trace. 0 is full stack trace, defaults to 0.

`quarkus.log.handler.gelf.filter-stack-trace` / Sets the stack-Trace filtering, defaults to false.

`quarkus.log.handler.gelf.timestamp-pattern` / Sets the timestamp format in Java Date pattern, defaults to yyyy-MM-dd HH:mm:ss,SSS.

`quarkus.log.handler.gelf.level` / Sets the log level using java.util.logging.Level class, defaults to ALL.

`quarkus.log.handler.gelf.facility` / The name of the facility, defaults to jboss-logmanager.

`quarkus.log.handler.gelf.extract-stack-trace` / Posts Stack-Trace to StackTrace field, defaults to true.

`quarkus.log.handler.gelf.additional-field.<field>.<subfield>` / Posts additional fields (ie `quarkus.log.handler.gelf.additional-field.field1.type=String`)

Author Alex Soto
Java Champion, Working at Red Hat