

Docs RPC

1. Definire structs in caso di multipli parametri

```
struct numbers {  
    int a;  
    int b;  
}
```

2. Definire operazioni

```
program ADD_PROG{  
    version ADD_VERS{  
        int add(numbers)=1;  
    }  
}
```

3. Eseguire `rpcgen`

```
rpcgen -a -C add.x
```

4. Scrivere implementazioni di client e server

```
/*  
 * This is sample code generated by rpcgen.  
 * These are only templates and you can use them  
 * as a guideline for developing your own functions.  
 */  
  
#include "calc.h"  
  
int *  
add_1_svc(Operands *argp, struct svc_req *rqstp)  
{  
    static int result;  
  
    /*
```

```

        * insert server code here
        */

    return &result;
}

int *
sub_1_svc(Operands *argp, struct svc_req *rqstp)
{
    static int    result;

    /*
     * insert server code here
     */

    return &result;
}

```

```

/*
 * This is sample code generated by rpcgen.
 * These are only templates and you can use them
 * as a guideline for developing your own functions.
 */

#include "calc.h"

void
calc_prog_1(char *host)
{
    CLIENT *clnt;
    int    *result_1;
    Operands  add_1_arg;
    int    *result_2;
    Operands  sub_1_arg;

#ifdef DEBUG
    clnt = clnt_create (host, CALC_PROG, CALC_VERS, "udp")

```

```

        if (clnt == NULL) {
            clnt_pcreateerror (host);
            exit (1);
        }
    #endif /* DEBUG */

    result_1 = add_1(&add_1_arg, clnt);
    if (result_1 == (int *) NULL) {
        clnt_perror (clnt, "call failed");
    }
    result_2 = sub_1(&sub_1_arg, clnt);
    if (result_2 == (int *) NULL) {
        clnt_perror (clnt, "call failed");
    }
    #ifndef DEBUG
        clnt_destroy (clnt);
    #endif /* DEBUG */
}

int
main (int argc, char *argv[])
{
    char *host;

    if (argc < 2) {
        printf ("usage: %s server_host\n", argv[0]);
        exit (1);
    }
    host = argv[1];
    calc_prog_1 (host);
    exit (0);
}

```

5. D'ora in poi si può compilare

```
make -f Makefile.add
```

6. Avvia il server

```
sudo ./add_server
```

7. Avvia il client

```
sudo ./add_client localhost
```