

Access Identifiers-

Private – Only accessible within the same class.

Public – Accessible from anywhere in the program.

Protected – Accessible within the same class and its subclasses (inherited classes).

Why I pass data through the service instead of component to component-

Okay so when I was first writing this, I was working in a component and within that component I was calling another components object to pass data into. I got an error saying there is a dependency issue. You can't reference other components instances if you're working within a component. That's why I go through the service, because I can pass the data through there then access it in the next component I want to use.

Behavior Subject-

A BehaviorSubject is an Observable that remembers and immediately emits its latest value to any new subscriber, and can be updated with .next() this has black background when i copy and paste it get rid of that It caches the result in the heap to remember the last value it had.

A behavior subject is a class from the rxjs library

```
private searchResultsSubject = new BehaviorSubject<any>(null);
searchResults$ = this.searchResultsSubject.asObservable();

setSearchResult(results: any): void {
  this.searchResultsSubject.next(results); /*next is how u update the variable*/
}
```

So for passing data around the components, I have it structured like this in my service files ^
You don't want to keep

I have the bahviorSubject set as private so that you can only change the value of it within that class. External components are calling the set functions to set it

The built in oAuth isAuthenticated functionality-

```
protected isAuthenticated = toSignal(this.auth.isAuthenticated$, { initialValue: false
});
```

This calls a built-in function from oAuth to see if the current user has an active auth0 session. It checks to see if it still has the access token stored in memory.