



# **Secret Vault on Aptos Audit Report**

Version 1.0

*X: @AlexScherbatyuk*

August 21, 2025

# Secret Vault on Aptos Audit Report

Alexander Scherbatyuk

August 21, 2025

Prepared by: X: @AlexScherbatyuk Lead Auditors: - Alexander Scherbatyuk

## Table of Contents

- Table of Contents
- Protocol Summary
- Disclaimer
- Risk Classification
- Audit Details
  - Scope
  - Roles
- Executive Summary
  - Issues found
- Findings
  - Medium
    - \* [H-1] Unauthorized retrieve, anyone can read an owner secret
  - Low
    - \* [L-1] Secret cannot be updated, no update path (owner cannot change secret due to move\_to overwrite abort)

Protocol Summary

SecretVault is a Move smart contract application for storing a secret on the Aptos blockchain. Only the owner should be able to store a secret and then retrieve it later. Others should not be able to access the secret.

Disclaimer

The @AlexScherbatyuk makes all effort to find as many vulnerabilities in the code in the given time period, but holds no responsibilities for the findings provided in this document. A security audit by the team is not an endorsement of the underlying business or product. The audit was time-boxed and the review of the code was solely on the security aspects of the Solidity implementation of the contracts.

Risk Classification

		Impact		
		High	Medium	Low
Likelihood	High	H	H/M	M
	Medium	H/M	M	M/L
	Low	M	M/L	L

We use the CodeHawks severity matrix to determine severity. See the documentation for more details.

Audit Details

Scope

```
1 sources/  
2 --- secret_vault.move
```

## Roles

Owner - Only the owner may set and retrieve their secret

## Executive Summary

### Issues found

Severity	Number of issues found
High	0
Medium	1
Low	1
Info	0
Gas Optimizations	0
Total	2

## Findings

### Medium

#### [H-1] Unauthorized retrieve, anyone can read an owner secret

**Description:** Normal behavior is that only the owner may set and retrieve their secret. Current behavior is that anyone can read the owner's secret by simply passing @owner into the view function. The function authorizes based on a user-provided address parameter, not the transaction signer.

```
1 #[view]
2 @> public fun get_secret (caller: address):String acquires Vault{
3 @>   assert! (caller == @owner,NOT_OWNER);
4       let vault = borrow_global<Vault >(@owner);
5       vault.secret
6 }
```

**Impact:** Breaks core confidentiality and main functionality. The protocols that trusted their users' secrets to be stored using this contract are at risk of a security breach. Users may potentially lose data or funds.

**Proof of Concept:** The test shows that a non-owner can read the owner's secret by calling the view function with @owner as the argument. There's no signer-based auth; the function authorizes purely on the caller-supplied parameter.

```
1  #[test(owner = @0xcc, attacker = @0x456)]
2  public fun test_anyone_can_read_owner_secret(owner: &signer,
3      attacker: &signer) {
4      account::create_account_for_test(signer::address_of(owner));
5      account::create_account_for_test(signer::address_of(attacker));
6
7      let secret = b"top secret";
8      vault::set_secret(owner, secret);
9
10     let leaked: String = vault::get_secret(@owner);
11     assert!(leaked == string::utf8(secret), 100);
12 }
```

**Recommended Mitigation:** Enforce signer-based authentication for secrets to be read only by actual owner.

```
1  #[view]
2  - public fun get_secret (caller: address):String acquires Vault{
3  + public fun get_secret(caller: &signer): String acquires Vault {
4  -     assert! (caller == @owner, NOT_OWNER);
5  +     assert!(signer::address_of(caller) == @owner, NOT_OWNER);
6      let vault = borrow_global<Vault>(@owner);
7      vault.secret
8  }
```

## Low

### [L-1] Secret cannot be updated, no update path (owner cannot change secret due to move\_to overwrite abort)

**Description:** Normal behaviour is that owner can use update vault Current behaviour owner cannot update secret, due to move\_to overwrite abort.

```
1
2  public entry fun set_secret(caller:&signer,secret:vector<u8>){
3      let secret_vault = Vault{secret: string::utf8(secret)};
4      @> move_to(caller,secret_vault);
5      event::emit(SetNewSecret {});
6  }
```

**Impact:** The current architecture allows one secret per vault, so the update is the intended behavior. Breaks functionality and disrupts the intended path.

**Proof of Concept:** This test proves that the owner cannot update the secret because `move_to` cannot overwrite an existing resource.

```
1  #[test(owner = @0xcc)]
2  #[expected_failure]
3  public fun test_owner_cannot_update_secret(owner: &signer) {
4      account::create_account_for_test(signer::address_of(owner));
5      let secret1 = b"first";
6      let secret2 = b"second";
7      vault::set_secret(owner, secret1);
8      // This should abort because move_to cannot overwrite an
9      // existing resource
10     vault::set_secret(owner, secret2);
11 }
```

**Recommended Mitigation:** This mitigation allows the owner to update the secret or create a vault and set an initial secret. Additionally, this code enforces access restrictions, allowing only the owner to set or update a secret.

```
1 - public entry fun set_secret(caller:&signer,secret:vector<u8>){
2 + public entry fun set_secret(caller: &signer, secret: vector<u8>)
3   acquires Vault {
4 +   assert!(signer::address_of(caller) == @owner, NOT_OWNER);
5 +   if (exists<Vault>(@owner)) {
6 +       let vault_ref = borrow_global_mut<Vault>(@owner);
7 +       vault_ref.secret = string::utf8(secret);
8 +   } else {
9 +       move_to(caller, Vault { secret: string::utf8(secret) });
10 +   }
11   let secret_vault = Vault{secret: string::utf8(secret)};
12   move_to(caller,secret_vault);
13   }
14   event::emit(SetNewSecret {});
15 }
```