



# Extended Context-Free Grammars Parsing with Generalized LL

**Author:** Artem Gorokhov

Saint Petersburg State University  
Programming Languages and Tools Lab, JetBrains

4/March/2017

# Motivation



[Java SE](#) > [Java SE Specifications](#) > [Java Language Specification](#)

## Chapter 18. Syntax

This chapter presents a grammar for the Java programming language.

The grammar presented piecemeal in the preceding chapters (§2.3) is much better for exposition, but it is not well suited as a basis for a parser. The grammar presented in this chapter is the basis for the reference implementation. Note that it is not an LL(1) grammar, though in many cases it minimizes the necessary look ahead.

The grammar below uses the following BNF-style conventions:

- $[x]$  denotes zero or one occurrences of  $x$ .
- $\{x\}$  denotes zero or more occurrences of  $x$ .
- $(x \mid y)$  means one of either  $x$  or  $y$ .

```
Identifier:  
    IDENTIFIER  
  
QualifiedIdentifier:  
    Identifier { . Identifier }  
  
QualifiedIdentifierList:  
    QualifiedIdentifier { , QualifiedIdentifier }  
  
CompilationUnit:  
    [[Annotations] package QualifiedIdentifier ;]  
        {ImportDeclaration} {TypeDeclaration}  
  
ImportDeclaration:  
    import [static] Identifier { . Identifier } [ . * ] ;  
  
TypeDeclaration:  
    ClassOrInterfaceDeclaration  
    ;  
  
ClassOrInterfaceDeclaration:  
    {Modifier} (ClassDeclaration | InterfaceDeclaration)
```

# Motivation

```
identifier: IDENTIFIER
qualifiedIdentifier: identifier (. identifier)*
qualifiedIdentifierList: qualifiedIdentifier (, qualifiedIdentifier)*
compilationUnit:
    [[Annotations] Package qualifiedIdentifier ;]
    (importDeclaration)* (typeDeclaration)*
importDeclaration: Import [Static] identifier (. identifier)* [. *] ;
typeDeclaration: classOrInterfaceDeclaration ;
classOrInterfaceDeclaration:
    (Modifier)* (ClassDeclaration | InterfaceDeclaration)
```

```
identifier: IDENTIFIER
qualifiedIdentifier: identifier many_1
many_1:
    | . identifier many_1
qualifiedIdentifierList: qualifiedIdentifier many_2
many_2:
    | COMMA qualifiedIdentifier many_2
compilationUnit: opt_1 many_3 many_4
opt_2:
    | Annotations
opt_1:
    | opt_2 Package qualifiedIdentifier ;
many_3:
    | importDeclaration many_3
many_4:
    | typeDeclaration many_4
importDeclaration:
    Import opt_3 identifier many_5 opt_4 ;
opt_3:
    | Static
many_5:
    | . identifier many_5
opt_4:
    | . *
typeDeclaration: classOrInterfaceDeclaration ;
classOrInterfaceDeclaration:
    many_6 ( ClassDeclaration | InterfaceDeclaration
many_6:
    | Modifier many_6
```

# Extended Context-Free Grammar

$$S : a M^*$$
$$M : a? (B K)^+$$
$$| u B$$
$$B : c \mid \varepsilon$$

# Existing solutions

- Mostly LL(k) and LR(k) algorithms
- **No** solution for arbitrary ECFG

# Generalized LL

- Based on LL
- Admit arbitrary CFG(including ambiguous)


# Generalized LL

- Based on LL
- Admit arbitrary CFG(including ambiguous)
- **Works only with BNF grammars**

RA for grammar  $G_0$

Grammar  $G_0$

$S : a^* S b? \mid a \Rightarrow$






# Recursive Automata Minimization

Grammar  $G_1$

$S: K K K K K K \mid K a K K K K$

$K: S K \mid a K \mid a$




# Derivation Trees for Recursive Automata


Input:

*aacb*

Automaton:



Derivation trees:




# SPPF for Recursive Automata


Input:

*aacb*

Automaton:



Shared Packed Parse Forest:



Mb highlight each tree?

- Descriptors queue
- Descriptor  $(G, i, U, T)$  uniquely defines parsing process state
  - ▶  $G$  - position in grammar
  - ▶  $i$  - position in input
  - ▶  $U$  - stack node
  - ▶  $T$  - current parse forest root

- Descriptors queue
- Descriptor  $(G, i, U, T)$  uniquely defines parsing process state
  - ▶  $G$  - **position in grammar**
  - ▶  $i$  - position in input
  - ▶  $U$  - stack node
  - ▶  $T$  - current parse forest root

- Descriptors queue
- Descriptor (G, i, U, T) uniquely defines parsing process state
  - ▶ G - **state of RA**
  - ▶ i - position in input
  - ▶ U - stack node
  - ▶ T - current parse forest root


# Input processing

Input :  $bc$

Grammar:

$$\begin{aligned} S &: a C_{opt} \\ &| b C_{opt} \\ &| S C_{opt} \\ C_{opt} &: \varepsilon \mid c \end{aligned}$$

Automaton :




# Input processing

Input : • *bc*

Grammar:

$$\begin{array}{lcl} S : & a C\_opt & \\ & | \quad b C\_opt & \\ & | \quad S C\_opt & \\ C\_opt : & \varepsilon \mid c & \end{array}$$

Automaton :





# Input processing


Input : •  $bc$

Grammar:

$S$  : •  $a C_{opt}$   
| •  $b C_{opt}$   
| •  $S C_{opt}$

$C_{opt}$  :  $\varepsilon$  |  $c$


Automaton :



# Input processing

Input : •  $bc$

Automaton :




# Evaluation

## Grammar $G_1$

$S: K K K K K K \mid K a K K K K$

$K: S K \mid a K \mid a$

## RA for grammar $G_1$



## Experiment results for input $a^{40}$

	Descriptors	Stack Edges	Stack Nodes	SPPF Nodes
BNF Grammar	7,940	6,974	80	111,127,244
Minimized RA	5,830	4,234	80	74,292,078
Difference	27%	39%	0 %	33 %

# Why did we make it?

Graph parsing results

	Descriptors	Stack Edges	Stack Nodes	Time, min
BNF Grammar	21,134,080	7,482,789	2,731,529	02.26
Minimized RA	9,153,352	2,792,330	839,148	01.25
Difference	57%	63%	69 %	45 %