




Parsing Techniques for Graph Analysis

Semyon Grigorev, Kate Verbitskaia

JetBrains Research, Programming Languages and Tools Lab
Saint Petersburg University

October 22, 2017

Language-Constrained Path Filtering



Navigation through a graph

- Are nodes A and B on the same level of hierarchy?
- Is there a path of form $Up^n Down^n$?
- Find all paths of form $Up^n Down^n$ which start from the node A

- (How) Can an automaton generate phrases in some specific (context-free) language?
- (How) Can a program produce some specific chain of the subprogram calls?

Language-Constrained Path Filtering: More Formal

- $\mathbb{G} = (\Sigma, N, P)$ — context-free grammar
- $G = (V, E, L)$ — directed graph
 - ▶ $v \xrightarrow{l} u \in E$
 - ▶ $L \subseteq \Sigma$
- $\omega(p) = \omega(v_0 \xrightarrow{l_0} v_1 \xrightarrow{l_1} \dots \xrightarrow{l_{n-2}} v_{n-1} \xrightarrow{l_{n-1}} v_n) = l_0 l_1 \dots l_{n-1}$
- $R = \{p \mid \text{exists } N_i \in N \text{ such that } \omega(p) \in L(\mathbb{G}, N_i)\}$

- Graph database querying (Yannakakis. 1990; Hellings. 2014; Zhang. 2016)
- Code analysis
 - ▶ Static analysis via context-free and linear conjunctive language reachability
 - ★ alias analysis (Zhang, Su. 2017)
 - ★ points-to analysis (Xu, Rountev, Sridharan. 2009)
 - ▶ Dynamically generated strings analysis (Verbitskaia, Grigorev, Avdyukhin. 2015)
 - ▶ Multiple input parsing (Scott, Johnstone. 2016)
- ...


Existing Approaches

- Do not use the power of advanced parsing techniques
 - ▶ Are mostly based on CYK
(Zhang, et al. “Context-Free Path Queries on RDF Graphs.”;
Hellings. “Conjunctive Context-Free Path Queries.”)
 - ▶ Do not provide useful structural representation of result
- Impose restrictions on input
 - ▶ Do not process input graphs with cycles
(Sevon, Eronen. “Subgraph Queries by Context-Free Grammars.”)
 - ▶ Are restricted to certain grammar classes

Open Problems

- Development of efficient algorithms
- Result representation for query debugging and further processing
- Processing of various types of grammars (ECFG, conjunctive, etc)

Example




$$S \rightarrow a S b$$

$$S \rightarrow \textit{Middle}$$


$$\textit{Middle} \rightarrow a b$$

Query: a grammar for the language $L = \{a^n b^n \mid n \geq 1\}$ with an additional marker for the middle of the path


Example




Input graph



Query result: SPPF




Tree for the path $0 \rightsquigarrow 3$




Tree for the path $0 \rightsquigarrow 0$


Example




Input graph



Query result: SPPF



Tree for the path $0 \rightsquigarrow 3$



Tree for the path $0 \rightsquigarrow 0$

Our Approaches

- Relaxed parsing of dynamically generated SQL-queries
- Context-free path querying with structural representation of result
- Context-free path querying by matrix multiplication
- Parser combinators for context-free path querying

Relaxed Parsing of Dynamically Generated SQL-queries


- Verbitskaia, Grigorev, Avdyukhin. 2015
- Based on RNGLR parsing algorithm (Scott, Johnstone)
- Static analysis of dynamically generated (SQL)code

```
IF @X = @Y SET @TABLE = '#table1'
```

```
ELSE      SET @TABLE = 'table2'
```

```
EXECUTE
```

```
('SELECT x FROM ' + @TABLE + ' WHERE ISNULL(n,0) > 1')
```



Context-Free Path Querying with Structural Representation of Result

- Grigorev, Ragozina. 2016
- Based on GLL parsing algorithm (Scott, Johnstone)
- General-purpose context-free path querying algorithm which can produce user-friendly representation of result
- Worst-case space complexity

$$O(|V|^3 + |E|)$$

- Worst-case time complexity

$$O\left(|V|^3 * \max_{v \in V} (deg^+(v))\right)$$

Context-Free Path Querying by Matrix Multiplication

- Azimov, Grigorev. 2017
- Inspired by works of Valiant and Okhotin
- GPGPU utilization for context-free path querying
- Worst-case time complexity

$$O(|V|^2|N|^3(BMM(|V|) + BMU(|V|)))$$

- ▶ BMM — Boolean Matrix Multiplication
- ▶ BMU — Boolean Matrix Union

Parser Combinators for Context-Free Path Querying

- Smolina, Verbitskaia. 2017
- Based on Meerkat: a general parser combinator library for Scala (Afroozeh, Izmaylova)
- Context-free path querying without DSLs
 - ▶ May be more friendly for the developers of static code analysis tools
 - ▶ Data-dependent parsing (in progress)

- Graphs — the set of ontologies
- Query is classical “same-generation query”

$$S \rightarrow \text{subClassOf}^{-1} S \text{ subClassOf}$$

$$S \rightarrow \text{type}^{-1} S \text{ type}$$

$$S \rightarrow \text{subClassOf}^{-1} \text{subClassOf}$$

$$S \rightarrow \text{type}^{-1} \text{type}$$

Evaluation: Results

Ontology	#edg	time (ms)		
		CYK ¹	GLL	Matrix
skos	252	1044	10	12
generations	273	6091	19	13
travel	277	13971	24	30
univ-bench	293	20981	25	15
people-pets	640	82081	89	32
atom-primitive	425	515285	255	22
biomedical- measure-primitive	459	420604	261	20
pizza	1980	3233587	697	24
wine	1839	4075319	819	54
g1	8688	—	1926	82
g2	14712	—	6246	185
g3	15840	—	7014	127

¹Zhang, et al. "Context-Free Path Queries on RDF Graphs."

Future Work: Other Grammars and Language Classes Intersection

- Context-free grammars intersection: Nederhof, “The Language Intersection Problem for Non-Recursive Context-Free Grammars”
 - ▶ Compressed strings processing
 - ▶ Grammar-compressed graphs querying
- Approximated intersection of regular and conjunctive/boolean languages
 - ▶ More expressive query languages
- ...

Future Work: Mechanization in Coq

- Bar-Hillel theorem
- GLL-based algorithms
- Other algorithms for grammars intersection
- Basic (parsing) algorithms verification
- Base for complex algorithms verification

Contact Information

- Semyon Grigorev: semen.grigorev@jetbrains.com
- Kate Verbitskaia: ekaterina.verbitskaya@jetbrains.com
- YaccConstructor: <https://github.com/YaccConstructor>