

Evaluation of Matrix-Based Context-Free Path Querying Algorithm

Iaroslav Sokolov
Saint Petersburg State University
7/9 Universitetskaya nab.
St. Petersburg, Russia 199034
sokolov.yas@gmail.com

Vladimir Kutuev
Saint Petersburg State University
7/9 Universitetskaya nab.
St. Petersburg, Russia 199034
vladimir.kutuev@gmail.com

Nikita Mishin
Saint Petersburg State University
7/9 Universitetskaya nab.
St. Petersburg, Russia 199034
mishinnikitam@gmail.com

Egor Nemchinov
Saint Petersburg State University
7/9 Universitetskaya nab.
St. Petersburg, Russia 199034
nemchegor@gmail.com

Egor Spirin
Saint Petersburg State University
7/9 Universitetskaya nab.
St. Petersburg, Russia 199034
egor@spirin.tech

Sergey Gorbatyuk
Saint Petersburg State University
7/9 Universitetskaya nab.
St. Petersburg, Russia 199034
sergeygorbatyuk171@gmail.com

Semyon Grigorev
semen.grigorev@jetbrains.com
Saint Petersburg State University
7/9 Universitetskaya nab.
St. Petersburg, Russia 199034
JetBrains Research
Universitetskaya emb., 7-9-11/5A
St. Petersburg, Russia 199034

ABSTRACT

A clear and well-documented \LaTeX document is presented as an article formatted for publication by ACM in a conference proceedings or journal publication. Based on the “acmart” document class, this article presents and explains many of the common variations, as well as many of the formatting elements an author may use in the preparation of the documentation of their work.

CCS CONCEPTS

• **Computer systems organization** → **Embedded systems**; *Redundancy*; Robotics; • **Networks** → Network reliability;

KEYWORDS

datasets, neural networks, gaze detection, text tagging

ACM Reference format:

Iaroslav Sokolov, Nikita Mishin, Egor Spirin, Vladimir Kutuev, Egor Nemchinov, Sergey Gorbatyuk, and Semyon Grigorev. 2018. Evaluation of Matrix-Based Context-Free Path Querying Algorithm. In *Proceedings of Woodstock '18: ACM Symposium on Neural Gaze Detection*, Woodstock, NY, June 03–05, 2018 (Woodstock '18), 4 pages.

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for components of this work owned by others than the author(s) must be honored. Abstracting with credit is permitted. To copy otherwise, or republish, to post on servers or to redistribute to lists, requires prior specific permission and/or a fee. Request permissions from permissions@acm.org.

Woodstock '18, June 03–05, 2018, Woodstock, NY

© 2018 Copyright held by the owner/author(s). Publication rights licensed to Association for Computing Machinery.

ACM ISBN 978-1-4503-9999-9/18/06...\$15.00

<https://doi.org/10.1145/1122445.1122456>

<https://doi.org/10.1145/1122445.1122456>

1 INTRODUCTION

Graph querying, Context-Free Path Querying (CFPQ), applications in different areas. Performance is important for practical tasks.

Matrix-based algorithm. Pretty simple. Performance problems. CPU/GPGPU based implementation. Investigate and compare.

There is no publically available standartized dataset for algorithms evaluation. We collect some data and propose possible candidate for it.

Research question: comparison of differend implementations of matrix-based CFPQ. We implement and compare performance.

Contribution

- Implementation. Source code is available on GitHub:!!!!!!
- Evaluation
- Dataset for evaluation. Available. Data format. Reference values.

This paper is organized as follows. !!!!

2 MATRIX-BASED ALGORITHM FOR CFPQ

Matrix-based algorithm for CFPQ was proposed by Rustam Azimov [4]. This algorithm can be expressed in few lines of code in terms of matrices operations, and it is a sufficient advantage for implementation. It was shown that GPGPU utilization for queries evaluation can significantly improve performance in comparison with other implementations [4] even float matrices used instead of boolean matrices.

Pseudocode of the algorithm is presented in listing 1.

Algorithm 1 Context-free path querying algorithm

```

1: function CONTEXTFREEPATHQUERYING( $D, G$ )
2:    $n \leftarrow$  the number of nodes in  $D$ 
3:    $E \leftarrow$  the directed edge-relation from  $D$ 
4:    $P \leftarrow$  the set of production rules in  $G$ 
5:    $T \leftarrow$  the matrix  $n \times n$  in which each element is  $\emptyset$ 
6:   for all  $(i, x, j) \in E$  do ▷ Matrix initialization
7:      $T_{i,j} \leftarrow T_{i,j} \cup \{A \mid (A \rightarrow x) \in P\}$ 
8:   end for
9:   while matrix  $T$  is changing do
10:     $T \leftarrow T \cup (T \times T)$  ▷ Transitive closure calculation
11:   end while
12:   return  $T$ 
13: end function

```

Here $D = (V, E)$ be the input graph and $G = (N, \Sigma, P)$ be the input grammar. Each cell of the matrix T contains the set of nonterminals such that $N_k \in T[i, j] \iff \exists p = v_i \dots v_j$ —path in D , such that $N_k \xRightarrow{*}_G \omega(p)$, where $\omega(p)$ is a word formed by labels along path p . Thus, this algorithm solves reachability problem, or, according Hellings [6], process CFPQs by using relational query semantics.

As you can see, performance-critical part of this algorithm is a matrix multiplication. Note, that the set of nonterminals is finite, we can represent the matrix T as a set of boolean matrices: one for each nonterminal. In this case the matrix update operation be $T_{N_i} \leftarrow T_{N_i} + (T_{N_j} \times T_{N_k})$ for each production $N_i \rightarrow N_j N_k$ in P . Thus we can reduce CFPQ to boolean matrices multiplication. After such transformation we can apply the next optimization: we can skip update if there are no changes in the matrices T_{N_j} and T_{N_k} at the previous iteration.

Thus, the most important part is efficient implementation of operations over boolean matrices, and in this work we compare effects of utilization of different approaches to matrices multiplication. All our implementations are based on the optimized version of the algorithm.

3 IMPLEMENTATION

We implement matrix-based algorithm for CFPQ by using a number of different programming languages and tools. Our goal is to investigate effects of the next features of implementation.

- **GPGPU utilization.** It is well-known that GPGPUs are suitable for matrices operations, but performance of whole solution depends on task details: overhead on data transferring may negate effect of parallel computations. Moreover, it is believed that GPGPUs is not suitable for boolean calculations [?]. Can GPGPUs utilization for CFPQ improve performance in comparison with CPU version?
- **Existing libraries utilization** is a good practice in software engineering. Is it possible to achieve high performance by using existing libraries for matrices operations or we need to create own solution to get more control?
- **Low-level programming.** GPGPU programming is traditionally low-level programming by using C-based languages (CUDA C, OpenCL C). On the other hand, there are number of approaches to create GPGPU-based solution by using

such high-level languages as a Python. Can we get high-performance solution by using such approaches?

- **Sparse matrices.** Real graphs often are sparse, but not always. Is it suitable to use sparse matrix representation for CFPQ?

We provide next implementations for investigation.

- **CPU-based solutions**
 - Sparse matrices multiplication by using Scipy [7] in Python programming language.
 - Dense matrices multiplication by using m4ri¹ [1] library which implements 4 russian method [3] in C language. It is one of the best implementation of 4 russian method [2].
- **GPGPU-based solutions**
 - Manual implementation of 4 russian method in CUDA C.
 - Manual implementation of naïve boolean matrix multiplication in CUDA C.
 - Manual implementation of naïve boolean matrix multiplication in Python by using numba compiler².

Generic notes on optimizations. Notes on data transferring. On matrix changes tracking (we should multiply pair of matrices only if one of them changed in last iteration)

3.1 m4ri

Description of impl 1 [1]

3.2 Python sparse CPU

Description of impl 2

3.3 CUDA naïve

Description of impl 3

3.4 CUDA 4 russian method

Description of impl 4

3.5 Python + CUDA

Description of impl 5

3.6 Something else?

Description of impl n

4 DATASET DESCRIPTION

We create and publish a dataset for CFPQ algorithms evaluation. This dataset contains both the real data and synthetic data for different specific cases (such as theoretical worst case).

All data is presented in text-based format to simplify usage in different environments. Grammars are in Chomsky Normal Form and are stored in the files with yrd extension. Each line is a rule in form of triple or pair. The example of grammar representation is presented in figure 1

¹Actually we use pull request which is not merged yet: <https://bitbucket.org/malb/m4ri/pull-requests/9/extended-m4ri-to-multiplication-over-the/diff>

²Numba is a JIT compiler which supports GPGPU for subset of Python programming. Official page: <http://numba.pydata.org/>. Access date: 03.05.2019




Figure 1: Example of grammar representation in the yrd file

Graphs are represented as a set of triples (edges) and are stored in the files with txt extension. Example of graph is presented in figure ??.

```
0 A 1
1 A 2
2 A 0
0 B 4
4 B 0
```

Figure 2: Example of graph representation in txt file

Each case is a pair of set of graphs and set of grammars. Cases are placed in folders with case-specific name. Grammars and graph are placed in subfolders with names Grammars and Matrices respectively.

The dataset includes the cases data.

- RDFs from [?] and two variants of the same generation query which is classical queries for CFPQ [?].
- Worst case for CFPQ which is proposed by Hellings [?].
- Cycle to full
- Sparse graphs from [5]. Query is a same generation query

5 EVALUATION

We evaluate all described implementations on all data and queries from presented dataset.

For evaluation we use PC with the next characteristics.

- OS
- CPU
- RAM
- GPU
- Libs versions
- Python runtime

Compiler options, Python runtime, etc.

Results of evaluation are presented in tables below.

First is a !!! dataset.

We can see, that in this case !!!!

In this case !!!!!

For such type of graphs !!!!

Finally, we can conclude that

- On GPU utilization
- On Existing libraries
- On Low-level programming
- On sparse matrices

Table 1: !!!!

	Query 1	Query 2
Implementation	1	2
	1	2
4	5	6
7	8	9

Table 2: !!!!

	Query 1	Query 2
Implementation	1	2
	1	2
4	5	6
7	8	9

Table 3: !!!!

	Query 1	Query 2
Implementation	1	2
	1	2
4	5	6
7	8	9

Table 4: !!!!

	Query 1	Query 2
Implementation	1	2
	1	2
4	5	6
7	8	9

6 CONCLUSION AND FUTURE WORK

We present !!!

Our evaluation shows that !!!

First direction for future research is a more detailed CFPQ algorithms investigation. We should do More evaluation on sparse matrices on GPGPUs.

Also it is necessary to implement and evaluate solutions for graphs which is not fit in RAM. There is a set of technics for huge matrices multiplication. Is it possible to dopt it for CFPQ

Another direcion is a dataset improvement. More data. More grammars/queries.

ACKNOWLEDGMENTS

The research was supported by the Russian Science Foundation grant 18-11-00100 and a grant from JetBrains Research.

REFERENCES

- [1] Martin Albrecht and Gregory Bard. 2019. *The M4RI Library*. The M4RI Team. <https://bitbucket.org/malb/m4ri>
- [2] MR Albrecht, GV Bard, and W Hart. 2008. Efficient multiplication of dense matrices over GF (2). *arXiv preprint arXiv:0811.1714* (2008).
- [3] Vladimir L'vovich Arlazarov, Yefim A Dinitz, MA Kronrod, and IgorAleksandrovich Faradzhev. 1970. On economical construction of the transitive closure of an oriented graph. In *Doklady Akademii Nauk*, Vol. 194. Russian Academy of Sciences, 487–488.

- [4] Rustam Azimov and Semyon Grigorev. 2018. Context-free Path Querying by Matrix Multiplication. In *Proceedings of the 1st ACM SIGMOD Joint International Workshop on Graph Data Management Experiences & Systems (GRADES) and Network Data Analytics (NDA) (GRADES-NDA '18)*. ACM, New York, NY, USA, Article 5, 10 pages. <https://doi.org/10.1145/3210259.3210264>
- [5] Zhiwei Fan, Jianqiao Zhu, Zuyu Zhang, Aws Albarghouthi, Paraschos Koutris, and Jignesh Patel. 2018. Scaling-Up In-Memory Datalog Processing: Observations and Techniques. *arXiv preprint arXiv:1812.03975* (2018).
- [6] Jelle Hellings. 2014. Conjunctive context-free path queries. In *Proceedings of ICDT'14*. 119–130.
- [7] Eric Jones, Travis Oliphant, Pearu Peterson, et al. 2001–. SciPy: Open source scientific tools for Python. <http://www.scipy.org/> [Online; accessed 5.3.2019].