

Generalized LL Parsing Generalization

Semyon Grigorev

Saint Petersburg State University

7/9 Universitetskaya nab.

St. Petersburg, 199034 Russia

semen.grigorev@jetbrains.com, Anastasiya Ragozins, Artyom Gorokhov

February 4, 2017

Today data for parsing is not only linear string, and context-free grammar is not only programming language specification. Classical example is a graph parsing where input is a graph and grammar is a paths constraints specification. Also you can find such generalizations of parsing as Multi-string parsing presented at Parsing@SLE-2016, Abstract parsing [3], ETC. All of them are special cases of the Bar-Hillel theorem and can be generalized, but today many of them are separated solutions.

Current the next tasks.

- Context-free path querying for graph data bases.
- Context-free pattern search in metagenomical assemblies. Not only regular but also CF-compressed input processing which is actual for metagenomic assembly preprocessing. Sequitur compression algorithm.
- Multiple input parsing (Scott ...). For lexing ambiguities solving.

We have some experience in graph parsing and GLL. Our GLL-based graph parsing algorithm is faster than presented at WWW [1]. End some ideas of application: Error recovery as a graph parsing. Thus, the goal of our work is an abstract framework for parsing based on generalization of GLL parsing algorithm [2] which proposed by Scott and J. Also we want to investigate practical areas of application.

References

- [1] Ch, “Contex-free rdf querying”, *Theoretical Computer Science*, V. 516, p. 101–120, January 2014
- [2] Scott, “GLL parsing”, *Theoretical Computer Science*, V. 516, p. 101–120, January 2014
- [3] ccc, “Abstract LR”, *Theoretical Computer Science*, V. 516, p. 101–120, January 2014