

Parsing by Matrix Multiplication for String Matching [★]

Yuliya Susanina^{1,2}[0000–1111–2222–3333], Anna Yaveyn³[1111–2222–3333–4444], and
Semyon Grigorev^{1,2}[2222–3333–4444–5555]

¹ Saint Petersburg State University, 7/9 Universitetskaya nab.
St. Petersburg, 199034 Russia

² JetBrains Research, Universitetskaya emb., 7-9-11/5A
St. Petersburg, Russia
jsusanina@gmail.com, semen.grigorev@jetbrains.com

³ ...
...

Abstract. Recent research has shown that the theory of formal languages can be used in bioinformatics. While using parsing for processing nucleotide sequences it became necessary to find an easily adaptable to the string-matching problem parsing algorithm, and as such field of application as bioinformatics requires working with large amount of data, it should be highly efficient. The asymptotically fastest parsing algorithm was proposed by Valiant and based on matrix multiplication. The original version of matrix-based algorithm is difficult to apply to the string-matching problem. In this paper we present a modification of Valiant’s algorithm dealing with the problem mentioned above. The modification has a succinct proof of correctness and is implemented.

Keywords: Parsing · Matrix multiplication · Context-free grammars · String-matching · Bioinformatics.

1 Introduction

Since the theory of context-free grammars was developed by Noam Chomsky, its utility has been extensively studied [1, 2]. The classic application of context-free grammars is describing natural and programming languages. Recent research has shown that the theory of formal languages and, in particular, context-free languages can be used in bioinformatics [3–6].

There are a number of different approaches to solve the recognition and classification problems in bioinformatics, some of them are based on the researches claiming that the secondary structure of the nucleotide sequence (DNA and RNA) contains an important information about the organism species. The specific features of the secondary structure can be described by some context-free grammar, and therefore the recognition problem can be reduced to parsing –

[★] Supported by organization x.

verification if some nucleotide sequence can be derived in this grammar. That means we try to find the substrings possessing these specific features and further we can draw conclusions about the organism's origin based on the availability and location of the found substrings. So it is necessary to find an easily adaptable to the string-matching problem algorithm, moreover, as such field of application as bioinformatics requires working with large amount of data, it should be highly efficient.

The majority of parsing algorithms either had the cubic-time complexity (Kasami [8], Younger [9], Earley [10]) or could work only with sub-classes of context-free grammars (Bernardy, Claussen [7]), until Leslie Valiant presented new, asymptotically more efficient parsing algorithm based on matrix multiplication [11] that can be applied to any context-free grammar. Valiant's algorithm computes the parsing table for a linear input, where each element of this table is responsible for deriving a particular substring. By offloading the most time-consuming computations on a Boolean matrix multiplication, Valiant has achieved an improvement in time complexity, which is $O(BMM(n)\log(n))$ for an input string of size n , where $BMM(n)$ is the number of operations needed to multiply two Boolean matrices of size $n \times n$. In addition, Okhotin generalized the matrix-based algorithm to conjunctive and Boolean grammars which are the natural extensions of context-free grammars which have more expressive power and also improved its performance and understandability [12]. Nevertheless, Valiant's algorithm is difficult to apply to the string-matching problem, as its original version will have to make many unnecessary matrix multiplication calls.

This paper aims to present a modification of Valiant's algorithm dealing with the problem described above. We divide the parsing table into successively computed layers of disjoint submatrices of the same size through the reorganization of the matrix multiplication order. We also prove the correctness of the modification and that time complexity is the same as for the original algorithm. The applicability of our modification for the string-matching problem in practice is further shown.

2 Background

In this section we briefly introduce the key definitions and the necessary parsing algorithm. Before describing the Valiant's algorithm, we would like to mention one of the basic recognition algorithms known as CYK (the Cocke-Younger-Kasami algorithm), by which we show the main Valiant's idea that made such time complexity possible.

2.1 Preliminaries

An alphabet Σ is a finite nonempty set of symbols. Σ^* is a set of all finite strings over Σ . A grammar is a quadruple (Σ, N, R, S) , where Σ is a finite set of terminals, N is a finite set of nonterminals, R is a finite set of productions of

the form $\alpha \rightarrow \gamma$, where $\alpha \in V^*NV^*$, $\gamma \in V^*$, $V = \Sigma \cup N$ and $S \in N$ is a start symbol.

Definition 1 Grammar $G = (\Sigma, N, R, S)$ is called context-free, if $\forall r \in R$ are of the form $A \rightarrow \beta$, where $A \in N, \beta \in V^+$.

Definition 2 Context-free grammar $G = (\Sigma, N, R, S)$ is said to be in Chomsky normal form if $\forall r \in R$ are of the form:

- $A \rightarrow BC$,
- $A \rightarrow a$,
- $S \rightarrow \epsilon$,

where $A, B, C \in N, a \in \Sigma, \epsilon$ is an empty string.

Definition 3 $L_G(A)$ is language of grammar $G_A = (\Sigma, N, R, A)$, which means all the sentences that can be derived in a finite number of steps from the start symbol A.

2.2 Parsing by matrix multiplication

The main problem of parsing is to verify if the input string belongs to the language of some given grammar G . We will describe the Cocke-Younger-Kasami algorithm and the most asymptotically efficient parsing algorithm, which works for all context-free grammars, Valiant's parsing algorithm, based on matrix multiplication. In this paper we use the rewritten version of Valiant's algorithm proposed by Alexander Okhotin.

The CYK algorithm is a basic parsing algorithm. Its main idea is to construct for an input string $a_1a_2...a_n$ a parsing table T of size $n \times n$, where

$$T_{i,j} = \{A | a_{i+1}...a_j \in L_G(A)\} \quad \forall i < j \quad (1)$$

and $G = (\Sigma, N, R, S)$ is a context-free grammar in Chomsky normal form.

The elements of T are filled successively beginning with

$$T_{i-1,i} = \{A | A \rightarrow a_i \in R\} \quad (2)$$

Then,

$$T_{i,j} = f(P_{i,j}) \quad (3)$$

where

$$P_{i,j} = \bigcup_{k=i+1}^{j-1} T_{i,k} \times T_{k,j} \quad (4)$$

$$f(P) = \{A | \exists A \rightarrow BC \in R : (B, C) \in P\} \quad (5)$$

The input string $a_1a_2...a_n$ belongs to L_G if and only if $S \in T_{0,n}$.

Algorithm 1: Parsing by matrix multiplication: Valiant's Version

Input: Grammar $G = (\Sigma, N, R, S)$, $w = a_1 \dots a_n$, $n \geq 1$, $a_i \in \Sigma$, where $n + 1$ — power of two

```

1  main():
2    compute(0, n + 1);
3  accept if and only if  $S \in T_{0,n}$ 

4  compute( $l, m$ ): if  $m - l \geq 4$  then
5    compute( $l, \frac{l+m}{2}$ );
6    compute( $\frac{l+m}{2}, m$ )
7  end

8  complete( $l, \frac{l+m}{2}, \frac{l+m}{2}, m$ )

9  complete( $l, m, l', m'$ ): if  $m - l = 4$  and  $m = l'$  then
10    $T_{l,l+1} = \{A | A \rightarrow a_{l+1} \in R\}$ ;
11 end
12 else if  $m - l = 1$  and  $m < l'$  then
13    $T_{l,l'} = f(P_{l,l'})$ ;
14 end
15 else if  $m - l > 1$  then
16    $B = (l, \frac{l+m}{2}, \frac{l'+m'}{2}, m')$ ,  $B' = (\frac{l+m}{2}, m, l', \frac{l'+m'}{2})$ ,
       $C = (\frac{l+m}{2}, m, l', \frac{l'+m'}{2})$ ,  $D = (l, \frac{l+m}{2}, l', \frac{l'+m'}{2})$ ,
       $D' = (\frac{l+m}{2}, m, \frac{l'+m'}{2}, m')$ ,  $E = (l, \frac{l+m}{2}, \frac{l'+m'}{2}, m')$ ;
17   complete(C);
18    $P_D = P_D \cup (T_B \times T_C)$ ;
19   complete(D);
20    $P_{D'} = P_{D'} \cup (T_C \times T_{B'})$ ;
21   complete(D');
22    $P_E = P_E \cup (T_B \times T_{D'})$ ;
23    $P_E = P_E \cup (T_D \times T_{B'})$ ;
24   complete(E)
25 end
26 complete( $l, \frac{l+m}{2}, \frac{l+m}{2}, m$ )

```

The time complexity of this algorithm is $O(n^3)$. Valiant proposed to offload the most intensive computations to the Boolean matrix multiplication. As the most time-consuming is computing $\bigcup_{k=i+1}^{j-1} T_{i,k} \times T_{k,j}$, Valiant rearranged computation of $T_{i,j}$, in order to use multiplication of submatrices of T.

Definition 4 Let $X \in (2^N)^{m \times l}$ and $Y \in (2^N)^{l \times n}$ be two submatrices of parsing table T. Then, $X \times Y = Z$, where $Z \in (2^{N \times N})^{m \times n}$ and $Z_{i,j} = \bigcup_{k=1}^l X_{i,k} \times Y_{k,j}$.

In **Algorithm 1** full pseudo-code of Valiant's algorithm written in the terms proposed by Okhotin, is presented. All elements of T and P are initialized by empty sets. Then, the elements of these two table are successively filled by two recursive procedures.

The procedure *compute*(l, m) constructs the correct values of $T_{i,j} \forall l \leq i < j < m$.

The procedure *complete*(l, m, l', m') constructs the submatrix $\forall T_{i,j} \ l \leq i < m, l' \leq j < m'$. This procedure assumes $T_{i,j} \forall l \leq i < j < m, l' \leq i < j < m'$ are already constructed and the current value of $P[i, j] = \{(B, C) | \exists (m \leq k < l') : a_{i+1} \dots a_k \in L(B), a_{k+1} \dots a_j \in L(C)\} \forall l \leq i < m, l' \leq j < m'$.

Then Valiant described that product of multiplying of two submatrices of parsing table T can be provided as $|N|^2$ Boolean matrices (for each pair of non-terminals). Denote matrix corresponding to pair $(B, C) \in N \times N$ as $Z^{(B,C)}$, then $Z_{i,j}^{(B,C)} = 1$ if and only if $(B, C) \in Z_{i,j}$. It should also be noted that $Z^{(B,C)} = X^B \times Y^C$. So, matrix multiplication in **Definition 4** can be replaced by Boolean matrix multiplication, each of which can be computed independently. Following these changes, time complexity of **Algorithm 1** is $O(|G|BMM(n)\log(n))$ for an input string of length n, where BMM(n) is the number of operations needed to multiply two Boolean matrices of size $n \times n$.

3 Modification of Valiant's algorithm

In this section we describe the modification of Valiant's algorithm, which has a number of advantages, such as possibility to broke it down into several subtasks that can be processed independently. Also this version can be simply applied to the string-matching problem, which often arises in text editing, DNA and RNA sequence analysis.

The main change of this modification is to divide the parsing table into layers of disjoint submatrices of the same size. The division, we have made from the reorganization of the matrix multiplication order, is presented in **Figure 1**. The layers are computes successively from the bottom up.

Let us consider the pseudo-code of the modification, which is written in **Algorithm 2**. The procedure *main*() computes the lowest layer ($T_{l,l+1}$), and then divide the table into layers, described earlier, and computes them through the *completeVLayer*() call. Thus, *main*() computes all elements of parsing table T correctly.

Algorithm 2: Parsing by matrix multiplication: Modified Version

Input: Grammar $G = (\Sigma, N, R, S)$, $w = a_1 \dots a_n$, $n \geq 1$, $a_i \in \Sigma$, where $n + 1$ — power of two

```

1  main():
2  for  $l \in \{1, \dots, n\}$  do
3       $T_{l,l+1} = \{A | A \rightarrow a_{l+1} \in R\}$ 
4  end
5  for  $1 \leq i < k$  do
6       $\text{layer} = \text{constructLayer}(i)$ ;
7       $\text{completeVLayer}(\text{layer})$ 
8  end
9  constructLayer(i):
10  $\{B | \exists k \geq 0 : B = (k * 2^i, (k + 1) * 2^i, (k + 1) * 2^i, (k + 2) * 2^i)\}$ 
11 completeLayer(M):
12 if  $\forall (l, m, l', m') \in M \quad (m - l = 1)$  then
13     for  $(l, m, l', m') \in M$  do
14          $T_{l,l'} = f(P_{l,l'})$ ;
15     end
16 end
17 else
18      $\text{bottomLayer} = \{( \frac{l+m}{2}, m, l', \frac{l'+m'}{2} ) | (l, m, l', m') \in M\}$ ;
19      $\text{completeLayer}(\text{bottomLayer})$ ;
20      $\text{completeVLayer}(M)$ 
21 end
22 completeVLayer(M):
23  $\text{leftSubLayer} = \{(l, \frac{l+m}{2}, l', \frac{l'+m'}{2}) | (l, m, l', m') \in M\}$ ;
24  $\text{rightSubLayer} = \{( \frac{l+m}{2}, m, \frac{l'+m'}{2}, m' ) | (l, m, l', m') \in M\}$ ;
25  $\text{topSubLayer} = \{(l, \frac{l+m}{2}, \frac{l'+m'}{2}, m' ) | (l, m, l', m') \in M\}$ ;
26  $\text{multiplicationTask1} =$ 
     $\{(l, m, l', m'), (l, m, m, 2m - l), (m, 2m - l, l', m') | (l, m, l', m') \in \text{leftSubLayer}\} \cup$ 
     $\{(l, m, l', m'), (l, m, 2l' - m', l'), (2l' - m', l', l', m') | (l, m, l', m') \in \text{rightSubLayer}\}$ ;
27  $\text{multiplicationTask2} =$ 
     $\{(l, m, l', m'), (l, m, m, 2m - l'), (m, 2m - l, l', m') | (l, m, l', m') \in \text{topSubLayer}\}$ ;
28  $\text{multiplicationTask3} =$ 
     $\{(l, m, l', m'), (l, m, 2l' - m', l'), (2l' - m', l', l', m') | (l, m, l', m') \in \text{topSubLayer}\}$ ;
29  $\text{performMultiplications}(\text{multiplicationTask1})$ ;
30  $\text{completeLayer}(\text{leftSubLayer} \cup \text{rightSubLayer})$ ;
31  $\text{performMultiplications}(\text{multiplicationTask2})$ ;
32  $\text{performMultiplications}(\text{multiplicationTask3})$ ;
33  $\text{completeLayer}(\text{topSubLayer})$ 

```

Denote some subsidiary functions for matrix m :

- $bottom(m) = (\frac{l+m}{2}, m, l', \frac{l'+m'}{2})$,
- $left(m) = (l, \frac{l+m}{2}, l', \frac{l'+m'}{2})$,
- $right(m) = (\frac{l+m}{2}, m, \frac{l'+m'}{2}, m')$,
- $top(m) = (l, \frac{l+m}{2}, \frac{l'+m'}{2}, m')$.

The procedure $completeVLayer(M)$ takes an array of disjoint submatrices M . For each $m = (l, m, l', m') \in M$ this procedure computes $left(m)$, $right(m)$, $top(m)$. The procedure assumes that the elements of $bottom(m)$ and all $T_{i,j} \forall l \leq i < j < m, l' \leq i < j < m'$ are already constructed. Also it is assumed that the current value of $P[i, j] = \{(B, C) | \exists (m \leq k < l') : a_{i+1} \dots a_k \in L(B), a_{k+1} \dots a_j \in L(C)\} \forall l \leq i < m, l' \leq j < m'$.

The procedure $completeLayer(M)$ also takes an array of disjoint submatrices M , but unlike the previous one, it computes $T_{i,j} \forall (i, j) \in m$. This procedure, just as in the previous case, assumes that $T_{i,j} \forall l \leq i < j < m, l' \leq i < j < m'$ are already constructed and the current value of $P[i, j] = \{(B, C) | \exists (m \leq k < l') : a_{i+1} \dots a_k \in L(B), a_{k+1} \dots a_j \in L(C)\} \forall l \leq i < m, l' \leq j < m'$.

Algorithm 3 describes how the procedure $performMultiplication(task)$, where $task$ is an array of a triple of submatrices, works. It is worth mentioning that, as distinct from the original algorithm, $|tasks| \geq 1$ and all these multiplications can be computed independently.

Algorithm 3:

```

1 performMultiplication(task):
2   for  $(m, m1, m2) \in M$  do
3      $P_m = P_m \cup (T_{m1} \times T_{m2})$ ;
4   end

```

4 Proof of correctness

We provide the proof of correctness and time complexity for the proposed modification in this section.

Theorem 1. *Let M be a submatrix array. Assume that $T[i, j] = \{A | a_{i+1} \dots a_j \in L(A)\} \forall l \leq i < j < m, l' \leq i < j < m'$ and $P[i, j] = \{(B, C) | \exists (m \leq k < l') : a_{i+1} \dots a_k \in L(B), a_{k+1} \dots a_j \in L(C)\} \forall l \leq i < m, l' \leq j < m' \forall (l, m, l', m') \in M$.*

Then the procedure $completeLayer(M)$, returns correctly computed sets of $T[i, j] \forall l \leq i \leq m, l' \leq j \leq m' \forall (l, m, l', m') \in M$.

Proof. Induction on $m - l$. (Hereinafter denoting (l, m, l', m') as a typical example of array M , and all the computations are implemented for all submatrices in M).

The base case: $m - l = 1$. There is only one element to compute, and $P[l, l'] = \{(B, C) | a_{l+1} \dots a_{l'} \in L(B)L(C)\}$. Further, algorithm computes $f(P[l, l']) = \{A | a_{l+1} \dots a_{l'} \in L(A)\}$, so $T[l, l']$ computed correctly.

For the induction step, assume that $(l1, m1, l2, m2)$ is correctly computed for $m2 - l2 = m1 - l1 > m - l$.

Let us consider complete $completeLayer(M)$, where $m - l > 1$.

Firstly, consider $completeLayer(bottom = \{(\frac{l+m}{2}, m, l', \frac{l'+m'}{2})\})$, as theorem conditions are fulfilled, then this call returns correct sets $T[i, j] \forall (i, j) \in bottom$ (hereinafter is means $\forall (i, j) \in m \forall m \in bottom$). All submatrices with size $m1 - l1 > m - l$, all previous layers and also $bottom(M)$ are correct, so, $completeVLayer(M)$ can be called, and $multiplicationByTask(task1)$ adds to each $P[i, j] \forall (i, j) \in left = \{(\frac{l+m}{2}, m, l', \frac{l'+m'}{2})\}$ all pairs $\{(B, C) | \exists (\frac{l+m}{2} \leq k < l') : a_{i+1} \dots a_k \in L(B), a_{k+1} \dots a_j \in L(C)\}$ and $\forall (i, j) \in right = \{(\frac{l+m}{2}, m, \frac{l'+m'}{2}, m')\}$ all pairs $\{(B, C) | \exists (m < k < \frac{l'+m'}{2}) : a_{i+1} \dots a_k \in L(B), a_{k+1} \dots a_j \in L(C)\}$. Now all the theorem conditions are fulfilled so, it is possible to call $completeLayer(left \cup right)$, which returns correct sets $T[i, j] \forall (i, j) \in (left \cup right)$.

Next, $multiplicationByTask(task2)$ and $multiplicationByTask(task3)$ add to each $P[i, j] \forall (i, j) \in top = \{(l, \frac{l+m}{2}, \frac{l'+m'}{2}, m')\}$ all pairs $\{(B, C) | \exists (\frac{l+m}{2} \leq k < m) \text{ and } (l' \leq k < \frac{l'+m'}{2}) : a_{i+1} \dots a_k \in L(B), a_{k+1} \dots a_j \in L(C)\}$. Now all the theorem conditions are fulfilled so, it is possible to call $completeLayer(top)$, which returns correct sets $T[i, j] \forall (i, j) \in top$.

Thus, all $T[i, j] \forall (i, j) \in M$ are computed correctly.

Theorem 2. Let M be a submatrix array. Assume that, $T[i, j] = \{A | a_{i+1} \dots a_j \in L(A)\} \forall l \leq i < j < m, l' \leq i < j < m'$ and $\forall b1 \leq i < b2, b3 \leq j < b4$, where $(b1, b2, b3, b4) = (\frac{l+m}{2}, m, l', \frac{l'+m'}{2})$, also $P[i, j] = \{(B, C) | \exists (m \leq k < l') : a_{i+1} \dots a_k \in L(B), a_{k+1} \dots a_j \in L(C)\} \forall l \leq i < m, l' \leq j < m' \forall (l, m, l', m') \in M$.

Then, the procedure $completeVLayer(M)$, returns correctly computed sets of $T[i, j] \forall l \leq i \leq m, l' \leq j \leq m' \forall (l, m, l', m') \in M$.

Proof. The proof is similar to the proof of Theorem 1.

Note 1. Function $constructLayer(i)$ returns $2^{k-i} - 1$ matrices of size 2^i .

Lemma 1.

- $\forall i \in \{1, \dots, k-1\} \sum |layer|$ for the calls of $completeVLayer(layer)$ where $\forall (l, m, l', m') \in layer$ with $m - l = 2^{k-i}$ is exactly $2^{2i-1} - 2^{i-1}$;
- $\forall i \in \{1, \dots, k-1\}$ products of submatrices of size $2^{k-i} \times 2^{k-i}$ are calculated exactly $2^{2i-1} - 2^i$

Proof. The base case: $i = 1$. $completeVLayer(layer)$ where $\forall (l, m, l', m') \in layer$ with $m - l = 2^{k-1}$ is called only once in the $main()$ and $|layer| = 1$. So, $2^{2i-1} - 2^{i-1} = 2^1 - 2^0 = 1$.

For the induction step, assume that $\forall i \in \{1, \dots, j\} \sum |layer|$ for the calls of $completeVLayer(layer)$ where $\forall (l, m, l', m') \in layer$ with $m - l = 2^{k-i}$ which is exactly $2^{2i-1} - 2^{i-1}$.

Let us consider $i = j + 1$.

Firstly, it is the call of $completeVLayer(costructLayer(k - i))$, where $costructLayer(i)$ returns $2^i - 1$ matrices of size 2^i . Secondly, $completeVLayer(layer)$ is called 3 times for the left, right and top submatrices of size $2^{k-(i-1)}$. Finally, $completeVLayer(layer)$ is called 4 times for the bottom, left, right and top submatrices of size $2^{k-(i-2)}$, except $2^{i-2} - 1$ matrices which were already computed.

Then, $\sum |layer| = 2^i - 1 + 3 \times (2^{2(i-1)-1} - 2^{(i-1)-1}) + 4 \times (2^{2(i-2)-1} - 2^{(i-2)-1}) - (2^{i-2} - 1) = 2^{2i-1} - 2^{i-1}$.

To calculate the number of products of submatrices of size $2^{k-i} \times 2^{k-i}$, we consider the calls of $completeVLayer(layer)$ where $\forall (l, m, l', m') \in layer$ with $m - l = 2^{k-(i-1)}$, which is $2^{2(i-1)-1} - 2^{(i-1)-1}$. During these calls $performMultiplications$ run 3 times, $|multiplicationTask1| = 2 \times 2^{2(i-1)-1} - 2^{(i-1)-1}$ and $|multiplicationTask2| = |multiplicationTask3| = 2^{2(i-1)-1} - 2^{(i-1)-1}$. So, the number of products of submatrices of size $2^{k-i} \times 2^{k-i}$ is $4 \times (2^{2(i-1)-1} - 2^{(i-1)-1}) = 2^{2i-1} - 2^i$.

Theorem 3. *The time complexity of the Algorithm 1 is $O(|G|BMM(n)\log(n))$ for an input string of length n , where G is a context-free grammar in Chomsky normal form, $BMM(n)$ is the number of operations needed to multiply two Boolean matrices of size $n \times n$.*

Proof. The proof is almost identical with that of the theorem given by Okhotin [12], because, as shown in the last lemma, the Algorithm 1 has the same number of products of submatrices.

5 Applications

Next we discuss the main cause of developing this modification. Our aim was adaptation of Valiant's algorithm for string-matching problem.

So if we want to find all substrings of size s which can be derived from a start symbol for an input string of size $n = 2^k$, we need to compute layers with submatrices of size $\leq 2^{l'}$, where $2^{l'-2} < s \leq 2^{l'-1}$.

$$l' = k - (m - 2), (m - 2) = k - l'$$

$$C \sum_{i=m}^k 2^{2i-1} \cdot 2^{\omega(k-i)} \cdot f(2^{k-i}) = C \cdot 2^{\omega l'} \sum_{i=2}^{l'} 2^{(2-\omega)i} \cdot 2^{2(k-l')-1} \cdot f(2^{l'-i}) \leq C \cdot 2^{\omega l'} f(2^{l'}) \cdot 2^{2(k-l')-1} \sum_{i=2}^{l'} 2^{(2-\omega)i} = BMM(2^{l'}) \cdot 2^{2(k-l')-1} \sum_{i=2}^{l'} 2^{(2-\omega)i}$$

Thus, time complexity for searching all substrings is $O(|G|BMM(2^{l'})(l'-1))$, while time complexity for the full input string is $O(|G|BMM(2^k)(k-1))$. In contrast to the modification, Valiant's algorithm completely calculate at least 2 triangle submatrices of size $\frac{n}{2}$, as it is shown on the **Figure 2**, which mean minimum asymptotic complexity $O(|G|BMM(2^{k-1})(k-2))$. Make a conclusion that the modification is asymptotically faster for substrings of size $s \ll n$ than the original algorithm.

6 Conclusion

The main goal of this work was to find an effective solution for the string-matching problem that arose at the intersection of the theory of formal languages and bioinformatics. We proposed a modification of Valiant's algorithm partially dealing with this problem. Also we proved its applicability by showing the asymptotic complexity concerning substring searching.

References

1. Chomsky, N.: On certain formal properties of grammars. *Information and control* **2**(2), 137–167 (1959)
2. Chomsky, N. and Schutzenberger M. P.: The algebraic theory of context-free languages. In: *Studies in Logic and the Foundations of Mathematics* vol. 35. pp. 118–161 Elsevier (1963)
3. Rivas, E. and Eddy, S. R.: The language of RNA: a formal grammar that includes pseudoknots. *Bioinformatics* **16**(4), 334–340 (2000)
4. Knudsen, B. and Hein, J.: RNA secondary structure prediction using stochastic context-free grammars and evolutionary history. *Bioinformatics (Oxford, England)* **15**(6), 446–454 (1999)
5. Yuan, C. and Lei, J. and Cole, J. and Sun, Y.: Reconstructing 16S rRNA genes in metagenomic data. *Bioinformatics* **31**(12), i35–i43 (2015)
6. Dowell, R. D. and Eddy, S. R.: Evaluation of several lightweight stochastic context-free grammars for RNA secondary structure prediction. *BMC bioinformatics* **5**(1), 71 (2004)
7. Bernardy, J.P., Claessen K.: Efficient divide-and-conquer parsing of practical context-free languages. In: *ACM SIGPLAN Notices*, vol. 48. no. 9, pp. 111–122 ACM (2013)
8. Kasami, T.: An efficient recognition and syntax-analysis algorithm for context-free languages. *Coordinated Science Laboratory Report* no. R-257 (1966)
9. Younger, D.H.: Recognition and parsing of context-free languages in time n^3 . *Information and control* **10**(2), 189–208 (1967)
10. Earley, J.: An efficient context-free parsing algorithm. *Communications of the ACM* **13**(2), 94–102 (1970)
11. Valiant, L. G.: General context-free recognition in less than cubic time. *Journal of computer and system sciences* **10**(2), 308–315 (1975)
12. Okhotin, A.: Parsing by matrix multiplication generalized to Boolean grammars. *Theoretical Computer Science* **516**, 101–120 (2014)