

# Evaluation of the Context-Free Path Querying Algorithm Based on Matrix Multiplication

Nikita Mishin  
Iaroslav Sokolov  
Egor Spirin  
mishinnikitam@gmail.com  
sokolov.yas@gmail.com  
egor@spirin.tech  
Saint Petersburg State University  
St. Petersburg, Russia

Vladimir Kutuev  
Egor Nemchinov  
Sergey Gorbatyuk  
vladimir.kutuev@gmail.com  
nemchegor@gmail.com  
sergeygorbatyuk171@gmail.com  
Saint Petersburg State University  
St. Petersburg, Russia

Semyon Grigorev  
s.v.grigoriev@spbu.ru  
semen.grigorev@jetbrains.com  
Saint Petersburg State University  
St. Petersburg, Russia  
JetBrains Research  
St. Petersburg, Russia

## ABSTRACT

Recently proposed matrix multiplication based algorithm for context-free path querying (CFPQ) offloads the most performance-critical parts onto boolean matrices multiplication. Thus, it is possible to utilize modern parallel hardware and software to achieve high performance of CFPQ easily. In this work, we provide results of empirical performance comparison of different implementations of this algorithm on both real data and synthetic data for the worst cases.

## CCS CONCEPTS

• **Information systems** → Query languages for non-relational engines; • **Theory of computation** → Grammars and context-free languages; *Parallel computing models*; • **Computing methodologies** → Massively parallel algorithms; • **Computer systems organization** → Single instruction, multiple data.

## KEYWORDS

Context-free path querying, transitive closure, graph databases, context-free grammar, GPGPU, CUDA, matrix multiplication, boolean matrix

### ACM Reference Format:

Nikita Mishin, Iaroslav Sokolov, Egor Spirin, Vladimir Kutuev, Egor Nemchinov, Sergey Gorbatyuk, and Semyon Grigorev. 2018. Evaluation of the Context-Free Path Querying Algorithm Based on Matrix Multiplication. In *Proceedings of GRADES-NDA 2019: the 2nd Joint International Workshop on Graph Data Management Experiences & Systems (GRADES) and Network Data Analytics (NDA) 2019 (GRADES-NDA 2019)*. ACM, New York, NY, USA, 4 pages. <https://doi.org/10.1145/1122445.1122456>

## 1 INTRODUCTION

Language-constrained path querying [? ], and particularly Context-Free Path Querying (CFPQ) [? ] widely used for graph-structured

data analysis in such areas as biological data analysis, RDF, network analysis. Huge amount of the real-world data makes performance of CFPQ evaluation critical for practical tasks, and number of algorithms for CFPQ evaluation proposed recently [? ].

One of the most promising algorithm is a matrix-based algorithm, proposed by Rustam Azimov [? ]. This algorithm offloads the most critical computations onto boolean matrices multiplication. As a result, it is pretty simple for implementation and allows one to utilize modern massive-parallel hardware for CFPQs evaluation. Implementation provided by authors utilizes GPGPU by using CuSparse<sup>1</sup> library which is floating point sparse matrices multiplication library. Even it does not use advanced algorithms for boolean matrices, it outperforms existing algorithms. It is necessary to investigate an effect of specific algorithms and implementation techniques on performance of CFPQ.

One of problems is that there is no publicly available standard dataset for CFPQ algorithms evaluation which includes both graph-structured data and queries.

In this work, we do empirical performance comparison of different implementations of matrices multiplication based algorithm for CFPQ on both real data and synthetic data for the worst cases. We make the following contributions in this paper.

- (1) We provide a number of implementations of the matrix multiplication based CFPQ algorithm, which utilizes different modern software and hardware. Source code is available on GitHub!!!
- (2) We collect and publish a dataset which contains both real data and syntactic data for worst cases. This dataset contains data and queries in the simple textual format, so it can be used for other algorithms evaluation easily. We hope that this dataset can be a base for unified benchmark for CFPQ algorithms.
- (3) Evaluation. We show that !!!

## 2 MATRIX-BASED ALGORITHM FOR CFPQ

Matrix-based algorithm for CFPQ was proposed by Rustam Azimov [4]. This algorithm can be expressed in few lines of code in terms of matrices operations, and it is a sufficient advantage for implementation. It was shown that GPGPU utilization for queries evaluation can significantly improve performance in comparison with other implementations [4] even float matrices used instead of boolean matrices.

<sup>1</sup>!!!

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for components of this work owned by others than the author(s) must be honored. Abstracting with credit is permitted. To copy otherwise, or republish, to post on servers or to redistribute to lists, requires prior specific permission and/or a fee. Request permissions from [permissions@acm.org](mailto:permissions@acm.org).

GRADES-NDA 2019, June 30, 2019, Amsterdam, Netherlands

© 2018 Copyright held by the owner/author(s). Publication rights licensed to ACM.

ACM ISBN 978-1-4503-9999-9/18/06...\$15.00

<https://doi.org/10.1145/1122445.1122456>

Pseudocode of the algorithm is presented in listing 1.

**Algorithm 1** Context-free path quering algorithm

---

```

1: function CONTEXTFREEPATHQUERYING( $D, G$ )
2:    $n \leftarrow$  the number of nodes in  $D$ 
3:    $E \leftarrow$  the directed edge-relation from  $D$ 
4:    $P \leftarrow$  the set of production rules in  $G$ 
5:    $T \leftarrow$  the matrix  $n \times n$  in which each element is  $\emptyset$ 
6:   for all  $(i, x, j) \in E$  do ▷ Matrix initialization
7:      $T_{i,j} \leftarrow T_{i,j} \cup \{A \mid (A \rightarrow x) \in P\}$ 
8:   end for
9:   while matrix  $T$  is changing do
10:     $T \leftarrow T \cup (T \times T)$  ▷ Transitive closure calculation
11:   end while
12:   return  $T$ 
13: end function

```

---

Here  $D = (V, E)$  be the input graph and  $G = (N, \Sigma, P)$  be the input grammar. Each cell of the matrix  $T$  contains the set of nonterminals such that  $N_k \in T[i, j] \iff \exists p = v_i \dots v_j$ —path in  $D$ , such that  $N_k \xrightarrow{*}_G \omega(p)$ , where  $\omega(p)$  is a word formed by labels along path  $p$ . Thus, this algorithm solves reachability problem, or, according Hellings [6], process CFPQs by using relational query semantics.

As you can see, performance-critical part of this algorithm is a matrix multiplication. Note, that the set of nonterminals is finite, we can represent the matrix  $T$  as a set of boolean matrices: one for each nonterminal. In this case the matrix update operation be  $T_{N_i} \leftarrow T_{N_i} + (T_{N_j} \times T_{N_k})$  for each production  $N_i \rightarrow N_j N_k$  in  $P$ . Thus we can reduce CFPQ to boolean matrices multiplication. After such transformation we can apply the next optimization: we can skip update if there are no changes in the matrices  $T_{N_j}$  and  $T_{N_k}$  at the previous iteration.

Thus, the most important part is efficient implementation of operations over boolean matrices, and in this work we compare effects of utilization of different approaches to matrices multiplication. All our implemetations are based on the optimized version of the algorithm.

### 3 IMPLEMENTATION

We implement matrix-based algorithm fo CFPQ by using a number of different programming languages and tools. Our goal is to investigate effects of the next features of implmentation.

- **GPGPU utilization.** It is mell-known that GPGPUs are sutable for matrices operations, but performance of whole solution depends on task details: overhead on data transferring may negate effect of parallel computations. Moreover, it is believed that GPGPUs is not sutable boolean calculations [? ]. Can GPGPUs utilization for CFPQ improve performance in comparison with CPU version?
- **Existing libraries utilization** is a good practice in software engeneering. Is it possible to achainve highe performance by using existing libraries for matrices operations or we need to create own solution to get more control?
- **Low-level programming.** GPGPU programming is traditionally low-level programming by using C-based languages

(CUDA C, OpenCL C). On the other hand, there are number of approaches to create GPGPU-based solution by ysing such high-level languages as a Python. Can we get high-performance solution by using such approaches?

- **Sparse matrices.** Real graphs often are sparse, but not always. Is it sutable to use sparse matrix representation for CFPQ?

We provide next implementations for investigation.

- CPU-based solutions

**[Scipy]** Saprsre matrices multiplication by using Scipy [8] in Python programming language.

**[M4RI]** Dense matrices multiplication by using m4ri<sup>2</sup> [1] library which implements 4 russian method [3] in C language. This library choosen because it is one of performnat implementation of 4 russian method [2].

- GPGPU-based solutions

**[GPU4R]** Manual implemenattion of 4 russian metod in CUDA C.

**[GPU\_N]** Manual implementation of naïve boolean matrix multiplication in CUDA C.


**[GPU\_Py]** Manual implementation of naïve boolean matrix multiplication in Pyton by using numba compiler<sup>3</sup>.

Generic notes on optimizations. Notes on data transferring. On matrix changes tracking (we should multiply pair of matrices only if one of them changed in last iteration)

### 4 DATASET DESCRIPTION

We create and publish a dataset for CFPQ algorithms evaluation. This dataset contains both the real data and syntetic data for different specific cases, such as theoretical worst case, or matrices representation specific worst cases.

Our goal is querying algorithms evaluation, not a graph storages or graph databases evaluation, so all data is presented in text-based format to simplify usage in different environments. Grammars are in Chomscy Normal Form and are stored in the files with yrd extension. Each line is a rule in form of triple or pair. The example of grammar representation is presented in figure 1



**Figure 1: Example of grammar representation in the yrd file**

Graphs are represented as a set of triples (edges) and are stored in the files with txt extension. Example of graph is presented in figure 2.

<sup>2</sup>Actually we use pull request which is not merged yet: <https://bitbucket.org/malb/m4ri/pull-requests/9/extended-m4ri-to-multiplication-over-the/diff>. The original library implements operations over  $GF(2)$ , and this pull request contains operations over boolean semiring

<sup>3</sup>Numba is a JIT compiler which supports GPGPU for subset of Python programming. Official page: <http://numba.pydata.org/>. Access date: 03.05.2019




Figure 2: Example of graph representation in txt file

Each case is a pair of set of graphs and set of grammars: each query (grammar) should be applied to each graph. Cases are placed in folders with case-specific name. Grammars and graph are placed in subfolders with names Grammars and Matrices respectively.

It is known that variants of the *same generation query* ?? are classical example of queries that are context-free but not regular, so we use this type of queries in our evaluation. The dataset includes data for next cases.

**[RDF]** The set of real RDF files (ontologies) from [9] and two variants of the same generation query (figures ??).

**[Worst]** Theoretical worst case for CFPQ time complexity which is proposed by Hellings [7]: graph is a two cycles of co-prime lengths with single common vertex. First cycle labelled by open bracket and the second cycle is labelled by close bracketed. Query is a grammar for  $A^n B^n$  language (grammar  $G_1$ , figure 1).

**[Full]** The case when input graph is sparse, but result is a full graph. Such case may be a hard for sparse matrices representation. As an input graph we use a cycle all edges of which is labelled by the same token. As a queries we use two grammars which describe arbitrary repetition of a token: unambiguous and highly ambiguous grammar (figure ??).

**[Sparse]** Sparse graphs from [5] which emulates realistic sparse data. Query is a same generation query.

## 5 EVALUATION

We evaluate all described implementations on all data and queries from presented dataset.

For evaluation we use PC with the next characteristics.

- OS
- CPU
- RAM
- GPU
  - Name
  - GHz
  - RAM
  - Threads
  - ...
- Libs versions
- Python runtime

Compiler options, Python runtime, etc.

Results of evaluation are presented in tables below. Time is measured in milliseconds. Time for each algorithm is an average time of 10 runs.

First is a **[RDF]** dataset. Results are presented in a table 1.

We can see, that in this case !!!!

Results of theoretical worst case (**[Worst]** dataset) is presented in table 2.

Table 2: Worst case evaluation results

#V	Scipy	M4RI	GPU4R	GPU_N	GPU_Py	CuSprs
16	0.032	!!!	0.008	0.002	!!!	!!!
32	0.118	!!!	0.034	0.008	!!!	!!!
64	0.476	!!!	0.133	0.032	!!!	!!!
128	2.194	!!!	0.562	0.129	2.751	!!!
256	15.299	!!!	3.088	0.544	11.883	!!!
512	121.287	!!!	13.685	2.499	43.563	!!!
1024	1593.284	!!!	88.064	19.357	217.326	!!!
2048	-	-	-	325.174	-	!!!

In this case !!!!! In this case !!!!!

Next is a **[Sparse]** dataset. Results are presented in table 3.

Table 3: Sparse graphs querying results

Graph	Scipy	M4RI	GPU4R	GPU_N	GPU_Py	CuSprs
G5k	10.352	!!!	0.113	0.041	0.216	!!!
G10k	37.286	!!!	0.435	0.215	1.331	!!!
G10k-0.01	97.607	!!!	0.273	0.138	0.763	!!!
G10k-0.1	!!!	!!!	0.223	0.114	0.859	!!!
G20k	150.774	!!!	1.842	1.274	6.180	!!!
G40k	-	!!!	11.663	8.393	37.821	!!!
G80k	-	!!!	88.366	65.886	-	!!!

For such type of graphs !!!!

The last dataset is a **[Full]**, and results a shown in table 4

Finally, we can conclude that

- On GPU utilization
- On Existing libraries
- On Low-level programming
- On sparse matrices

## 6 CONCLUSION AND FUTURE WORK

We provide a number of implementations of matrix-based algorithm for context-free path querying, collect a dataset for evaluation and provide results of evaluation of our implementation on collected dataset. Our evaluation shows that!!!

log cfg. datalog -> cfg or to boolean/conjunctive

First direction for future research is a more detailed CFPQ algorithms investigation. We should do more evaluation on sparse matrices on GPGPUs.

Also it is necessary to implement and evaluate solutions for graphs which is not fit in RAM. There is a set of technics for huge matrices multiplication. Is it possible to do it for CFPQ

Another direction is a dataset improvement. First of all, it is necessary to collect more data, and more grammars/queries. Especially it would be interesting to add to dataset more real graphs and more real queries. Secondly, it is necessary to !!! data format to be able

**Table 1: RDFs querying results**

RDF			Query 1						Query 2					
Name	#V	#E	Scipy	M4RI	GPU4R	GPU_N	GPU_Py	CuSprs	Scipy	M4RI	GPU4R	GPU_N	GPU_Py	CuSprs
atom-primitive			0.003	!!!	0.002	0.001	0.005	!!!	0.001	!!!	0.001	< 0.001	0.002	!!!
biomedical-mesure-primitive			0.003	!!!	0.002	0.001	0.005	!!!	0.004	!!!	0.001	< 0.001	0.005	!!!
foaf			0.002	!!!	0.002	< 0.001	0.005	!!!	0.001	!!!	0.001	< 0.001	0.002	!!!
funding			0.004	!!!	0.004	0.001	0.005	!!!	0.002	!!!	0.003	< 0.001	0.004	!!!
generations			0.003	!!!	0.002	< 0.001	0.005	!!!	0.001	!!!	0.001	< 0.001	0.002	!!!
people_pets			0.003	!!!	0.003	0.001	0.007	!!!	0.001	!!!	0.001	< 0.001	0.003	!!!
pizza			0.006	!!!	0.003	0.001	0.006	!!!	0.002	!!!	0.002	< 0.001	0.005	!!!
skos			0.002	!!!	0.002	< 0.001	0.005	!!!	< 0.001	!!!	0.001	< 0.001	0.002	!!!
travel			0.003	!!!	0.002	< 0.001	0.006	!!!	0.001	!!!	0.001	< 0.001	0.003	!!!
univ-bench			0.002	!!!	0.002	< 0.001	0.005	!!!	0.001	!!!	0.001	< 0.001	0.003	!!!
wine			0.007	!!!	0.004	0.001	0.007	!!!	0.001	!!!	0.003	< 0.001	0.003	!!!

**Table 4: Full querying results**

#V	Query 1						Query 2					
	Scipy	M4RI	GPU4R	GPU_N	GPU_Py	CuSprs	Scipy	M4RI	GPU4R	GPU_N	GPU_Py	CuSprs
10	0.001	!!!	< 0.001	< 0.001	0.002	!!!	0.002	!!!	0.001	0.001	0.004	!!!
50	0.002	!!!	0.001	< 0.001	0.003	!!!	0.005	!!!	0.002	0.001	!!!	!!!
100	0.007	!!!	0.002	< 0.001	0.003	!!!	0.023	!!!	0.005	0.001	0.007	!!!
200	0.040	!!!	0.002	0.001	0.004	!!!	0.105	!!!	0.004	0.001	0.007	!!!
500	0.480	!!!	0.003	0.001	0.004	!!!	1.636	!!!	0.007	0.001	0.010	!!!
1000	3.741	!!!	0.005	0.001	0.006	!!!	13.071	!!!	0.009	0.001	0.009	!!!
2000	40.309	!!!	0.019	0.003	0.017	!!!	93.676	!!!	0.030	0.005	0.026	!!!
5000	651.343	!!!	0.125	0.038	0.150	!!!	!!!	!!!	0.195	0.075	0.239	!!!
10000	-	!!!	0.552	0.315	0.840	!!!	!!!	!!!	1.055	0.648	1.838	!!!
25000	-	!!!	7.252	5.314	15.521	!!!	-	!!!	15.240	10.961	36.495	!!!
50000	-	!!!	58.751	44.611	129.641	!!!	-	!!!	130.203	91.579	!!!	!!!
80000	-	!!!	256.579	190.343	641.260	!!!	-	!!!	531.694	376.691	!!!	!!!

to evaluate different algorithms. Collaboration with community is required.

## ACKNOWLEDGMENTS

The research was supported by the Russian Science Foundation grant 18-11-00100 and a grant from JetBrains Research.

## REFERENCES

- [1] Martin Albrecht and Gregory Bard. 2019. *The M4RI Library*. The M4RI Team. <https://bitbucket.org/malb/m4ri>
- [2] MR Albrecht, GV Bard, and W Hart. 2008. Efficient multiplication of dense matrices over GF (2). *arXiv preprint arXiv:0811.1714* (2008).
- [3] Vladimir L'vovich Arlazarov, Yefim A Diniz, MA Kronrod, and IgorAleksandrovich Faradzhiev. 1970. On economical construction of the transitive closure of an oriented graph. In *Doklady Akademii Nauk*, Vol. 194. Russian Academy of Sciences, 487–488.
- [4] Rustam Azimov and Semyon Grigorev. 2018. Context-free Path Querying by Matrix Multiplication. In *Proceedings of the 1st ACM SIGMOD Joint International Workshop on Graph Data Management Experiences & Systems (GRADES) and Network Data Analytics (NDA) (GRADES-NDA '18)*. ACM, New York, NY, USA, Article 5, 10 pages. <https://doi.org/10.1145/3210259.3210264>
- [5] Zhiwei Fan, Jianqiao Zhu, Zuyu Zhang, Aws Albarghouthi, Paraschos Koutris, and Jignesh Patel. 2018. Scaling-Up In-Memory Datalog Processing: Observations and Techniques. *arXiv preprint arXiv:1812.03975* (2018).
- [6] Jelle Hellings. 2014. Conjunctive context-free path queries. In *Proceedings of ICDT'14*. 119–130.
- [7] Jelle Hellings. 2015. Querying for Paths in Graphs using Context-Free Path Queries. *arXiv preprint arXiv:1502.02242* (2015).
- [8] Eric Jones, Travis Oliphant, Pearu Peterson, et al. 2001–2019. SciPy: Open source scientific tools for Python. <http://www.scipy.org/> [Online; accessed 5.3.2019].
- [9] X. Zhang, Z. Feng, X. Wang, G. Rao, and W. Wu. 2016. Context-free path queries on RDF graphs. In *International Semantic Web Conference*. Springer, 632–648.