

Error Recovery By Using Graph Parsing

Marat Khabibullin
St. Petersburg Academic
University
194021, Khlopina Str 8/3
St. Petersburg, Russia
maratx387@gmail.com

Andrei Ivanov
St. Petersburg State University
198504, Universitetsky
prospekt 28
Peterhof, St. Petersburg,
Russia
ivanovandrew2004@qma

Semyon Grigorev
St. Petersburg State University
198504, Universitetsky
prospekt 28
Peterhof, St. Petersburg,
Russia
m_rsdpisuy@gmail.com

ABSTRACT

[illegible]

Keywords

!!!!

1. INTRODUCTION

2. ERROR RECOVERY ALGORITHM

Additional edges with error markers goes forward and with all tokens, goes in the its start vertex (as a result we have loops). Number of edges may be optimized by filtering with FIRST/REST and other functions

Select the best tree from SPPF after parsing finish.

Priority queue for descriptors. How to choose priority function?

Priority is a number of additional edges (not from the original input) in processed prefix. Suffix length.

3. EVALUATION

Calc.

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for components of this work owned by others than the author(s) must be honored. Abstracting with credit is permitted. To copy otherwise, to republish, to post on servers or to redistribute to lists, requires prior specific permission and/or a fee. Request permissions from permissions@acm.org.

Grammar.

Input generation

Timing. Original GLL. GLL with error recovery.

Cases: without errors, error in the end of file, in the middle, and in the start.

4. DISCUSSION AND CONCLUSION

Prorotype.

Future Work

Evaluation. BlackBox project.

Related Work