

Bar-Hillel Theorem Mechanization in Coq

Sergey Bozhko, Leyla Khatbullina, **Semyon Grigorev**

JetBrains Research, Programming Languages and Tools Lab
Saint Petersburg University

July 05, 2019

- Yet another attempt to automate proof correctness checking
- In some systems — a way to create correct by construction algorithms
 - ▶ Coq

- Nontrivial proofs checking
- Correctness of algorithms

The Bar-Hillel Theorem

Theorem (Bar-Hillel)

If L_1 is a context-free language and L_2 is a regular language, then $L_1 \cap L_2$ is context-free.

Context-Free Path Quierying (CFPQ)

- $\mathbb{G} = (\Sigma, N, P)$ — context-free grammar
 - ▶ $L(\mathbb{G}, A) = \{w \mid A \Rightarrow^* w\}$

Context-Free Path Quierying (CFPQ)

- $\mathbb{G} = (\Sigma, N, P)$ — context-free grammar
 - ▶ $L(\mathbb{G}, A) = \{w \mid A \Rightarrow^* w\}$
- $G = (V, E, L)$ — directed graph
 - ▶ $v \xrightarrow{l} u \in E$
 - ▶ $L \subseteq \Sigma$

Context-Free Path Quierying (CFPQ)

- $\mathbb{G} = (\Sigma, N, P)$ — context-free grammar
 - ▶ $L(\mathbb{G}, A) = \{w \mid A \Rightarrow^* w\}$
- $G = (V, E, L)$ — directed graph
 - ▶ $v \xrightarrow{l} u \in E$
 - ▶ $L \subseteq \Sigma$
- $\omega(\pi) = \omega(v_0 \xrightarrow{l_0} v_1 \xrightarrow{l_1} \cdots \xrightarrow{l_{n-2}} v_{n-1} \xrightarrow{l_{n-1}} v_n) = l_0 l_1 \cdots l_{n-1}$

Context-Free Path Quierying (CFPQ)

- $\mathbb{G} = (\Sigma, N, P)$ — context-free grammar
 - ▶ $L(\mathbb{G}, A) = \{w \mid A \Rightarrow^* w\}$
- $G = (V, E, L)$ — directed graph
 - ▶ $v \xrightarrow{l} u \in E$
 - ▶ $L \subseteq \Sigma$
- $\omega(\pi) = \omega(v_0 \xrightarrow{l_0} v_1 \xrightarrow{l_1} \cdots \xrightarrow{l_{n-2}} v_{n-1} \xrightarrow{l_{n-1}} v_n) = l_0 l_1 \cdots l_{n-1}$
- $R_A = \{(n, m) \mid \exists n\pi m, \text{ such that } \omega(\pi) \in L(\mathbb{G}, A)\}$

Context-Free Path Quierying (CFPQ)

- $\mathbb{G} = (\Sigma, N, P)$ — context-free grammar
 - ▶ $L(\mathbb{G}, A) = \{w \mid A \Rightarrow^* w\}$
- $G = (V, E, L)$ — directed graph
 - ▶ $v \xrightarrow{l} u \in E$
 - ▶ $L \subseteq \Sigma$
- $\omega(\pi) = \omega(v_0 \xrightarrow{l_0} v_1 \xrightarrow{l_1} \dots \xrightarrow{l_{n-2}} v_{n-1} \xrightarrow{l_{n-1}} v_n) = l_0 l_1 \dots l_{n-1}$
- $R_A = \{(n, m) \mid \exists n\pi m, \text{ such that } \omega(\pi) \in L(\mathbb{G}, A)\}$
- $P_A = \{\pi \mid \pi \text{ is a path in } G, \text{ such that } \omega(\pi) \in L(\mathbb{G}, A)\}$

Applications of CFPQ

- Graph data base querying
 - ▶ Yannacakis !!!
 - ▶ Static code analysis

Applications of CFPQ

- Graph data base querying
 - ▶ Yannacakis !!!
 - ▶ Static code analysis
- Static code analysis
 - ▶ Reps !!!
 - ▶ Static code analysis

Sketch of the Proof

- 1 Assume that there is a contextfree grammar G_{CNF} in Chomsky normal form, such that $L(G_{CNF}) = L_1$

Sketch of the Proof

- 1 Assume that there is a contextfree grammar G_{CNF} in Chomsky normal form, such that $L(G_{CNF}) = L_1$
- 2 Assume that there is a set of regular languages $\{A_1 \dots A_n\}$ where each A_i is recognized by a DFA with precisely one final state and $L_2 = A_1 \cup \dots \cup A_n$

Sketch of the Proof

- ① Assume that there is a contextfree grammar G_{CNF} in Chomsky normal form, such that $L(G_{CNF}) = L_1$
- ② Assume that there is a set of regular languages $\{A_1 \dots A_n\}$ where each A_i is recognized by a DFA with precisely one final state and $L_2 = A_1 \cup \dots \cup A_n$
 - ▶ If $L \neq \emptyset$ and L is regular then L is the union of regular language A_1, \dots, A_n where each A_i is accepted by a DFA with exactly one final state

Sketch of the Proof

- ① Assume that there is a contextfree grammar G_{CNF} in Chomsky normal form, such that $L(G_{CNF}) = L_1$
- ② Assume that there is a set of regular languages $\{A_1 \dots A_n\}$ where each A_i is recognized by a DFA with precisely one final state and $L_2 = A_1 \cup \dots \cup A_n$
 - ▶ If $L \neq \emptyset$ and L is regular then L is the union of regular language A_1, \dots, A_n where each A_i is accepted by a DFA with exactly one final state
- ③ For each A_i we can explicitly define a grammar of the intersection:
 $L(G_{CNF}) \cap A_i$

Sketch of the Proof

- ① Assume that there is a contextfree grammar G_{CNF} in Chomsky normal form, such that $L(G_{CNF}) = L_1$
- ② Assume that there is a set of regular languages $\{A_1 \dots A_n\}$ where each A_i is recognized by a DFA with precisely one final state and $L_2 = A_1 \cup \dots \cup A_n$
 - ▶ If $L \neq \emptyset$ and L is regular then L is the union of regular language A_1, \dots, A_n where each A_i is accepted by a DFA with exactly one final state
- ③ For each A_i we can explicitly define a grammar of the intersection: $L(G_{CNF}) \cap A_i$
- ④ Finally, join them together with the operation of the union

Hofmann's Results Generalization

Jana Hofmann provides mechanization of the part of CFL in the Coq

- Basic definitions: terminal, nonterminal, grammar, word, ...

Hofmann's Results Generalization

Jana Hofmann provides mechanization of the part of CFL in the Coq

- Basic definitions: terminal, nonterminal, grammar, word, ...
- **Context-Free grammar to the Chomsky Normal Form conversion**

Hofmann's Results Generalization

Jana Hofmann provides mechanization of the part of CFL in the Coq

- Basic definitions: terminal, nonterminal, grammar, word, ...
- **Context-Free grammar to the Chomsky Normal Form conversion**

```
Inductive ter : Type :=  
| T : nat -> ter.
```

Jana Hofmann

Hofmann's Results Generalization

Jana Hofmann provides mechanization of the part of CFL in the Coq

- Basic definitions: terminal, nonterminal, grammar, word, ...
- **Context-Free grammar to the Chomsky Normal Form conversion**

```
Inductive ter : Type :=  
  | T : nat -> ter.
```

Jana Hofmann

```
Inductive ter : Type :=  
  | T : Tt -> ter.
```

We need an arbitrary type for terminals and nonterminals!

Hofmann's Results Generalization

Jana Hofmann provides mechanization of the part of CFL in the Coq

- Basic definitions: terminal, nonterminal, grammar, word, ...
- **Context-Free grammar to the Chomsky Normal Form conversion**

```
Inductive ter : Type :=  
| T : nat -> ter.
```

Jana Hofmann

```
Inductive ter : Type :=  
| T : Tt -> ter.
```

We need an arbitrary type for
terminals and nonterminals!

And now we should carefully rewrite all existing stuff ...

DFA Splitting

If $L \neq \emptyset$ and L is regular then L is the union of regular language A_1, \dots, A_n where each A_i is accepted by a DFA with precisely one final state

DFA Splitting

If $L \neq \emptyset$ and L is regular then L is the union of regular language A_1, \dots, A_n where each A_i is accepted by a DFA with precisely one final state

Lemma `correct_split`:

```
forall dfa w,  
  dfa_language dfa w <->  
  exists sdfa,  
    In sdfa (split_dfa dfa) /\ s_dfa_language sdfa w.
```

Chomsky Induction


Lemma

Let G be a grammar in CNF. Consider an arbitrary nonterminal $N \in G$ and phrase which consists only of terminals w . If w is derivable from N and $|w| \geq 2$, then there exists two nonterminals N_1, N_2 and two phrases w_1, w_2 such that: $N \rightarrow N_1 N_2 \in G$, $\text{der}(G, N_1, w_1)$, $\text{der}(G, N_2, w_2)$, $|w_1| \geq 1$, $|w_2| \geq 1$ and $w_1 ++ w_2 = w$.

Chomsky Induction

Lemma

Let G be a grammar in CNF. Consider an arbitrary nonterminal $N \in G$ and phrase which consists only of terminals w . If w is derivable from N and $|w| \geq 2$, then there exists two nonterminals N_1, N_2 and two phrases w_1, w_2 such that: $N \rightarrow N_1 N_2 \in G$, $\text{der}(G, N_1, w_1)$, $\text{der}(G, N_2, w_2)$, $|w_1| \geq 1$, $|w_2| \geq 1$ and $w_1 ++ w_2 = w$.



Chomsky Induction in Coq

```
Definition syntactic_analysis_is_possible :=  
forall (G : grammar) (A : var) (w : phrase),  
  der G A w -> (R A w \in G)  
    \/  
    (exists rhs, R A rhs \in G /\ derf G rhs w).
```

```
Variable grammars: seq (var * grammar).
```

```
Theorem correct_union:
```

```
forall word,
```

```
  language (grammar_union grammars) (V (start Vt))  
    (to_phrase word)
```

```
<->
```

```
exists s_l,
```

```
  language (snd s_l) (fst s_l) (to_phrase word)
```

```
 /\
```

```
  In s_l grammars.
```

The Final Theorem

Theorem

For any two decidable types $\mathbf{T}t$ and $\mathbf{N}t$ for types of terminals and nonterminals correspondingly. If there exists a bijection from $\mathbf{N}t$ to \mathbb{N} and syntactic analysis is possible (in the sense of our definition), then for any DFA \mathbf{dfa} and any context-free grammar \mathbf{G} , there exists the context-free grammar G_{INT} , such that $L(G_{INT}) = L(G) \cap L(\mathbf{dfa})$.

The Final Theorem in Coq

```
Theorem grammar_of_intersection_exists:  
  exists  
    (NewNonterminal: Type)  
    (IntersectionGrammar: @grammar Terminal NewNonterminal)  
    St,  
  forall word,  
    dfa_language dfa word /\ language G S (to_phrase word)  
    <->  
    language IntersectionGrammar St (to_phrase word).
```

Conclusion

- We present mechanized in Coq proof of the Bar-Hillel theorem on the closure of context-free languages under intersection with the regular languages
- We generalize the results of Jana Hofmann and Gert Smolka
 - ▶ The definition of the terminal and nonterminal alphabets in context-free grammar were made generic
 - ▶ All related definitions and theorems were adjusted to work with the updated definition
- All results are published at GitHub and are equipped with automatically generated documentation

- Ruy J. G. B. de Queiroz vs Jana Hifmann
 - ▶ We use results of Jana Hofman
 - ▶ Results of Ruy J. G. B. de Queiroz looks more mature
 - ▶ Is it possible to create one “true” solution in this area?
 - ★ Wether our grammar-based proof is always better then PDA-based one?

Future work

- Ruy J. G. B. de Queiroz vs Jana Hifmann
 - ▶ We use results of Jana Hofman
 - ▶ Results of Ruy J. G. B. de Queiroz looks more mature
 - ▶ Is it possible to create one “true” solution in this area?
 - ★ Whether our grammar-based proof is always better than PDA-based one?
- Mechanization of practical algorithms which are just implementation of the Bar-Hillel theorem
 - ▶ Context-free path querying algorithm, based on CYK or even on GLL parsing algorithm
 - ▶ Certified algorithm for context-free constrained path querying for graph databases

Contact Information

- Semyon Grigorev:
 - ▶ s.v.grigoriev@spbu.ru
 - ▶ Semen.Grigorev@jetbrains.com
- Sergey Bozhko:
 - ▶ Max Planck Institute for Software Systems (MPI-SWS), Saarbrücken, Germany
 - ▶ sbozhko@mpi-sws.com
- Leyla Khatbullina:
 - ▶ St.Petersburg Electrotechnical University “LETI”, St.Petersburg, Russia
 - ▶ leila.xr@gmail.com
- Sources: https://github.com/YaccConstructor/YC_in_Coq

Thanks!