

Rytter for CFPQ

Semyon Grigorev
Saint Petersburg State University
St. Petersburg, Russia
semen.grigorev@jetbrains.com

Ekaterina Shemetova
Saint Petersburg State University
St. Petersburg, Russia
nozhkin.ii@gmail.com

ABSTRACT

Abstract

CCS CONCEPTS

• Information systems → Graph-based database models; Query languages for non-relational engines; • Software and its engineering → Functional languages; • Theory of computation → Grammars and context-free languages;

KEYWORDS

Graph Databases, Language-Constrained Path Problem, Context-Free Path Querying, Parser Combinators, Generalized LL, GLL, Neo4J, Scala

ACM Reference Format:

Semyon Grigorev and Ekaterina Shemetova. 2018. Rytter for CFPQ. In *Proceedings of ACM Conference (Conference'17)*. ACM, New York, NY, USA, 5 pages. <https://doi.org/10.1145/nnnnnnn.nnnnnnn>

1 INTRODUCTION

Two steps reduction of CFPQs to Boolean matrix multiplication. First step is reduction of arbitrary CFPQ to Dyck query. Second step is adoption Rytter's results from [?] for graph.

2 FROM ARBITRARY CFPQ TO DYCK QUERY

This reduction is inspired by the construction described in [1].

Consider a context-free grammar $\mathcal{G} = (\Sigma, N, P, S)$ in BNF where Σ is a terminal alphabet, N is a nonterminal alphabet, P is a set of productions, $S \in N$ is a start nonterminal. Also we denote a directed labeled graph by $G = (V, E, L)$ where $E \subseteq V \times L \times V$ and $L \subseteq \Sigma$.

We should construct new input graph G' and new grammar \mathcal{G}' such that \mathcal{G}' specifies a Dyck language and there is a simple mapping from $\text{CFPQ}(\mathcal{G}', G')$ to $\text{CFPQ}(\mathcal{G}, G)$. Step-by-step example with description is provided below.

Let the input grammar is

$$\begin{aligned} S &\rightarrow a S b \mid a C b \\ C &\rightarrow c \mid C c \end{aligned}$$

The input graph is presented in fig. ??

(1) Let $\Sigma_0 = \{t_i, t_j \mid t_i \in \Sigma\}$.

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for components of this work owned by others than ACM must be honored. Abstracting with credit is permitted. To copy otherwise, or republish, to post on servers or to redistribute to lists, requires prior specific permission and/or a fee. Request permissions from permissions@acm.org.

Conference'17, July 2017, Washington, DC, USA

© 2018 Association for Computing Machinery.

ACM ISBN 978-x-xxxx-xxxx-x/YY/MM...\$15.00

<https://doi.org/10.1145/nnnnnnn.nnnnnnn>






Figure 1: The input graph

- (2) Let $N_0 = \{N_i, N_j \mid N \in N\}$.
- (3) Let $M_{\mathcal{G}} = (V_{\mathcal{G}}, E_{\mathcal{G}}, L_{\mathcal{G}})$ is a directed labeled graph, where $L_{\mathcal{G}} \subseteq (\Sigma_0 \cup N_0)$. This graph is created the same manner as described in [1] but we do not require the grammar be in CNF. Let $x \in V_{\mathcal{G}}$ and $y \in V_{\mathcal{G}}$ is "start" and "final" vertices respectively. This graph may be treated as a finite automaton, so it can be minimized and we can compute an ε -closure if the input grammar contains ε productions. The graph $M_{\mathcal{G}}$ for our example is:



The minimized graph:



The *IMPLIED* relation:

$(B, 2, 3) \Rightarrow (S, 1, 3)$	$(B, 2, 4) \Rightarrow (S, 1, 4)$	$(B, 2, 2) \Rightarrow (S, 1, 2)$	$(B, 2, 1) \Rightarrow (S, 1, 1)$
$(B, 3, 4) \Rightarrow (S, 2, 4)$	$(B, 3, 3) \Rightarrow (S, 2, 3)$	$(B, 3, 2) \Rightarrow (S, 2, 2)$	$(B, 3, 1) \Rightarrow (S, 2, 1)$
$(B, 1, 2) \Rightarrow (S, 3, 2)$	$(B, 1, 3) \Rightarrow (S, 3, 3)$	$(B, 1, 4) \Rightarrow (S, 3, 4)$	$(B, 1, 1) \Rightarrow (S, 3, 1)$
$(S_1, 2, 3) \Rightarrow (S, 1, 3)$	$(S_1, 2, 4) \Rightarrow (S, 1, 4)$	$(S_1, 2, 2) \Rightarrow (S, 1, 2)$	$(S_1, 2, 1) \Rightarrow (S, 1, 1)$
$(S_1, 3, 4) \Rightarrow (S, 2, 4)$	$(S_1, 3, 3) \Rightarrow (S, 2, 3)$	$(S_1, 3, 2) \Rightarrow (S, 2, 2)$	$(S_1, 3, 1) \Rightarrow (S, 2, 1)$
$(S_1, 1, 2) \Rightarrow (S, 3, 2)$	$(S_1, 1, 3) \Rightarrow (S, 3, 3)$	$(S_1, 1, 4) \Rightarrow (S, 3, 4)$	$(S_1, 1, 1) \Rightarrow (S, 3, 1)$
$(A, 2, 3) \Rightarrow (S, 1, 3)$	$(A, 2, 4) \Rightarrow (S, 1, 4)$	$(A, 2, 2) \Rightarrow (S, 1, 2)$	$(A, 2, 1) \Rightarrow (S, 1, 1)$
$(A, 3, 4) \Rightarrow (S, 2, 4)$	$(A, 3, 3) \Rightarrow (S, 2, 3)$	$(A, 3, 2) \Rightarrow (S, 2, 2)$	$(A, 3, 1) \Rightarrow (S, 2, 1)$
$(S, 2, 3) \Rightarrow (S_1, 2, 4)$	$(S, 1, 3) \Rightarrow (S_1, 1, 4)$	$(S, 3, 3) \Rightarrow (S_1, 3, 4)$	$(S, 4, 3) \Rightarrow (S_1, 4, 3)$
$(S, 3, 4) \Rightarrow (S_1, 3, 3)$	$(S, 4, 4) \Rightarrow (S_1, 4, 3)$	$(S, 2, 4) \Rightarrow (S_1, 2, 3)$	$(S, 1, 4) \Rightarrow (S_1, 1, 3)$

Grid:

- (4) For each $v \in V$ create M_G^v : unique instance of M_G .
 - (5) New graph G' is a graph G where each label t is replaced with t_j^i and some additional edges are created:
 - Add an edge (v', S_i, v) for each $v \in V$.
 - And the respective M_G^v for each $v \in V$:
 - reattach all edges outgoing from x^v ("start" vertex of M_G^v) to v ;
 - reattach all edges incoming to y^v ("final" vertex of M_G^v) to v .
- New input graph is ready:
- (6) New grammar $\mathcal{G}' = (\Sigma', N', P', S')$ where $\Sigma' = \Sigma_0 \cup N_0$, $N' = \{S'\}$, $P' = \{S' \rightarrow b_i S' b_j; S' \rightarrow b_i b_j \mid b_i, b_j \in \Sigma'\} \cup \{S' \rightarrow S' S'\}$ is a set of productions, $S' \in N'$ is a start nonterminal.

Now, if $\text{CFPQ}(\mathcal{G}', G')$ contains a pair (u'_0, v') such that $e = (u'_0, S_i, u'_1) \in E'$ is an extension edge (step 5, first subitem), then $(u'_1, v') \in \text{CFPQ}(\mathcal{G}, G)$.

In our example, we can find the following path: $7 \xrightarrow{S_i} 1 \xrightarrow{S_j} 22 \xrightarrow{b_i} 25 \xrightarrow{C_i} 26 \xrightarrow{a_i} 1 \xrightarrow{a_i} 2 \xrightarrow{C_i} 33 \xrightarrow{C_i} 34 \xrightarrow{C_i} 2 \xrightarrow{C_i} 3 \xrightarrow{C_i} 43 \xrightarrow{C_i} 3 \xrightarrow{C_i} 4 \xrightarrow{b_i} 5$. Edge $7 \xrightarrow{S_i} 1$ is the extension, so $(1,5)$ should be in $\text{CFPQ}(\mathcal{G}, G)$ and it is true.

3 GRAPH INPUT


Let the input grammar is

$$\begin{aligned} S &\rightarrow a S b \\ S &\rightarrow a b \end{aligned}$$

The input grammar in CNF is

$$\begin{aligned} S &\rightarrow A S_1 \\ S_1 &\rightarrow S B \\ S &\rightarrow A B \\ A &\rightarrow a \\ B &\rightarrow b \end{aligned}$$


Let the input graph is



We should introduce the *id* implication such that for every $A \in \text{IMPLIED}$

- $id \times A = A \times id$

In order to compute transitive closure in logarithmic time we add self-loop with weight $\{id\}$ to each vertex.







Figure 2: The same generation query (Query 2) in Meerkat



Note that our graph is a Cartesian product of the graph H and V with respective matrices.

$H =$

$$\begin{pmatrix} \{id\} & \emptyset & \emptyset & \emptyset \\ \emptyset & \{id\} & \emptyset & \emptyset \\ \emptyset & \emptyset & \{id\} & \{(A, S); (S, S_1)\} \\ \emptyset & \emptyset & \{(A, S); (S, S_1)\} & \{id\} \end{pmatrix}$$

$V =$

$$\begin{pmatrix} \{id\} & \emptyset & \emptyset & \emptyset \\ \emptyset & \{id\} & \{(B, S); (S_1, S)\} & \emptyset \\ \emptyset & \emptyset & \{id\} & \{(B, S); (S_1, S)\} \\ \emptyset & \{(B, S); (S_1, S)\} & \emptyset & \{id\} \end{pmatrix}$$

Matrix of $G = V \otimes I + I \otimes H$ where I is identity matrix of size $n \times n$ and \otimes is a Kronecker product.

One step is APSP (or transitive closure) of G . It can be computed as $(V \otimes I + I \otimes H)^{(n^2)}$. It can be "over approximated" as $M = (V^{(n^2)} \otimes I + V^{(n^2)} \otimes H^{(n^2)} + I \otimes H^{(n^2)})$. Now we should check validity of nonterminals. It can be done by multiplication of vector x and M . $x * (V^{(n^2)} \otimes I + V^{(n^2)} \otimes H^{(n^2)} + I \otimes H^{(n^2)}) = x * V^{(n^2)} \otimes I + x * V^{(n^2)} \otimes H^{(n^2)} + x * I \otimes H^{(n^2)}$.

It is known that $(B \otimes C) * \text{vec}(X) = Y \equiv C * X * B^T = Y$. Hence $\text{vec}(X) * (B \otimes C) = Y \equiv C^T * X^T * B^T$. As a result, we can compute distance matrix as $I^T * X * V^{(n^2)} + (H^{(n^2)})^T * X * V^{(n^2)} + (H^{(n^2)})^T * X * I$.

$H^2 =$

$$\begin{pmatrix} \{id\} & \emptyset & \emptyset & \emptyset \\ \emptyset & \{id\} & \{(A, S); (S, S_1)\} & \emptyset \\ \emptyset & \emptyset & \{id; (A, S_1)\} & \{(A, S); (S, S_1)\} \\ \emptyset & \emptyset & \{(A, S); (S, S_1)\} & \{id; (A, S_1)\} \end{pmatrix}$$

$H^4 = H^2$

$(H^2)^T =$

$$\begin{pmatrix} \{id\} & \emptyset & \emptyset & \emptyset \\ \{(A, S); (S, S_1)\} & \emptyset & \emptyset & \emptyset \\ \{id; (A, S_1)\} & \emptyset & \emptyset & \emptyset \\ \{(A, S); (S, S_1)\} & \emptyset & \emptyset & \emptyset \end{pmatrix}$$

$V^2 =$

$$\begin{pmatrix} \{id\} & \emptyset & \emptyset & \emptyset \\ \emptyset & \{id\} & \{(B, S); (S_1, S)\} & \emptyset \\ \emptyset & \{(B, S); (S_1, S)\} & \{id\} & \emptyset \\ \emptyset & \emptyset & \emptyset & \{id\} \end{pmatrix}$$

$V^4 = V^2$

$$\begin{pmatrix} \{id\} & \emptyset & \emptyset & \emptyset \\ \emptyset & \{id\} & \{(B, S); (S_1, S)\} & \emptyset \\ \emptyset & \{(B, S); (S_1, S)\} & \{id\} & \emptyset \\ \emptyset & \emptyset & \emptyset & \{id\} \end{pmatrix}$$

$X^T =$

$$\begin{pmatrix} \emptyset & \{(\perp, A)\} & \emptyset & \emptyset \\ \emptyset & \emptyset & \{(A, S); (S, S_1)\} & \emptyset \\ \emptyset & \emptyset & \emptyset & \{(\perp, B)\} \\ \emptyset & \{(\perp, B)\} & \emptyset & \emptyset \end{pmatrix}$$

$X^T * V^2 =$

$$\begin{pmatrix} \emptyset & \{(\perp, A); (S, S_1)\} & \emptyset & \emptyset \\ \emptyset & \emptyset & \emptyset & \{(\perp, A)\} \\ \{(\perp, B)\} & \emptyset & \{(\perp, A)\} & \emptyset \\ \emptyset & \{(\perp, B)\} & \{(\perp, S)\} & \emptyset \end{pmatrix}$$

$(H^2)^T * X^T =$


$$\begin{pmatrix} \emptyset & \{(\perp, A)\} & \emptyset & \emptyset \\ \emptyset & \emptyset & \emptyset & \{(\perp, A)\} \\ \{(\perp, B)\} & \emptyset & \{(\perp, A); (\perp, S_1)\} & \emptyset \\ \emptyset & \{(\perp, B)\} & \{(\perp, S)\} & \emptyset \end{pmatrix}$$

$(H^2)^T * X^T * V^2 =$

$$\begin{pmatrix} \emptyset & \{(\perp, A)\} & \emptyset & \emptyset \\ \emptyset & \emptyset & \emptyset & \{(\perp, A)\} \\ \{(\perp, B)\} & \emptyset & \{(\perp, A); (\perp, S_1)\} & \{(\perp, S)\} \\ \emptyset & \{(\perp, B)\} & \{(\perp, S)\} & \emptyset \end{pmatrix}$$

$(X^T * V^2 + (H^2)^T * X^T * V^2 + (H^2)^T * X^T)^T =$

$$\begin{pmatrix} \emptyset & \emptyset & \{(\perp, B)\} & \emptyset \\ \{(\perp, A)\} & \emptyset & \emptyset & \{(\perp, B)\} \\ \emptyset & \emptyset & \{(\perp, A); (\perp, S_1)\} & \{(\perp, S)\} \\ \emptyset & \{(\perp, A)\} & \{(\perp, S)\} & \emptyset \end{pmatrix}$$


 $H =$

$$\begin{pmatrix} \{id\} & \emptyset & \emptyset & \emptyset \\ \emptyset & \{id\} & \{(A, S)\} & \emptyset \\ \emptyset & \emptyset & \{id\} & \{(A, S); (S, S_1)\} \\ \emptyset & \emptyset & \{(A, S); (S, S_1)\} & \{id\} \end{pmatrix}$$

 $V =$

$$\begin{pmatrix} \{id\} & \emptyset & \{(B, S_1)\} & \emptyset \\ \emptyset & \{id\} & \{(B, S); (S_1, S)\} & \{(B, S_1)\} \\ \emptyset & \emptyset & \{id\} & \{(B, S); (S_1, S)\} \\ \emptyset & \{(B, S); (S_1, S)\} & \emptyset & \{id\} \end{pmatrix}$$

REFERENCES

- [1] Krishnendu Chatterjee, Bhavya Choudhary, and Andreas Pavlogiannis. 2017. Optimal Dyck Reachability for Data-dependence and Alias Analysis. *Proc. ACM Program. Lang.* 2, POPL, Article 30 (Dec. 2017), 30 pages. <https://doi.org/10.1145/3158118>