

# Closure of Context-Free Languages Under Intersection With Regular Languages is Mechanized in Coq

Ley  
Position1  
Department1  
Institution1  
City1, State1, Saint-Petersburg  
gkerfimf@gmail.com

1

databases, for example, it may be necessary for reasoning on security aspects and, thus, we should create certified solutions for query executing. Certified parsing may be critical for Web [? ], as far as certified regular expressions for input validation. As a result we can find big a number of works on regular expressions mechanization and certification [? ], and number of certified parsers [? ]. On the other hand, mechanization (formalization) is important itself as theoretical results mechanization and verification, and many work done on formal languages theory mechanization [? ]. Also it is important to have a base for reasoning about parsing algorithms and other problems on languages intersection.

It is the well-known fact that context-free languages are closed under intersection with regular languages. Theoretical result is the Bar-Hillel theorem [3] which has constructive proof and provides construction for resulting language description. Thus the Bar-Hillel theorem mechanization is a good start point for certified application development and important part of formal language theory mechanization as one of fundamental results. And this work is aimed to provide such mechanization in Coq.

Our current work is a first step: we provide mechanization of theoretical results on context-free and regular languages intersection. We choose Smolka's and !!! results on context-free languages mechanization [? ] as a base for our work. The main contribution of this paper may be summarized as follows.

- We provide constructive proof of the Bar-Hillel theorem in Coq.
- We generalize Smolka's CFL results: terminals is abstract types....
- All code are published on GitHub: [https://github.com/YaccConstructor/YC\\_in\\_Coq](https://github.com/YaccConstructor/YC_in_Coq).

This work is organized as follows. First of all, in the section ?? we formulate Bar-Hillel theorem and provide sketch of it's proof. The next part is brief discussion of the Chomsky normal form in section ?. After that we describe our solution in the section ?. This description is splitted into steps with respect to provided sketch and contains basic definitions, Smolka's results generalization, trivial cases handling, and steps summarization as a final proof. Finally we discuss related works in the section ?? and provide some discussion of presented work and possible directions for future research in the section ?.

## 2 Bar-Hillel Theorem

Original Bar-Hillel theorem and proof which we use as base. We work with the next formulation of the theorem.

**Lemma 2.1.** *If  $L$  is a context free language and  $\varepsilon \notin L$  then there is grammar in Chomsky Normal Form that generates  $L$ .*

**Lemma 2.2.** *If  $L \neq \emptyset$  and  $L$  is regular then  $L$  is the union of regular language  $A_1, \dots, A_n$  where each  $A_i$  is accepted by a DFA with exactly one final state.*

**Theorem 2.3.** *If  $L_1$  is a context free language and  $L_2$  is a regular language then  $L_1 \cap L_2$  is context free.*

Sketch of the proof:

1. By lemma 2.1 we can assume that there is a context-free grammar  $G_{CNF}$  in Chomsky normal form, such that  $L(G_{CNF}) = L_1$
2. By lemma 2.2 we can assume that there is a set of regular languages  $\{A_1 \dots A_n\}$  where each  $A_i$  is recognized by a DFA with exactly one final state and  $L_2 = A_1 \cup \dots \cup A_n$
3. For each  $A_i$  we can explicitly define a (?) grammar of the intersection:  $L(G_{CNF}) \cap A_i$
4. Finally, we join them together with the (?) operation of union

## 3 The Chomsky Normal Form

One of important part of our proof is the fact that any context-free language can be described with grammar in Chomsky Normal Form (CNF) or, equally, any context-free grammar can be converted in grammar in CNF which specifies the same language. Let us remind the definition of CNF and main steps of algorithm for CFG to CNF conversion.

**Definition 3.1** (Chomsky Normal Form). Let define that context-free grammar is in CNF if:

- start nonterminal is not occurs in right side of rules,
- all rules have one of the next form:  $N_i \rightarrow t_i$ ,  $N_i \rightarrow N_j N_k$  or  $S \rightarrow \varepsilon$  where  $N_i, N_j, N_k$  are nonterminals,  $t_i$  is terminal and  $S$  is start nonterminal.

Steps of transformation.

1. Eliminate the start symbol from right-hand sides of rules.
2. Eliminate rules with nonsolary terminals
3. Eliminate rules which right-hand side contains more than two nonterminals
4. Delete  $\varepsilon$ -rules.
5. Eliminate unit rules.

As far as Bar-Hillel theorem operates with arbitrary context-free languages but proof requires grammar CNF, it is necessary to create certified algorithm for arbitrary CFG to CNF conversion. We want to reuse existing proof of conversion of arbitrary context-free grammar to CNF. We choose Smolka's version which contains proof for conversion to CNF in the next form.

CNF!!!

Listing 1. TODO

## 4 B-H in Coq

In this section we describe in detail all the fundamental parts of the proof. Also in this section, we briefly describe motivation to use the chosen definitions. In addition, we discuss the advantages and disadvantages of using of third-party proofs.

Overall goal of this section is to provide step-by-step algorithm of constructing the CNF grammar of the intersection of two languages. Final formulation of the obtained theorem can be found in the last subsection.

All code are published on GitHub <sup>1</sup>.

### 4.1 Smolka's code generalization

In this section, we describe the exact steps taken to use the proof of TODO:Smolka's theorem in the proof of this article's theorem.

A substantial part of this proof relies on the work of TODO:Smolka. From this work(?) many definitions and theorems were taken. Namely, the definition of a grammar, definitions of a derivation in grammar, some auxiliary lemmas about the decidability of properties of grammar/derivation, we also use the theorem that states that there always exists the transformation from context-free grammar to grammar in Chomsky Normal Form (CNF).

However, this proof had one major flaw that we needed to fix. One could define a terminal symbol as in inductive type over natural numbers[TODO].

```
Inductive ter : Type := | T : nat -> ter.
```

Listing 2. TODO

That is how it was done in TODO:Smolka. However for purposes of our proof, we need to consider nonterminals over the alphabet of triples. Therefore, it was decided to add polymorphism over the target alphabet. Namely, let  $Tt$  and  $Vt$  be types with decidable relation of equality, then we can define the types of terminal and nonterminal over alphabets  $Tt$  and  $Vt$  respectively as follows (???)

```
Inductive ter : Type := | T : Tt -> ter.
Inductive var : Type := | V : Vt -> var.
```

Listing 3. TODO

The proof of Smolka has a clear structure, therefore only part of the proof where the use of natural numbers was essential has become incorrect. One of the grammar transformations (namely deletion of long rules) requires the creation of many new non-terminals. In the original proof for this purpose, the maximum over non-terminals included in the

<sup>1</sup>[https://github.com/YaccConstructor/YC\\_in\\_Coq](https://github.com/YaccConstructor/YC_in_Coq)

grammar was used. However, it is impossible for an arbitrary type.

To tackle this problem we introduce an additional assumption on alphabet types for terminals and nonterminals. We require an existence of the bijection between natural numbers and alphabet of terminals as well as nonterminals.

Another difficulty is that the original work defines grammar as a list of rules (without a distinct starting nonterminal). Thus, in order to define the language that is defined by a grammar, one needs to specify the grammar and a starting terminal. This leads to the fact that the theorem about the equivalence of a CF grammar and the corresponding CNF grammar isn't formulated in the most general way, namely it guarantees equivalence only for non-empty words.

```
Lemma language_normal_form
  (G: grammar) (A: var) (u: word):
  u <> [] ->
  (language G A u <->
   language (normalize G) A u).
```

Listing 4. TODO, CHECK

Changes in the definition of grammar or language would lead to significant code corrections. However, the question of whether the empty word is derivable is decidable for both the CF grammar and the DFA. Therefore, it is possible to simply consider two cases (1) when the empty word is derivable in the grammar and (2) when the empty word is not derivable.

### 4.2 Part ..: derivation and so on

In this section, we introduce the basic definitions used in the article.

We define a symbol is either a terminal or a nonterminal.

```
Inductive symbol : Type :=
| Ts : ter -> symbol
| Vs : var -> symbol.
```

Listing 5. TODO

Next we define a word and a phrase as lists of terminals and symbols respectively.

```
Definition word := list ter.
Definition phrase := list symbol.
```

Listing 6. TODO

The notion of nonterminal doesn't make sense for DFA, but in order to construct derivation in grammar we need to use nonterminal in intermediate states. For phrases, we

introduce a predicate that defines whenever a phrase consists of only terminals. And if so, the phrase it can be safely converted to the corresponding word.

We inheriting the definition of CFG from [Smplka] paper. Rule is defined as a pair of a nonterminal and a list of symbols. Grammar is a list of rules.

```

Inductive rule : Type :=
| R : var -> phrase -> rule.

Definition grammar := list rule.

```

#### Listing 7. TODO

An important step towards the definition of a language (?) governed (formed?)(?) by a grammar is the definition of derivability. Having  $der(G, A, p)$  — means that phrase  $p$  is derivable in grammar  $G$  starting from(?) nonterminal  $A$ .

```

Inductive der (G : grammar)
  (A : var) : phrase -> Prop :=
| vDer : der G A [Vs A]
| rDer l : (R A l) el G -> der G A l
| replN B u w v :
  der G A (u ++ [Vs B] ++ w) ->
  der G B v -> der G A (u ++ v ++ w).

```

#### Listing 8. TODO

Proof of TODO requires grammar to be in CNF. We used statement that every grammar in convertible into CNF from TODO:Smolka work.

... ..

### 4.3 General scheme of the proof

General scheme of our proof is based on constructive proof presented by [? ]. In the following subsections the main steps of the proof are presented. Overall, we will adhere to the following plan.

1. First we consider trivial case, when DFA has no state (TODO: del this?)
2. Every CF language can be converted to CNF
3. Every DFA can be presented as an union of DFAs with single final state
4. Intersecting grammar in CNF with DFA with one final state
5. Proving than union of CF languages is CF language

### 4.4 Part one: trivial case

(TODO: del?)

### 4.5 Part two: regular language and automata

In this section we describe definitions of DFA and DFA with exactly one final state, we also present function that converts any DFA to a set of DFA with one final state and lemma that states this split is well-defined(?).

We assume that regular language by definition is described by DFA. As the definition of an DFA, we have chosen a general definition, which does not impose any restrictions on the type of input symbols and the number of states. Thus, in our case, the DFA is a 5-tuple, (1) a state type, (2) a type of input symbols, (3) a start state, (4) a transition function, and (5) a list of final states.

```

Context {State T: Type}.
Record dfa: Type :=
mkDfa {
  start: State;
  final: list State;
  next: State -> (@ter T) -> State;
}.

```

#### Listing 9. TODO

Next we define a function that would evaluate the final state of the automaton if it starts from state  $s$  and receives a word  $w$ .

```

Fixpoint final_state
  (next_d: dfa_rule)
  (s: State)
  (w: word): State :=
match w with
| nil => s
| h :: t => final_state next_d (next_d s h) t
end.

```

#### Listing 10. TODO

We say that the automaton accepts a word  $w$  being in state  $s$  if the function  $[final\_state\_sw]$  ends in one of the final states. Finally, we say that an automaton accepts a word  $w$ , if the DFA starts from the initial state and ends in one of the final states.

In order to define the DFA with exactly one final state, it is necessary to replace the list of final states by one final state in the definition of an(?) ordinary DFA. The definitions of "accepts" and "dfa\_language" vary slightly.

Similarly, we can define functions  $s\_accepts$  and  $s\_dfa\_language$  for sDFA. Since in this case, there is only one final state, to define function  $s\_accepts$  it is enough to check the state in which the automaton stopped with the finite state. The function  $s\_dfa\_language$  repeats the function  $dfa\_language$ , except that the function must use  $s\_accepts$  instead of accepts.



```

441 Record s_dfa : Type :=
442   s_mkDfa {
443     s_start: State;
444     s_final: State;
445     s_next: State -> (@ter T) -> State;
446   }.

```

#### Listing 11. TODO

Now we can define a function that converts an ordinary DFA into a set of DFAs with exactly one final state. Let  $d$  be a dfa. Then the list of its final states is known. For each such state, one can construct a copy of the original dfa, but with one current final state.

```

456 Fixpoint split_dfa_list
457   (st_d : State)
458   (next_d : dfa_rule)
459   (f_list : list (State)): list (s_dfa) :=
460 match f_list with
461 | nil => nil
462 | h :: t => (s_mkDfa st_d h next_d)
463           :: split_dfa_list st_d next_d t
464 end.

```

```

466 Definition split_dfa (d: dfa) :=
467   split_dfa_list (start d) (next d) (final d).

```

#### Listing 12. TODO

```

472 Lemma correct_split:
473   forall dfa w,
474     dfa_language dfa w <=>
475     exists sdfa,
476       In sdfa (split_dfa dfa) /\
477       s_dfa_language sdfa w.

```

#### Listing 13. TODO

We prove theorem that the function of splitting preserves the language.

**Theorem 4.1.** *Let  $dfa$  be an arbitrary dfa and  $w$  be a word. Then the fact that  $dfa$  accepts  $w$  implies that there exists a single-state dfa  $s\_dfa$ , such that  $s\_dfa \in split\_dfa(dfa)$ . And vice versa, For any  $s\_dfa \in split\_dfa(dfa)$  the fact that  $s\_dfa$  accepts a word  $w$  implies that  $dfa$  also accepts  $w$ .*

**Proof.**

#### 4.6 Part ..: Chomsky induction

In this section, we introduce the notion of Chomsky induction.

Naturally many statements about properties of language's words can be proved by induction over derivation structure. Unfortunately, grammar can derive phrase as an intermediate step, but DFA supposed to work only with words, so we can't simply apply induction over derivation structure. To tackle this problem we create custom induction principle for grammars in CNF.

The main point is that if we have a grammar in CNF, we can always divide the word into two parts, each of which is derived only from one nonterminal. Note that if we naively take a step back, we can get nonterminal in the middle of the word. Such a situation will not make any sense for DFA.

With induction we always work with subtrees that describes some part of word. Here is a picture of subtree describing intuition behind the Chomsky induction.

TODO: add picture

TODO: add Lemma derivability\_backward\_step.

More formally: Let  $G$  be a grammar in CNF. Consider an arbitrary nonterminal  $N \in G$  and phrase which consists only on terminals  $w$ . If  $w$  is derivable from  $N$  and  $|w| \geq 2$ , then there exist (TODO:s) two nonterminals  $N_1, N_2$  and subphrases of  $w - w_1, w_2$  such that:  $N \rightarrow N_1 N_2 \in G$ ,  $der(N_1, w_1)$ ,  $der(N_2, w_2)$ ,  $|w_1| \geq 1$ ,  $|w_2| \geq 1$  and  $w_1 ++ w_2 = w$ .

**Proof.**

Let  $G$  be a grammar in CNF. And  $P$  be a predicate on nonterminals and phrases (i.e.  $P : var \rightarrow phrase \rightarrow Prop$ ). Let us also assume that the following two hypotheses are satisfied: (1) for every terminal production (i.e. in the form  $N \rightarrow a$ ) of grammar  $G$ ,  $P(r, [Tsr])$  and (2) for every  $N, N_1, N_2 \in G$  and two phrases which consist only of terminals  $w_1, w_2$ , if  $P(N_1, w_1)$ ,  $P(N_2, w_2)$ ,  $der(G, N_1, w_1)$  and  $der(G, N_2, w_2)$  then  $P(N, w_1 ++ w_2)$ . Then for any nonterminal  $N$  and any phrase consisting only of terminals  $w$ , the fact that  $w$  is derivable from  $N$  implies  $P(N, w)$ .

**Proof?.** There is a constant  $n$  such that  $|w| \leq n$ . We prove the statement by induction on  $n$ .

Base:  $n = 0$ ,

Induction step:

TODO: add some text

As one might notice, TODO

#### 4.7 Part ..: intersection

Since we already have lemmas about the transformation of a grammar to CNF and the transformation a DFA to a DFA with exactly one state, further we assume that we have (1) DFA with exactly one final state —  $dfa$  and (2) grammar in CNF —  $G$ . In this section, we describe the proof of the lemma, which states that for any grammar in CNF and any automaton with exactly one state, there is the intersection grammar.

#### 4.7.1 Function

Next we present adaptation of the algorithm given in [].

Let  $G_{INT}$  be the grammar of intersection. In  $G_{INT}$  nonterminals presented as triples  $(from \times var \times to)$  where  $from$  and  $to$  are states of  $dfa$ , and  $var$  is a nonterminal of(in?)  $G$ .

Since  $G$  is a grammar in CNF, it has only two type of productions: (1)  $N \rightarrow a$  and (2)  $N \rightarrow N_1 N_2$ , where  $N, N_1, N_2$  are nonterminals and  $a$  is a terminal.

For every production  $N \rightarrow N_1 N_2$  in  $G$  we generate a set of productions of the form  $(from, N, to) \rightarrow (from, N_1, m)(m, N_2, to)$  where:  $from, m, to$  — goes through all  $dfa$  states.

```

Definition convert_nonterm_rule_2
  (r r1 r2: _)
  (state1 state2 : _) :=
  map (fun s3 => R (V (s1, r, s3))
    [Vs (V (s1, r1, s2));
     Vs (V (s2, r2, s3))])
    list_of_states.

```

```

Definition convert_nonterm_rule_1
  (r r1 r2: _)
  (s1 : _) :=
  flat_map (convert_nonterm_rule_2 r r1 r2 s1)
    list_of_states.

```

```

Definition convert_nonterm_rule (r r1 r2: _) :=
  flat_map (convert_nonterm_rule_1 r r1 r2)
    list_of_states.

```

#### Listing 14. TODO

For every production of the form  $N \rightarrow a$  we add a set of productions  $(from, N, (dfa\_step(from, a))) \rightarrow a$  where:  $from$  — goes through all  $dfa$  states and  $dfa\_step(from, a)$  is the state in which the  $dfa$  appears after receiving terminal  $a$  in state  $from$ .

```

Definition convert_terminal_rule
  (next: _)
  (r: _)
  (t: _): list TripleRule :=
  map (fun s1 => R (V (s1, r, next s1 t)) [Ts t])
    list_of_states.

```

#### Listing 15. TODO

Next we join the functions above to get a generic function that works for both types of productions. Note that since the grammar is in CNF,(?) the third alternative can never be the case.

Note that at this point we do not have any manipulations with starting rules. Nevertheless(?), the hypothesis of the

```

Definition convert_rule (next: _) (r: _ ) :=
  match r with
  | R r [Vs r1; Vs r2] =>
    convert_nonterm_rule r r1 r2
  | R r [Ts t] =>
    convert_terminal_rule next r t
  | _ => [] (* Never called *)
  end.

Definition convert_rules
  (rules: list rule) (next: _): list rule :=
  flat_map (convert_rule next) rules.

(* Maps grammar and s_dfa to grammar over triples *)
Definition convert_grammar grammar s_dfa :=
  convert_rules grammar (s_next s_dfa).

```

#### Listing 16. TODO

uniqueness of the final state of the DFA, will help us unambiguously introduce the starting nonterminal of the grammar of intersection.

#### 4.7.2 Correctness

TODO: add some text

In the interest of clarity of exposition, we skip some auxiliary lemmas, such as "we can get the initial grammar from the grammar of intersection by projecting the triples back to terminals/nonterminals ". Also note that the grammar after the conversion remains in CFN. Since the transformation of rules does not change the structure of the rules, but only replaces one(?!?) terminals and nonterminals with others.

Next we prove the two main lemmas. Namely, the derivability in the initial grammar and the  $s\_dfa$  implies the derivability in the grammar of intersection. And the other way around, the derivability in the grammar of intersection implies the derivability in the initial grammar and the  $s\_dfa$ .

Let  $G$  be a grammar in CNF. In order to use Chomsky Induction we also assume that syntactic analysis is possible.

**Theorem 4.2.** *Let  $s\_dfa$  be an arbitrary DFA, let  $r$  be a nonterminal of grammar  $G$ , let  $from$  and  $to$  be two states of the DFA. We also pick an arbitrary word —  $w$ . If in grammar  $G$  it is possible to derive  $w$  out of  $r$  and starting from the state  $from$  when  $w$  is received, the  $s\_dfa$  ends up in state  $to$ , then word  $w$  is also derivable in grammar  $(convert\_rules\ G\ next)$  from the nonterminal  $(V\ (from, r, to))$ .*

**Proof.** TODO. In another case, it would be logical to use induction on the derivation structure in  $G$ . But as it was discussed earlier, this is not the case, otherwise we will get a phrase (list of terminals and nonterminals) instead of a word.

Let's apply chomsky induction principle with

$$P := \text{funrphr} \Rightarrow \forall (\text{next} : \text{dfa\_rule})(\text{fromto} : \text{DfaState}),$$

$$\text{final\_statenextfrom}(\text{to}_w \text{ordphr}) = \text{to} \rightarrow$$

$$\text{der}(\text{convert\_rulesGnext})(V(\text{from}, r, \text{to}))\text{phr}.$$

We will get the bla-bla, bla-bla, bla-bla-bla

Since a language is just a bla-bla-bla, we use the lemma above to prove bla-bla-bla

#### 4.8 Part ..: union

After the previous step, we have a list of grammars of CF languages, in this section, we provide a function by which we construct a grammar of the union of languages.

For this, we need nonterminals from every language to be from different nonintersecting sets. To achieve this we add labels to nonterminals. Thus, each grammar of the union would have its own unique ID number, all nonterminals within one grammar will have the same ID which coincides with the ID of a grammar. In addition, it is necessary to introduce a new starting nonterminal of the union.

```
Inductive labeled_Vt : Type :=
| start : labeled_Vt
| lV : nat -> Vt -> labeled_Vt.
```

```
Definition label_var (label: nat)
(v: @var Vt): @var
labeled_Vt :=
V (lV label v).
```

#### Listing 17. TODO

Construction of new grammar is quite simple. The function that constructs the union grammar takes a list of grammars, then, it (1) splits the list into head  $[h]$  and tail  $[tl]$ , (2) labels  $[length\ tl]$  to  $h$ , (3) adds a new rule from the start nonterminal of the union to the start nonterminal of the grammar  $[h]$ , finally (4) the function is recursively called on the tail  $[tl]$  of the list.

##### 4.8.1 Equivalence proof

In this section, we prove that function *grammar\_union* constructs a correct grammar of union language indeed. Namely, we prove the following theorem.

**Theorem 4.3.** *Let grammars be a sequence of pairs of starting nonterminals and grammars. Then for any word  $w$ , the fact that  $w$  belongs to language of union is equivalent to the fact that there exists a grammar  $(st, gr) \in grammars$  such that  $w$  belongs to language generated by  $(st, gr)$ .*

**Proof of theorem 4.3.** Since the statement is formulated as an equivalence, we divide the proof into two parts:

1. If  $w$  belongs to the union language, then  $w$  belongs to one

**Definition** label\_grammar label grammar := ...

**Definition** label\_grammar\_and\_add\_start\_rule

```
label
grammar :=
let '(st, gr) := grammar in
(R (V start) [Vs (V (lV label st))])
:: label_grammar label gr.
```

**Fixpoint** grammar\_union

```
(grammars : seq (@var Vt * (@grammar Tt Vt)))
: @grammar
Tt
labeled_Vt :=
match grammars with
| [] => []
| (g::t) =>
label_grammar_and_add_start_rule
(length t)
g ++ (grammar_union t)
end.
```

#### Listing 18. TODO

**Variable** grammars: seq (var \* grammar).

**Theorem** correct\_union:

```
forall word,
language (grammar_union grammars)
(V (start Vt)) (to_phrase word) <=>
exists s_l,
language (snd s_l) (fst s_l)
(to_phrase word) /\
In s_l grammars.
```

#### Listing 19. TODO

of the initial language.

2. If  $w$  belongs to one of the initial language, then  $w$  belongs to the union language.

The fact that  $(st, grammar) \in grammars$  implies that there exist  $gr1$  and  $gr2$  such that:  $gr1 + +(st, grammar) :: gr2 = grammars$ .

Proof. This proved through induction over  $l$ . assume  $l = h :: t$ , then either word accepted by  $h$  or tail. If word accepted by  $h$  If word accepted by  $l$ . We just proving that adding one more language to union preserves word derivability. Which is equivalent to proving that adding new rules to grammar preserves word derivability

2. If we have derivation for some word in new grammar lanager we can provide derivate in for some language from union.

Proof. Here we converting derivability procedure for language union into derivability procedure of one of language. Then we proving that in derivation we can use rules from only one language at time. Finally we converting derivation by simple relabelling back all nonterminals.

#### 4.9 Part N: taking all parts together

TODO: add some text

**Theorem 4.4.** *For any two decidable types Terminal and Non-terminal for type of terminals and nonterminals correspondingly. If there exists bijection from Nonterminal to  $\mathbb{N}$  and syntactic analysis in the sense of definition TODO is possible, then for any DFA dfa which accepts Terminal and any grammar G, there exists the grammar of intersection  $L(\text{DFA})$  and G.*

Proof.

## 5 Related Works

There is a big number of works in mechanization of different parts of formal languages theory and certified implementations of parsing algorithms and algorithms for graph data base querying. These works use different tools, such as Coq, Agda, Isabelle/HOL, and aimed to different problems such as theory mechanisation or executable algorithm certification.

Huge work was done by Ruy de Queiroz who formalize different parts of formal language theory, such as pumping lemma [19], context-free grammar simplification [19] and closure properties [18] in Coq. All these results are summarized in [20].

Another part of formal languages formalization in Coq by Gert Smolka et.al. [5, 6].

Also exist some works by Denis Firsov who implement in Agda many parts of formal language theory and parsing algorithms: CYK [8], Chomsky Normal Form [9], etc [7].

Certified parsers parser generators.

In HOL4.

Certified prolog querying in Coq [4]

## 6 Conclusion

We present mechanized proof of Bar-Hillel theorem on closure of context-free languages under intersection with regular one. Also we generalize results of Smolka and !!! : generalized terminal alphabet. It makes More flexible and ease for reusing. All results are published at GitHub.

One of direction of future research is mechanization of practical algorithms which are just implementation of Bar-Hillel theorem. For example, context-free path querying algorithm, based on CYK [?] or even on GLL [23] parsing algorithm [10]. Final target here is certified CFPQ alike Regular by Vardi

Yet another direction is mechanization of other problems on language intersection which can be useful for applications. For example, intersection of two context-free grammars one

of which describes finite language [15, 16]. It may be useful for compressed data processing.

## Acknowledgments

We are grateful to Ekaterina Verbitskaia for discussion, careful reading, and pointing out some mistakes. The research was supported by the Russian Science Foundation grant No. 18-11-00100 and by the grant from JetBrains Research.

## References

- [1] Serge Abiteboul and Victor Vianu. 1999. Regular Path Queries with Constraints. *J. Comput. System Sci.* 58, 3 (1999), 428 – 452. <https://doi.org/10.1006/jcss.1999.1627>
- [2] Faisal Alkhateeb. 2008. *Querying RDF(S) with Regular Expressions*. Theses. Université Joseph-Fourier - Grenoble I. <https://tel.archives-ouvertes.fr/tel-00293206>
- [3] Yehoshua Bar-Hillel, Micha Perles, and Eli Shamir. 1961. On formal properties of simple phrase structure grammars. *Sprachtypologie und Universalienforschung* 14 (1961), 143–172.
- [4] Angela Bonifati, Stefania Dumbrava, and Emilio Jesús Gallego Arias. 2018. Certified Graph View Maintenance with Regular Datalog. *arXiv preprint arXiv:1804.10565* (2018).
- [5] Christian Doczkal, Jan-Oliver Kaiser, and Gert Smolka. 2013. A constructive theory of regular languages in Coq. In *International Conference on Certified Programs and Proofs*. Springer, 82–97.
- [6] Christian Doczkal and Gert Smolka. 2017. Regular Language Representations in the Constructive Type Theory of Coq. (2017).
- [7] Denis Firsov. 2016. Certification of Context-Free Grammar Algorithms. (2016).
- [8] Denis Firsov and Tarmo Uustalu. 2014. Certified CYK parsing of context-free languages. *Journal of Logical and Algebraic Methods in Programming* 83, 5-6 (2014), 459–468.
- [9] Denis Firsov and Tarmo Uustalu. 2015. Certified normalization of context-free grammars. In *Proceedings of the 2015 Conference on Certified Programs and Proofs*. ACM, 167–174.
- [10] Semyon Grigorev and Anastasiya Ragozina. 2016. Context-Free Path Querying with Structural Representation of Result. *arXiv preprint arXiv:1612.08872* (2016).
- [11] J. Hellings. 2014. Conjunctive context-free path queries. (2014).
- [12] Jelle Hellings. 2015. Querying for Paths in Graphs using Context-Free Path Queries. *arXiv preprint arXiv:1502.02242* (2015).
- [13] André Koschmieder and Ulf Leser. 2012. Regular path queries on large graphs. In *International Conference on Scientific and Statistical Database Management*. Springer, 177–194.
- [14] Yi Lu, Lei Shang, Xinwei Xie, and Jingling Xue. 2013. An incremental points-to analysis with CFL-reachability. In *International Conference on Compiler Construction*. Springer, 61–81.
- [15] Mark-Jan Nederhof and Giorgio Satta. 2002. Parsing non-recursive context-free grammars. In *Proceedings of the 40th Annual Meeting on Association for Computational Linguistics*. Association for Computational Linguistics, 112–119.
- [16] Mark-Jan Nederhof and Giorgio Satta. 2004. The language intersection problem for non-recursive context-free grammars. *Information and Computation* 192, 2 (2004), 172–184.
- [17] Polyvios Pratikakis, Jeffrey S Foster, and Michael Hicks. 2006. Existential label flow inference via CFL reachability. In *International Static Analysis Symposium*. Springer, 88–106.
- [18] Marcus VM Ramos and Ruy JGB de Queiroz. 2015. Formalization of closure properties for context-free grammars. *arXiv preprint arXiv:1506.03428* (2015).
- [19] Marcus VM Ramos, Ruy JGB de Queiroz, Nelma Moreira, and José Carlos Bacelar Almeida. 2015. Formalization of the pumping lemma



- for context-free languages. *arXiv preprint arXiv:1510.04748* (2015).
- [20] Marcus Vinícius Midena Ramos, Ruy JGB de Queiroz, Nelma Moreira, and José Carlos Bacelar Almeida. 2016. On the Formalization of Some Results of Context-Free Language Theory. In *International Workshop on Logic, Language, Information, and Computation*. Springer, 338–357.
- [21] Jakob Rehof and Manuel Fähndrich. 2001. Type-base flow analysis: from polymorphic subtyping to CFL-reachability. *ACM SIGPLAN Notices* 36, 3 (2001), 54–66.
- [22] Thomas Reps, Susan Horwitz, and Mooly Sagiv. 1995. Precise Interprocedural Dataflow Analysis via Graph Reachability. In *Proceedings of the 22Nd ACM SIGPLAN-SIGACT Symposium on Principles of Programming Languages (POPL '95)*. ACM, New York, NY, USA, 49–61. <https://doi.org/10.1145/199448.199462>
- [23] Elizabeth Scott and Adrian Johnstone. 2010. GLL parsing. *Electronic Notes in Theoretical Computer Science* 253, 7 (2010), 177–189.
- [24] Dimitrios Vardoulakis and Olin Shivers. 2010. CFA2: a context-free approach to control-flow analysis. In *European Symposium on Programming*. Springer, 570–589.
- [25] Dacong Yan, Guoqing Xu, and Atanas Rountev. 2011. Demand-driven Context-sensitive Alias Analysis for Java. In *Proceedings of the 2011 International Symposium on Software Testing and Analysis (ISSTA '11)*. ACM, New York, NY, USA, 155–165. <https://doi.org/10.1145/2001420.2001440>
- [26] Qirun Zhang and Zhendong Su. 2017. Context-sensitive Data-dependence Analysis via Linear Conjunctive Language Reachability. *SIGPLAN Not.* 52, 1 (Jan. 2017), 344–358. <https://doi.org/10.1145/3093333.3009848>
- [27] Xiaowang Zhang, Zhiyong Feng, Xin Wang, Guozheng Rao, and Wenrui Wu. 2016. Context-Free Path Queries on RDF Graphs. In *The Semantic Web – ISWC 2016*, Paul Groth, Elena Simperl, Alasdair Gray, Marta Sabou, Markus Krötzsch, Freddy Lecue, Fabian Flöck, and Yolanda Gil (Eds.). Springer International Publishing, Cham, 632–648.