

# Graph Parsing Application for Bioinformatics Problems

*Grammar-based approach for graph structured data analysis*

Semyon Grigorev<sup>1</sup>, Artem Gorokhov<sup>1</sup>, Rustam Azimov<sup>1</sup>

<sup>1</sup>*Saint Petersburg State University, JetBrains, St. Petersburg, Russia*

**E-mail:** [semen.grigorev@jetbrains.com](mailto:semen.grigorev@jetbrains.com)



## Motivation

Biomedical databases contain huge amount of rich data which can be represented as a labelled graph. In order to investigate such data, it may be useful to extract connections with specific constraints. One natural way to provide constraints is to specify the language of paths labels which can be done by using of grammars. For example, one can use context-free grammars with the productions  $\{S \rightarrow aSb; S \rightarrow \varepsilon\}$  to query paths which labels should take form of  $ab; aabb; aaabbb; \dots$ , or, generally, should belong to the language  $L = \{a^n b^n, n \geq 0\}$ . This approach is named *context-free path querying* (or graph parsing) and can be applied to some problems in bioinformatics such as metagenomic assemblies analysis or graph data base querying.

## Context-free path querying

## Database querying

One of the examples of database querying is an analysis of graphs where vertices correspond to entities and concepts such as gene or phenotype while edges represent the known relationships such as “codes for”, “interacts with”, etc.

Example of graph structured data [4] is presented below.

Querying paths with special constraints may shed light upon unknown before links between vertices, forming the basis for new hypotheses.

## References

- [1] Semyon Grigorev and Anastasiya Ragozina. Context-free path querying with structural representation of result. *arXiv preprint arXiv:1612.08872*, 2016.
- [2] Ekaterina Verbitskaia, Semyon Grigorev, and Dmitry Avdyukhin. Relaxed parsing of regular approximations of string-embedded languages. In *International Andrei Ershov Memorial Conference on Perspectives of System Informatics*, pages 291–302. Springer, 2015.
- [3] Rustam Azimov and Semyon Grigorev. Graph parsing by matrix multiplication. *arXiv preprint arXiv:1707.01007*, 2017.
- [4] Petteri Sevon and Lauri Eronen. Subgraph queries by context-free grammars. *Journal of Integrative Bioinformatics (JIB)*, 5(2):157–172, 2008.

## Results

- We propose the graph parsing algorithms based on different parsing techniques [1, 2, 3].
- We solve some problems of existing approaches (such as cycles processing problem, [4]).
- Our solution provides an ability to use GPGPU and multi-core systems for graph parsing which can be useful for large biological data analysis.

### Performance comparison of context-free querying algorithms

| Graph | #edges | #results | GLL(ms) | GPGPU(ms) |
|-------|--------|----------|---------|-----------|
| $g_1$ | 8688   | 141072   | 1926    | 82        |
| $g_2$ | 14712  | 532576   | 6246    | 185       |
| $g_3$ | 15840  | 449560   | 7014    | 127       |

## Future Research

- Currently, we are working on long subsequences of 16s rRNA reconstruction from metagenomic assembly.
- We want to find new applications for context-free graph querying techniques and implement required tools.

## Metagenomic assemblies analysis

Metagenomic assemblies can be presented as graph structured data. Some sequences have specific secondary structure, which can be described in terms of a context-free grammar, and this grammar can be used for searching and classification.

## Acknowledgments

This work is supported by grant from JetBrains Research.

## Information

All materials available on GitHub: <https://github.com/YaccConstructor>