

# Evaluation of the Context-Free Path Querying Algorithm Based on Matrix Multiplication

Nikita Mishin  
Iaroslav Sokolov  
Egor Spirin  
mishinnikitam@gmail.com  
sokolov.yas@gmail.com  
egor@spirin.tech  
Saint Petersburg State University  
7/9 Universitetskaya nab.  
St. Petersburg, Russia 199034

Vladimir Kutuev  
Egor Nemchinov  
Sergey Gorbatyuk  
vladimir.kutuev@gmail.com  
nemchegor@gmail.com  
sergeygorbatyuk171@gmail.com  
Saint Petersburg State University  
7/9 Universitetskaya nab.  
St. Petersburg, Russia 199034

Semyon Grigorev  
s.v.grigoriev@spbu.ru  
semen.grigorev@jetbrains.com  
Saint Petersburg State University  
7/9 Universitetskaya nab.  
St. Petersburg, Russia 199034  
JetBrains Research  
Universitetskaya emb., 7-9-11/5A  
St. Petersburg, Russia 199034

## ABSTRACT

Recently proposed matrix multiplication based algorithm for context-free path querying (CFPQ) offloads the most performance-critical parts onto boolean matrices multiplication. Thus, it is possible to utilize modern parallel hardware and software to achieve high performance of CFPQ easily. In this work, we provide results of empirical performance comparison of different implementations of this algorithm on both real data and synthetic data for the worst cases.

## CCS CONCEPTS

• **Information systems** → **Query languages for non-relational engines**; • **Theory of computation** → **Grammars and context-free languages**; *Parallel computing models*; • **Computing methodologies** → **Massively parallel algorithms**; • **Computer systems organization** → *Single instruction, multiple data*;

## KEYWORDS

Context-free path querying, transitive closure, graph databases, context-free grammar, GPGPU, CUDA, matrix multiplication, boolean matrix

### ACM Reference format:

Nikita Mishin, Iaroslav Sokolov, Egor Spirin, Vladimir Kutuev, Egor Nemchinov, Sergey Gorbatyuk, and Semyon Grigorev. 2018. Evaluation of the Context-Free Path Querying Algorithm Based on Matrix Multiplication. In *Proceedings of GRADES-NDA 2019: the 2nd Joint International Workshop on Graph Data Management Experiences & Systems (GRADES) and Network Data Analytics (NDA) 2019, Amsterdam, Netherlands, June 30, 2019 (GRADES-NDA 2019)*, 5 pages.  
<https://doi.org/10.1145/1122445.1122456>

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for components of this work owned by others than the author(s) must be honored. Abstracting with credit is permitted. To copy otherwise, or republish, to post on servers or to redistribute to lists, requires prior specific permission and/or a fee. Request permissions from [permissions@acm.org](mailto:permissions@acm.org).

GRADES-NDA 2019, June 30, 2019, Amsterdam, Netherlands

© 2018 Copyright held by the owner/author(s). Publication rights licensed to Association for Computing Machinery.

ACM ISBN 978-1-4503-9999-9/18/06...\$15.00  
<https://doi.org/10.1145/1122445.1122456>

## 1 INTRODUCTION

Language-constrained path querying [5], and particularly Context-Free Path Querying (CFPQ) [14] widely used for graph-structured data analysis in such areas as biological data analysis, RDF, network analysis. Huge amount of the real-world data makes performance of CFPQ evaluation critical for practical tasks, and number of algorithms for CFPQ evaluation proposed recently [7, 9, 11–13, 15].

One of the most promising algorithm is a matrix-based algorithm, proposed by Rustam Azimov [4]. This algorithm offloads the most critical computations onto boolean matrices multiplication. As a result, it is pretty simple for implementation and allows one to utilize modern massive-parallel hardware for CFPQs evaluation. Implementation provided by authors utilizes GPGPU by using cuSPARSE<sup>1</sup> library which is floating point sparse matrices multiplication library. Even it does not use advanced algorithms for boolean matrices, it outperforms existing algorithms.

It is necessary to investigate an effect of specific algorithms and implementation techniques on performance of CFPQ. One of problems is that there is no publically available standard dataset for CFPQ algorithms evaluation which includes both graph-structured data and queries.

In this work, we do empirical performance comparison of different implementations of matrices multiplication based algorithm for CFPQ on both real data and synthetic data for the worst cases. We make the following contributions in this paper.

- (1) We provide a number of implementations of the matrix multiplication based CFPQ algorithm, which utilizes different modern software and hardware. Source code is available on GitHub!!!
- (2) We collect and publish a dataset which contains both real data and syntactic data for worst cases. This dataset contains data and queries in the simple textual format, so it can be used for other algorithms evaluation easily. We hope that this dataset can be a base for unified benchmark for CFPQ algorithms.
- (3) We provide evaluation results which shows that !!!

<sup>1</sup>cuSparse is a library for GPGPU utilization for sparse matrices multiplication. Official documentation: <https://docs.nvidia.com/cuda/cusparse/index.html>. Access date: 12.03.2019

## 2 MATRIX-BASED ALGORITHM FOR CFPQ

Matrix-based algorithm for CFPQ was proposed by Rustam Azimov [4]. This algorithm can be expressed in few lines of code in terms of matrices operations, and it is a sufficient advantage for implementation. It was shown that GPGPU utilization for queries evaluation can significantly improve performance in comparison with other implementations [4] even float matrices used instead of boolean matrices.

Pseudocode of the algorithm is presented in listing 1.

---

**Algorithm 1** Context-free path quering algorithm
 

---

```

1: function CONTEXTFREEPATHQUERYING( $D, G$ )
2:    $n \leftarrow$  the number of nodes in  $D$ 
3:    $E \leftarrow$  the directed edge-relation from  $D$ 
4:    $P \leftarrow$  the set of production rules in  $G$ 
5:    $T \leftarrow$  the matrix  $n \times n$  in which each element is  $\emptyset$ 
6:   for all  $(i, x, j) \in E$  do ▷ Matrix initialization
7:      $T_{i,j} \leftarrow T_{i,j} \cup \{A \mid (A \rightarrow x) \in P\}$ 
8:   end for
9:   while matrix  $T$  is changing do
10:     $T \leftarrow T \cup (T \times T)$  ▷ Transitive closure calculation
11:   end while
12:   return  $T$ 
13: end function
  
```

---

Here  $D = (V, E)$  be the input graph and  $G = (N, \Sigma, P)$  be the input grammar. Each cell of the matrix  $T$  contains the set of nonterminals such that  $N_k \in T[i, j] \iff \exists p = v_i \dots v_j$ —path in  $D$ , such that  $N_k \xrightarrow{*}_G \omega(p)$ , where  $\omega(p)$  is a word formed by labels along path  $p$ . Thus, this algorithm solves reachability problem, or, according Hellings [8], process CFPQs by using relational query semantics.

As you can see, performance-critical part of this algorithm is a matrix multiplication. Note, that the set of nonterminals is finite, we can represent the matrix  $T$  as a set of boolean matrices: one for each nonterminal. In this case the matrix update operation be  $T_{N_i} \leftarrow T_{N_i} + (T_{N_j} \times T_{N_k})$  for each production  $N_i \rightarrow N_j N_k$  in  $P$ . Thus we can reduce CFPQ to boolean matrices multiplication. After such transformation we can apply the next optimization: we can skip update if there are no changes in the matrices  $T_{N_j}$  and  $T_{N_k}$  at the previous iteration.

Thus, the most important part is efficient implementation of operations over boolean matrices, and in this work we compare effects of utilization of different approaches to matrices multiplication. All our implementations are based on the optimized version of the algorithm.

## 3 IMPLEMENTATION

We implement matrix-based algorithm for CFPQ by using a number of different programming languages and tools. Our goal is to investigate effects of the next features of implementation.

- **GPGPU utilization.** It is well-known that GPGPUs are suitable for matrices operations, but performance of whole solution depends on task details: overhead on data transferring may negate effect of parallel computations. Can GPGPUs

utilization for CFPQ improve performance in comparison with CPU version?

- **Existing libraries utilization** is a good practice in software engineering. Is it possible to achieve higher performance by using existing libraries for matrices operations or we need to create own solution to get more control?
- **Low-level programming.** GPGPU programming is traditionally low-level programming by using C-based languages (CUDA C, OpenCL C). On the other hand, there are number of approaches to create GPGPU-based solution by using such high-level languages as a Python. Can we get high-performance solution by using such approaches?
- **Sparse matrices.** Real graphs often are sparse, but not always. Is it suitable to use sparse matrix representation for CFPQ?

We provide next implementations for investigation.

- **CPU-based solutions**
  - [**Scipy**] Sparse matrices multiplication by using Scipy [10] in Python programming language.
  - [**M4RI**] Dense matrices multiplication by using m4ri<sup>2</sup> [1] library which implements 4 russian method [3] in C language. This library chosen because it is one of the fastest implementation of 4 russian method [2].
- **GPGPU-based solutions**
  - [**GPU4R**] Manual implementation of 4 russian method in CUDA C.
  - [**GPU\_N**] Manual implementation of naïve boolean matrix multiplication in CUDA C.
  - [**GPU\_Py**] Manual implementation of naïve boolean matrix multiplication in Python by using numba compiler<sup>3</sup>.

As far as number of matrices and its size can be statically defined at the start, all GPGPU based implementations allocate all required memory on the GPGPU only once, at the start of computations. By this way it is possible to significantly reduce overhead on data transferring: all input data loads to GPGPU at the start, and result loads from GPGPU to the host at the finish. No active data transferring and memory allocating during query computation.

## 4 DATASET DESCRIPTION

We create and publish a dataset for CFPQ algorithms evaluation. This dataset contains both the real data and synthetic data for different specific cases, such as theoretical worst case, or matrices representation specific worst cases.

Our goal is querying algorithms evaluation, not a graph storages or graph databases evaluation, so all data is presented in text-based format to simplify usage in different environments. Grammars are in Chomsky Normal Form and are stored in the files with yrd extension. Each line is a rule in form of triple or pair. The example of grammar representation is presented in figure 1

<sup>2</sup>Actually we use pull request which is not merged yet: <https://bitbucket.org/malb/m4ri/pull-requests/9/extended-m4ri-to-multiplication-over-the-diff>. The original library implements operations over  $GF(2)$ , and this pull request contains operations over boolean semiring

<sup>3</sup>Numba is a JIT compiler which supports GPGPU for subset of Python programming. Official page: <http://numba.pydata.org/>. Access date: 03.05.2019




Figure 1: Example of grammar representation in the yrd file

Graphs are represented as a set of triples (edges) and are stored in the files with txt extension. Example of graph is presented in figure 2.




Figure 2: Example of graph representation in txt file

Each case is a pair of set of graphs and set of grammars: each query (grammar) should be applied to each graph. Cases are placed in folders with case-specific name. Grammars and graph are placed in subfolders with names Grammars and Matrices respectively.

It is known that variants of the *same generation query* ?? are classical example of queries that are context-free but not regular, so we use this type of queries in our evaluation. The dataset includes data for next cases.

**[RDF]** The set of real RDF files (ontologies) from [15] and two variants of the same generation query (figures ??) which describes hierarchy analysis.

**[Worst]** Theoretical worst case for CFPQ time complexity which is proposed by Hellings [9]: graph is a two cycles of coprime lengths with single common vertex. First cycle labelled by open bracket and the second cycle is labelled by close bracketed. Query is a grammar for  $A^n B^n$  language (grammar  $G_1$ , figure 1).

**[Full]** The case when input graph is sparse, but result is a full graph. Such case may be a hard for sparse matrices representation. As an input graph we use a cycle all edges of which is labelled by the same token. As a queries we use two grammars which describe arbitrary repetition of a token: unambiguous and highly ambiguous grammar (figure ??).

**[Sparse]** Sparse graphs from [6] which generated by the GT-graph graph generator, and emulates realistic sparse data. Names of these graphs have a form  $G_n-p$ , where  $n$  represents the total number of vertices, each pair of vertices is connected by probability  $p$ . Query is a same generation query.

## 5 EVALUATION

We evaluate all described implementations on all data and queries from presented dataset. Our goal is to compare CFPQ evaluation algorithms, so we exclude time required for load data from files. Time required for data transferring is included.

For evaluation we use PC with the next characteristics.

- OS
- CPU
- RAM
- GPU
  - Name
  - GHz
  - RAM
  - Threads
  - ...

Results of evaluation are presented in tables below. Time is measured in milliseconds. Time for each algorithm is an average time of 10 runs.

First is a **[RDF]** dataset. Results are presented in a table 1.

We can see, that in this case running time for all our implementations smaller than time for reference implementation, and that **[GPU\_N]** is faster than other implementations while other implementations demonstrate similar performance. Also it is obvious that performance improvement in comparison with first implementations is huge and it is necessary to select new significantly biggest RDF files.

Results of theoretical worst case (**[Worst]** dataset) is presented in table 2.

Table 2: Worst case evaluation results

#V	Scipy	M4RI	GPU4R	GPU_N	GPU_Py	CuSprs
16	0.032	< 0.001	0.008	0.002	!!!	!!!
32	0.118	0.001	0.034	0.008	!!!	!!!
64	0.476	0.041	0.133	0.032	!!!	!!!
128	2.194	0.226	0.562	0.129	2.751	!!!
256	15.299	1.994	3.088	0.544	11.883	!!!
512	121.287	23.204	13.685	2.499	43.563	!!!
1024	1593.284	528.521	88.064	19.357	217.326	!!!
2048	-	-	-	325.174	-	!!!

In this case !!!!! In this case !!!!!

Next is a **[Sparse]** dataset. Results are presented in table 3.

Table 3: Sparse graphs querying results

Graph	Scipy	M4RI	GPU4R	GPU_N	GPU_Py	CuSprs
G5k-0.001	10.352	0.647	0.113	0.041	0.216	!!!
G10k-0.001	37.286	2.395	0.435	0.215	!!!	!!!
G10k-0.01	97.607	1.455	0.273	0.138	0.763	!!!
G10k-0.1	!!!	1.050	0.223	0.114	0.859	!!!
G20k-0.001	150.774	11.025	1.842	1.274	6.180	!!!
G40k-0.001	-	97.841	11.663	8.393	37.821	!!!
G80k-0.001	-	1142.959	88.366	65.886	-	!!!

**Table 1: RDFs querying results**

RDF			Query 1						Query 2					
Name	#V	#E	Scipy	M4RI	GPU4R	GPU_N	GPU_Py	CuSprs	Scipy	M4RI	GPU4R	GPU_N	GPU_Py	CuSprs
atom-primitive			0.003	0.002	0.002	0.001	0.005	!!!	0.001	< 0.001	0.001	< 0.001	0.002	!!!
biomedical-mesure-primitive			0.003	0.005	0.002	0.001	0.005	!!!	0.004	< 0.001	0.001	< 0.001	0.005	!!!
foaf			0.002	0.009	0.002	< 0.001	0.005	!!!	0.001	< 0.001	0.001	< 0.001	0.002	!!!
funding			0.004	0.007	0.004	0.001	0.005	!!!	0.002	< 0.001	0.003	< 0.001	0.004	!!!
generations			0.003	0.003	0.002	< 0.001	0.005	!!!	0.001	< 0.001	0.001	< 0.001	0.002	!!!
people_pets			0.003	0.003	0.003	0.001	0.007	!!!	0.001	< 0.001	0.001	< 0.001	0.003	!!!
pizza			0.006	0.008	0.003	0.001	0.006	!!!	0.002	< 0.001	0.002	< 0.001	0.005	!!!
skos			0.002	0.004	0.002	< 0.001	0.005	!!!	< 0.001	< 0.001	0.001	< 0.001	0.002	!!!
travel			0.003	0.005	0.002	< 0.001	0.006	!!!	0.001	< 0.001	0.001	< 0.001	0.003	!!!
univ-bench			0.002	0.004	0.002	< 0.001	0.005	!!!	0.001	< 0.001	0.001	< 0.001	0.003	!!!
wine			0.007	0.006	0.004	0.001	0.007	!!!	0.001	< 0.001	0.003	< 0.001	0.003	!!!

For such type of graphs !!!! Note that we estimate only query execution time, so it is hard to compare our results with results presented in [6]. But it would be interesting to do such comaprison in future because running time of our [GPU\_N] implementation is significantly smaller than provided in [6].

The last dataset is a [Full], and results a shown in table 4

Finally, we can cocnclude that

- On GPU utilization
- On Existinnng libraries
- On Low-level programming
- On sparse matrices

## 6 CONCLUSION AND FUTURE WORK

We provide a number of implementations of matrix-based algorithm for context-free path querying, collect a dataset for evaluation and provide results of evaluation of our implementation on collected dataset. Our evaluation shows that GPGPU utilization for boolean matrices multiplication can significantly increase perfprmance of CFPQs evaluation, but requires more research on implementattion details.

First direction for future research is a more detailed CFPQ algorithms investigation. We should do more evaluation on sparse matrices on GPGPUs and investigate technics for high-performance GPGPU code creation.

Also it is nessessary to implement and evaluate solutions for graphs which is not fit in RAM, and for big queries which disallow to allocate all requred matrices on single GPGPU. We hope that it is possible to utilize existing technics for huge matrices multiplication for this problem.

Another direcion is a dataset improvement. First of all, it is necessary to collect more data, and more grammars/queries. Especially it would be interesting to add to dataset more real graphs and more real queries. Secondly, it is nessessary to discuss and fix data format to be able to evaluate different algorithms. We think that it is necessary to create public dataset for CFPQ algorithms evaluation, and collaboration with community is required.

## ACKNOWLEDGMENTS

The research was supported by the Russian Science Foundation grant 18-11-00100 and a grant from JetBrains Research.

## REFERENCES

- [1] Martin Albrecht and Gregory Bard. 2019. *The M4RI Library*. The M4RI Team. <https://bitbucket.org/malb/m4ri>
- [2] MR Albrecht, GV Bard, and W Hart. 2008. Efficient multiplication of dense matrices over GF (2). *arXiv preprint arXiv:0811.1714* (2008).
- [3] Vladimir L'vovich Arlazarov, Yefim A Dinitz, MA Kronrod, and IgorAleksandrovich Faradzhev. 1970. On economical construction of the transitive closure of an oriented graph. In *Doklady Akademii Nauk*, Vol. 194. Russian Academy of Sciences, 487–488.
- [4] Rustam Azimov and Semyon Grigorev. 2018. Context-free Path Querying by Matrix Multiplication. In *Proceedings of the 1st ACM SIGMOD Joint International Workshop on Graph Data Management Experiences & Systems (GRADES) and Network Data Analytics (NDA) (GRADES-NDA '18)*. ACM, New York, NY, USA, Article 5, 10 pages. <https://doi.org/10.1145/3210259.3210264>
- [5] Chris Barrett, Riko Jacob, and Madhav Marathe. 2000. Formal-language-constrained path problems. *SIAM J. Comput.* 30, 3 (2000), 809–837.
- [6] Zhiwei Fan, Jianqiao Zhu, Zuyu Zhang, Aws Albarghouthi, Paraschos Koutris, and Jignesh Patel. 2018. Scaling-Up In-Memory Datalog Processing: Observations and Techniques. *arXiv preprint arXiv:1812.03975* (2018).
- [7] Semyon Grigorev and Anastasiya Ragozina. 2017. Context-free Path Querying with Structural Representation of Result. In *Proceedings of the 13th Central & Eastern European Software Engineering Conference in Russia (CEE-SECR '17)*. ACM, New York, NY, USA, Article 10, 7 pages. <https://doi.org/10.1145/3166094.3166104>
- [8] Jelle Hellings. 2014. Conjunctive context-free path queries. In *Proceedings of ICDT'14*. 119–130.
- [9] Jelle Hellings. 2015. Querying for Paths in Graphs using Context-Free Path Queries. *arXiv preprint arXiv:1502.02242* (2015).
- [10] Eric Jones, Travis Oliphant, Pearu Peterson, et al. 2001–2019. SciPy: Open source scientific tools for Python. <http://www.scipy.org/> [Online; accessed 5.3.2019].
- [11] Ciro M. Medeiros, Martin A. Musicante, and Umberto S. Costa. 2018. Efficient Evaluation of Context-free Path Queries for Graph Databases. In *Proceedings of the 33rd Annual ACM Symposium on Applied Computing (SAC '18)*. ACM, New York, NY, USA, 1230–1237. <https://doi.org/10.1145/3167132.3167265>
- [12] Fred C. Santos, Umberto S. Costa, and Martin A. Musicante. 2018. A Bottom-Up Algorithm for Answering Context-Free Path Queries in Graph Databases. In *Web Engineering*. Tommi Mikkonen, Ralf Klamma, and Juan Hernández (Eds.). Springer International Publishing, Cham, 225–233.
- [13] Ekaterina Verbitskaia, Ilya Kirillov, Ilya Nozkin, and Semyon Grigorev. 2018. Parser Combinators for Context-free Path Querying. In *Proceedings of the 9th ACM SIGPLAN International Symposium on Scala (Scala 2018)*. ACM, New York, NY, USA, 13–23. <https://doi.org/10.1145/3241653.3241655>
- [14] Mihalis Yannakakis. 1990. Graph-theoretic methods in database theory. In *Proceedings of the ninth ACM SIGACT-SIGMOD-SIGART symposium on Principles of*

**Table 4: Full querying results**

#V	Query 1						Query 2					
	Scipy	M4RI	GPU4R	GPU_N	GPU_Py	CuSprs	Scipy	M4RI	GPU4R	GPU_N	GPU_Py	CuSprs
100	0.007	!!!	0.002	< 0.001	0.003	!!!	0.023	!!!	0.005	0.001	0.007	!!!
200	0.040	!!!	0.002	0.001	0.004	!!!	0.105	!!!	0.004	0.001	0.007	!!!
500	0.480	!!!	0.003	0.001	0.004	!!!	1.636	!!!	0.007	0.001	0.010	!!!
1000	3.741	!!!	0.005	0.001	0.006	!!!	13.071	!!!	0.009	0.001	0.009	!!!
2000	40.309	!!!	0.019	0.003	0.017	!!!	93.676	!!!	0.030	0.005	0.026	!!!
5000	651.343	!!!	0.125	0.038	0.150	!!!	!!!	!!!	0.195	0.075	0.239	!!!
10000	-	!!!	0.552	0.315	0.840	!!!	!!!	!!!	1.055	0.648	1.838	!!!
25000	-	!!!	7.252	5.314	15.521	!!!	-	!!!	15.240	10.961	36.495	!!!
50000	-	!!!	58.751	44.611	129.641	!!!	-	!!!	130.203	91.579	!!!	!!!
80000	-	!!!	256.579	190.343	641.260	!!!	-	!!!	531.694	376.691	!!!	!!!

database systems. ACM, 230–242.

- [15] X. Zhang, Z. Feng, X. Wang, G. Rao, and W. Wu. 2016. Context-free path queries on RDF graphs. In *International Semantic Web Conference*. Springer, 632–648.