

#### PPoPP 2020



# POSTER: Optimizing GPU Programs by Partial Evaluation

Aleksey Tyurin, Daniil Berezun, Semyon Grigorev

JetBrains Research, Programming Languages and Tools Lab Saint Petersburg University

February 24, 2020

## Big Data Processing

- Substring matching ⇒ Data curving (cyber forensics)
- 2D convolution ⇒ Image processing
- Filtering by using HMMs ⇒ Homology search (bioinformatics)

## Big Data Processing

- Substring matching ⇒ Data curving (cyber forensics)
- 2D convolution ⇒ Image processing

```
● Filtering by using HMN One filter for many data chunks ⇒ many procedure runs

-_global___ void handreData
(int* filterParams, int* data, ...)

{
...
```

### Big Data Processing

- Substring matching ⇒ Data curving (cyber forensics)
- 2D convolution ⇒ Image processing

```
• Filtering by using HMN One filter for many data chunks ⇒ many procedure runs

-_global__ void hand eData
(int* filterParams, int* data, ...)

{
...
}
```

filterParams is static during one data processing session

How can we use this fact to optimize our procedure?

```
handleData (filterParams, data)
{
  res = new List()
  for d in data
     for e in filterParams
        if d % e == 0
        then res.Add(d)
  return res
}
```

```
partial evaluator
\llbracket handleData 
rbracket \llbracket filterParams, data 
rbracket = \llbracket \llbracket mix 
rbracket \llbracket handleData, filterParams 
rbracket \rrbracket \llbracket data 
rbracket
   handleData
                                                                handleDatamiv
                                                             [[mix]][handleData, [2; 3]]]
handleData (filterParams, data)
    res = new List()
    for d in data
         for e in filterParams
              if d \% e == 0
              then res.Add(d)
    return res
```

```
partial evaluator
\llbracket handleData 
rbracket [filterParams, data] = \llbracket \llbracket mix 
rbracket [filterParams] 
rbracket [data]
  handleData
                                                  handleData<sub>miv</sub>
                                               [[mix]][handleData, [2; 3]]]
                                               handleData (data)
handleData (filterParams, data)
                                                  res = new List()
   res = new List()
   for d in data
                                                  for d in data
                                                     if d % 2 == 0 ||
       for e in filterParams
                                                        d \% 3 == 0
           if d \% e == 0
                                                    then res.Add(d)
           then res.Add(d)
                                                  return res
   return res
                                               }
```

```
partial evaluator
\llbracket handleData 
rbracket [filterParams, data] = \llbracket \llbracket mix 
rbracket [filterParams] 
rbracket [data]
  handleData
                                                  handleData<sub>miv</sub>
                                               [[mix]][handleData, [2; 3]]]
                                               handleData (data)
handleData (filterParams, data)
                                                  res = new List()
   res = new List()
   for d in data
                                                  for d in data
                                                     if d % 2 == 0 ||
       for e in filterParams
                                                        d \% 3 == 0
           if d \% e == 0
                                                     then res.Add(d)
           then res.Add(d)
                                                  return res
   return res
                                               }
```

#### **Evaluation Setup**

- We use AnyDSL framework for specialization
  - Special DSL which can be specialized and compiled
  - Ahead-of-time specialization

#### **Evaluation Setup**


- We use AnyDSL framework for specialization
  - Special DSL which can be specialized and compiled
  - Ahead-of-time specialization
- Algorithms
  - Naïve multiple substring matching
  - 2D convolution

#### **Evaluation Setup**

- We use AnyDSL framework for specialization
  - ▶ Special DSL which can be specialized and compiled
  - ► Ahead-of-time specialization
- Algorithms
  - Naïve multiple substring matching
  - 2D convolution
- Hardware
  - ▶ GTX-1070: Pascal architecture, 8GB GDDR5, 1920 CUDA cores
  - ▶ Tesla T4: Turing architecture, 16GB GDDR6, 2560 CUDA cores

## Evaluation: Substring Matching

- Application: data curving
- Subject string: byte sequence from real hard drive
- Patterns: 16 file signatures from GCK's file signatures table<sup>1</sup>




Results for GTX-1070

Results for Tesla T4

<sup>1</sup>https://www.garykessler.net/library/file\_sigs.html

#### Evaluation: 2D Convolution

- Application: image processing
- Subject image: random image of size 1GB
- Filters: random square filters with diameter 3 to 255



Results for GTX-1070

Results for Tesla T4

#### Future Research

- Migration to CUDA C partial evaluator
  - ► LLVM.mix: partial evaluator for LLVM IR
- Reduction of specialization overhead
  - ► To be applicable in run-time
- Integration with shared memory register spilling
  - "RegDem: Increasing GPU Performance via Shared Memory Register Spilling" (Putt Sakdhnagool et.al. 2019)
- Evaluation on real-world examples
  - Homology search in bioinformatics
  - Regular expression matching for traffic analysis, log processing
  - Graph database querying
  - Ray tracing, path tracing

#### Contact Information

- Semyon Grigorev:
  - s.v.grigoriev@spbu.ru
  - ► Semen.Grigorev@jetbrains.com
- Aleksey Tyurin: alekseytyurinspb@gmail.com
- Daniil Berezun: daniil.berezun@jetbrains.com

## Thanks!