



Python

Strings



Copyright © Software Carpentry 2010

This work is licensed under the Creative Commons Attribution License

See <http://software-carpentry.org/license.html> for more information.

Strings are sequences of characters

Strings are sequences of characters

No separate character type: just a string of length 1

Strings are sequences of characters

No separate character type: just a string of length 1

Indexed exactly like lists

Strings are sequences of characters

No separate character type: just a string of length 1

Indexed exactly like lists

```
name = 'Darwin'  
print name[0], name[-1]  
D n
```

for iterates through characters

for iterates through characters

```
name = 'Darwin'  
for c in name:  
    print c
```

D

a

r

w

i

n

Use either ' or " (as long as they match)

Use either ' or " (as long as they match)

```
print 'Alan', "Turing"
```

Alan Turing

Use either ' or " (as long as they match)

```
print 'Alan', "Turing"
```

Alan Turing

Strings are the same no matter how they're created

Use either ' or " (as long as they match)

```
print 'Alan', "Turing"
```

Alan Turing

Strings are the same no matter how they're created

```
print 'Alan' == "Alan"
```

True

Strings are compared character by character
from left to right

Strings are compared character by character
from left to right

```
print 'a' < 'b'
```

True

Strings are compared character by character
from left to right

```
print 'a' < 'b'
```

True

```
print 'ab' < 'abc'
```

True

Strings are compared character by character
from left to right

```
print 'a' < 'b'
```

True

```
print 'ab' < 'abc'
```

True

```
print '1' < '9'
```

True

Strings are compared character by character
from left to right

```
print 'a' < 'b'
```

True

```
print 'ab' < 'abc'
```

True

```
print '1' < '9'
```

True

```
print '100' < '9'
```

True

Strings are compared character by character
from left to right

```
print 'a' < 'b'
```

True

```
print 'ab' < 'abc'
```

True

```
print '1' < '9'
```

True

```
print '100' < '9'
```

True

```
print 'A' < 'a'
```

True

Strings are *immutable* : cannot be changed in place

Strings are *immutable* : cannot be changed in place

```
name = 'Darwin'
```

```
name[0] = 'C'
```

TypeError: 'str' object does not support item assignment

Strings are *immutable* : cannot be changed in place

```
name = 'Darwin'
```

```
name[0] = 'C'
```

TypeError: 'str' object does not support item assignment

Immutability improves performance

Strings are *immutable* : cannot be changed in place

```
name = 'Darwin'
```

```
name[0] = 'C'
```

TypeError: 'str' object does not support item assignment

Immutability improves performance

See later how immutability improves programmers'
performance

Use + to concatenate strings

Use + to concatenate strings

```
name = 'Charles' + ' ' + 'Darwin'  
print name  
Charles Darwin
```

Use + to concatenate strings

```
name = 'Charles' + ' ' + 'Darwin'  
print name  
Charles Darwin
```

Concatenation always produces a new string

Use + to concatenate strings

```
name = 'Charles' + ' ' + 'Darwin'  
print name  
Charles Darwin
```

Concatenation always produces a new string

```
original = 'Charles'
```


original → 'Charles'

Use + to concatenate strings

```
name = 'Charles' + ' ' + 'Darwin'  
print name  
Charles Darwin
```

Concatenation always produces a new string

```
original = 'Charles'  
name = original
```



Use + to concatenate strings

```
name = 'Charles' + ' ' + 'Darwin'  
print name  
Charles Darwin
```

Concatenation always produces a new string

```
original = 'Charles'  
name = original  
name += ' Darwin'
```

original → 'Charles'

name → 'Charles Darwin'

Often used to format output

Often used to format output

```
print 'reagent: ' + str(reagent_id) + ' produced ' + \
      str(percentage_yield) + '% yield'
```

Often used to format output

```
print 'reagent: ' + str(reagent_id) + ' produced ' + \
      str(percentage_yield) + '% yield'
```

There's a better way...

Use string % value to format output

Use string % value to format output

```
output = 'reagent: %d' % 123
```

```
print output
```

```
reagent: 123
```


Use string % value to format output

```
output = 'reagent: %d' % 123
```

```
print output
```

reagent: 123

```
percentage_yield = 12.3
```

```
print 'yield: %6.2f' % percentage_yield
```

yield: 12.30

And string % (v1, v2, ...) for multiple values

And string % (v1, v2, ...) for multiple values

```
reagent_id = 123
percentage_yield = 12.3
print 'reagent: %d produced %f%% yield' % \
    (reagent_id, percentage_yield)
reagent: 123 produced 12.30% yield
```

And string % (v1, v2, ...) for multiple values

```
reagent_id = 123
percentage_yield = 12.3
print 'reagent: %d produced %f%% yield' % \
    (reagent_id, percentage_yield)
reagent: 123 produced 12.30% yield
```

% operator turns double '%%' into single '%'

Use `\n` to represent a newline character

Use `\n` to represent a newline character

Use `\'` for single quote, `\''` for double quote

Use `\n` to represent a newline character

Use `\'` for single quote, `\''` for double quote

```
print 'There isn\'t time\nto do it right.'
```

*There isn't time
to do it right.*

Use `\n` to represent a newline character

Use `\'` for single quote, `\"` for double quote

```
print 'There isn\'t time\nto do it right.'
```

*There isn't time
to do it right.*

```
print "But you said,\n\"There is time to do it over.\""
```

*But you said,
"There is time to do it over."*

Use `\\` for a literal `\` character

Use `\\` for a literal `\` character

```
print 'Most mathematicians write a\\b instead of a%b.'
```

Most mathematicians write a\b instead of a%b.

Use `\` for a literal `\` character

```
print 'Most mathematicians write a\\b instead of a%b.'
```

Most mathematicians write a\b instead of a%b.

Common pattern with *escape sequences*

Use `\` for a literal `\` character

```
print 'Most mathematicians write a\\b instead of a%b.'
```

Most mathematicians write a\b instead of a%b.

Common pattern with *escape sequences*

- Use a character to mean "what follows is special"

Use `\\` for a literal `\` character

```
print 'Most mathematicians write a\\b instead of a%b.'
```

Most mathematicians write a\b instead of a%b.

Common pattern with *escape sequences*

- Use a character to mean "what follows is special"
- Double it up to mean "that character itself"


Use triple quotes (either kind) for multi-line strings

Use triple quotes (either kind) for multi-line strings

```
quote = """We can only see  
a short distance ahead,  
but we can see plenty there  
that needs to be done."""
```

Use triple quotes (either kind) for multi-line strings

```
quote = """We can only see
a short distance ahead,
but we can see plenty there
that needs to be done."""
```



d , \n b u

Use triple quotes (either kind) for multi-line strings

```
quote = """We can only see  
a short distance ahead,  
but we can see plenty there  
that needs to be done."""
```

```
quote = 'We can only see\na short distance ahead\n' + \  
    'but we can see plenty there\nthat needs to be done.'
```

Strings have methods

Strings have methods

```
name = 'newTON'  
print name.capitalize(), name.upper(), name.lower(), name
```

Newton NEWTON newton newTON

Strings have methods

```
name = 'newTON'
print name.capitalize(), name.upper(), name.lower(), name
Newton NEWTON newton newTON

dna = 'acggtggtcac'
print dna.count('g'), dna.count('x')
4 0
```

Strings have methods

```
name = 'newTON'
print name.capitalize(), name.upper(), name.lower(), name
Newton NEWTON newton newTON

dna = 'acggtggtcac'
print dna.count('g'), dna.count('x')
4 0

print dna.find('t'), dna.find('t', 5), dna.find('x')
4 7 -1
```

Strings have methods

```
name = 'newTON'
print name.capitalize(), name.upper(), name.lower(), name
Newton NEWTON newton newTON

dna = 'acggtggtcac'
print dna.count('g'), dna.count('x')
4 0

print dna.find('t'), dna.find('t', 5), dna.find('x')
4 7 -1

print dna.replace('t', 'x'), dna
acggxggxcac acggtggtcac
```

Strings have methods

```
name = 'newTON'
print name.capitalize(), name.upper(), name.lower(), name
Newton NEWTON newton newTON

dna = 'acggtggtcac'
print dna.count('g'), dna.count('x')
4 0

print dna.find('t'), dna.find('t', 5), dna.find('x')
4 7 -1

print dna.replace('t', 'x')
acggxggxcac acggtggtcac

print dna.replace('gt', '')
acggcac
```

Can chain method calls together

Can chain method calls together

```
element = 'cesium'  
print element.upper().center(10, '.')
```

Can chain method calls together

```
element = 'cesium'  
print element.upper().center(10, '.')
```



convert to upper case

Can chain method calls together

```
element = 'cesium'  
print element.upper().center(10, '.')
```



center in a field

10 characters wide

Can chain method calls together

```
element = 'cesium'  
print element.upper().center(10, '.')  
..CESIUM..
```



narrated by

Dominique Vuvan

October 2010



Copyright © Software Carpentry 2010

This work is licensed under the Creative Commons Attribution License

See <http://software-carpentry.org/license.html> for more information.