

This is a test First and second peer review notes. Include the names of those present and also document the comments that were made.

ECEN - 340 FINAL LAB PEER REVIEW-1

Instructions
Each "team" meet with one other team and answer the following questions about the other team. Share one copy from your team's findings with the other team. One copy to Bro. Watson.

My Team Name (or Members) Brock Davis
Other Team's Name (or Members) Alex

1. Basic Description of the other Team's Project:
A printer app. Use joystick to make marks on LCD screen, pressing the buttons. Places the color.
2. Areas of Learning from the other Team (One thing you like):
Combination of screen and joystick to make a more robust mouse.
3. Potential Difficulties or Roadblocks you might see (if you were doing it):
LCD screen set up without flickering or messing up with joystick.
4. One thing the other team might consider to make it better/easier:
Start with black & white then move to color.

ECEN - 340 FINAL LAB PEER REVIEW PART II.

Instructions
Each "team" meet with one other team and answer the following questions about the other team. Share one copy from your team's findings with the other team. One copy to Bro. Watson.

My Team Name (or Members) Matthew Spitzer & Prabir Gull
Other Team's Name (or Members) Alex Turner

1. Basic Description of the other Team's Project:
LCD screen with joystick and buttons to draw.
2. Areas of Learning from the other Team (One thing you like):
 - Learning to communicate with the screen.
 - Learning to use joystick.
3. Ask the other team about one thing they corrected, due to feedback:
Starting small and making small changes.
4. With your reviewer(s), think of at least one type of "product" your design could be used in:
Like this.

These peer reviews were conducted based on my original project. Due to hardware failure I had to pivot to a new project. Since we were low on time I was unable to redo these peer reviews. That being said I did my best to act on the feedback I did receive. I started small and got more complex and I made sure that the display worked and did not glitch or flicker in any way.

A description of the project. Include diagrams of the project if it includes external components.

As I am sure you know I originally was going to make a drawing pad. However I was having a lot of trouble with the LCD and SPI connection. I was able to get something to display but then I bricked my display and decided I wasn't worth breaking more displays so I went with a different project.

My project is like a bob-it game. You have until the timer runs out to press the correct button. You have 4 options left, right, up and down. If you get the button correct it increases your score which the on board leds show. If you get the button wrong it decreases the time by 2 seconds. There is a menu which scrolls welcoming the user to the gauntlet and explaining the user can press up to start or right to see the high score. Once you press right you can press right again to get back to the main menu. Once the time runs out there are two ending messages. One is if the user got a new high score the other is just a regular one. Both messages inform the user they can play again if they press up.

Verilog code.

Final_Project.v:

```
`timescale 1ns / 1ps
```

```
module Final_Project(
```

```
    input clk,
```

```
    input btnC, input btnR, input btnL, input btnU, input btnD,
```

```
    output [15:0] led,
```

```
    output [6:0] seg,
```

```
    output [3:0] an
```

```
);
```

```
    wire left, right, up, down, center;
```

```
    wire mem_we;
```

```
    wire [15:0] score_read, score_write, score;
```

```

wire [1:0] dir;

wire [6:0] count_down;


// UPDATED: 4 bits for debug_state
wire [3:0] debug_state;

wire new_record;


debounce_buttons U_Debounce(

    .clk(clk),

    .btnL(btnL), .btnR(btnR), .btnU(btnU), .btnD(btnD), .btnC(btnC),

    .left(left), .right(right), .up(up), .down(down), .center(center)

);


game_logic U_Game(

    .clk(clk),

    .rst(center),

    .btnL(left), .btnR(right), .btnU(up), .btnD(down),

    .dir_out(dir),

    .count_down(count_down),

    .score(score),

    .score_read(score_read),

    .score_write(score_write),

    .mem_we(mem_we),

    .debug_state(debug_state),

```

```
        .new_record(new_record)
    );
```

```
memory U_Memory(
    .we(mem_we), .clk(clk), .addr(4'b0),
    .data_in(score_write), .data_out(score_read)
);
```

```
segdisplay_driver U_SegDisplay(
    .clk(clk),
    .rst(center),
    .count_down(count_down),
    .dir(dir),
    .score(score),
    .high_score_val(score_read), // CONNECTED: Pass read score to display
    .game_state(debug_state),
    .is_new_record(new_record),
    .seg(seg),
    .an(an)
);
```

```
// LEDs
```

```
assign led[3:0] = debug_state; // Shows 4-bit state
```

```
assign led[4] = up;
```

```
assign led[5] = down;

assign led[6] = left;

assign led[7] = right;

assign led[15:8] = score[7:0];
```

```
endmodule
```

debounce_buttons.v:

```
`timescale 1ns / 1ps
```

```
module debounce_buttons (

    input clk,

    input btnL, btnC, btnR, btnU, btnD,

    output left, center, right, up, down

);

    wire clk_deb;

    debounce_div div1 (.clk(clk), .clk_deb(clk_deb));

    btn_debounce u_btn (.clk(clk_deb), .btn_in(btnU), .btn_status(up));

    btn_debounce d_btn (.clk(clk_deb), .btn_in(btnD), .btn_status(down));

    btn_debounce l_btn (.clk(clk_deb), .btn_in(btnL), .btn_status(left));

    btn_debounce r_btn (.clk(clk_deb), .btn_in(btnR), .btn_status(right));

    btn_debounce c_btn (.clk(clk_deb), .btn_in(btnC), .btn_status(center));

endmodule
```

debounce_div.v:

```
`timescale 1ns / 1ps
```

```
module debounce_div(
```

```
    input clk,
```

```
    output clk_deb
```

```
);
```

```
    reg [15:0] cnt;
```

```
    assign clk_deb = cnt[15];
```

```
    initial cnt = 0;
```

```
    always @(posedge clk)
```

```
        cnt <= cnt + 1;
```

```
endmodule
```

btn_debounce.v:

```
`timescale 1ns / 1ps
```

```
module btn_debounce(
```

```
    input clk,
```

```

input btn_in,

output wire btn_status

);

reg [19:0] btn_shift;

always @ (posedge clk)

    btn_shift <= {btn_shift[18:0], btn_in};

assign btn_status = &btn_shift;

endmodule

```

game_logic.v:

```

`timescale 1ns / 1ps

module game_logic(

    input clk,

    input rst,

    input btnL, btnR, btnU, btnD,

    output reg [1:0] dir_out,

    output reg [6:0] count_down,

    output reg [15:0] score,

    input [15:0] score_read,

    output reg [15:0] score_write,

    output reg mem_we,

```

```
output [3:0] debug_state,  
output reg new_record  
);
```

```
// STATE DEFINITIONS
```

```
localparam IDLE      = 4'd0;  
localparam NEW_ROUND  = 4'd1;  
localparam WAIT_INPUT = 4'd2;  
localparam CHECK_FAIL = 4'd3;  
localparam SAVE_SCORE = 4'd4;  
localparam GAME_OVER  = 4'd5;  
localparam WAIT_REL    = 4'd6;  
localparam WAIT_REL_RETRY = 4'd7;  
localparam WAIT_TO_HS  = 4'd8;  
localparam VIEW_HS     = 4'd9;  
localparam WAIT_TO_IDLE = 4'd10;  
localparam WAIT_FROM_GO = 4'd11;
```

```
reg [3:0] state = IDLE;
```

```
reg [31:0] timer_count;
```

```
reg [1:0] dir;
```

```
// LFSR Random Generator linear feedback shift register
```

```
reg [3:0] lfsr = 4'b1011;
```

```
always @(posedge clk) begin
```

```
    lfsr <= {lfsr[2:0], lfsr[3] ^ lfsr[2]};
```

```
end
```

```
// Timer Pulse
```

```
wire pulse_1sec;
```

```
clk_gen #(.COUNTER_MAX(100_000_000)) timer_pulse_inst (
```

```
    .clk(clk), .rst(rst), .en_10hz(pulse_1sec)
```

```
);
```

```
assign debug_state = state;
```

```
initial begin
```

```
    score = 0;
```

```
    state = IDLE;
```

```
    count_down = 30;
```

```
    new_record = 0;
```

```
end
```

```
always @(posedge clk) begin
```

```
    if (rst) begin
```

```
        state <= IDLE;
```

```
        score <= 0;
```

```
        mem_we <= 0;
```

```

    count_down <= 0;

    dir_out <= 2'd2;

    new_record <= 0;
end else begin

    mem_we <= 0;

    count_down <= timer_count[6:0];


case (state)

    // --- MAIN MENU ---

    IDLE: begin

        count_down <= 30;

        dir_out <= 2'd2;

        new_record <= 0;


        if (btnU) begin

            score <= 0;

            timer_count <= 30;

            state <= WAIT_REL;

        end

        else if (btnR) begin

            state <= WAIT_TO_HS;

        end

    end
end

```

```
// --- MENU NAVIGATION ---
```

```
WAIT_TO_HS: begin
```

```
    if (!btnR) state <= VIEW_HS;
```

```
end
```

```
VIEW_HS: begin
```

```
    if (btnR) state <= WAIT_TO_IDLE;
```

```
end
```

```
WAIT_TO_IDLE: begin
```

```
    if (!btnR) state <= IDLE;
```

```
end
```

```
WAIT_FROM_GO: begin
```

```
    if (!btnU) state <= IDLE; // Return to menu only when button released
```

```
end
```

```
// --- GAMEPLAY ---
```

```
WAIT_REL: begin
```

```
    if (!btnU && !btnD && !btnL && !btnR) state <= NEW_ROUND;
```

```
end
```

```
WAIT_REL_RETRY: begin
```

```
    if (!btnU && !btnD && !btnL && !btnR) state <= WAIT_INPUT;
```

```
end
```

```
NEW_ROUND: begin
```

```
    dir <= lfsr[1:0];
```

```

    dir_out <= lfsr[1:0];

    state <= WAIT_INPUT;

end

WAIT_INPUT: begin

    if (pulse_1sec) begin

        if (timer_count > 0) timer_count <= timer_count - 1;

        else state <= CHECK_FAIL;

    end

    if ((dir != 0 && btnL) || (dir != 1 && btnR) || (dir != 2 && btnU) || (dir != 3 && btnD))

begin

        if (timer_count > 2) begin

            timer_count <= timer_count - 2;

            state <= WAIT_REL_RETRY;

        end else begin

            timer_count <= 0;

            state <= CHECK_FAIL;

        end

    end

    else if ((dir == 0 && btnL) || (dir == 1 && btnR) || (dir == 2 && btnU) || (dir == 3 &&
btnD)) begin

        score <= score + 1;

        state <= WAIT_REL;

    end

end

```

end

CHECK_FAIL: begin

if (score > score_read) begin

score_write <= score;

mem_we <= 1;

new_record <= 1;

state <= SAVE_SCORE;

end else begin

state <= GAME_OVER;

end

end

SAVE_SCORE: begin

mem_we <= 0;

state <= GAME_OVER;

end

GAME_OVER: begin

count_down <= 0;

if (btnU) state <= WAIT_FROM_GO; // NEW: Press U to restart

end

endcase

end

```
    end  
endmodule
```

clk_gen.v:

```
`timescale 1ns / 1ps
```

```
module clk_gen #(  
    // Default: 100MHz clock / 10Hz target = 10,000,000 cycles  
    // If you want it SLOWER (e.g., 1 count per second), change this to 100,000,000  
    parameter COUNTER_MAX = 10_000_000  
)(  
    input clk,  
    input rst,  
    output reg en_10hz  
);  
  
    reg [26:0] count;  
  
    always @ (posedge clk) begin  
        if (rst) begin  
            count <= 0;  
            en_10hz <= 0;  
        end else begin  
            if (count >= COUNTER_MAX - 1) begin
```

```

        count <= 0;

        en_10hz <= 1; // 1-cycle enable pulse

    end else begin

        count <= count + 1;

        en_10hz <= 0;

    end

end

end

end

endmodule

```

memory.v:

```

`timescale 1ns / 1ps

```

```

module memory(

    input wire clk,

    input wire we,

    input wire [3:0] addr,

    input wire [15:0] data_in,

    output reg [15:0] data_out

);

    reg [15:0] mem [15:0];

    initial begin

        mem[0] = 0;
    end

```

```
    mem[1] = 0;
    mem[2] = 0;
    mem[3] = 0;
end

always@(posedge clk) begin
    if (we)
        mem[addr] <= data_in;
        data_out <= mem[addr];
    end
endmodule
```

segdisplay_driver.v:

```
`timescale 1ns / 1ps

module segdisplay_driver(
    input clk,
    input rst,
    input [6:0] count_down,
    input [1:0] dir,
    input [15:0] score,
    input [15:0] high_score_val,
    input [3:0] game_state,
    input is_new_record,
```

```
output reg [6:0] seg,  
output reg [3:0] an  
);
```

```
reg [19:0] refresh_counter;  
always @(posedge clk or posedge rst) begin  
    if (rst) refresh_counter <= 0;  
    else refresh_counter <= refresh_counter + 1;  
end  
wire [1:0] digit_select = refresh_counter[19:18];
```

```
reg [24:0] scroll_timer;  
always @(posedge clk or posedge rst) begin  
    if (rst) scroll_timer <= 0;  
    else scroll_timer <= scroll_timer + 1;  
end  
wire scroll_tick = (scroll_timer == 0);
```

```
reg [6:0] scroll_ptr;  
always @(posedge clk or posedge rst) begin  
    if (rst) scroll_ptr <= 0;  
    else if (scroll_tick) scroll_ptr <= scroll_ptr + 1;  
end
```

```
reg [5:0] char_index;
```

```
// Character Constants
```

```
localparam C_0=0, C_1=1, C_2=2, C_3=3, C_4=4, C_5=5, C_6=6, C_7=7, C_8=8, C_9=9;
```

```
localparam C_L=10, C_r=11, C_U=12, C_d=13, C_SPC=14, C_DASH=15;
```

```
localparam C_A=16, C_b=17, C_C=18, C_E=19, C_F=20, C_G=21, C_H=22, C_J=23;
```

```
localparam C_n=24, C_o=25, C_P=26, C_S=27, C_t=28, C_y=29, C_l=30, C_M=31;
```

```
always @(*) begin
```

```
    // DEFAULT ANODES
```

```
    case(digit_select)
```

```
        2'b00: an = 4'b1110;
```

```
        2'b01: an = 4'b1101;
```

```
        2'b10: an = 4'b1011;
```

```
        2'b11: an = 4'b0111;
```

```
    endcase
```

```
// --- STATE DISPLAY LOGIC ---
```

```
// 1. GAME OVER (State 5) or WAIT FROM GO (State 11)
```

```
if (game_state == 4'd5 || game_state == 4'd11) begin
```

```
    if (is_new_record) begin
```

```
        case(digit_select)
```

```
            2'b00: char_index = get_newrecord_char(scroll_ptr + 3);
```

```

        2'b01: char_index = get_newrecord_char(scroll_ptr + 2);
        2'b10: char_index = get_newrecord_char(scroll_ptr + 1);
        2'b11: char_index = get_newrecord_char(scroll_ptr);

    endcase

end else begin

    case(digit_select)

        2'b00: char_index = get_gameover_char(scroll_ptr + 3);
        2'b01: char_index = get_gameover_char(scroll_ptr + 2);
        2'b10: char_index = get_gameover_char(scroll_ptr + 1);
        2'b11: char_index = get_gameover_char(scroll_ptr);

    endcase

end

end

// 2. IDLE / MENU (State 0)

else if (game_state == 4'd0 || game_state == 4'd10) begin

    case(digit_select)

        2'b00: char_index = get_welcome_char(scroll_ptr + 3);
        2'b01: char_index = get_welcome_char(scroll_ptr + 2);
        2'b10: char_index = get_welcome_char(scroll_ptr + 1);
        2'b11: char_index = get_welcome_char(scroll_ptr);

    endcase

end

```

```
// 3. VIEW HIGH SCORE (State 9) or WAIT TO HS (State 8)
```

```
else if (game_state == 4'd9 || game_state == 4'd8) begin
```

```
    case(digit_select)
```

```
        2'b00: char_index = get_highscore_char(scroll_ptr + 3);
```

```
        2'b01: char_index = get_highscore_char(scroll_ptr + 2);
```

```
        2'b10: char_index = get_highscore_char(scroll_ptr + 1);
```

```
        2'b11: char_index = get_highscore_char(scroll_ptr);
```

```
    endcase
```

```
end
```

```
// 4. PLAYING
```

```
else begin
```

```
    case(digit_select)
```

```
        2'b00: begin // Direction
```

```
            case(dir)
```

```
                2'd0: char_index = C_L;
```

```
                2'd1: char_index = C_r;
```

```
                2'd2: char_index = C_U;
```

```
                2'd3: char_index = C_d;
```

```
            endcase
```

```
        end
```

```
        2'b01: char_index = C_SPC; // Blank
```

```
        2'b10: char_index = (count_down % 10); // Timer
```

```
        2'b11: char_index = (count_down / 10); // Timer
```

```

        endcase

    end

end

// --- TEXT FUNCTIONS ---

// IDLE: "EnTER THE GAUntLEt  PrESS U TO PLAY  PrESS r FOR SCorE    " (Length 58)

function [5:0] get_welcome_char;

    input [6:0] pos;

    begin

        case(pos % 58)

            0: get_welcome_char = C_E; 1: get_welcome_char = C_n; 2: get_welcome_char =
C_t;

            3: get_welcome_char = C_E; 4: get_welcome_char = C_r; 5: get_welcome_char =
C_SPC;

            6: get_welcome_char = C_t; 7: get_welcome_char = C_H; 8: get_welcome_char =
C_E;

            9: get_welcome_char = C_SPC; 10: get_welcome_char = C_G; 11:
get_welcome_char = C_A;

            12: get_welcome_char = C_U; 13: get_welcome_char = C_n; 14: get_welcome_char
= C_t;

            15: get_welcome_char = C_L; 16: get_welcome_char = C_E; 17: get_welcome_char
= C_t;

            18: get_welcome_char = C_SPC; 19: get_welcome_char = C_SPC; 20:
get_welcome_char = C_SPC;

            21: get_welcome_char = C_P; 22: get_welcome_char = C_r; 23: get_welcome_char =
C_E;

            24: get_welcome_char = C_S; 25: get_welcome_char = C_S; 26: get_welcome_char
= C_SPC;

```

```

        27: get_welcome_char = C_U; 28: get_welcome_char = C_SPC; 29:
get_welcome_char = C_t;

        30: get_welcome_char = C_o; 31: get_welcome_char = C_SPC; 32:
get_welcome_char = C_P;

        33: get_welcome_char = C_L; 34: get_welcome_char = C_A; 35: get_welcome_char
= C_y;

        36: get_welcome_char = C_SPC; 37: get_welcome_char = C_SPC; 38:
get_welcome_char = C_SPC;

        39: get_welcome_char = C_P; 40: get_welcome_char = C_r; 41: get_welcome_char =
C_E;

        42: get_welcome_char = C_S; 43: get_welcome_char = C_S; 44: get_welcome_char
= C_SPC;

        45: get_welcome_char = C_r; 46: get_welcome_char = C_SPC; 47:
get_welcome_char = C_F;

        48: get_welcome_char = C_o; 49: get_welcome_char = C_r; 50: get_welcome_char =
C_SPC;

        51: get_welcome_char = C_S; 52: get_welcome_char = C_C; 53: get_welcome_char
= C_o;

        54: get_welcome_char = C_r; 55: get_welcome_char = C_E;

        default: get_welcome_char = C_SPC;

    endcase

end

endfunction

```

```

// HIGH SCORE: "HALL OF FAME  SCoRE XX  PrESS r TO bACK  " (Length 46)

```

```

function [5:0] get_highscore_char;

```

```

    input [6:0] pos;

```

```

    begin

```

```

        case(pos % 46)

```

0: get_highscore_char = C_H; 1: get_highscore_char = C_A; 2: get_highscore_char = C_L;

3: get_highscore_char = C_L; 4: get_highscore_char = C_SPC; 5: get_highscore_char = C_o;

6: get_highscore_char = C_F; 7: get_highscore_char = C_SPC; 8: get_highscore_char = C_F;

9: get_highscore_char = C_A; 10: get_highscore_char = C_M; 11: get_highscore_char = C_E;

12: get_highscore_char = C_SPC; 13: get_highscore_char = C_SPC; 14: get_highscore_char = C_SPC;

15: get_highscore_char = C_S; 16: get_highscore_char = C_C; 17: get_highscore_char = C_o;

18: get_highscore_char = C_r; 19: get_highscore_char = C_E; 20: get_highscore_char = C_SPC;

21: get_highscore_char = (high_score_val / 10) % 10;

22: get_highscore_char = (high_score_val % 10);

23: get_highscore_char = C_SPC; 24: get_highscore_char = C_SPC; 25: get_highscore_char = C_SPC;

26: get_highscore_char = C_P; 27: get_highscore_char = C_r; 28: get_highscore_char = C_E;

29: get_highscore_char = C_S; 30: get_highscore_char = C_S; 31: get_highscore_char = C_SPC;

32: get_highscore_char = C_r; 33: get_highscore_char = C_SPC; 34: get_highscore_char = C_t;

35: get_highscore_char = C_o; 36: get_highscore_char = C_SPC; 37: get_highscore_char = C_b;

38: get_highscore_char = C_A; 39: get_highscore_char = C_C; 40: get_highscore_char = C_F;

```

        default: get_highscore_char = C_SPC;

    endcase

end

endfunction

// GAME OVER: "LEGE nD FALLE n  SCo rE XX  PrESS U TO ME nU    " (Length 47)

function [5:0] get_gameover_char;

    input [6:0] pos;

    begin

        case(pos % 47)

            0: get_gameover_char = C_L; 1: get_gameover_char = C_E; 2: get_gameover_char =
C_G;

            3: get_gameover_char = C_E; 4: get_gameover_char = C_n; 5: get_gameover_char =
C_d;

            6: get_gameover_char = C_SPC; 7: get_gameover_char = C_F; 8:
get_gameover_char = C_A;

            9: get_gameover_char = C_L; 10: get_gameover_char = C_L; 11: get_gameover_char
= C_E;

            12: get_gameover_char = C_n; 13: get_gameover_char = C_SPC; 14:
get_gameover_char = C_SPC;

            15: get_gameover_char = C_S; 16: get_gameover_char = C_C; 17:
get_gameover_char = C_o;

            18: get_gameover_char = C_r; 19: get_gameover_char = C_E; 20:
get_gameover_char = C_SPC;

            21: get_gameover_char = (score / 10) % 10;

            22: get_gameover_char = (score % 10);

```

```
23: get_gameover_char = C_SPC; 24: get_gameover_char = C_SPC; 25:  
get_gameover_char = C_SPC;
```

```
26: get_gameover_char = C_P; 27: get_gameover_char = C_r; 28:  
get_gameover_char = C_E;
```

```
29: get_gameover_char = C_S; 30: get_gameover_char = C_S; 31:  
get_gameover_char = C_SPC;
```

```
32: get_gameover_char = C_U; 33: get_gameover_char = C_SPC; 34:  
get_gameover_char = C_t;
```

```
35: get_gameover_char = C_o; 36: get_gameover_char = C_SPC; 37:  
get_gameover_char = C_M;
```

```
38: get_gameover_char = C_E; 39: get_gameover_char = C_n; 40:  
get_gameover_char = C_U;
```

```
default: get_gameover_char = C_SPC;
```

```
endcase
```

```
end
```

```
endfunction
```

```
// NEW RECORD: "A nEU LEgEnd RIeS SCoRE XX PrESS U TO MEnU " (Length 52)
```

```
function [5:0] get_newrecord_char;
```

```
input [6:0] pos;
```

```
begin
```

```
case(pos % 52)
```

```
0: get_newrecord_char = C_A; 1: get_newrecord_char = C_SPC;
```

```
2: get_newrecord_char = C_n; 3: get_newrecord_char = C_E; 4: get_newrecord_char  
= C_U;
```

```
5: get_newrecord_char = C_SPC; 6: get_newrecord_char = C_L; 7:  
get_newrecord_char = C_E;
```

```
8: get_newrecord_char = C_G; 9: get_newrecord_char = C_E; 10:  
get_newrecord_char = C_n;
```

11: get_newrecord_char = C_d; 12: get_newrecord_char = C_SPC; 13:
get_newrecord_char = C_r;

14: get_newrecord_char = C_l; 15: get_newrecord_char = C_S; 16:
get_newrecord_char = C_E;

17: get_newrecord_char = C_S; 18: get_newrecord_char = C_SPC; 19:
get_newrecord_char = C_SPC;

20: get_newrecord_char = C_S; 21: get_newrecord_char = C_C; 22:
get_newrecord_char = C_o;

23: get_newrecord_char = C_r; 24: get_newrecord_char = C_E; 25:
get_newrecord_char = C_SPC;

26: get_newrecord_char = (score / 10) % 10;

27: get_newrecord_char = (score % 10);

28: get_newrecord_char = C_SPC; 29: get_newrecord_char = C_SPC; 30:
get_newrecord_char = C_SPC;

31: get_newrecord_char = C_P; 32: get_newrecord_char = C_r; 33:
get_newrecord_char = C_E;

34: get_newrecord_char = C_S; 35: get_newrecord_char = C_S; 36:
get_newrecord_char = C_SPC;

37: get_newrecord_char = C_U; 38: get_newrecord_char = C_SPC; 39:
get_newrecord_char = C_t;

40: get_newrecord_char = C_o; 41: get_newrecord_char = C_SPC; 42:
get_newrecord_char = C_M;

43: get_newrecord_char = C_E; 44: get_newrecord_char = C_n; 45:
get_newrecord_char = C_U;

default: get_newrecord_char = C_SPC;

endcase

end

```

endfunction

// DECODER

always @(*) begin

    case(char_index)

        C_0: seg = 7'b1000000; C_1: seg = 7'b1111001; C_2: seg = 7'b0100100; C_3: seg =
7'b0110000;

        C_4: seg = 7'b0011001; C_5: seg = 7'b0010010; C_6: seg = 7'b0000010; C_7: seg =
7'b1111000;

        C_8: seg = 7'b0000000; C_9: seg = 7'b0010000;

        C_L: seg = 7'b1000111; C_r: seg = 7'b0101111; C_U: seg = 7'b1000001; C_d: seg =
7'b0100001;

        C_SPC: seg = 7'b1111111; C_DASH: seg = 7'b0111111;

        C_A: seg = 7'b0001000; C_b: seg = 7'b0000011; C_C: seg = 7'b1000110; C_E: seg =
7'b0000110;

        C_F: seg = 7'b0001110; C_G: seg = 7'b0000010; C_H: seg = 7'b0001001; C_J: seg =
7'b1110001;

        C_n: seg = 7'b0101011; C_o: seg = 7'b0100011; C_P: seg = 7'b0001100; C_S: seg =
7'b0010010;

        C_t: seg = 7'b0000111; C_y: seg = 7'b0010001; C_l: seg = 7'b1111001;

        C_M: seg = 7'b0101010; // M looks kinda like n with extra line? or two n's? Using
pseudo-M

        default: seg = 7'b1111111;

    endcase

end

endmodule

```

Figures and graphs necessary to describe the project, including simulation results.



Figure 1: Test bench of my final project




Figure 2: Diagram of my final project

A conclusion statement. As part of the conclusion statement, the level of functionality should be discussed.

My first project failed but my other project was a complete success able to complete every aspect of the project as described in the project descriptions section. I was able to learn how to get scrolling text on the 7 segment display. I also learned how to make a game using tons of different states allowing me to get user input, display a timer and display a score. Finally I learned resilience. I tried as long as I could to get my original project to work but when I had to cut ties I did to ensure that I would have enough time to make a new project. This taught me that even when things don't work out to press on until something does.