

## Netsukuku topology

<http://netsukuku.freaknet.org>  
AlpT (@freaknet.org)

This document is part of Netsukuku.

Copyright © 2007 Andrea Lo Pumo aka AlpT <alpt@freaknet.org>. All rights reserved.

# Contents

<b>1</b>	<b>Preface</b>	<b>1</b>
<b>2</b>	<b>The general idea</b>	<b>1</b>
<b>3</b>	<b>Basic definitions</b>	<b>1</b>
<b>4</b>	<b>Network topology</b>	<b>1</b>
4.1	Fractal topology . . . . .	2
4.1.1	Level 1 . . . . .	2
4.1.2	Level n . . . . .	2
4.1.3	Membership . . . . .	3
4.2	Fractal map . . . . .	4
4.2.1	IP v4 and v6 . . . . .	5
4.2.2	Internal and external map . . . . .	



## 4.1 Fractal topology

### 4.1.1 Level 1

The QSPN algorithm is able to operate independently on any level, consid-












Figure 4: The gnodes  $G_1$ ,  $G_2$  a()1(d)]TJF119.963Tf19.3720Td[(G)]TJF76.974Tf7.833-1

and thus to  $C$ .  $C$  will send the packet again to  $B$







## 7 Network dynamics

### 7.3 Level $n$

The dynamics for the update of high levels are mainly governed by rule 6 and 7 of flat levels (see 6.3



## 7.5 Gnode hook

When a node creates a new gnode, it will choose a random gnode ID, and thus a random ip.

