



ANDROID STATIC ANALYSIS REPORT

app_icon

 GOwallet


File Name: gowallet-1.0.2-android-release.apk

Package Name: org.gowallet.pow

Scan Date: Sept. 7, 2026, 3:32 a.m.

App Security Score: 59/100 (MEDIUM RISK)

Grade:



FINDINGS SEVERITY

 HIGH	 MEDIUM	 INFO	 SECURE	 HOTSPOT
1	7	2	2	1

FILE INFORMATION

File Name: gowallet-1.0.2-android-release.apk

Size: 92.3MB

MD5: 55a45029694308951ec2f551d823efae

SHA1: 99f984d12f35d1c9a0f75c73ab96bae26c4958cf

SHA256: c944ad5725d5836e5428459043a82f217267b68db7b4dce20ec8a9afa2b37b4a

APP INFORMATION

App Name: GOwallet

Package Name: org.gowallet.pow

Main Activity: org.gowallet.pow.MainActivity

Target SDK:

Min SDK:

Max SDK:

Android Version Name:

Android Version Code:

APP COMPONENTS

Activities: 3
Services: 0
Receivers: 2
Providers: 2
Exported Activities: 0
Exported Services: 0
Exported Receivers: 1
Exported Providers: 0

CERTIFICATE INFORMATION

Binary is signed
v1 signature: False
v2 signature: True
v3 signature: True
v4 signature: False
v3.1 signature: False
v3.2 signature: False
X.509 Subject: CN=GOwallet Local Signing
Signature Algorithm: rsassa_pkcs1v15
Valid From: 2026-09-06 06:09:09+00:00
Valid To: 2054-01-22 06:09:09+00:00
Issuer: CN=GOwallet Local Signing
Serial Number: 0x415a4aee06af83be
Hash Algorithm: sha256
md5: 99c8f6622546bf04e0802fb34225664d
sha1: ed00428a5532cc6bd79599cbcb8a71e85138628a
sha256: 6e796fcb039900ddf4e0bd6b488fe524f665049b37fc480454fcf0f4c5a43f6e
sha512: dcb755e4b32ef2c64e10b7ced792ae77d91110287b633b60fbbbb7f1f8cb22b83d4715c0dda7fa00c9cc9f1727e0fcef71491e090e0ba9b7ba203da445fd5da6
PublicKey Algorithm: rsa
Bit Size: 3072
Fingerprint: 5e9108c5b64845aaf2b78814c389b21f1760893b53ce16b0d956a63c77c02354
Found 1 unique certificates

APPLICATION PERMISSIONS

PERMISSION	STATUS	INFO	DESCRIPTION
android.permission.USE_FINGERPRINT	normal	allow use of fingerprint	This constant was deprecated in API level 28. Applications should request USE_BIOMETRIC instead.
android.permission.INTERNET	normal	full Internet access	Allows an application to create network sockets.
android.permission.CAMERA	dangerous	take pictures and videos	Allows application to take pictures and videos with the camera. This allows the application to collect images that the camera is seeing at any time.
android.permission.HIDE_OVERLAY_WINDOWS	normal	Prevent non-system-overlay windows	Allows an app to prevent non-system-overlay windows from being drawn on top of it.
android.permission.ACCESS_NETWORK_STATE	normal	view network status	Allows an application to view the status of all networks.
android.permission.VIBRATE	normal	control vibrator	Allows the application to control the vibrator.
android.permission.POST_NOTIFICATIONS	dangerous	allows an app to post notifications.	Allows an app to post notifications
android.permission.USE_BIOMETRIC	normal	allows use of device-supported biometric modalities.	Allows an app to use device supported biometric modalities.
org.gowallet.pow.DYNAMIC_RECEIVER_NOT_EXPORTED_PERMISSION	unknown	Unknown permission	Unknown permission from android reference

FILE	DETAILS	
55a45029694308951ec2f551d823efae.apk	FINDINGS	DETAILS
	Manipulator Found	Resources Confusion
classes.dex	FINDINGS	DETAILS
	Anti-VM Code	Build.FINGERPRINT check Build.MODEL check Build.MANUFACTURER check Build.PRODUCT check Build.HARDWARE check Build.BOARD check possible Build.SERIAL check
	Compiler	r8
classes2.dex	FINDINGS	DETAILS
	Compiler	r8

 NETWORK SECURITY

NO	SCOPE	SEVERITY	DESCRIPTION
----	-------	----------	-------------

CERTIFICATE ANALYSIS

HIGH: 0 | WARNING: 0 | INFO: 1

TITLE	SEVERITY	DESCRIPTION
Signed Application	info	Application is signed with a code signing certificate

MANIFEST ANALYSIS

HIGH: 0 | WARNING: 2 | INFO: 0 | SUPPRESSED: 0

NO	ISSUE	SEVERITY	DESCRIPTION
1	Launch Mode of activity (org.gowallet.pow.MainActivity) is not standard.	warning	An Activity should not be having the launch mode attribute set to "singleTask/singleInstance" as it becomes root Activity and it is possible for other applications to read the contents of the calling Intent. So it is required to use the "standard" launch mode attribute when sensitive information is included in an Intent.
2	Broadcast Receiver (androidx.profileinstaller.ProfileInstallReceiver) is Protected by a permission, but the protection level of the permission should be checked. Permission: android.permission.DUMP [android:exported=true]	warning	A Broadcast Receiver is found to be shared with other apps on the device therefore leaving it accessible to any other application on the device. It is protected by a permission which is not defined in the analysed application. As a result, the protection level of the permission should be checked where it is defined. If it is set to normal or dangerous, a malicious application can request and obtain the permission and interact with the component. If it is set to signature, only applications signed with the same certificate can obtain the permission.

CODE ANALYSIS

HIGH: 1 | WARNING: 4 | INFO: 2 | SECURE: 1 | SUPPRESSED: 0

NO	ISSUE	SEVERITY	STANDARDS	FILES
				A1/c.java A1/f.java B/i.java C/A.java C/B.java C/D.java C/v.java C/w.java C/x.java C/y.java H/j.java I/d.java I1/b.java J2/b.java L/AbstractC0245y.java L/C0221c0.java L/O.java L/S.java L/V.java L0/a.java L0/b.java L0/c.java N/e.java O/i.java R/b.java R/d.java V/a.java X/AbstractComponentCallbacksC0277q.j ava X/C.java X/C0261a.java X/C0262b.java X/C0266f.java X/DialogInterfaceOnCancelListenerC027 5o.java X/K.java X/N.java X/Q.java X/S.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
1	The App logs information. Sensitive information should never be logged.	info	CWE: CWE-532: Insertion of Sensitive Information into Log File OWASP MASVS: MSTG-STORAGE-3	X/V.java X/b0.java Y/c.java b1/C0321e.java b1/g.java c1/AbstractC0342a.java c2/C0351i.java com/dexterous/flutterlocalnotifications/ActionBroadcastReceiver.java com/dexterous/flutterlocalnotifications/FlutterLocalNotificationsPlugin.java com/dexterous/flutterlocalnotifications/ScheduledNotificationReceiver.java com/journeyapps/barcodescanner/a.java com/journeyapps/barcodescanner/b.java d2/C0409i.java f/d.java i0/AbstractC0487a.java j/LayoutInflaterFactory2C0551e.java j/n.java j/t.java j/v.java m0/C0586a.java m0/C0590e.java n/g.java o/MenuItemC0614c.java p/AbstractC0657w.java p/C0660z.java p/D.java p/N.java p/P.java p/Q.java p/U.java p/V.java p/g0.java p/h0.java p/j0.java p0/f.java p0/o.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
				s/AbstractC0693i.java s/AbstractC0695k.java s/C0688d.java s/C0689e.java s/C0690f.java s/C0692h.java s/C0696l.java u/AbstractC0710b.java u0/C0712a.java v0/C0726a.java v0/q.java v0/u.java v0/y.java w0/C0740b.java w0/h.java w0/k.java w1/f.java y1/l.java z/d.java z/k.java z/r.java z1/AbstractC0803c.java z1/C0801a.java z1/g.java z1/h.java z1/l.java z1/n.java z1/q.java
2	App can read/write to External Storage. Any App can read data written to External Storage.	warning	CWE: CWE-276: Incorrect Default Permissions OWASP Top 10: M2: Insecure Data Storage OWASP MASVS: MSTG-STORAGE-2	A/c.java A1/f.java c2/AbstractC0350h.java c2/C0351i.java
3	This App copies data to clipboard. Sensitive data should not be copied to clipboard as other applications can access it.	info	OWASP MASVS: MSTG-STORAGE-10	io/flutter/plugin/editing/l.java io/flutter/plugin/platform/C0509i.java
4	The App uses an insecure Random Number Generator.	warning	CWE: CWE-330: Use of Insufficiently Random Values OWASP Top 10: M5: Insufficient Cryptography OWASP MASVS: MSTG-CRYPTO-6	t2/AbstractC0708a.java t2/b.java u2/C0723a.java

NO	ISSUE	SEVERITY	STANDARDS	FILES
5	The App uses the encryption mode CBC with PKCS5/PKCS7 padding. This configuration is vulnerable to padding oracle attacks.	high	CWE: CWE-649: Reliance on Obfuscation or Encryption of Security-Relevant Inputs without Integrity Checking OWASP Top 10: M5: Insufficient Cryptography OWASP MASVS: MSTG-CRYPTO-3	s/AbstractC0693i.java x1/h.java
6	Files may contain hardcoded sensitive information like usernames, passwords, keys etc.	warning	CWE: CWE-312: Cleartext Storage of Sensitive Information OWASP Top 10: M9: Reverse Engineering OWASP MASVS: MSTG-STORAGE-14	com/dexterous/flutterlocalnotifications/ FlutterLocalNotificationsPlugin.java com/dexterous/flutterlocalnotifications/i solate/IsolatePreferences.java com/dexterous/flutterlocalnotifications/ models/NotificationDetails.java
7	App creates temp file. Sensitive information should never be written into a temp file.	warning	CWE: CWE-276: Incorrect Default Permissions OWASP Top 10: M2: Insecure Data Storage OWASP MASVS: MSTG-STORAGE-2	com/journeyapps/barcodescanner/b.jav a
8	This app has capabilities to prevent tapjacking attacks.	secure	OWASP MASVS: MSTG-PLATFORM-9	org/gowallet/pow/MainActivity.java

SHARED LIBRARY BINARY ANALYSIS

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
----	---------------	----	-----	-----------------	-------	-------	---------	---------	---------------------

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
1	x86_64/libsqlite3.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__memcpy_chk', '__memset_chk', '__strchr_chk', '__memmove_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
2	x86_64/libisar.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__pwrite_chk', '__vsprintf_chk', '__write_chk', '__pread_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
3	x86_64/libsecp256k1.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
4	x86_64/libflutter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Not Applicable info RELRO checks are not applicable for Flutter/Dart binaries	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__fwrite_chk', '__read_chk', '__write_chk', '__memcpy_chk', '__strcpy_chk', '__pread_chk', '__strlen_chk', '__memmove_chk', '__poll_chk', '__readlink_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
5	x86_64/libapp.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
6	armeabi-v7a/libsqlite3.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__memcpy_chk', '__memset_chk', '__strchr_chk', '__memmove_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
7	armeabi-v7a/libisar.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__pwrite_chk', '__write_chk', '__pread_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
8	armeabi-v7a/libsecp256k1.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
9	arm64-v8a/libsqlite3.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__memcpy_chk', '__memset_chk', '__strchr_chk', '__memmove_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
10	arm64-v8a/libisar.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__pwrite_chk', '__vsprintf_chk', '__write_chk', '__pread_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
11	arm64-v8a/libsecp256k1.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
12	arm64-v8a/libflutter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Not Applicable info RELRO checks are not applicable for Flutter/Dart binaries	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__fwrite_chk', '__read_chk', '__write_chk', '__memcpy_chk', '__strcpy_chk', '__pread_chk', '__strlen_chk', '__memmove_chk', '__poll_chk', '__readlink_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
13	arm64-v8a/libapp.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
14	x86_64/libsqlite3.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__memcpy_chk', '__memset_chk', '__strchr_chk', '__memmove_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
15	x86_64/libisar.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__pwrite_chk', '__vsprintf_chk', '__write_chk', '__pread_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
16	x86_64/libsecp256k1.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
17	x86_64/libflutter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Not Applicable info RELRO checks are not applicable for Flutter/Dart binaries	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__fwrite_chk', '__read_chk', '__write_chk', '__memcpy_chk', '__strcpy_chk', '__pread_chk', '__strlen_chk', '__memmove_chk', '__poll_chk', '__readlink_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
18	x86_64/libapp.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
19	armeabi-v7a/libsqlite3.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__memcpy_chk', '__memset_chk', '__strchr_chk', '__memmove_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
20	armeabi-v7a/libisar.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__vsprintf_chk', '__pwrite_chk', '__write_chk', '__pread_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
21	armeabi-v7a/libsecp256k1.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
22	arm64-v8a/libsqlite3.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__strlen_chk', '__memcpy_chk', '__memset_chk', '__strchr_chk', '__memmove_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
23	arm64-v8a/libisar.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__pwrite_chk', '__vsprintf_chk', '__write_chk', '__pread_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
24	arm64-v8a/libsecp256k1.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Full RELRO info This shared object has full RELRO enabled. RELRO ensures that the GOT cannot be overwritten in vulnerable ELF binaries. In Full RELRO, the entire GOT (.got and .got.plt both) is marked as read-only.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
25	arm64-v8a/libflutter.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	True info This binary has a stack canary value added to the stack so that it will be overwritten by a stack buffer that overflows the return address. This allows detection of overflows by verifying the integrity of the canary before function return.	Not Applicable info RELRO checks are not applicable for Flutter/Dart binaries	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	True info The binary has the following fortified functions: ['__fwrite_chk', '__read_chk', '__write_chk', '__memcpy_chk', '__strcpy_chk', '__pread_chk', '__strlen_chk', '__memmove_chk', '__poll_chk', '__readlink_chk']	True info Symbols are stripped.

NO	SHARED OBJECT	NX	PIE	STACK CANARY	RELRO	RPATH	RUNPATH	FORTIFY	SYMBOLS STRIPPED
26	arm64-v8a/libapp.so	True info The binary has NX bit set. This marks a memory page non-executable making attacker injected shellcode non-executable.	Dynamic Shared Object (DSO) info The shared object is build with -fPIC flag which enables Position independent code. This makes Return Oriented Programming (ROP) attacks much more difficult to execute reliably.	False high This binary does not have a stack canary value added to the stack. Stack canaries are used to detect and prevent exploits from overwriting return address. Use the option -fstack-protector-all to enable stack canaries. Not applicable for Dart/Flutter libraries unless Dart FFI is used.	No RELRO high This shared object does not have RELRO enabled. The entire GOT (.got and .got.plt both) are writable. Without this compiler flag, buffer overflows on a global variable can overwrite GOT entries. Use the option -z,relro,-z,now to enable full RELRO and only -z,relro to enable partial RELRO.	None info The binary does not have run-time search path or RPATH set.	None info The binary does not have RUNPATH set.	False warning The binary does not have any fortified functions. Fortified functions provides buffer overflow checks against glibc's commons insecure functions like strcpy, gets etc. Use the compiler option -D_FORTIFY_SOURCE=2 to fortify functions. This check is not applicable for Dart/Flutter libraries.	True info Symbols are stripped.

NIAP ANALYSIS v1.3

NO	IDENTIFIER	REQUIREMENT	FEATURE	DESCRIPTION
----	------------	-------------	---------	-------------

BEHAVIOUR ANALYSIS

RULE ID	BEHAVIOUR	LABEL	FILES
00022	Open a file from given absolute path of the file	file	A1/f.java C0/d.java O1/d.java c2/C0351i.java com/journeyapps/barcodescanner/b.java
00202	Make a phone call	control	v0/y.java
00203	Put a phone number into an intent	control	v0/y.java
00063	Implicit intent(view a web page, make a phone call, etc.)	control	B0/d.java com/dexterous/flutterlocalnotifications/FlutterLocalNotificationsPlugin.java d2/C0408h.java u/AbstractC0710b.java v0/C0726a.java v0/q.java v0/y.java
00051	Implicit intent(view a web page, make a phone call, etc.) via setData	control	d2/C0408h.java v0/C0726a.java v0/q.java v0/y.java
00191	Get messages in the SMS inbox	sms	p/U.java

RULE ID	BEHAVIOUR	LABEL	FILES
00036	Get resource file from res/raw directory	reflection	com/dexterous/flutterlocalnotifications/FlutterLocalNotificationsPlugin.java p/U.java v0/C0726a.java v0/q.java
00147	Get the time of current location	collection location	j/v.java
00075	Get location of the device	collection location	j/v.java
00115	Get last known location of the device	collection location	j/v.java
00013	Read file and put it into a stream	file	A0/c.java A1/f.java C/D.java C/w.java D0/i.java V/a.java com/dexterous/flutterlocalnotifications/FlutterLocalNotificationsPlugin.java o2/AbstractC0632i.java
00012	Read data and put it into a buffer stream	file	A0/c.java A1/f.java V/a.java
00011	Query data from URI (SMS, CALLLOGS)	sms calllog collection	B0/d.java
00187	Query a URI and check the result	collection sms calllog calendar	B0/d.java R/d.java
00077	Read sensitive data(SMS, CALLLOG, etc)	collection sms calllog calendar	B0/d.java R/b.java R/d.java

RULE ID	BEHAVIOUR	LABEL	FILES
00161	Perform accessibility service action on accessibility node info	accessibility service	io/flutter/view/AccessibilityViewEmbedder.java io/flutter/view/k.java
00173	Get bounds in screen of an AccessibilityNodeInfo and perform action	accessibility service	M/s.java io/flutter/view/AccessibilityViewEmbedder.java
00175	Get notification manager and cancel notifications	notification	z/r.java
00091	Retrieve data from broadcast	collection	A1/f.java
00121	Create a directory	file command	A1/f.java
00125	Check if the given file path exist	file	A1/f.java O1/d.java
00104	Check if the given path is directory	file	A1/f.java
00183	Get current camera parameters and change the setting.	camera	z1/h.java
00209	Get pixels from the latest rendered image	collection	J1/C0209s.java
00210	Copy pixels from the latest rendered image into a Bitmap	collection	J1/C0209s.java

ABUSED PERMISSIONS

TYPE	MATCHES	PERMISSIONS
Malware Permissions	4/25	android.permission.INTERNET, android.permission.CAMERA, android.permission.ACCESS_NETWORK_STATE, android.permission.VIBRATE
Other Common Permissions	0/44	

Malware Permissions:

Top permissions that are widely abused by known malware.

Other Common Permissions:

Permissions that are commonly abused by known malware.

! OFAC SANCTIONED COUNTRIES

This app may communicate with the following OFAC sanctioned list of countries.

DOMAIN	COUNTRY/REGION
--------	----------------

DOMAIN MALWARE CHECK

DOMAIN	STATUS	GEOLOCATION
xmlpull.org	ok	IP: 185.199.110.153 Country: United States of America Region: Pennsylvania City: California Latitude: 40.065632 Longitude: -79.891708 View: Google Map

DOMAIN	STATUS	GEOLOCATION
www.slf4j.org	ok	IP: 31.97.181.89 Country: United Kingdom of Great Britain and Northern Ireland Region: England City: Bowness-on-Windermere Latitude: 54.363312 Longitude: -2.918590 View: Google Map
www.unicode.org	ok	IP: 104.26.10.47 Country: United States of America Region: California City: San Francisco Latitude: 37.775700 Longitude: -122.395203 View: Google Map
ns.adobe.com	ok	No Geolocation information available.
api.flutter.dev	ok	IP: 199.36.158.100 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map
dartbug.com	ok	IP: 216.239.34.21 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map

DOMAIN	STATUS	GEOLOCATION
developer.android.com	ok	IP: 142.250.199.238 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map
www.w3.org	ok	IP: 104.18.22.19 Country: United States of America Region: California City: San Francisco Latitude: 37.775700 Longitude: -122.395203 View: Google Map
journeyapps.com	ok	IP: 54.230.70.75 Country: India Region: Karnataka City: Bengaluru Latitude: 12.976230 Longitude: 77.603287 View: Google Map
docs.flutter.dev	ok	IP: 199.36.158.100 Country: United States of America Region: California City: Mountain View Latitude: 37.405991 Longitude: -122.078514 View: Google Map

DOMAIN	STATUS	GEOLOCATION
github.com	ok	IP: 20.205.243.166 Country: United States of America Region: Washington City: Redmond Latitude: 47.682899 Longitude: -122.120903 View: Google Map
xml.org	ok	IP: 172.67.205.113 Country: United States of America Region: California City: San Francisco Latitude: 37.775700 Longitude: -122.395203 View: Google Map

EMAILS

EMAIL	FILE
appro@openssl.org	lib/x86_64/libflutter.so
appro@openssl.org	lib/arm64-v8a/libflutter.so
appro@openssl.org	apktool_out/lib/x86_64/libflutter.so
appro@openssl.org	apktool_out/lib/arm64-v8a/libflutter.so

HARDCODED SECRETS

POSSIBLE SECRETS
"library_zxingandroidembedded_author" : "JourneyApps"
"library_zxingandroidembedded_authorWebsite" : "https://journeyapps.com/"
0000000100100011010001010110011110001001101010111001101110111100010203040506071011121314151617202122232425262730313233343536374041424344454647505152535455565760616263646566677071727374757677000102030405060708090a0b0c0d0e0f101112131415161718191a1b1c1d1e1f202122232425262728292a2b2c2d2e2f303132333435363738393a3b3c3d3e3f404142434445464748494a4b4c4d4e4f505152535455565758595a5b5c5d5e5f606162636465666768696a6b6c6d6e6f707172737475767778797a7b7c7d7e7f808182838485868788898a8b8c8d8e8f909192939495969798999a9b9c9d9e9fa0a1a2a3a4a5a6a7a8a9aaabacadaeafb0b1b2b3b4b5b6b7b8b9babbcbdbbebf0c1c2c3c4c5c6c7c8c9cacbcccdcecf0d1d2d3d4d5d6d7d8d9daddbcdddedfe0e1e2e3e4e5e6e7e8e9eaebeceedeef0f1f2f3f4f5f6f7f8f9fafbfcfdfeff
00010203040506070809101112131415161718192021222324252627282930313233343536373839404142434445464748495051525354555657585960616263646566676869707172737475767778798081828384858687888990919293949596979899
00010203040506070809101112131415161718192021222324252627282930313233343536373839404142434445464748495051525354555657585960616263646566676869707172737475767778798081828384858687888990919293949596979899000000010010001101000101011001111000100110101011110011011110111100010203040506071011121314151617202122232425262730313233343536374041424344454647505152535455565760616263646566677071727374757677000102030405060708090a0b0c0d0e0f101112131415161718191a1b1c1d1e1f202122232425262728292a2b2c2d2e2f303132333435363738393a3b3c3d3e3f404142434445464748494a4b4c4d4e4f505152535455565758595a5b5c5d5e5f606162636465666768696a6b6c6d6e6f707172737475767778797a7b7c7d7e7f808182838485868788898a8b8c8d8e8f909192939495969798999a9b9c9d9e9fa0a1a2a3a4a5a6a7a8a9aaabacadaeafb0b1b2b3b4b5b6b7b8b9babbbcbdbbebf0c1c2c3c4c5c6c7c8c9cacbcccdcecf0d1d2d3d4d5d6d7d8d9daddbcdddedfe0e1e2e3e4e5e6e7e8e9eaebeceedeef0f1f2f3f4f5f6f7f8f9fafbfcfdfeff
00112233445566778899
0123456789ABCDEF0123456789abcdef
0123456789abcdefABCDEF
0123456789abcdefABCDEFx+
0451907c2eaa8467e848c0067bfe8ed4
18446744073709551615
5f77625673248ee5846fbcaf5d3e1a3878386fd7

POSSIBLE SECRETS
6b00bc3880198600130e1cf62b8f8a93494488cc
8df24be66531469e576a806749a0202ae26b8d08
c9c2ab54ba1f5f46360f1b4f35d849cd3f080e6fc2b6c60e91b16c63f69a1e33
VGhpcyBpcyB0aGUga2V5IGZvciBhIHNIY3VyZSBzdG9yYWdlIEFFUyBLZXkk
VGhpcyBpcyB0aGUga2V5IGZvciBhIHNIY3VyZSBzdG9yYWdlIEFFUyBLZXkk
VGhpcyBpcyB0aGUga2V5IGZvciBhIHNIY3VyZSBzdG9yYWdlICg
vkCmdPushDescriptorSetWithTemplate2KHR

SCAN LOGS

Timestamp	Event	Error
2026-09-07 03:32:07	Generating Hashes	OK
2026-09-07 03:32:07	Extracting APK	OK
2026-09-07 03:32:07	Unzipping	OK
2026-09-07 03:32:07	Parsing APK with androguard	OK

2026-09-07 03:32:07	Extracting APK features using aapt/aapt2	OK
2026-09-07 03:32:07	Getting Hardcoded Certificates/Keystores	OK
2026-09-07 03:32:09	Parsing AndroidManifest.xml	OK
2026-09-07 03:32:09	Extracting Manifest Data	OK
2026-09-07 03:32:09	Manifest Analysis Started	OK
2026-09-07 03:32:09	Performing Static Analysis on: GOWallet (org.gowallet.pow)	OK
2026-09-07 03:32:15	Fetching Details from Play Store: org.gowallet.pow	OK
2026-09-07 03:32:18	Checking for Malware Permissions	OK
2026-09-07 03:32:18	Fetching icon path	OK
2026-09-07 03:32:18	Library Binary Analysis Started	OK
2026-09-07 03:32:18	Analyzing lib/x86_64/libsqlite3.so	OK

2026-09-07 03:32:18	Analyzing lib/x86_64/libisar.so	OK
2026-09-07 03:32:18	Analyzing lib/x86_64/libsecp256k1.so	OK
2026-09-07 03:32:18	Analyzing lib/x86_64/libflutter.so	OK
2026-09-07 03:32:18	Analyzing lib/x86_64/libapp.so	OK
2026-09-07 03:32:18	Analyzing lib/armeabi-v7a/libsqlite3.so	OK
2026-09-07 03:32:18	Analyzing lib/armeabi-v7a/libisar.so	OK
2026-09-07 03:32:18	Analyzing lib/armeabi-v7a/libsecp256k1.so	OK
2026-09-07 03:32:18	Analyzing lib/arm64-v8a/libsqlite3.so	OK
2026-09-07 03:32:18	Analyzing lib/arm64-v8a/libisar.so	OK
2026-09-07 03:32:18	Analyzing lib/arm64-v8a/libsecp256k1.so	OK
2026-09-07 03:32:18	Analyzing lib/arm64-v8a/libflutter.so	OK

2026-09-07 03:32:19	Analyzing lib/arm64-v8a/libapp.so	OK
2026-09-07 03:32:19	Analyzing apktool_out/lib/x86_64/libsqlite3.so	OK
2026-09-07 03:32:19	Analyzing apktool_out/lib/x86_64/libisar.so	OK
2026-09-07 03:32:19	Analyzing apktool_out/lib/x86_64/libsecp256k1.so	OK
2026-09-07 03:32:19	Analyzing apktool_out/lib/x86_64/libflutter.so	OK
2026-09-07 03:32:19	Analyzing apktool_out/lib/x86_64/libapp.so	OK
2026-09-07 03:32:19	Analyzing apktool_out/lib/armeabi-v7a/libsqlite3.so	OK
2026-09-07 03:32:19	Analyzing apktool_out/lib/armeabi-v7a/libisar.so	OK
2026-09-07 03:32:19	Analyzing apktool_out/lib/armeabi-v7a/libsecp256k1.so	OK
2026-09-07 03:32:19	Analyzing apktool_out/lib/arm64-v8a/libsqlite3.so	OK
2026-09-07 03:32:19	Analyzing apktool_out/lib/arm64-v8a/libisar.so	OK

2026-09-07 03:32:19	Analyzing apktool_out/lib/arm64-v8a/libsecp256k1.so	OK
2026-09-07 03:32:19	Analyzing apktool_out/lib/arm64-v8a/libflutter.so	OK
2026-09-07 03:32:19	Analyzing apktool_out/lib/arm64-v8a/libapp.so	OK
2026-09-07 03:32:19	Reading Code Signing Certificate	OK
2026-09-07 03:32:20	Running APKiD 3.1.0	OK
2026-09-07 03:32:26	Updating Trackers Database....	OK
2026-09-07 03:32:26	Detecting Trackers	OK
2026-09-07 03:32:27	Decompiling APK to Java with JADX	OK
2026-09-07 03:32:36	Converting DEX to Smali	OK
2026-09-07 03:32:36	Code Analysis Started on - java_source	OK
2026-09-07 03:32:39	Android SBOM Analysis Completed	OK

2026-09-07 03:32:40	Android SAST Completed	OK
2026-09-07 03:32:40	Android API Analysis Started	OK
2026-09-07 03:32:41	Android API Analysis Completed	OK
2026-09-07 03:32:41	Android Permission Mapping Started	OK
2026-09-07 03:32:42	Android Permission Mapping Completed	OK
2026-09-07 03:32:42	Android Behaviour Analysis Started	OK
2026-09-07 03:32:43	Android Behaviour Analysis Completed	OK
2026-09-07 03:32:43	Extracting Emails and URLs from Source Code	OK
2026-09-07 03:32:44	Email and URL Extraction Completed	OK
2026-09-07 03:32:44	Extracting String data from APK	OK
2026-09-07 03:32:44	Extracting String data from SO	OK

2026-09-07 03:32:46	Extracting String data from Code	OK
2026-09-07 03:32:46	Extracting String values and entropies from Code	OK
2026-09-07 03:32:46	Performing Malware check on extracted domains	OK
2026-09-07 03:32:51	Saving to Database	OK

Report Generated by - MobSF v4.5.2

Mobile Security Framework (MobSF) is an automated, all-in-one mobile application (Android/iOS/Windows) pen-testing, malware analysis and security assessment framework capable of performing static and dynamic analysis.

© 2026 Mobile Security Framework - MobSF | [Ajin Abraham](#) | [OpenSecurity](#).