

homework-2

Packages

Question 1

```
install.packages("aRtsy")
```

`install.packages()` is used to install a package on the computer, while `library()` is used to load an installed package into the current R session. Usually, a package only needs to be installed once, but `library()` needs to be run every time when starting a new R session and want to use that package.

Question 2

```
library(aRtsy)
```


The Collatz conjecture is a mathematical problem involving positive integers. If a number is even, divide it by 2; if it is odd, multiply it by 3 and add 1. The conjecture states that repeating this process will eventually reach 1 for any positive integer.

The Collatz equation is $f(n) = n/2$, while n is even, $f(n) = 3n + 1$, while n is odd.

Question 3

Part a

```
set.seed(10)
canvas_collatz(
  colors = c("blue"),
  n = 10
)
```



The `canvas_collatz()` function creates plot based on the Collatz sequence. In this code, `colors = c("blue")` makes the lines blue, and `n = 10` tells the function to use 10 random starting integers to create the lines.

Part b

- 1.The output is different each time because `canvas_collatz()` uses randomly selected starting integers. Since the random values can change each time when the code is run, the resulting plot can also change.
- 2.This can be troublesome in a .qmd file because rendering the document multiple times could produce different figures. This makes the results harder to get the same result each time.
- 3.The `set.seed()` function sets the starting point for R's random number generator. Using the same seed allows the random results to be reproduced, so the same artwork can be generated each time the document is rendered, which can be helpful for others to understand the plot.