Sheet Shrink: Efficient Spreadsheet Cleanup

Alexander Aue-Johr
Institute of Rural Studies
Thünen-Institute
Braunschweig, Germany
Harz University of Applied Sciences
Doctoral Candidate, Germany
ORCID 0009-0001-8683-3630




Fig. 1. Recorded development run on 144 Enron workbooks selected for large absolute XLSX reductions, using 12 workers. Work intervals follow workbook admission order (WB denotes workbook, numbered by admission). Thread labels identify worker lanes. The lower view compares the three largest uncompressed packages on one linear byte scale. Curves connect worksheet S2 in WB 1 to its work items. Observed wall time was 17.077 s.

***Abstract*—Spreadsheet packages can contain large populations of empty or redundant cell records that increase storage and ingestion costs. Cleanup must distinguish this structural redundancy from small formatting or dependency witnesses that preserve required workbook behavior. We present Sheet Shrink, a byte-oriented OOXML cleanup system that rewrites stored XLSX packages before opening them in Excel. It combines workbook-context analysis, local rewrite decisions, compact formatting representatives, and bounded parallel execution. We define its preservation contract and separate intentional policy choices from defects. Cleanup screening processed 1,182 Destatis, 8,623 Data.gov, and 30,301 prepared Enron XLSX inputs, reducing their aggregate compressed bytes by 15.48%, 5.29%, and 18.92%, respectively. Data.gov additionally had 494 unsupported-namespace skips. In a stress cohort of 147 workbooks chosen for large absolute reductions, 134 had targeted native comparisons against their selected originals and seven further observations used documented normalized baselines. Six lacked an eligible comparison. Independent native controls illustrate how retaining small formatting witnesses can preserve Excel's rendering. These measurements describe the selected capture scope.**




Fig. 2. Schematic cleanup families. Redundant cell formatting includes inherited fills and borders. Every pair has layout, protection and dependency guards. Row promotion requires compatible fixed-height context. Hidden-value removal admits guarded constant tails of at least 4,096 cells ending at XFD. *Whitespace removal is optional. Required witnesses and cell coordinates are retained.

I. Introduction

Spreadsheet files are both data containers and executable visual documents. A user can store a compact table in a workbook whose worksheet parts contain large numbers of otherwise empty cells. Such records can increase the work required to decompress and interpret the package. Removing every empty-looking record is unsafe. An empty cell can preserve a border, override an inherited fill, or influence automatic row height through its font. A whitespace value can prevent text from extending into its neighbour. Cleanup therefore requires a model of the effects that stored structures have on the document.

A motivating case is the Destatis migration workbook `wanderungen-2010120217005.xlsx`. In worksheet `Tabelle 3.4`, 21 rows each contain numeric zeros from column L through Excel's final column XFD. Those tails alone contain 343,833 stored values. They are hidden content, so removing them requires a stated admission policy and dependency checks in addition to empty-format cleanup. Section III-E describes the case and the values that the conservative policy deliberately retains.

For an XLSX input, Sheet Shrink makes these decisions from the stored package before loading the workbook in Excel. Its cleanup stage has no native rendering or calculated row-height observations. An Excel-hosted method can inspect the loaded layout and evaluate candidate edits against native observations. Our method instead retains compact source structures whose required effects follow from package analysis and the preservation rules. Native Excel is used later to evaluate the output. Legacy XLS conversion is a separately measured preparation stage.

Specialized spreadsheet parsing has demonstrated the importance of decompression, parsing, memory use and parallel execution for data loading [1]. Our problem adds a transformation obligation. The output remains an editable XLSX workbook and must retain required data, dependencies and visible presentation under a stated contract. File size alone is an inadequate measure of success. A smaller file that changes an important row height has failed that obligation.

Figure 2 summarizes guarded reductions across cells, rows, columns and workbook metadata. Sheet Shrink reuses existing style indices and compact witnesses to preserve required effects. Native saving can additionally compact style and shared-string tables.

The performance objective includes the complete user operation. For a sufficiently bloated workbook, we seek to make cleanup followed by opening the cleaned file faster than directly opening its original. This objective must be measured, including the cases where cleanup adds overhead. A single-thread comparison separates improvements in work performed from gains due to extra processing resources. Parallel corpus experiments then examine throughput and memory.

The paper develops the preservation model, the small-footprint mechanisms that implement it, and an evaluation combining structural checks with native visual observations. The evaluation distinguishes completed observations, unsupported inputs and unresolved differences. Historical Python implementations provide context for the engineering progression. Their different cleanup rules require separate output and correctness accounting in any timing comparison.

II. Preservation and Comparison Contract

A. Observable spreadsheet behavior

A spreadsheet package contains more than the populated table that a user sees. Individual cell records can carry formatting, protection, references, or values that affect other cells. Conversely, the presence of a stored record does not establish that it contributes to the intended presentation. Sheet Shrink targets production cleanup of such packages while retaining the structures needed by its preservation contract. Aggressive historical configurations are separate test artifacts and are excluded from the production subject of this paper.

The relevant visual area includes cells with meaningful values or formulas, empty cells with effective visible fills or borders, and graphical objects. Formatting inherited from rows or columns can contribute to this area. Conditional formatting and text extending into adjacent cells can also affect what is visible. The union of the original and transformed relevant areas is required when checking removed content. Layout changes in otherwise empty trailing rows or columns are permitted by the contract. Changes that move or alter relevant content remain subject to validation.

B. Information available before native loading

The cleanup decision uses stored values, formulas, styles, references and layout attributes. Native effective row heights and candidate before/after images are available only in the separate validation workflow. Stored custom heights can be retained directly. For automatically sized rows, a font-bearing blank can still require a representative even when its payload is empty.

An Excel-hosted alternative could measure a row, remove candidates and write the measured height as an explicit custom

height. SpreadsheetML provides a *customHeight* attribute for that policy [2]. Applying this technique requires a trusted height for the chosen renderer and a contract for replacing automatic sizing with a fixed height. The evaluated cleanup derives its compact preservation decisions from package context.

C. Removal decisions and compact preservation

A record can be eligible for removal only after accounting for its required contribution. An empty cell may still influence automatic row height through its font. A whitespace-only value may stop text from extending from an adjacent cell. Referenced hidden content can influence displayed values and charts. These cases require different reasoning from a test for an absent payload.

The preservation strategy retains a small representative when that representative can preserve a required effect. Row-font sentinels and guarded promotion of an existing style into a row format are examples. Their applicability depends on inherited formatting, gaps, merges, protection, and the available style records. An unresolved case retains the required source representation. The objective is to remove eligible bloat throughout the package while keeping the preservation footprint small.

The production policy admits separately guarded hidden constant tails and retains ordinary nonempty hidden tables, including unreferenced values. Tail admission depends on dependency and layout checks [3]. Absence of a reference alone does not authorize general hidden-data removal. A future Excel-hosted cleanup stage could measure native layout before replacing additional sentinels or whitespace blockers. Such a stage is outside the implementation evaluated here.

D. Validation and attribution boundaries

DeltaSieve compares selected regions of independently rebuilt original and Sheet Shrink workbooks in the same installed Excel environment [10]. Ordinary-save and rebuild controls retain information for attributing differences introduced by Excel. Excel save-only controls distinguish cleanup effects from changes introduced by serialization and recalculation. For XLS sources, conversion precedes the XLSX cleanup subject and has its own failure accounting. A file requiring repair or inaccessible protected content receives an explicit unsuccessful outcome.

Targeted visual equality is an observation over the selected regions. We evaluate the selection mechanism separately with native reference captures and mutations. Unequal pixels are retained for investigation. Repeated rendering controls, volatile dependencies, and capture geometry help classify their cause. The results section must report the completed coverage and unresolved findings at its fixed evaluation cutoff.

III. Method

A. Representation and analysis stages

Figure 3 summarizes the cleanup pipeline. The input is an XLSX ZIP package. The output retains its workbook structure and cell coordinates while removing records admitted by the preservation policy. Package metadata supplies style components, shared strings, relationships, merged regions and dependency sources. These contexts are prepared before cell-local decisions, so an index or an empty payload is never sufficient by itself to establish redundancy.

Require: Workbook package W, cleanup policy P
Ensure: Cleaned package or explicit unsuccessful outcome
Check supported serialization of W
Resolve styles, strings, layout and references
for all worksheets in W **do**
    Classify content and effective formatting
    Identify protected references and layout anchors
    Select guarded removals under P
    Retain compact font and geometry witnesses
    Rewrite admitted records and retain other effects
end for
Reconcile names and calculation-chain changes
Assemble output with unaffected package members
Publish only a successfully completed package

Fig. 3. Sheet Shrink's logical cleanup stages. Guards are resolved before removal. Worksheet scheduling and chunking preserve these decisions.

Worksheet analysis consumes decompressed byte buffers without constructing an XML object for every cell. A state machine separates worksheet headers, column records, sheet data, merge information and the remaining suffix. In cell and row regions, bounded tag and attribute readers track hierarchy and quoting. Thus text resembling a coordinate inside a quoted metadata value cannot become a cell address. Small overlap state recognizes markers spanning input-buffer boundaries. Parsed metadata is retained only where later decisions require it. Names, references and other interpreted values can still require decoding. The implementation does not assume that arbitrary worksheet text is ASCII.

This organization reduces per-record allocation, but does not imply constant memory in worksheet size. The current implementation retains the sheet-data bytes, contexts and candidate metrics needed by subsequent passes. Decompression, rewriting, compression and retained analysis structures all contribute to peak memory. The supported input domain is normal unprefixed Transitional SpreadsheetML. Unsupported namespaces, encodings and ambiguous core structures follow explicit preservation or exclusion paths [3]. Eligibility checks inspect bounded package-root headers and declarations encountered during streaming to identify unsupported representations before native opening.

Figure 4 makes the worksheet preprocessor's control states explicit. The dispatcher separates column, cell and merge contexts. Read boundaries preserve partial state, and complete row prefixes can progress without consuming an unfinished row. Reconstruction follows successful arrival at the worksheet end.

B. Parser correctness and regression controls

Byte-oriented scanning transfers XML recognition and state-transition obligations to the implementation. Mature SAX and DOM libraries provide extensively exercised syntax




Fig. 4. The six worksheet-stream states. Child readers return to the same worksheet dispatcher. Row-aligned progress retains a partial row across reads. The lower box summarizes error outcomes. Reaching the end state permits reconstruction, with workbook publication subject to its own completion checks.

handling, while application-specific scanners require explicit checks for element boundaries, quoted attributes, empty elements and incomplete input. Memory-safe execution still permits a scanner to misclassify content and emit an incorrect workbook. A rare serialization can expose such a defect after many successful inputs.

Our development history supplies a concrete example. A Data.gov workbook used `<v xml:space="preserve">` for visible string values. A scanner recognizing only the literal `<v>` classified these cells as empty and removed a heading and other strings. The correction recognizes valid element-name delimiters and retains attributed value and inline-string elements. Negative controls reject longer lookalike names such as `<value>` [4]. A separate defined-name regression ensures that a self-closing element cannot consume the following paired element during replacement [5].

Terminal-state checks are equally important. The worksheet stream must reach its closing state before output publication. An incomplete parse raises an error, removes partial output and preserves any existing destination. Integration fixtures exercise this failure after another worksheet has already been processed [6]. Streaming diagnostics additionally test comments, CDATA, quotes, nesting limits and source offsets across every input chunk size of their small fixtures. These diagnostic readers and the cleanup scanner have separate regression coverage.

At the time of writing, 31 correctness tests in the dedicated XML, namespace, shared-string, range, defined-name and streaming-reader modules exercise parsing and recognition behavior. A further 155 correctness tests in the cell, row and tail suites cover preservation witnesses, inheritance masks and content boundaries. Additional tests cover dependencies, styles, output construction and execution behavior. Counts refer to test functions, with parameterized fixture iterations counted once. The artifact records the source revision, test paths and counting criteria.

Source

```
<row r="2">
 <c r="A2">...</c>
 <c r="B2" s="1"/>
- <c r="C2" s="1"/>
</row>
```

Guarded result

```
<row r="2">
 <c r="A2">...</c>
 <c r="B2" s="1"/>
</row>
```

Original

Font witness control			
10 pt text			
Next visible row			

One witness

Font witness control			
10 pt text			
Next visible row			

No witness

Font witness control			
10 pt text			
Next visible row			

Fig. 5. A reduced font-witness control. A2 uses Arial 10, while empty B2 and C2 use Arial 18. Red marks the removed duplicate. The source and one-witness native vector exports match after a full rebuild in Excel 16.0 build 20326. Removing both empty Arial 18 cells reduces row 2 from 23.25 to 12.75 points and moves the following row. XML is abbreviated. These are constructed native print controls with gridlines, separate from the corpus regression.

C. *Effects and compact preservation witnesses*

A numeric value, formula or inline string is content. In particular, zero and a shared-formula follower with no independent formula text remain content. An empty cell is classified by its effective formatting in the cell, row and column context. An explicit no-fill or borderless style can suppress a visible inherited effect. It remains necessary whenever deletion would expose that effect. Conversely, an explicit no-fill with nothing to clear can be redundant. Style components and application flags are therefore interpreted together.

Automatic row height introduces a different dependency. An empty cell's font can determine row height and move later content. Sheet Shrink retains a required font representative instead of every repeated occurrence. Equivalent font records can share an identity even when their style indices differ. Selection also respects local column-font masks and merged spans. A witness elsewhere in the row does not automatically replace a required local mask. Figure 5 isolates the mechanism in a constructed native Excel control. One witness preserves the observed height. Removing both moves the next visible row.

A fixed height eliminates this automatic-height effect, but an empty font-bearing cell can still affect the text baseline in a row containing text. The cleaner therefore distinguishes

an empty fixed-height row from a fixed-height text row. Protection metadata does not erase a required font contribution. Protection formats inside the retained data extent also preserve interaction semantics, while separately guarded exterior tails can be removed.

Other witnesses preserve relationships between coordinates. Center-across-selection requires the contiguous blank span following the text cell. A borderless row can mask column borders, and an empty height-bearing row can determine their vertical extent. Column widths remain necessary when they support visible row borders. A chart can inherit a number format from an empty first series cell. These structures extend the preservation problem beyond the last nonempty value. Figure 6 shows an Enron counterexample in which Check Performance's smaller output exposes a different inherited fill. The observation concerns the pictured rebuilt region.

D. Guarded promotion and tail pruning

A second compaction replaces repeated cell styles with an existing row format. The row must be visible, unprotected and without an existing row style. Both a stored height and an enabled `customHeight` flag are required. A stored `ht` alone does not freeze automatic sizing. Content cells, merged cells, missing positions and inherited column formats must remain compatible with the proposed row format. Figure 7 illustrates the full-width case [7].

The dominant empty-cell style occurs at least twice. Selection counts unsuitable styles too, then applies eligibility checks. Otherwise an eligible minority could incorrectly replace an unsuitable majority. Ties choose the smaller existing style index. Dense promotion requires at least 1,024 occurrences. A bounded-gap route admits at most 64 missing columns and restores required original formats only under its inheritance checks. Sparse promotion requires equivalent inheritance at every absent position and excludes merged sparse rows. Uniform-fill promotion additionally checks content-cell fills. Unknown metadata or style identities prevent promotion and retain the ordinary cleanup path.

Tail pruning removes formatting-only structure beyond retained content and layout anchors. Font-only blanks after the last relevant anchor need not preserve the position of nonexistent later content. Visible fills, borders, conditional regions and drawing anchors can still extend that boundary. A white row fill is redundant only when compatible column fills cover every column through XFD. An uncovered column breaks that argument. Compatible extraneous column ranges can be coalesced, but local overrides and border-supporting geometry remain.

E. Hidden content and the Wanderungen case

Ordinary hidden nonempty tables remain intact. The separate constant-tail policy admits only a dense horizontal suffix of at least 4,096 identical signed integers, hidden and ending at XFD, subject to cell-level layout and dependency guards. Gaps, formulas, text, differing values and unsupported numeric forms reject the band. Source cells contribute before style cleanup. The common zero path compares value bytes directly, while one admitted row span replaces per-cell entries in the later reference map. Temporary row-local candidates still exist.

The motivating migration workbook contains 21 such zero tails in `Tabelle 3.4`: rows 11–30 and 32, from L through XFD. Each contains 16,373 zeros, totaling 343,833. Source ZIP inspection confirms these counts and retains the source hash. The historical cleanup investigation records 376,573 removed zeros across two worksheets, alongside 243 preserved nonzero values and a retained short 237-zero tail [8]. The full abbreviated XML example is included in the companion atlas. These are content removals under an explicit structural policy. A deliberate constant full-width matrix can meet the same heuristic, so repetition alone does not establish user intent.

F. Workbook dependencies and deferred rewriting

Reference-sensitive candidates remain pending until workbook-level analysis has seen supported formulas, names, chart and object formulas, and pivot dependencies. A formula on a later worksheet can otherwise refer to content already removed. References resolve through workbook relationships and sheet scope. Shared-formula followers move relative axes while retaining absolute axes. The implementation protects enclosing source rectangles without expanding each follower cell. Dynamic addressing, unresolved scope and unsupported expressions prevent the required deletion argument [9].

A known reference intersecting an admitted hidden span protects the entire span. Only admitted candidates reach rewriting. Removing a payload need not remove its format if that format still masks an inherited effect. After deferred changes, affected rows lose their stale tail anchors and pass through cleanup again. Otherwise records retained solely because of the removed anchor would survive incorrectly. Whitespace removal is disabled in Default because whitespace can control text overflow and row layout.

Package metadata has separate predicates. Calculation-chain cleanup resolves removed cells by sheet identity and preserves unresolved mappings. The cleaner does not evaluate formulas or manufacture replacement caches. Built-in alias cleanup currently matches name and local scope without proving equality of the two formula bodies. This is a specific limitation of that policy.

G. Parallel work and output ownership

Figure 8 relates the task hierarchy to a schematic execution across threads. Worksheet identity remains shared across its chunks, while ordered assembly separates execution order from output order. Workbook, worksheet and row-chunk work share the cleanup execution budget. A permit limits active workbooks and remains held through output finalization. Workers can process other workbooks while one long worksheet remains active. Large worksheets expose row-aligned chunks to Rayon, allowing idle workers to help without splitting a row's font, promotion or tail decisions. The chunk planner estimates byte-sized work, then adjusts boundaries to complete rows. Small ranges use the serial path. Each chunk




Fig. 6. Empty cells can preserve a visible fill. In Enron case `ccde4294bab9094d7d73`, an explicit gray B31 cell masks a pink column format (column XF 51, cell XF 98). The retained Original and Sheet Shrink Default vector exports match in `PL-Consolidated!A25:H37` after full rebuild of the retained rebuild/Save controls. Check Performance removes the mask and exposes pink. The source excerpt is shortened. The print-renderer equality observation covers this region.




Fig. 7. Guarded dense-row promotion reuses an existing XF and keeps the value cell. Red marks removed lines and green marks added lines. The illustration omits the repeated middle cells. The full-width regression removes 16,383 empty cell records under the visible fixed-height, unprotected-row and inheritance guards. Dense promotion requires at least 1,024 occurrences. Required fill, border, protection and font effects at missing positions are preserved. XML is abbreviated and style indices are local. Additional XML examples accompany the paper.

receives isolated metrics, and results are assembled in source order.

Ready chunks participate in admission decisions for new worksheets. A smaller sheet can yield admission while larger chunk work is pending. This priority is an implementation policy over the common work-stealing pool, not a distinct semantic rule. Batches retain only a bounded number of chunk results while the assembled output grows. Workbook contexts, the output buffer and deferred candidates remain additional memory consumers. Thread count, active-workbook count and writer count are separate experimental parameters.

Changed worksheet members are precompressed in parallel and handed to a workbook writer. The writer owns ZIP mutation and publishes a completed partial output only after processing succeeds. Unaffected members can reuse compressed bytes. If all entries are original, the source workbook is copied byte for byte. A fast unchanged-entry classification can use CRC32 and uncompressed length. That shortcut is collision-prone, and exact byte verification is available. Preservation and timing experiments must record which identity policy was used. Cryptographic evidence reuse is a separate validation mechanism.

The method retains existing style and shared-string indices rather than globally renumbering their tables. This avoids unrelated rewrites and permits copy-through of unaffected members. It also leaves reductions requiring native save or global table compaction outside the cleanup subject. Work events retain the relation between workbook, worksheet and chunk jobs for diagnosis and replay. The UI is an observation tool, not evidence that unobserved regions are unchanged.

IV. Evaluation

The evaluation asks three questions. RQ1 examines compressed package reduction and the remaining preservation footprint. RQ2 measures cleanup time, memory and the combined cleanup-plus-opening operation. RQ3 examines structural preservation and observed native presentation under the stated validation scope.

A. Corpus identity and outcome accounting

The evaluation treats Data.gov, Destatis and Enron as distinct populations. Archive checksums, member names and duplicate occurrences identify each selected corpus version. Legacy XLS conversion is reported separately from XLSX cleanup. The EDRM Enron v2 XML extraction supplies 34,065 distinct SHA-256-addressed candidates, including legacy Excel and other OLE objects. This input frame is separate from the prepared Enron XLSX population evaluated below. Extraction provenance, manifests and import checks accompany the experiment.

The native visual stress cohort selects the 49 whole workbooks with the largest absolute compressed-file byte reduction in each corpus, totaling 147 original identities. All processor baselines use those same identities. Preparation, cleanup and visual-comparison outcomes are counted separately.

Table I reports the frozen Data.gov and Destatis XLSX source inventories; each archive member has a SHA-256 identity. Reported outcomes distinguish completed comparisons, differences, failures, unsupported representations and unfinished work, with retries counted separately. Exact package




Fig. 8. Hierarchical parallelism in Sheet Shrink. Workbook admission bounds active inputs, while worksheet tasks and row-aligned chunks use the common Rayon pool. Matching colors connect the hierarchy to an illustrative thread schedule. B 1–B 3 belong to one worksheet and can execute on different threads. Their results are assembled in source order. A submitted larger chunk can defer a smaller worksheet. Bar lengths are schematic. Individual steal events are not recorded by the current work observer.

TABLE I
FROZEN XLSX SOURCE INVENTORIES. SIZES ARE DECIMAL GB OF LISTED WORKBOOK FILES AND DO NOT MEASURE COMPLETED NATIVE COVERAGE.

Corpus	XLSX members	XLSX total (GB)
Data.gov	9,117	25.273
Destatis	1,182	2.364

identity can bypass visual comparison; failed captures provide no equality observation.

B. Cleanup screening outcomes

Fresh release-build runs produced 1,182 Destatis, 8,623 Data.gov, and 30,301 prepared Enron XLSX outputs. Across those outputs, aggregate compressed file bytes fell by 15.48%, 5.27%, and 18.87%, respectively. The smaller, equal-size, and larger output counts were 1,045/30/107 for Destatis, 4,755/3,522/346 for Data.gov, and 21,565/8,415/321 for Enron. Hash checks confirmed byte identity for all equal-size outputs in these runs. Data.gov also had 494 unsupported-namespace skips. With sixteen workbook slots and sixteen Rayon threads, elapsed times were 119.7, 1,134.5, and 181.6 s, respectively, including analysis statistics and full replay events alongside concurrent native validation [11]. All three runs reached completion with zero reported processing failures. The host used an AMD Ryzen 7 7800X3D with eight physical cores, sixteen logical processors, 95.1 GiB OS-visible RAM and Windows 11 Home build 26200. Interactive execution replays accompany the Destatis, Data.gov and prepared Enron XLSX runs. Their terminal event clocks include final reporting and can differ slightly from the cleanup timing endpoint above. Each recording retains source and publication checksums, with local output paths projected to basenames. Playback loads the complete history into browser memory and supports seeking and accelerated inspection of workbook, worksheet and chunk events. Successful processing of these inputs does not establish correctness for every valid serialization. These namespace exclusions occurred only in Data.gov in the evaluated runs. These descriptive results include files that grew and use only processed input bytes as the denominator. Enron's denominator begins after preparation. Visual preservation is evaluated separately. Figure 9 shows the workbook and worksheet distributions for these runs. Empty-cell cleanup and trailing layout rows account for prominent worksheet XML reductions. The contribution of column range merging is especially visible in Destatis. The worksheet panels exclude 88 prepared Enron workbooks without worksheet XML observations. Workbook payload sizes use all uncompressed ZIP member sizes. Among 9,117 Data.gov inputs, 493 workbooks contained explicitly prefixed worksheet data elements. After experimental namespace normalization and Default cleanup, only two produced smaller compressed packages, by 6.415% and 0.047% relative to the normalized baseline. Cell-record removal in other outputs did not reduce package size [12].

Corpus-driven development exposed both recognition and preservation defects. The Data.gov attributed-value failure is described in the method, and the Destatis automatic-height correction is examined below. Earlier Enron controls isolated deleted center-across-selection spans and fill masks by restoring only the affected original cell records. These findings motivate retained fixtures and native controls alongside the screening counts [14].

C. Sampling and reference controls

The random evaluation sample is selected from a frozen eligible frame with a recorded seed before inspecting visual findings. Strata use corpus identity, package size and structural features available before validation. Low-reduction and




Fig. 9. Full-corpus uncompressed-size reduction. Top, complete workbook payload from all ZIP member sizes recorded in the central directory. Middle, uncompressed worksheet XML. Bottom, worksheet XML reduction attributed to each recorded cleanup cause. Each curve independently sorts its observations from greatest to least reduction. The x-axis gives the fraction of observations traversed in that ordering. The common display ends at the 85th percentile. Remaining positive reductions are below 0.5 percentage points. The omitted tail includes unchanged outputs and growing workbooks (3/24/5) and worksheets (82/143/39), in Destatis/Enron/Data.gov order, retained in the accompanying data. Colors and hatching mark 50/80/90/95% reduction tiers. Data.gov's 494 unsupported-namespace inputs are excluded from these processed-output distributions. The worksheet panels cover 1,182 Destatis, 30,213 Enron and 8,623 Data.gov workbooks with recorded worksheet XML. Enron begins with prepared XLSX inputs.

unchanged files remain represented. A separately labelled development stress set contains large and historically problematic workbooks.

Feasible sampled files receive full native reference captures over the relevant visual area using a capture plan independent of the candidate selector. A full-reference timeout remains in the denominator. It is not replaced silently by an easier workbook. Mutations with known visible effects cover cell values, styles, geometry, conditional dependencies and objects. Mutations that Excel normalizes away are reported separately.

D. Performance and comparison subjects

We compared direct open–save trials with fresh six-worker Sheet Shrink cleanup followed by the same library. Across the two displayed laptop workbooks, all 33 Sheet Shrink trials completed under a 4 GiB commit limit, compared with 21 original trials. Median elapsed time improved in all seven fully completed pairs. Migration with openpyxl took 111.3 s directly and 9.7 s including cleanup. The accompanying benchmark receipts retain the individual phases and the second-pass measurements.

Tables II and III join the opening/memory case study through frozen file identities. The full experiment retains 288 opening/saving attempts across six variants and three repetitions. The selected Enron workbook has a separate eighteen-attempt follow-up on the larger-memory host, described below. Its measurements retain their own host and configuration. The tables display Migration and QT/RR, with Enron size evidence and a separate resource follow-up. The size table checks the exact retained comparator outputs against their manifest hashes. The timed Sheet Shrink outputs have recorded compressed sizes. Their per-trial uncompressed-member inventories and matched native pixel denominators

are unavailable. The follow-up controls compare separately generated outputs with native candidates through their full uncompressed-member manifests. The artifact contains source identities, report hashes, per-region diagnostic counts and all trial receipts.

The compact resource table reports total elapsed time and library working-set peaks. The artifact separately retains pipeline working sets and job-commit peaks. Each displayed time is a median of completed attempts, with memory maxima over all three attempts. Stopped attempts retain their elapsed time and memory boundary. CPU totals, individual timings and ranges remain available in the machine-readable artifact. Existing prepared-output variants measure subsequent library processing. Fresh Sheet Shrink rows include cleanup within the measured pipeline. The common host is a Ryzen 5 4500U laptop with six logical processors, 8 GiB installed RAM and Windows 11. Each job has a 4 GiB commit cap and a 900 s timeout, with the free-RAM reserve disabled. The Sheet Shrink executable is frozen at revision `765c480` and uses six Rayon and six writer workers. Native visual observations use the retained policy-v12 paired-rebuild protocol. Later software revisions and other hosts require their own identified measurement lanes.

E. Larger-memory-host follow-up

The four displayed workbook/library combinations that reached the laptop's 4 GiB commit ceiling were repeated on an AMD Ryzen 7 7800X3D host with sixteen logical processors and 102,066,212,864 OS-reported physical bytes. Each combination has three Original and three fresh Sheet Shrink pipeline attempts at both 4 GiB and 24 GiB aggregate process-tree commit limits, totaling 48 displayed attempts. The same frozen Sheet Shrink binary uses sixteen Rayon and sixteen writer workers with one active workbook. The controller maintains an 8 GiB reserve for physical RAM and commit headroom, with a 900-second per-trial timeout. Python 3.12.14, openpyxl 3.1.5, pandas 3.0.1, R 4.6.2, readxl 1.6.0 and writexl 2.0.1 identify the tested software lane [15].

At 4 GiB, all twelve Original attempts reached the memory limit, while all twelve fresh-cleanup pipelines completed. At 24 GiB, the six Original attempts for Migration/readxl and QT/RR/openpyxl completed. Migration's two pandas endpoints reached the memory limit in all six attempts. All twelve fresh-cleanup pipelines completed at that limit. Table IV retains these censored endpoints alongside successful medians. A memory-stop termination time receives no completed-runtime ratio.

The larger limit distinguishes memory censoring from completed processing cost for these selected cases. Native visual comparisons, a separate cleanup benchmark and read-only evidence analysis ran concurrently. Filesystem caches were retained. The measured ratios are descriptive paired results under that context. This host lane retains its own configuration and observations alongside the earlier six-worker laptop study. Across all 48 displayed trials, sampled physical RAM and commit headroom remained above the declared system reserve.

After the timing series, separately regenerated controls for both displayed inputs matched every uncompressed member name, length and SHA-256 of the retained native candidate identities. These representative controls contain 138 and 24 members for Migration and QT/RR. Migration's native observation uses a documented normalized baseline, and QT/RR's retained selected plan has zero captures. The full per-trial member inventories were not retained for the timed fresh outputs, whose archive hashes remain in the receipts. These qualifications delimit the native/resource association. A second cleanup was measured after each completed fresh pipeline, outside the timed endpoint. Its recorded ZIP identity flags do not establish general cleanup idempotence.

F. Enron selected-case follow-up

The Enron case uses the Enron workbook whose original SHA-256 begins `7298df9a6a76`. Its original archive contains 42,710,945 compressed bytes and 353,151,842 uncompressed member bytes. On the same larger-memory host, six variants each received three openpyxl 3.1.5 round-trip attempts, with a 4 GiB process-tree commit limit, an 8 GiB physical-RAM and commit reserve and a 300-second timeout [16]. All eighteen attempts have terminal receipts. Original and XLStylesTool reached the memory limit in all three attempts. Fresh Sheet Shrink cleanup followed by the library round trip completed with a median process-creation-to-exit time of 3.021 seconds and a maximum job-commit peak of 891.4 MiB. Prepared Check Performance, Inquire and NX-PowerLite outputs completed their library round trips with respective medians of 1.036, 1.054 and 1.101 seconds, and maximum job-commit peaks of approximately 535.6 MiB.

The external prepared-output endpoints omit their tools' preparation cost. The Sheet Shrink endpoint includes fresh cleanup, so these observations do not establish an end-to-end speed ranking among cleaners. Memory-limited attempts remain censored. Recorded commit peaks slightly exceed the configured 4 GiB boundary and are retained without clamping. Concurrent native comparisons and retained filesystem caches qualify this selected-case result. After the timed series, a separate fresh Sheet Shrink control matched all eighteen uncompressed member names, lengths and hashes of the retained native candidate. Its output has 384,724 compressed bytes and 2,581,673 uncompressed member bytes. This representative identity check links the control to the visual audit, while preserving that audit's selected-coverage limitations. The timed trials retain archive hashes, without full per-trial member inventories.

G. Distributed comparator measurements

The native comparison campaigns are distributed across Windows hosts to obtain coverage within the available experimental budget. Native opening, cleanup and saving can dominate the cost of large spreadsheet collections. Each observation therefore retains its host, source identity, configuration

and measurement boundary. Raw times remain associated with that host. Cross-tool ratios pair the same original workbook with a Sheet Shrink measurement on the same host. Host-specific ratios retain differences in workload, tool policy and session conditions. Each host and tool remains a separate plotted group. The frozen selection contains the 49 workbooks with the largest absolute compressed XLSX byte savings under the earlier Sheet Shrink screening in each of Destatis, Enron and Data.gov. The timing and preservation outcomes of this extreme-case panel apply to its selected inputs.

The present NXPowerLite lane uses a Lenovo 81YQ laptop with an AMD Ryzen 5 4500U (six physical cores and six logical processors), 8 GiB installed RAM (7.37 GiB OS-visible), a 512 GB Samsung MZALQ512HALU NVMe SSD and Windows 11 Home, build 26200. The recorded Windows power scheme is Energy Star. Other open Excel and validation processes are retained in the resource receipts. These observations characterize the recorded workstation workload, including any contention.

a) Comparator configuration: NXPowerLite Desktop 11.0.1 x64 uses the custom profile `Cell formatting focused - Top49`. Excess cell-formatting cleanup is enabled. In the Excel profile, image resizing, JPEG conversion, cropped-area deletion, embedded-object flattening, PNG color-depth reduction and embedded chart-data removal are disabled. Lossy image modification conflicts with the objective of exact visible preservation and is deliberately excluded from the comparison policy. The interface retains a JPEG quality control, set to 9. Verification of unchanged images therefore requires the output-level audit.

Consequently, every retained output is audited against the original bytes of media, drawings, charts and embedded objects. Of 147 attempted workbooks, 129 produced reduced packages and ten explicitly remained unchanged. Eight Enron inputs reported an internal NXPowerLite error on both the primary attempt and a diagnostic repeat after restarting the application. Five outputs recompressed PNG images with identical decoded RGBA pixels and image dimensions. A sixth changed an embedded Word document. These six outputs are retained separately and excluded from the formatting-focused timing figure. The remaining 133 outputs passed the protected-part audit. Native worksheet equivalence requires separate visual validation.

XLStylesTool UWP 3.0.1.0 supplies an additional same-host comparison with forced style normalization, name unhiding and wholesale external-name removal disabled. The earlier conversion queue retains 122 hash-matched inputs with a confirmed primary conversion event and its complete per-attempt resource receipt. The other 25 Top49 inputs lack that complete timing evidence and remain outside the timing figure. All 122 included outputs preserve the audited media and object parts byte-for-byte. The joint figure uses the intersection of 110 original workbooks, comprising 21 Destatis, 41 Enron and 48 Data.gov inputs. Both tools therefore use the same original files and repeated Sheet Shrink baselines within each plotted corpus group. The larger individual receipt sets remain available in the artifact. Table V retains the full 133-input NXPowerLite resource lane.

Inquire timings cover the full Excel workflow and are paired with repeated Sheet Shrink process timings for the same input and host. The retained Inquire workflow observations have one attempt per input; partial and failed attempts receive no completed-runtime ratio.

b) Timing and resources: Each included GUI observation has one primary timing measurement per input. Its operational cost limits replication, and its timing variability therefore remains unestimated. Diagnostic retries remain separate attempts. Elapsed time covers automated GUI orchestration through output confirmation and initial package verification. CPU measurements accumulate attributed process-tree user and kernel time. Working-set and private-byte peaks use a nominal 250 ms sampling interval. The existing warm application is reused, with one conversion worker and a 512 MiB RAM and commit reserve. The exact profile and per-attempt evidence accompany the results.

The paired Sheet Shrink experiment uses an optimized release build from revision `765c480`, one active workbook, one Rayon worker and one writer, with the default cleanup policy. One complete warm-up round precedes nine measured rounds over the same 147 source identities. Each round independently shuffles workbook order with a recorded seed. Each file starts a fresh CLI process, and measured wall time ends at process exit. Output hashing is outside this timing boundary. Filesystem caches are left unflushed after warm-up. Direct-child CPU and OS peak-working-set counters are retained, with private usage sampled at a nominal 10 ms polling interval. These memory observations have different sampling semantics from the GUI lane and are reported separately. All 1,470 invocations completed successfully. Each input produced the same package hash across warm-up and measured repetitions, and all 147 final outputs preserved the original bytes of the audited media and object parts. Across inputs, the median relative within-input interquartile range, $(Q_3 - Q_1)/\widetilde{t}$, was 0.84% over the nine measured repetitions.

Figure 10 retains raw times and workbook-level same-host ratios. Each denominator is the median of nine Sheet Shrink trials, and each numerator is the primary comparator observation. Across-workbook quartiles describe heterogeneity in this deliberately selected stress panel. They are distinct from uncertainty over repeated trials [17]. The ratio includes the stated interface and confirmation costs, and the tools have different cleanup policies. It therefore measures the observed cleanup workflows. Opening-time improvements and cleanup-plus-opening costs require their own readiness endpoints, as in the separate historical opening experiment.

H. Native validation of preservation rules

a) Row-height preservation.: In the Traffic workbook, promoting repeated empty-cell formatting into a row style changed an automatically determined height from 12.75 to 9 points, shifting subsequent content and changing 3,408 pixels in an independently specified reference region. Requiring an




Fig. 10. Same-host NXPowerLite and XLStylesTool cleanup workflow observations on the same 110 originals, paired with Sheet Shrink. Corpus labels give the shared input counts for each tool. Left, absolute times summarized across paired workbooks. Middle, workbook-level comparator time divided by the median Sheet Shrink time, on a logarithmic scale. A ratio above one indicates a shorter observed Sheet Shrink workflow. Interval marks show the interquartile range across workbooks. Right, all 49 selected inputs per corpus and tool, partitioned into plotted, other eligible, failed, protected-payload exclusions and incomplete timing receipts. Other eligible inputs lack an eligible counterpart in the other tool. Incomplete receipts do not imply conversion failure. No native visual-equivalence claim follows from timing eligibility.

explicit custom height before promotion restored byte-identical native captures [7].

b) Font representatives.: Two Destatis cases validate complementary font-preservation conditions. In a higher-education workbook, removing 87 blank cells carrying explicit default-font and no-fill metadata changed 25,640 pixels despite equal capture geometry and a pixel-identical original-versus-original control. Retaining the required representatives restored equality in an independently specified reference region. Legacy print-name aliases were normalized for opening and recorded separately. In a cultural-finance workbook, a blank cell's non-default font affected automatic row height despite an omitted `applyFont` flag; a stored height without `customHeight` did not prevent the change from 15 to 12.75 points. Retaining the representative restored pixel and geometry equality in the independent control and all 350 regions selected by the targeted capture policy.

c) Background definitions.: In a Destatis horticulture workbook, Sheet Shrink reduced column definitions from 128,912 to 2,197. A corrected DeltaSieve background-envelope guard reduced the capture selection from 16,101 to 165 regions; all 165 resulting image pairs were pixel-identical.

d) Validation boundaries.: In Wanderungen, excluding an empty trailing context row removed a spurious height finding. All 37 captured image pairs were pixel-identical under the DeltaSieve capture policy, while separate effective-height observations on two other worksheets remained unresolved [18]. These case studies validate specific preservation conditions within the recorded capture scopes; they do not establish exhaustive workbook or corpus-wide visual equivalence.

I. Targeted visual outcomes on the Top49 selection

A version-matched audit of the 49 workbooks with the largest absolute Sheet Shrink reductions in each corpus retained 42 Destatis, 46 Data.gov, and 46 Enron comparisons against the selected originals. Separately documented normalized baselines supplied five further Destatis and two further Enron observations. The remaining two, three, and one slots, respectively, had no eligible observation. Across both baseline categories, zero Destatis, seven Data.gov, and five Enron workbooks had recorded differences. These counts describe the selected capture scope and include findings whose cause

remains unresolved. The five Enron workbooks had six chart findings of 2–26 changed pixels with equal image dimensions and no reported geometry change. The missing Enron workbook required repair when opened in Excel, including after a separate legacy reconversion.

J. Evidence boundary

The selected controls demonstrate concrete preservation conditions and recorded failures. They do not estimate corpus-wide defect prevalence. Reduction results cover the frozen XLSX inventories. Matched cleanup-plus-opening measurements and independent native references cover selected cases. Broader reference coverage and matched whole-corpus cost remain open. Detailed development attempts, input hashes, native images and producer versions remain in the source-linked artifact. The main comparison separates those receipts from the reported completed observations.

TABLE II

OPENING/MEMORY CASE-STUDY INPUTS AND NATIVE VISUAL EVIDENCE. SIZES ARE DECIMAL MB. PAYLOAD IS THE SUM OF ALL UNCOMPRESSED ZIP-MEMBER SIZES. REDUCTION COLUMNS COMPARE EACH OUTPUT WITH ITS ORIGINAL. PENDING IDENTIFIES UNAVAILABLE EVIDENCE. PAIRED BARS SHOW ORIGINAL (GRAY) AND OUTPUT (BLUE/ORANGE), WITH ORIGINAL = 100%.

Variant	ZIP (reduction)	Payload (reduction)	Pixels D/N	Sheets	Geom.	State
Destatis Migration						
Original	16.927 (0%)	248.39 (0%)	Ref.	Ref.	Ref.	Ref.
Sheet Shrink	1.805 (89%)	Pending	Pending	Pending	Pending	Pending
NXPowerLite	11.741 (31%)	197.48 (20%)	Pending	Pending	Pending	M
XLStylesTool	16.923 (0.022%)	248.42 (-0.0095%)	Pending	Pending	Pending	M
Check Performance	1.817 (89%)	20.15 (92%)	Pending	Pending	Pending	M
Inquire	9.499 (44%)	116.44 (53%)	Pending	Pending	Pending	M
Data.gov QT/RR						
Original	121.949 (0%)	1350.77 (0%)	Ref.	Ref.	Ref.	Ref.
Sheet Shrink	3.848 (97%)	Pending	Pending	Pending	Pending	Pending
NXPowerLite	3.331 (97%)	29.98 (98%)	Pending	Pending	Pending	M
XLStylesTool	121.949 (1.9e-05%)	1350.77 (-7.8e-05%)	Pending	Pending	Pending	M
Check Performance	3.626 (97%)	25.59 (98%)	Pending	Pending	Pending	F
Inquire	3.878 (97%)	30.13 (98%)	Pending	Pending	Pending	M
Enron b2d0dfef						
Original	42.711 (0%)	353.15 (0%)	Ref.	Ref.	Ref.	Ref.
Sheet Shrink	Pending	Pending	Pending	Pending	Pending	Pending
NXPowerLite	Pending	Pending	Pending	Pending	Pending	Pending
XLStylesTool	Pending	Pending	Pending	Pending	Pending	Pending
Check Performance	Pending	Pending	Pending	Pending	Pending	Pending
Inquire	Pending	Pending	Pending	Pending	Pending	Pending

Sheet Shrink outputs are freshly generated in each six-worker trial. Their compressed size is recorded consistently across repetitions, while their uncompressed payload and matched native visual evidence remain pending. NXPowerLite uses the cell-formatting-focused profile. XLStylesTool retains the tested settings. Ref. identifies the original baseline. L denotes completed targeted captures with coverage limitations, M a memory-limit stop, F a failed attempt and Pending unavailable evidence. Sheets gives changed/observed/total worksheets. Geometry counts flagged capture findings. Pixel counts aggregate retained diagnostic observations under policy v12 after paired native rebuild. The total comparable-pixel denominator N remains pending. Different capture scopes and unresolved attribution constrain comparisons. Gray bars denote the original. Blue denotes a value at or below the original, and orange a larger value. Orange cell backgrounds mark observed visual differences. Each pair has a common zero. Original = 100%, with a shared linear scale within each workbook and size column. Absolute MB and reduction percentages accompany the bars.

TABLE III

OPENING/SAVING SUMMARY ON THE RYZEN 5 4500U LAPTOP WITH 8 GIB RAM. EACH CELL SHOWS MEDIAN TOTAL SECONDS ABOVE MAXIMUM SAMPLED LIBRARY WORKING SET IN MIB. THREE ATTEMPTS PER CONDITION, 4 GIB JOB-COMMIT CAP, 900 S TIMEOUT.

Endpoint	Original	Sheet Shrink	NXPowerLite	XLStylesTool	Check Performance	Inquire
Destatis Migration						
	111.30	9.67	83.58	111.13	9.11	54.96
openpyxl	2700	250	1996	2700	236	1530
	M	35.83	M	M	M	M
pandas to XLSX	3900	856	3900	3900	3900	3900
	M	11.54	M	M	M	M
pandas to CSV	3900	214	3900	3900	3900	3900
	20.34	9.92	17.94	20.17	5.34	9.99
Excel COM	429	309	409	428	259	324
	44.38	13.70	30.04	44.92	11.70	32.22
R openxlsx	824	317	684	831	286	564
	M	178.17	M	M	M	M
R readxl + writexl	4070	262	4070	4070	4072	4072
Data.gov QT/RR						
	M	19.84	12.26	M	12.07	12.39
openpyxl	3913	318	299	3913	299	303
	249.13	22.99	15.79	246.68	15.55	16.09
pandas to XLSX	327	346	327	327	327	327
	39.79	11.84	4.67	39.02	62.52	4.77
Excel COM	929	272	253	931	246	247
	140.86	11.28	4.26	140.40	3.55	4.32
R openxlsx	2453	242	224	2454	210	225
	11.90	10.06	2.94	11.89	2.88	2.96
R readxl + writexl	1341	258	240	1340	248	239

Sheet Shrink includes fresh cleanup through library exit. Other columns measure processing of prepared outputs, with their cleanup excluded. Completed cells have three successful attempts. M means all three attempts stopped at the memory limit, with reached library RSS retained below. Bars compare original (gray) and measured value (blue at or below, orange above) on a common linear scale per endpoint and metric, requiring completed originals. RSS covers library phases, with nominal 20 ms sampling. Pipeline working sets, OS job-commit peaks, cleanup/open/save phases, stopped elapsed times, CPU, ranges and all 288 receipts remain in the artifact. Separate host results follow below.

TABLE IV

SELECTED-CASE FOLLOW-UP UNDER A 24 GIB JOB-COMMIT LIMIT. ELAPSED TIME COVERS PROCESS CREATION THROUGH EXIT, INCLUDING FRESH CLEANUP IN THE PIPELINE. TIMES ARE MEDIANS OF THREE ATTEMPTS. COMMIT PEAKS ARE MAXIMA OVER THE THREE ATTEMPTS. M DENOTES THREE MEMORY-LIMIT STOPS. THE RAW RECEIPTS RETAIN RANGES, PHASE SAMPLES, WORKING SETS AND CPU COUNTERS.

Workbook / endpoint	Original (s)	Cleanup + endpoint (s)	Ratio	Original peak (GiB)	Pipeline peak (GiB)
Migration / pandas to XLSX	M	24.729	–	24.00	1.27
Migration / pandas to CSV	M	8.291	–	24.00	0.65
Migration / readxl + writexl	392.149	131.953	2.97	8.70	0.51
QT/RR / openpyxl	279.638	11.519	24.28	12.56	3.66

TABLE V

MEDIAN RESOURCE OBSERVATIONS ACROSS PAIRED WORKBOOKS ON THE LAPTOP. CPU IS PROCESS TIME IN SECONDS. WS IS WORKING SET IN MIB, USING OS PEAK COUNTERS FOR SHEET SHRINK AND SAMPLED PEAKS FOR NXPOWERLITE.

Corpus	Pairs	CPU Sheet Shrink	CPU NXPowerLite	WS Sheet Shrink	WS NXPowerLite
Destatis	44	1.24	5.45	54	248
Enron	41	0.70	4.19	51	306
Data.gov	48	6.73	10.49	415	146

V. Related Work

A. Workbook bloat and cleanup tools

Microsoft Check Performance removes cells associated with unnecessary formatting and other stored information from a loaded workbook [19]. Its documentation warns that optimization can remove pixel-art cells. Inquire's Clean Excess Cell Formatting command removes excess cells beyond the last nonblank cell and can change conditional-formatting coverage [20]. O'Beirne's published analysis of Excel 2013 Inquire discusses this command and criticizes its lack of information about planned and completed removals [21]. This historical analysis establishes published attention to cleanup and its transparency. Current product behavior requires version-specific evidence. These documented policies motivate comparing both reduction and preservation outcomes under explicit contracts.

Package-level cleanup also predates Sheet Shrink. XLStylesTool's developer describes an Open-XML-based cleaner for excessive and corrupted styles that operates independently of Excel's object model [22]. NXPowerLite Desktop 10 lists excess XLSX cell-format cleanup among its features [23]. Its engine description discusses formatted blank cells as a source of large worksheet parts [24]. These are relevant comparison subjects. Their available descriptions do not establish the guarded removal rules, compact row-font witnesses or native preservation outcomes examined here. Those properties require version-specific evidence. Sheet Shrink's positioning therefore includes its effect-aware rules, retained representatives and measured costs alongside its execution before native loading. Its removal decisions use persisted OOXML properties and workbook context. The cleanup phase has no native rendering observations or measured automatic row heights available to guide deletion or reconstruct layout. Small retained font and inheritance witnesses must preserve these effects when Excel later opens the result. Native validation supplies subsequent experimental evidence for the decisions described in the method.

B. Spreadsheet scalability and system optimization

Mack et al.'s CHI Extended Abstracts case study characterizes scalability problems reported in spreadsheet forums [25]. Rahman et al. benchmark Excel, LibreOffice Calc and Google Sheets on spreadsheet computations and examine indexing, data layout, incremental evaluation and shared computation [26]. These studies motivate performance work on spreadsheets. Their workloads assess system responsiveness and computation, while Sheet Shrink measures removable persisted representation and the cost of preparing workbooks for subsequent use.

DataSpread's storage engine integrates spreadsheet presentation with database storage and positional access [27]. Anti-Freeze schedules asynchronous formula computation to retain interactivity during updates [28]. Hillview distributes exploration of large datasets and uses compact visualization sketches [29]. TACO exploits regular formula-reference patterns to compact dependency graphs and query them directly [30]. These systems optimize storage, computation or exploration within a processing system. Sheet Shrink transforms an existing XLSX package into another editable workbook under a stated preservation contract. These optimization layers can be used together.

C. Spreadsheet loading and specialized parsing

SheetReader studies specialized XML parsing for efficient spreadsheet ingestion, including the coupling of decompression, parsing and parallel execution [1]. Specialized scanners assume syntax-recognition and state-transition obligations otherwise handled by established DOM or SAX implementations. Rare valid serializations can expose defects after many successful inputs. During baseline ingestion, we encountered an empty-cell parsing defect in SheetReader and submitted a correction with regression fixtures [31].

SheetReader loads worksheet data into analytical representations. Sheet Shrink rewrites an editable workbook whose required contents, dependencies and presentation must survive cleanup. Its byte-oriented scanner therefore combines XML recognition with preservation-specific guards. Corpus-scale processing and targeted regression controls exercise this implementation within its supported domain, while additional serializations and semantic cases can remain untested. The two systems address complementary sources of ingestion cost through the reader's processing strategy and the representation supplied to it.

D. Spreadsheet refactoring and validation

Hermans et al. detect formula smells and suggest refactorings to improve spreadsheet maintainability [32]. Their work connects structural changes to behavioral obligations. Sheet Shrink's removal rules additionally account for formatting inheritance and native layout effects of stored cells.

Spreadsheet slicing integrates dependency reasoning with testing and debugging [33]. Dependencies also constrain removal when retained formulas or graphical objects refer to candidate content. Workbook comparison tools provide observations about cell and format differences [34]. Our native validation protocol uses DeltaSieve's region selection and capture workflow [10], with independent references and mutation controls to evaluate selected coverage. These validation mechanisms provide evidence about cleanup outcomes after the package transformation.

VI. Discussion and Limitations

The preservation contract is narrower than all possible spreadsheet behavior. Rendering depends on the installed Excel version, fonts and calculation state. A selected-region observation has limited scope. Unsupported XML and unsuccessful opening or saving remain visible outcomes. The independent reference sample estimates behavior on its eligible population and cannot establish a universal absence of regressions.

Large reductions can coexist with small preservation witnesses. Font metadata, inheritance masks and content-bearing hidden tails therefore require separate conditions. The constant-tail policy remains a structural heuristic. The fast CRC/length identity shortcut is collision-prone, and the selected verification mode must accompany measurements. The built-in-name predicate also lacks a formula-body equivalence check. These limitations constrain preservation claims.

VII. Conclusion

Sheet Shrink addresses spreadsheet redundancy through effect-aware removal and compact preservation. Its implementation and evaluation distinguish compressed size, XML changes, execution cost and observed presentation.

Acknowledgment of AI Assistance

OpenAI ChatGPT and Codex assisted with drafting and editing the Abstract and Sections I–VII, literature discovery and organization, implementation and refactoring, test and experiment scripts, figure-generation code, and analysis of retained experiment evidence. This assistance included the method diagrams, XML examples and execution visualizations. Local agent workflows using these systems also supported overnight validation campaigns by inspecting status and logs, investigating stalled attempts, and documenting candidate visual regressions for author review.

The author directed development, reviewed source code, and performed manual testing and debugging. Agent observations supported investigation. Reported validation outcomes are grounded in the retained native captures and comparison records. The author remains responsible for the scientific claims, references, evidence selection, originality and final submitted content.

References

[1] H. Gavriilidis, F. Henze, E. T. Zacharatou, and V. Markl, "SheetReader: Efficient specialized spreadsheet parsing," *Information Systems*, 2023.

[2] Microsoft, "Row.CustomHeight property," Open XML SDK documentation, accessed November 9, 2026. [Online]. Available: https://learn.microsoft.com/en-us/dotnet/api/documentformat.openxml.spreadsheet.row.customheight

[3] SheetShrink project, "XLSX shrinking behavior," Versioned software specification, revision a7eef1a, 2026. [Online]. Available: https://github.com/Alexander-Aue-Johr/excel-shrink-rust/blob/a7eef1a/docs/behavior/shrinker.md

[4] ——, "Preserve attributed cell value elements," Revision 88c77f9, 2026. [Online]. Available: https://github.com/Alexander-Aue-Johr/excel-shrink-rust/commit/88c77f9557cd63d6ed887c5389ebb7e4a55452fc

[5] ——, "Preserve defined-name worksheet scope," Revision 5822800, 2026. [Online]. Available: https://github.com/Alexander-Aue-Johr/excel-shrink-rust/commit/582280043a56a0346cb891fb0b9bbf23b4a3a875

[6] ——, "Do not publish outputs from incomplete worksheet parses," Revision c608d4e, 2026. [Online]. Available: https://github.com/Alexander-Aue-Johr/excel-shrink-rust/commit/c608d4e5155fcbf584f9e2154a378c6f5fa42e2b

[7] ——, "Dense row promotion and inherited height," Versioned protocol and evidence, revision e5e4fe8, 2026. [Online]. Available: https://github.com/Alexander-Aue-Johr/excel-shrink-rust/blob/e5e4fe8/docs/visual-validation/experiments/traffic-row-height/README.md

[8] ——, "Hidden constant-tail investigation and wanderungen controls," Versioned evidence, revision 1b9ee98, 2026. [Online]. Available: https://github.com/Alexander-Aue-Johr/excel-shrink-rust/blob/1b9ee98/docs/visual-validation/investigations/hidden-constant-tails-20261104.md

[9] ——, "Xlsx shrinking behavior," Versioned protocol and evidence, revision 7ca7c2a, 2026. [Online]. Available: https://github.com/Alexander-Aue-Johr/excel-shrink-rust/blob/7ca7c2a/docs/behavior/shrinker.md

[10] "DeltaSieve: Targeted visual validation of spreadsheet transformations," Companion working manuscript prepared for ICDE 2027, 2026, supplementary material, related-manuscripts/deltasieve.pdf.

[11] SheetShrink project, "Complete-corpus distribution and replay measurements," Versioned evidence, revision ce3722cb, 2026. [Online]. Available: https://github.com/Alexander-Aue-Johr/excel-shrink-rust/blob/ce3722cb/docs/visual-validation/experiments/full-corpus-distribution-20261111.json

[12] ——, "Prefixed worksheet data inventory," Inventory, normalization trials and sampled native controls, revision 44d73f3, 2026. [Online]. Available: https://github.com/Alexander-Aue-Johr/excel-shrink-rust/blob/44d73f3/docs/visual-validation/experiments/prefixed-data/README.md

[13] Microsoft, "Xlfileformat enumeration," 2026, includes xlOpenXMLStrictWorkbook, value 61. [Online]. Available: https://learn.microsoft.com/en-us/dotnet/api/microsoft.office.interop.excel.xlfileformat

[14] SheetShrink project, "Confirmed default visual regressions," Controlled restoration evidence, revision 1b9ee98, 2026. [Online]. Available: https://github.com/Alexander-Aue-Johr/excel-shrink-rust/blob/1b9ee98/docs/visual-validation/confirmed-default-regressions.md

[15] "Bounded opening and saving follow-up," Supplementary experimental artifact, 2026, protocol, individual receipts, source snapshot and candidate-identity controls in evidence/bounded-open-save-followup.

[16] "Enron selected-case opening and saving follow-up," Supplementary experimental artifact, 2026, eighteen bounded receipts, protocol and representative native candidate identity control in evidence/enron-open-save-followup.

[17] T. Hoefler and R. Belli, "Scientific benchmarking of parallel computing systems: Twelve ways to tell the masses when reporting performance results," in *Proceedings of the International Conference for High Performance Computing, Networking, Storage and Analysis*. ACM, 2015, pp. 73:1–73:12.

[18] DeltaSieve project, "Targeted visual validation behavior, empty trailing row exclusion," Versioned protocol and evidence, revision 7ca7c2a, 2026. [Online]. Available: https://github.com/Alexander-Aue-Johr/excel-shrink-rust/blob/7ca7c2a/docs/behavior/targeted-validation.md

[19] Microsoft, "Cleanup cells in your workbook," accessed November 9, 2026. [Online]. Available: https://support.microsoft.com/en-us/excel/cleanup-cells-in-your-workbook

[20] ——, "Clean excess cell formatting on a worksheet in Excel for Windows," accessed November 9, 2026. [Online]. Available: https://support.microsoft.com/en-us/excel/clean-excess-cell-formatting-on-a-worksheet-in-excel-for-windows

[21] P. O'Beirne, "Excel 2013 Spreadsheet Inquire," in *Proceedings of the EuSpRIG 2013 Conference "Spreadsheet Risk Management"*. European Spreadsheet Risks Interest Group, 2013, also available as arXiv:1401.7586, deposited in 2014. [Online]. Available: https://eusprig.org/wp-content/uploads/1401.7586.pdf

[22] XLGeek, ".NET4.0 version of the XLStylesTool is now available," 2011, developer description, accessed November 9, 2026. [Online]. Available: https://sergeig888.wordpress.com/2011/03/21/net4-0-version-of-the-xlstylestool-is-now-available/

[23] M. Power, "What's new in NXPowerLite Desktop 10," vendor release description, accessed November 9, 2026. [Online]. Available: https://neuxpower.com/blog/whats-new-in-nxpowerlite-desktop-10

[24] ——, "Compression engine major upgrade—version 10," vendor description, accessed November 9, 2026. [Online]. Available: https://neuxpower.com/blog/wecompress-file-compressor-engine-upgrade

[25] K. Mack, J. Lee, K. Chang, K. Karahalios, and A. Parameswaran, "Characterizing scalability issues in spreadsheet software using online forums," in *Extended Abstracts of the 2018 CHI Conference on Human Factors in Computing Systems*. ACM, 2018. [Online]. Available: https://arxiv.org/abs/1801.03829

[26] S. Rahman, K. Mack, M. Bendre, R. Zhang, K. Karahalios, and A. Parameswaran, "Benchmarking spreadsheet systems," in *Proceedings of the 2020 ACM SIGMOD International Conference*

on Management of Data. ACM, 2020, pp. 1589–1599. [Online]. Available: https://sajjadur.net/files/benchmarking_spreadsheets.pdf

[27] M. Bendre, V. Venkataraman, X. Zhou, K. C.-C. Chang, and A. Parameswaran, "Towards a holistic integration of spreadsheets with databases: A scalable storage engine for presentational data management," in *2018 IEEE 34th International Conference on Data Engineering (ICDE)*. IEEE, 2018, pp. 113–124. [Online]. Available: https://arxiv.org/abs/1708.06712

[28] M. Bendre, T. Wattanawaroon, K. Mack, K. Chang, and A. Parameswaran, "Anti-Freeze for large and complex spreadsheets: Asynchronous formula computation," in *Proceedings of the 2019 International Conference on Management of Data*. ACM, 2019, pp. 1277–1294. [Online]. Available: https://people.eecs.berkeley.edu/~adityagp/papers/dataspread-async.pdf

[29] M. Budiu, P. Gopalan, L. Suresh, U. Wieder, H. Kruiger, and M. K. Aguilera, "Hillview: A trillion-cell spreadsheet for big data," *Proceedings of the VLDB Endowment*, vol. 12, no. 11, pp. 1442–1457, 2019. [Online]. Available: https://arxiv.org/abs/1907.04827

[30] D. Tang, F. Chen, C. De Leon, T. Wattanawaroon, J. Yun, S. Seshadri, and A. G. Parameswaran, "Efficient and compact spreadsheet formula graphs," in *2023 IEEE 39th International Conference on Data Engineering (ICDE)*. IEEE, 2023, pp. 2634–2646. [Online]. Available: https://arxiv.org/abs/2302.05482

[31] A. Aue-Johr, "Fix empty-cell parsing and preserve following cell positions," SheetReader core, pull request 5, submitted November 11, 2026. [Online]. Available: https://github.com/polydbms/sheetreader-core/pull/5

[32] F. Hermans, M. Pinzger, and A. van Deursen, "Detecting and refactoring code smells in spreadsheet formulas," *Empirical Software Engineering*, vol. 20, no. 2, pp. 549–575, 2015.

[33] J. Reichwein, G. Rothermel, and M. Burnett, "Slicing spreadsheets: An integrated methodology for spreadsheet testing and debugging," in *Proceedings of the Second Conference on Domain-Specific Languages*. USENIX, 1999, pp. 25–38. [Online]. Available: https://www.usenix.org/legacy/publications/library/proceedings/dsl99/full_papers/reichwein/reichwein_html/index.html

[34] Microsoft, "Basic tasks in spreadsheet compare," Microsoft Support, accessed November 8, 2026. [Online]. Available: https://support.microsoft.com/en-gb/excel/basic-tasks-in-spreadsheet-compare