

CRYPTOGRAPHY

December 15, 1998, 14–19

- You are allowed to use a calculator.
- Each solution should be written on a *separate sheet of paper*.
- You must *clearly* show the line of reasoning.
- If any data is lacking, make reasonable assumptions.

Good luck!

Problem 1

We wish to encrypt a memoryless source with alphabet $\mathcal{M} = \{0, 1, 2\}$ and $P(M = 0) = 1/2$, $P(M = 1) = 1/4$, $P(M = 2) = 1/4$. Let the key $K = (K_0, K_1, \dots, K_{l-1})$ be chosen uniformly from the set of binary l -tuples. A sequence of messages M_1, M_2, \dots, M_n is encrypted to a sequence of ciphertexts C_1, C_2, \dots, C_n by

$$C_i = M_i + K_{i \bmod l} \pmod{3}, \quad \forall i, 1 \leq i \leq n.$$

- Find the smallest value of l for which the unicity distance ("entydighetslängd") is larger than 200.
- Construct a new cipher for this source that has infinite unicity distance (but a finite key size).

(10 points)

Problem 2

- a) Find the shortest LFSR that generates the finite sequence

$$\mathbf{s} = [1, 0, 0, 1, \alpha^2 + \alpha + 1, \alpha^2 + \alpha, \alpha + 1],$$

where \mathbf{s} is defined over \mathbb{F}_8 using the irreducible polynomial $p(x) = x^3 + x + 1$ and $p(\alpha) = 0$.

- b) Show how to implement the LFSR obtained in a) using only binary delay units (“D-element”) and XOR-gates. Draw a picture!

(10 points)

Problem 3

In an RSA-system the public encryption function is denoted $E(M)$ and the secret decryption function is denoted $D(C)$, where M is the plaintext and C is the ciphertext.

The RSA-system has public parameters $(n, e) = (31897, 19)$.

- a) Find $C = E(M)$ if $M = 20000$.
- b) Prove that $D(E(M)) = M$ for the case $\gcd(M, n) = 1$.
- c) Prove that $D(E(M)) = M$ for the case $\gcd(M, n) \neq 1$. Hint: Use the Chinese remainder theorem.

(10 points)

Problem 4

- a) Suppose that in a Shamir Threshold Scheme we have $p = 167$, $k = 3$ and $n = 7$. The public x -coordinates are $x_i = i$, for $1 \leq i \leq 7$. Suppose that $\mathcal{B} = \{P_1, P_4, P_7\}$ pool their shares, which are 3, 13, and 57, respectively. Help them to calculate the secret K .
- b) A system providing authentication protection is constructed as follows: The key consists of two parts, $K = (k_1, k_2)$, where $k_i \in \mathbb{F}_{2^{10}}$, $1 \leq i \leq 2$. The plaintext is the 3-tuple $\mathbf{m} = (m_1, m_2, m_3)$ where $m_i \in \mathbb{F}_{2^{10}}$, $1 \leq i \leq 3$. The 3-tuple is associated with a polynomial $m(x)$ defined by $m(x) = m_1x + m_2x^2 + m_3x^3$. The ciphertext \mathbf{c} is now produced as

$$\mathbf{c} = (m_1, m_2, m_3, m(k_1) + k_2).$$

Determine P_I and P_S .

Hint: For any polynomial $p(x)$ over \mathbb{F}_q of degree k there are at most k different elements $\alpha \in \mathbb{F}_q$ for which $p(\alpha) = 0$.

(10 points)

Problem 5

Let $p_1(z) = z^{-6} + z^{-4} + 1$ and $p_2(z) = z^{-7} + z^{-3} + z^{-2} + z^{-1} + 1$ be two polynomials over \mathbb{F}_2 . Consider the following statements:

- a) The polynomial $p_1(z)$ is irreducible ("primpolynom").
- b) The LFSR with feedback polynomial $p_1(z)$ has cycle set $1(1) \oplus 9(7)$.
- c) The LFSR with feedback polynomial $p_1(z)p_2(z)$ has at least nine cycles of length 7.
- d) The shortest LFSR generating the sequence $[00000100010101]^\infty$ has feedback polynomial $p_1(z)$.
- e) All irreducible polynomials of degree 7 over \mathbb{F}_2 are primitive.

Choose for each of the five statements given above one of the following alternatives:

- i) Correct — I am uncertain
- ii) Wrong — I am uncertain
- iii) Correct — I am certain
- iv) Wrong — I am certain.

Correct answer according to i) or ii) gives 1 point.

Correct answer according to iii) or iv) gives 2 points.

Erroneous answer according to i) or ii) gives 0 points.

Erroneous answer according to iii) or iv) gives -2 points.

(Only answers are required!)

(10 points)
