

GROWATT THOR Smart EV Charger

THOR 11AD-SE/PE/SEW/PEW-V1

THOR 22AD-SE/PE/SEW/PEW-V1 (Three Phase)

- Compatible with all branded EV
- Integration in existing & new-installed PV system
- Charge EV with 100% renewable energy by surplus solar power
- APP smart control & smart scheduling
- IP65 design for indoor or outdoor use



GROWATT

P O W E R
- I N G O
T O M O -
R R O W O

Datasheet	THOR 11AD-SE/SEW	THOR 11AD-PE/PEW	THOR 22AD-SE/SEW	THOR 22AD-PE/PEW
Input & Output				
Input voltage		400V AC		
Input frequency		50/60Hz		
Output voltage		400V AC		
Max. output power	11kW		22kW	
Max. output current	16A		32A	
Charging interface type	IEC 62196-2, Type 2			
Connection	Dual plugs	Dual sockets	Dual plugs	Dual sockets
Cable Length	5m	/	5m	/
Protection				
Over voltage protection		Yes		
Under voltage protection		Yes		
Over load protection		Yes		
Short circuit protection		Yes		
Earth leakage protection	6mA DC fault current protection			
Over-temp protection		Yes		
Lightning protection		Yes		
Function and Accessory				
Ethernet/WIFI/4G		Yes/Yes/Opt		
LCD		Yes		
RCD	Type A + 6mA DC fault current protection			
Charge activation	APP/Plug&Charge/RFID			
LED Indicator light		Yes		
Emergency stop button		Yes		
Multiple workmodes	Fast/ PV Linkage/ Off-peak/ Load balancing			
Communication Protocol		OCPP 1.6		
MID meter		Opt		
Installation	Floor/ Wall mount			
General				
Protection degree		IP65		
Environment temperature		-25°C ~ +50°C		
Relative humidity		5-95% non-condensing		
Maximum altitude		<2000m		
Cooling	Natural cooling			
Standby power consumption		<8W		
Dimension (W/H/D)	420/1640/270mm			
Weight	17kg	19.5kg	17kg	17kg
CE, UKCA				