

EU SYN-600E-30

- Switching time $\leq 100\text{ms}$
- Supporting self-feeding and self-restoring
- Modular design, easy to install and maintain
- Automatically switch to the intermediate state when the power supply is missing



GROWATT

en.growatt.com

P O W E R
- I N G
T O M O -
R R O W O

Datasheet	EU SYN 600E-30	
Input Data(AC/Grid)		
Max. AC apparent power		330kVA
Nominal AC voltage		380/400/415V
AC grid frequency		50Hz/60Hz
Max. input current		600A
AC grid connection type		3P4W+PE
Input Data(GEN)		
Max. AC apparent power		330kVA
Nominal AC voltage		380/400/415V
AC grid frequency		50Hz/60Hz
Max. input current		600A
AC grid connection type		3P4W+PE
Output Data(Load)		
AC nominal power		300kW
Max. AC apparent power		330kVA
Nominal AC voltage/range		380/400/415V
Max. output current		600A
General Data		
Dimensions (W/H/D)		700/900/376mm
Weight		65kg
Operating temperature range		-25°C ~ 60°C (>50°C derating)
Altitude		4000m
Cooling		Nature convection
Protection degree		IP66
Installation		Wall Mountable

SHENZHEN GROWATT NEW ENERGY CO.,LTD All rights reserved. All specifications are subject to change without notice.