

```

[alande10@gal-i9 blocking-queue]$ nano Makefile
[alande10@gal-i9 blocking-queue]$ make clean
rm client client.o block_client block_client.o
rm: cannot remove 'client': No such file or directory
rm: cannot remove 'client.o': No such file or directory
rm: cannot remove 'block_client': No such file or directory
rm: cannot remove 'block_client.o': No such file or directory
make: [Makefile:17: clean] Error 1 (ignored)
[alande10@gal-i9 blocking-queue]$ make
g++ -std=c++17 -Wall -c -o client.o client.cpp
client.cpp:20:10: fatal error: rapidjson/document.h: No such file or directory
   20 | #include <rapidjson/document.h>
      |
compilation terminated.
make: *** [<built-in>: client.o] Error 1
[alande10@gal-i9 blocking-queue]$ █

```

Unable to get it to run on Centaurus, tried editing the Makefile and was unable to get it to run.

Was able to run on my laptop, it looked like it was quicker than the sequential version

Sequential at depth 4

```

alande10@Alexander:/mnt/c/WINDOWS/system32$ cd /
alande10@Alexander:/$ cd mnt/c/Users/Alex/parallel
alande10@Alexander:/mnt/c/Users/Alex/parallel$ ls
Makefile      block_client.cpp  client          client.o
block_client  block_client.o    client.cpp      rapidjson
alande10@Alexander:/mnt/c/Users/Alex/parallel$ ./client Tom%20Hanks 4
- Tom%20Hanks
Time to crawl: 0.469533s
alande10@Alexander:/mnt/c/Users/Alex/parallel$

```

Block queue at depth 4

```

alande10@Alexander:/mnt/c/Users/Alex/parallel$ ./block_client Tom%20Hanks 4
- Tom%20Hanks
Time to crawl: 0.270383s
alande10@Alexander:/mnt/c/Users/Alex/parallel$

```