DT1700
Breathalyzer



Bright Color LCD Display | High Accuracy | Fast Detection | Easy Integration

Introduction

DT1700 is a portable alcohol detector, engineered specifically for precision testing and rapid assessment. It delivers accurate and stable results for quick screening and reliable intoxication determination.

DT1700 has a 1.77-inch color LCD with clear visuals and audio prompts to prevent misinterpretation of breath alcohol testing results. In addition to its ergonomic bar design, it is equipped with a 1,500mAh lithium-ion battery, guaranteeing 24+ hours of standby availability. It offers a broad measurement range of 0 to 400mg per 100ml and tight error margins for intuitive operation. Most importantly, DT1700 is compatible with G4 Pro and can connect through USB Type-A, allowing centralized data logging and analysis.

Features

- Clear result indication: DT1700 delivers instant, color-coded test results-green for Pass, yellow for Drink, and red for Fail. With audible, text, and color indicators to reduce ambiguity.
- Measurement accuracy: When C ≤ 80 mg/100 ml, E (error) < ±4 mg/100 ml. When C > 80 mg/100 ml, E (error) < ±5%*C.
- No warm-up required: ready for testing immediately upon power-on.
- High-brightness 1.77-inch color LCD display: clear visibility in varied lighting.
- Compact ergonomic bar design: easy to carry for on-site testing.
- Long-standby time: rechargeable 1,500 mAh lithium-ion battery supports over 24 hours of standby time.

Specifications

Model	DT1700
Display	1.77"@Color LCD Display
Sensor	11mm electrochemical fuel cell
Measurement Accuracy	When C ≤ 80mg/100ml, E (error) < ±4mg/100ml; When C > 80mg/100ml, E (error) < ±5%*C
Measurement Range	0.0mg / 100ml to 400mg / 100ml (Breath Alcohol Concentration)
Tested Memory Capacity	20 Tested Memory
Mouthpiece	2*reuseable trumpet-shaped mouthpieces ; 4* disposable mouthpieces
Interface	USB Type-A
Power Supply	5V
Battery	1,500 mAh (Lithium Battery) Max. Standby Hours: 24 Hours

Product Life	Up to 3 Years (MTBF) / 20,000 Tests (MCBF)
Operating Temperature	0°C ~ 45°C
Operating Humidity	30% ~ 90% RH (Non-condensing)
Dimensions	140*57*27mm (L*W*H)
Certification	CE, Equivalent to RoHS.
Compatible Product	G4 Pro

Application Areas


Enterprises


Buildings


Factories


Financial Institutions


Campuses


Hotels


Hospitals


Public Service Institutions

ZKTECO CO.,LTD. www.zkteco.com E-mail: sales@zkteco.com

Copyright © 2025 ZKTECO CO., LTD. All rights reserved.