	REV.	DESCRIPTION						DAT	ſΕ	APPR	OVED	S	TATUS
								Ø6					
					< →			~~ 0					
		7	1	<u> </u>		 							
						NI	ОТЕ	:0.					
						1.			/E BUI	rrs an	d shari	P EDC	GES.
		80											
		∞											
									Ā				
								25					
		1	1						<u> </u>				
					. \						Genera	l Tole	rances
				_	\bot	2	.50	-			0-6		±0.1
											6-30 30-200)	±0.2 ±0.3
											200-50	0	±0.5
Dimension and toleranc		1		TOLE	RANCE	S UNLESS	PRC	DJECT			500-100	00	±0.8
NAM DESIGNED Design		SIGN	DATE	OTHER	WISE S	PECIFIED: ee table	NAI						
CHECKED				ANGUL	.AR	±0.5°	INAI	Sh	aft	with	D-Bor	e	
APPROVED	· (5- ~	D		BETWEE	-N	0.5x45°	MAI	TERIAL: /	Alumin	ium 6061			
C	MS	R		BORES	S		FINIS		NEXT A	note ASSY':			
Center for Manufac Faculty of Me LIDWORKS Educations	turing Sy	ystems and	Robotics	QUALIT	Ý \	/Ra 1.6	DIME	1 🗘	DPAM	/ING No.			REVIS
Faculty of Me LIDWORKS Educationa	cnanico I Institut	al Engineeri e of Techno ct. For Instri	ng Johnal Use	1:1 Only NOT	MEASURE	OILE 14		MM	DKA W	TING NO.			O