


Workload-Aware, Self-Designing Buffers in LSM-Engines


Alexander Ott, Subhadeep Sarkar

LSM Mem Buffers

LSMs Everywhere




LSM Memory Buffer




- Buffers disk writes in memory
- More efficient search for recent entries

Buffer Performance



The Problem

Buffer Configuration & Dynamic Workloads



Formal Definition

- only a few memory buffer implementations to use
- strengths and weaknesses of memory buffers are not known


Approximate the function $f(C, w_{t-1}) \rightarrow c_t$ where C is a subspace of the configuration space, w_{t-1} is the previous workload, and c_t is the new configuration. Given an approximation of f , optimize $o(c_t) \rightarrow p_t$, where p_t is the desired performance metric, e.g. minimizing insert latency, maximizing throughput.

Solution

Experimentation & Implementation

- implemented a vector that is not sorted during queries
- implemented a memory buffer using the trie data structure, which is more space efficient
- dissect existing memory buffer implementations and experimentally evaluate their performance tradeoffs
- added ability to dynamically configure RocksDB at runtime
- designed an ML-model that suggests the best buffer configuration for a given workload


ML Optimization using TPE+CMA-ES



Results

Effectiveness

Mean Memory Buffer Throughput for a Dynamic Workload




- dynamic memory buffer is able to achieve high throughput in both sections of the workload

Future work

- Exploring more memory buffer implementations
 - concurrency
 - hash trie
- Introducing more knobs to optimize
 - bucket count and prefix length for hash memory buffers
- Add more optimization targets

Gordon Science Research Fellows Endowment Fund established by the Cele H. and William B. Rubin Family Fund, Inc



Brandeis
UNIVERSITY

School of Arts and Sciences
Michtom School of Computer Science